



GGT STANDARD SWIVEL JOINTS

HIGHLY TENSILE GALVANIZED STEEL
RESISTANT AND LIGHT

GGT CONDUCTIVE SWIVEL JOINTS

THEY ARE SUITABLE TO WORK IN LIVE WORKING CONDITION

SPECIFICATION:
T < 100° WITH 225 A CONTINUOUS FLOW FOR 1 H

STANDARD SWIVEL JOINTS

CONDUCTIVE SWIVEL JOINTS

STANDARD SWIVEL JOINTS

MODEL	DIMENSIONS			WORKING LOAD	WEIGHT
	A	B	C max		
GGT001	106 mm	28 mm	10 mm	23 kN	0.3 Kg
GGT010	143 mm	40 mm	13 mm	37 kN	0.925 Kg
GGT020	184 mm	54 mm	18 mm	73 kN	2.15 Kg
GGT030	234 mm	60 mm	24 mm	120 kN	3.4 Kg
GGT040	322 mm	77 mm	28 mm	250 kN	8.2 Kg
GGT180	336 mm	81 mm	32 mm	250 kN	8.7 Kg
GGT260	403 mm	104 mm	38 mm	330 kN	19.5 Kg

CONDUCTIVE SWIVEL JOINTS

MODEL	DIMENSIONS			WORKING LOAD	WEIGHT
	A	B	C max		
GGT081	184 mm	54 mm	18 mm	60 kN	2 Kg
GGT170	243 mm	60 mm	24 mm	97 kN	3.4 Kg

