



Product Specifications

PR-C201		
	Print Method	Dye-sublimation retransfer printing
	Resolution	600DPI
Print	Input	R/G/B 256 level
	Output	Y/M/C/UV 256 level
	Printing area	Over the edge on CR-80 cards
Speed	Printing speed (Single printing: YMCK)	More than 22.5s full color YMCK (160 cards/hr)
	Printing speed (Double printing: YMCKK)	More than 36s full color YMCKK (100 cards/hr)
Capacity	Feeder capacity	250 cards (if card thickness is 0.76mm)
	Card exit capacity	250 cards (if card thickness is 0.76mm)
Cards	Card thickness	0.25 to 1.0 mmCard
	Card size CR-79 & CR-80	CR-79 & CR-80
	Card material	PVC, PET, PC, ABS (Except PVC cards need prior confirmation)
Display	Display	LCD Panel (with back light), LED, Operation
Size	Dimensions	17.13(H) × 13.39(W) × 12.60(D) In.
	Weight	Less than 33 lbs. (15kg)
Power	Power Source	90 - I25VAC 220 - 240VAC 50/60Hz
	Power consumption	Less than 3A (100V)
Temperature	Operating temperature	10 to 35°C - 20 to 80% humidity
Drivers	I/F	USB and Ethernet 10 Base-T, 100 Base-T
	Drivers	XP, Vista, Win 7 (32 & 64 bits), Win 8 (32 & 64 bits)
Ribbon	Ribbon capacity	500 images / roll (all ribbons)
	Film Ribbon	Clear Retransfer, Holographic Retransfer
	Ink Ribbon	YMCK, YMCKK, YMCKHs (except for PVC Card)
		YMCKI (for smart card), YMCFK (UV ink)
Agency Listing	Agency Listing	UL/CSA/CE/FCC
Warranty**	Printer	2 years
	Print head	Limited lifetime
Other	MTBF	100,000 prints
	Extendibility	2 USB HUBS (inside printer)
	Memory size	64MB
Options	Laminator	Available
	Encoder	Mag Encoder, Contact Encoder, Contactless Encoder

 $[\]ensuremath{^{*}\mathsf{Specifications}}$ subject to change without notice.





US Asia South East Asia Europe 100 Randolph Road, Somerset, New Jersey 08873 USA • +1 732-271-7369 • sales@teamnisca.com 2-1, Shibaura 1-chome Minato-ku, Tokyo 105-8005, Japan • 81-(0)3-5440-9809

25th Floor, Thaniya Plaza Building, 52 Silom Road, Suriyanwongse, Bangkok, 10500, Thailand • 66-(0)2-632-8077 KANEMATSU GmbH, Oststraße 34, 40211 Düsseldorf, Germany • +49 211 3689-255 • sales-EU@teamnisca.com





^{**} Contact Team NiSCA for details.