

ROTEX AUTOMATION EUROPE

Address : Bierstraat 117, 3011 XA Rotterdam, The Netherlands

Website : www.rotexautomation.com

E-mail : europe@rotexautomation.com

**DATASHEET**

Date : 02/10/2020
 Ordering Code : 34-III-24V-AC/DC-37-FR-H-01
 Item Code : F802000001
 Type of Solenoid : Explosion Proof Enclosure Ex d having integrated Terminals, Horizontal Cable Entry 1/2" NPT
 Size of Coil : III
 Voltage : 24V AC/DC (-20%, +20%) (RESISTANCE CAN'T BE MEASURED IN COIL ASSEMBLY)
 Enclosure Material : Aluminium cast powder coated
 Approval : CE - ATEX
 Special Version : Inbuilt full Rectifier with surge suppressor
 Power of Coil : 8W
 Insulation Class : H
 Certificate nr. : EXTENSION 01/12, CESI 03 ATEX 344
 Marking : Ex II 2G Ex d IIC T6/ T5/ T4 Gb
 Ex II 2D Ex tb IIIC T80°C/ T95°C/ T130°C Db, IP66
 -40 °C ≤ Ta ≤ 35 °C FOR T6
 -40 °C ≤ Ta ≤ 50 °C FOR T5
 -40 °C ≤ Ta ≤ 60 °C FOR T4

Created By: Jasmine Singh Print Date And Time: 02/10/2020 17:31

This is System Generated Report