

Abb Automation



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Abb Automation Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Abb Automation Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
R 25 %7 - 189hz 25kvar	
R 50 %7 - 189hz 50kvar	
R 100 %7 - 189hz 100kvar	
1sda038302r0001	Zub. f. Leistungsschalter E1-E6 Einschaltauslser
1sda038292r0001	A-Ausl. E1-E6 220-240V AC/DC Zub. f. Leistungsschalter E1-E6
1sda038312r0001	U-Ausl.E1-E6 220-230V AC/DC Zub. f. Leistungsschalter E1-E6
Rpba-01	Profibus Adapter Module
Rdcu-12c	Control Unit
Acs800-104-0580+c126+e250	Driver Module
Gae75-10	24VDC
Cas-22m	24VDC
Raio-01	Analogue I/O Extension Module
Rdio-01 /	Digital I/O Extension Module
1SDA067428R0001	XT1N 160 TMD 160-1600 4P FF IN = 100% Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 4-pin TMD 10xIth R160 InN = 100% ZNR: 85362090 Origin: IT Weight: 4,200 KG; Gross weight: 4,200 KG
1SDA067424R0001	XT1N 160 TMD 100-1000 4P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 4-pin TMD 10xIth R100 ZNR: 85362090 Origin: IT Weight:

	2.800 KG; Gross weight: 2.800 KG
1SDA068059R0001	XT3N 250 TMD 250-2500 3P FF Compact circuit breaker Tmax XT3 with front. Connections With the following configuration: XT3 N 250 firmly Front connections 3-pin TMD 10xIth R250 ZNR: 85362090 Origin: IT Weight: 6,800 KG; Gross weight: 6,800 KG
1SDA067418R0001	XT1N 160 TMD 160-1600 3P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 3-pin TMD 10xIth R160 ZNR: 85362090 Origin: IT Weight: 4,400 KG; Gross weight: 4,400 KG
1SDA067417R0001	XT1N 160 TMD 125-1250 3P FF Compact circuit breaker Tmax XT1 with front. Connections With the following configuration: XT1 N 160 firmly Front connections 3-pin TMD 10xIth R125 ZNR: 85362090 Origin: IT Weight: 6,600 KG; Gross weight: 6,600 KG
TB-B/PG21-PG11/R	EXPANSION / REDUCTION TYPE R AG = PG 21 / IG = PG 11
Typ PFRL 101B	Radial force transducer type PFRL 101B, Nominal force 1 kN, for z. B. Self-aligning ball bearing 2205, D2 = 52 mm, axle journal d = 25mm continuous, without bearings and spacer rings, Net weight 2 kg Order number: 3BSE 002 958 R15 Consists: 1 pc. 3BSE 023 315 R5 PFRL 101B load cell 1kN 2 pcs. 3BSE 023 155 R4 cover with hole D1 = D1 = 33 mm
PFEA111-65 Loadcel card	Cable connector, without cable For connection of the force transducer type PFRL 101 Order number: 3BSC 860 067 R1
V18345.10.1.0.2.2.1.00.1	// TZIDC DIGITAL POSITIONER ABB TYPE: V18345-1010221001 TZIDC digital positioner, intelligent, parameterizable, with display and control panel V18345 - Housing / assembly 10 Housing made of aluminum, painted, for Attachment to linear actuators according to DIN / IEC 534 / NAMUR or on rotary actuators according to VDI / VDE 3845 - control input / 1 control input 4 ... 20 mA, two-wire technology, Communication connection with plug connection for LKS adapter - Explosion protection 0 Without - Control output / safety position (with 2 single-acting, actuator is blocked Failure of the electrical power supply) - Connections 2 cables: thread 1 / 2-14 NPT, air line: 1 / 4-18 NPT thread - Optional extension with plug-in module 1 plug-in module for analogue feedback, for analog / digital feedback signal range 4 ... 20 mA, two-wire technology - Optional extension with 00 Without mechanical kit for digital feedback - Design (painting / marking) 1 standard Pos. 100: Statistical goods no .: 90328900 / country of origin: DE
3BSE 050 090 R65	Central unit type PFEA 111, for wall mounting, IP 65 Supply voltage: 24 V DC or 230 V AC Signal output: 0 - 10 V or 0 (4) - 20 mA Net weight 2 kg User manual,

	multilingual, on CD-ROM, Order number: 3BSE 050 090 R65
FEP311.025.A.1.D.1.D4.B.0.A.1.A.0.A.1.A.2.C.	1.B..H2....M1 FEP311 Nominal size 025 DN 25 (1 in.) - Lining material A PTFE - Electrode version 1 standard - Measuring electrode material D Hastelloy C-4 (2.4610) - Earthing accessories 1 standard - Process connection D4 flange DIN PN 40 - Process connection material B steel - Certificates 0 measuring tube with PED approval - Calibration A standard accuracy - Temperature range transducer / 1 standard transducer design / -20 ... 60 ° C Ambient temperature range (-4 ... 140 ° F) - Type plate A adhesive label - Signal cable length 0 Without cable - Explosion protection A Without - Degree of protection transmitter / sensor 1 IP 67 (NEMA 4X) / IP 67 (NEMA 4X) - Cable gland A M20 x 1.5 - Power supply 2 24 V AC / DC, 50 Hz - Signal inputs and outputs C HART + 20 mA active + pulses + Contact input / output - Presets / Diagnosis 1 parameters have factory settings / Standard diagnostic functions activated - Construction stand B Construction stand B DN3 - 150 / not PN16, PN40 and ASME CL150 - Housing design H2 two-chamber housing - Language of the documentation M1 German Pos. 100: Statistical goods no .: 9026900000 / country of origin: GB
ACS800-U4-0205-5+P901	
3BSE002959R0005	
216DB61 HESG324063R100/J	
NO T19039111- T190039112	CEWE ELITE447 PS:H,CL:0.5S, MOD:NNN CE447H05NNN
RMIO-01 PCB KIT : NO:6220434	
1SVR011700R0000	24 VDC, CC-E/STD
ES2000-9725	Ipn 2000A VA +-15...+-24V Np/Ns:1/5000 Rs25 Ω
CIRCUIT BREAKER DS 201A-C 6/0,03 1-POLE ABB	2CSR255140R1064
A-TRIGGER E1-E6-T8 220-240V AC/DC ABB	1SDA038292R0001
E-TRIGGER E1-E6-T8 220-240V AC/DC ABB	1SDA038302R0001
UNDERVOLTAGE RELEASE 220-230V AC/DC E1-E ABB	1SDA038312R0001
Protection Trip Units and Curves SACE	PR 122/P LSIG power supply auxiliary power supply : 24v dc +/- 20% maximum ripple 5% inrush current@24v -10A for 5ms rated power @ 24v -3W
Protection Trip Units and Curves SACE	PR 122/P LSI power supply auxiliary power supply : 24v dc +/- 20% maximum ripple 5% inrush current@24v -10A for 5ms rated power @ 24v -3W
	- Mounting A2 Switch rod mount up to 350 °F (176.6 °C) max process temperatures. When used with chamber

LMS100.A2.Y0.Y0.A1	insulation option, 800 °F (426.7 °C) max process temperatures - High Temperature Processes Insulation Y0 Standard, without insulation pad (standard Options gear clamp mounting) - Approvals Y0 General Purpose, (not for hazardous locations) - Electrical Cable Connection A1 Standard, 0.50 in. NPT-Female - Operating Temperature 30 °C - Chamber Insulation No
1SAP250600R0001	
V18345.20.2.0.4.6.1.00.1	TZIDC Digital positioner, intelligent, configurable, with display and control panel V18345 - Housing / assembly 20 aluminum housing, painted, with mechanical position indicator, for attachment to thrust drives according to DIN / IEC 534 / NAMUR or to part-turn actuators VDI / VDE 3845 - Control input / 2 control inputs 4 ... 20 mA, two-wire technology, Communication port with plug-in connection for LKS adapter and FSK module for HART communication - Explosion protection 0 None - Actuating output / safety position (with 4 double-acting, actuator is vented Failure of the electrical power supply) - Connections 6 cables: thread M20 x 1.5, air line: Thread G 1/4 - Optional expansion with plug-in module 1 plug-in module for analogue feedback, for analogue / digital feedback, signal range 4 ... 20 mA, two-wire technology - Optional extension with 00 without mechanical kit for digital return message - Design (painting / marking) 1 standard Pos. 100: Statistical goods no.: 90328100 / country of origin: DE
266GST.F.K.B.N.A.1-.E2..L1.B7	266GST Gauge Pressure Transmitter, Basic Accuracy 0.04% 266GST - Sensor measuring range limits / F 0.4 and 40 kPa (4 and 400 mbar, 1.6 and Overload limit 160 in. H2O) / 1 MPa (10 bar, 145 psi) - Diaphragm material / filling liquid K Hastelloy C-276 / silicone oil - Process connection Material / Type B Stainless steel AISI 316L (1.4404) / 1/2-14 NPT female thread - Gasket Material N None - Body Material / Electrical A Aluminum Alloy (Barrel Type) / 1/2-14 Connection NPT - Output 1 HART digital communication and 4 ... 20 mA - Explosion protection E2 ATEX II category 1/2 GD, flameproof Encapsulation Ex d - Integrated digital display (LCD) L1 With integrated LCD display - Fastening accessories / material B7 For horizontal or vertical pipe and Wall mounting / AISI 316 (1.4401) [1] Measuring Range -150 ... 0 inH2O@4C [1] Scale -150 ... 0 inH2O@4C [2] Measuring Range -150 ... 0 inH2O@4C [2] Scale -150 ... 0 inH2O@4C
2TLA020051R5100	7350024480306 ADAM DYN-INFO Security sensor IP69K, M12-5 pin
	266HSH gauge pressure transmitter, basic accuracy 0.075%, Overload limit up to 90 MPa / 900 bar / 13050 psi 266HSH - Sensor measuring range limits / Q 80 and 8000 kPa (0.8 and 80 bar, 11.6 and Overload Limit / Basic Accuracy 1160 psi) / 21 MPa (210 bar, 3045 psi) / Basic accuracy 0.06% - Diaphragm material / Filling liquid S Stainless steel (AISI 316L SST) / Silicone Oil

266HSH.Q.S.B.A.1-.VA...L1..B6....I2	(NACE) - Process Connection Material / Type B Stainless steel AISI 316L/ 1/2 in. -14 NPT-f (NACE) - Body Material / Electrical A Aluminum Alloy (Barrel Type) / 1/2-14 Connection NPT - Output 1 HART digital communication and 4 ... 20 mA - Ventilation / VA stainless steel AISI 316L (1.4404) Drain valve material (NACE) (wetted) - Integrated digital display (LCD) L1 Integrated LCD display with integrated Keys - Mounting accessories / material B6 For horizontal or vertical mounting on Pipe and Wall / Carbon Steel - Additional identification plate I2 measuring point and certification plate stainless steel, laser printing Pos. 100: Country of origin: IT
CR-M2LS	SERİ NO: 1SVR405651R1100
CM11A1	
(27-08-01-05-25) 87 T 550-E / R1214	COUPLING MODULE ETHER NET INTERFACE ON THE STATION BUS 87 T 550-E / R1214
(27-08-01-05-26) 81ET03-E/R1210	INPUT MODULE FOR TEMPERATURE SENSOR 16-FOLD, 81ET03-E/R1210
(27-08-01-05-27) 81EU01-E/R1210	UNIVERSAL INPUT MODULE FOT BINARY ANALOG TRANSMITTER TYPE:81EU01-E/R1210
(Motor Axis 5 Irb 6640) (Old 3hac17484-10)	
V68853 (Elektronik Contrac Ebn 853)	
3hac2493-1	
Motor Axis 4 Irb 6640) (Old 3hac033209-001)	
3gaa062312-Asc	M3AA63B-4
Mba 800 / Mba820xhn1_A00187_D_Xx	
3 Hac 17484 - 6/ 00	
Abb 12	
Sicherung Je 3 Stück	FCF1,FCF2,FCF3 2A
Filterelement For Acid Filter	8018013
Adp-Al34/FI/90 - Adaptaflex - Flexible Leitungssysteme	
Tzid-C (V18345-2020121001)	
Niin_12f213948 P/N_101c701	
Es2000-9725 / Ipn:2000a / Va:-+15 -+24v / Akim Sensörü	
242383554/X002/031234	
2rca025340a0001	

[Feeder Proction Relay](#)

MIF11P 100 ER H10

[\(Motor Axis 2-3 Irb 6600\) \(Old 3hac15882-2\)](#)