

Aco

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Aco Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Aco T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
AMMS-0-1-2-0	Universal fire measuring sensor Ceramic measuring surface Output 4 ... 20mA max. 70 C, including clamping ring +++ Incl. junction box "CONBOX VI" for sensor: -Aluminium housing, IP 65 - with integrated calibration interface
580-2101-00012	
AMMS-0-1-2-0	Universal moisture measurement sensor Ceramic measuring surface Output 4 20mA max 70C including clamping ring 9 30VDC IP67 Sensor cable 3m (standard) to the sensor and CONBOX, pluggable on both sides (plug and bush straight) IP68 ++++++ Incl. junction box "CONBOX VI" for sensor: -Aluminium housing, IP65 -with integrated calibration interface (calibration via AMMScontrol)
MOUNTING KIT MOISTURE SENSOR ACO SLOT	ADJUSTABLE 580-2101-00012
	Universal moisture measurement sensor ceramic measuring surface Output 4...20mA max. 70°C, incl. clamping ring Features: - power supply 9...30VDC, - highly wear-resistant ceramic measuring surface - integrated calibration encoder

AMMS-0-1-2-0	(2-point calibration) - Temperature compensation (electronics) - Standard signal output for humidity (for direct further processing with your PLC, etc.) - Stainless steel housing, IP 67 - Sensor cable 3m (standard), can be plugged into the sensor and CONBOX on both sides (straight plug and socket), IP68 +++++ incl. connection box "CONBOX VI" for sensor: - Aluminum housing, IP 65 - with integrated calibration interface (calibration via AMMScontrol)
AMMS-PC-SOFTWARE	AMMS CONTROL" for commissioning, service and calibration of the sensor; Incl. Configuration cable "AMMS-Cable+" - Operation with standard PC - Diagnostic function with display of the measuring parts, water content (humidity) - Entry of a media-specific calibration curve - up to 10 calibration points - Averaging calculation
R1035HV	Sensor carriage ACO sensor Stainless steel, hard chrome plated with mounting holes and sensor cutout
AMMS-0-1-2-0	Universal moisture measurement sensor ceramic measuring surface Output 4...20mA max. $\gamma O^{\wedge}C$, incl. clamping ring Characteristics: - power supply 9...30VDC, - highly wear-resistant ceramic measuring surface - integrated calibration encoder (2-point calibration) - Temperature compensation (electronics) - Standard signal output for humidity (for direct further processing with your PLC, etc.) - Stainless steel housing, IP 67 - Sensor cable 3m (standard), can be plugged into the sensor and GONBOX on both sides (straight plug and socket), IP68 +++++ incl. connection box "GONBOX VI" for sensor: -Aluminium housing, IP 65 - with integrated calibration interface (calibration via AMMScontrol)
AMMS-PG-SOFTWARE	"AMMS GONTROL" for Commissioning measurement, sen/ice and calibration tion of the sensor; Incl. Configuration cable "AMMS-Cable+" - Operation with standard PC - Diagnostic function with display of the measuring parts, water content (humidity) - Entry of a media-specific calibration curve - up to 10 calibration points - Averaging calculation
Mms-0-2-2-3	