

## Addi-Data

Garanti: 12 ay  
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.  
**Addi-Data** Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

*Firmamız Addi-Data Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*



rn	Aıklama
<a href="#">APCI-1710</a>	
<a href="#">APCI-3120-16-8</a>	
<a href="#">APCI-7420-3</a>	
<a href="#">CPCI-1710</a>	
<a href="#">MX232-G</a>	
<a href="#">APCIE-1500</a>	Digital I/O card 16 digital inputs, 24 V or 12 V, 14 of which are interruptible 16 digital outputs, 10-36 V, 500 mA/channel Galvanic isolation 1000 V Input and output filters watch dog, timer
<a href="#">PX901-DG</a>	Digital terminal board with housing Two-tier terminal board for connecting active sensors/actuators, 2 rows, with diodes and snap-on housing to standard mounting rails
<a href="#">ST010</a>	Standard I/O cable, 2m shielded paired round cable 37 pin SUB-D socket connector 37 pin SUB-D male connector
	Standard I/O cable, 5 m shielded paired round cable 37 pin

<a href="#">ST011</a>	SUB-D socket connector 37 pin SUB-D male connector, length 5m
<a href="#">APCI-1500</a>	Digital I/O card, 24V, PCI 32 digital inputs/outputs, galvanically isolated, 14 interrupt-capable inputs, input/output filters, Output current 500mA per channel, Resetting the outputs to "0" at power-on, 3 timers, watchdog Weight: 0.12 kg
<a href="#">PX901-DG</a>	Terminal board digital with housing Two-level terminal board for connecting active sensors/actuators, 2 rows, with diodes and housing to snap on to standard Support rails 0.205kg
<a href="#">ST010</a>	Standard I/O cable, 2m shielded twisted pair round cable 37 pin SUB-D socket connector 37 pin SUB-D pin connector Weight: 0.425 kg
<a href="#">St010</a>	
<a href="#">Apci-1710</a>	
<a href="#">Px901-Dg</a>	
<a href="#">Apci-7500-3</a>	
<a href="#">Pa1500</a>	
<a href="#">Apci-1500</a>	
<a href="#">Cpci-1710</a>	
<a href="#">Msx-E1701</a>	
<a href="#">St370-16</a>	
<a href="#">Apci-3001-8</a>	
<a href="#">Px8001</a>	