

## Aflex Hose

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Aflex Hose** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Aflex Hose T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">PTFE smooth hose type Bioflex</a>	Ultra GP/AS/SS/SI, inliner PTFE black and conductive, with spiral and braid Stainless steel, with transparent silicone cover DN 40 Operating pressure = max. 16 bar Length = 1500 mm *** - Hose management program: yes - Different hose number: no - Colored identification tape: no - Suggested testing interval: 1 year - Test certificate: yes -> Pressure test -> FDA -> WAZ 3.1 for clamps -> Operating instructions - CE marking: yes *** - Connection on both sides: clamp fitting DIN 32676 series A DN 40 DIN plate OD 50.5mm, bore 38mm made of stainless steel 1.4435 without lining
<a href="#">hose aflex hose ltd dn40/1.5 bfxu 16/32</a>	
<a href="#">Corroflon Gp/As/Ss 3"</a>	conductive, with stainless steel mesh 1.4301 and black extruded EPDM blanket 3 "x 1,000 mm Bds. Loose flange DN 80 EN 1092-1 / 02 PN 16 made of stainless steel 1.4404 with PTFE flare
<a href="#">Corroflon Gp/As/Ss 2"</a>	conductive, with stainless steel mesh 1.4301 and black extruded EPDM blanket 2 "x 1,000 mm Bds. Loose flange DN 50 EN 1092-1 / 02 PN 16 made of stainless steel 1.4404 with

	PTFE flare
<a href="#">Corroflon Gp/As/Ss 4"</a>	conductive, with stainless steel mesh 1.4301 and black extruded EPDM blanket 4 "x 1,000 mm Bds. Loose flange DN 100 EN 1092-1 / 02 PN 16 made of stainless steel 1.4301 with PTFE flare
<a href="#">Corroflon Gp / As / Ss 1/2"</a>	CORROFLON GP / AS / SS conductive, FDA compliant with stainless steel mesh 1.4301 and black extruded EPDM blanket 1/2 "x 500 mm Bds. Loose flange DN 15 EN 1092-1 / 02 PN 16 made of stainless steel 1.4404 with PTFE flare