



Ahlborn

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Ahlborn Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Ahlborn T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
MA710	Precision measuring device ALMEMO 710, 10 inputs. ALMEMO measuring device of the latest generation V7! Mobile device with stand. > Case set with accessories, see below. < 10 inputs for all ALMEMO sensors (standard, D6, D7). Large 5.7" color graphic display with bright illumination. Convenient operation via touch screen. Increased measurement accuracy, fast measurement rate. data logger function with internal memory (up to 1.5 million readings) or with external memory plug with SD card ZA1904SD (not included!). Universal measuring device, extensive functions for everyone areas of application. Built-in barometric air pressure sensor. Real-time clock, buffered by built-in lithium battery. Battery operation with built-in lithium battery, charging in the device. Scope of delivery: 1. ALMEMO 710 measuring device including built-in lithium battery 2. ZA1312NA11 power adapter 3. USB Data Cable ZA1919DKU 4. Measuring tool case ZB9710TK 5. Quick Start Guide A notice: WinControl version 7 or higher is suitable as measurement software. For versions 6 or older, an update of WinControl necessary! For online measurement with quick measurement query from ALMEMO D7 sensors, the additional option SW5600WCO11 needed. The parts included in the delivery, battery pack and/or lithium-ion batteries, are not set Dangerous goods within the meaning of the dangerous goods regulations as well as the traffic regulations and are in accordance with Part II of PI 967.
FKA613	Force transducer type K 1613 possible are: 0.5 kN / 1 kN / 2 kN / 5 kN / 10 kN / 20 kN (Range 50 kN with article number FKA6135) Radial cable outlet, 3 m, with ALMEMO connector plug
FWA225LWH	Displacement sensor type LWH 225 Usable path 225 mm ALMEMO system with 2 m connection cable
Za9060vkc50	
Fha646-E1-Za9060vk2	
Zka029ra	
May-90	

Ma24501
Fd991233ms
Zk9029fb
Za5690-Mu
Zk9029fs
Za9021fst
Fda602s6k
Zb2295ssl
Fhad4641
Fha646-E1-Za9060vkc100
Ma26908ks
Fha646-E1
Ma25904as
Lt01901
Ma24901
Fha646-E1-Za9060vk4
Fta122I0050h
Ma25903s-Za1312na1-Za1945-Dk
Za9060vkc20
Za1919dku
Mr783851p
Ft015I0050+zk9029fs+zk9029fb
Ma20201+za9020bko
Or7838is4
Fd8214m20u