

## Amc

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Amc** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Amc T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Nx2a4p</a>	4 CHANNEL, HT OR HTT SELECTABLE
<a href="#">1733</a>	RESOLVER INTERFACE MODULE, 10 BIT, 3 CHANNEL
<a href="#">1542</a>	RESOLVER INTERFACE MODULE, 13 BIT, 2 CHANNEL
<a href="#">10a8</a>	
<a href="#">1833</a>	MODICON QUANTUM: RESOLVER INTERFACE MODULE, 10 BIT, THREE CHANNEL, SINGLE RESOLVER TRANSDUCER, 800 I/O
<a href="#">1932</a>	10 BIT, TWO CHANNEL, SINGLE RESOLVER TRANSDUCER (90-70)
<a href="#">3602</a>	2 AXIS STEPPER CONTROLLER MODULE, W/ INTERPOLATION
<a href="#">Htt-425d-F1e-1000</a>	RESOLVER
<a href="#">Nx3a1e</a>	INDUSTRIAL NETWORK, RESOLVER PLS, 8 OUTPUT, 16 MAX., 16 INPUT
<a href="#">1941</a>	13 BIT, ONE CHANNEL, SINGLE RESOLVER TRANSDUCER (90-

	70)
<a href="#">Model 12a8</a>	
<a href="#">Ht-20-12</a>	RESOLVER TRANSDUCER GEARED MULTI-TURN 1/4IN SHAFT
<a href="#">1242</a>	RESOLVER INTERFACE MODULE FOR CONTROLLOGIX, 13 BIT, 2 CHANNEL. CONFIGURABLE FOR SINGLE OR MULTI-TURN, H25, HT OR HTT TRANSDUCERS
<a href="#">Nx2e4t</a>	4 CHANNEL
<a href="#">Nx1f2#</a>	2 AXIS STEPPER CONTROLLER/INDEXER, ENCODER FEEDBACK REQUIRES 2 STEPPER DRIVES
<a href="#">Dc425-#####</a>	INCOMPLETE PART NUMBER, CALL TO ORDER. ANALOG, 4-20 MA, SINGLE AND MULTI-TURN
<a href="#">Dr100re15a40nac - Obsolete, Replaced By Dprahir-01 5a400, Dprahir-01 5s400</a>	
<a href="#">1541</a>	RESOLVER INTERFACE MODULE, 13 BIT, 1 CHANNEL
<a href="#">1844</a>	MODICON QUANTUM: RESOLVER INTERFACE MODULE, 13 BIT, FOUR CHANNEL, SINGLE RESOLVER TRANSDUCER, 800 I/O
<a href="#">Sd17098ip</a>	STEPPER DRIVES- 9.8 AMP RMS (13.7 A PEAK), 170 VOLT INDEXER WITH DRIVER, MICRO-STEPPING. FOR ALL AMCI MOTORS
<a href="#">1731h</a>	RESOLVER INTERFACE MODULE, 10 BIT, 1 CHANNEL, SINGLE SLOT
<a href="#">Nx2e4e</a>	4 CHANNEL
<a href="#">Nx1f4p</a>	4 AXIS STEPPER CONTROLLER/INDEXER, ENCODER FEEDBACK REQUIRES 4 STEPPER DRIVES, NETWORK CONNECTED
<a href="#">Dprahir-01 5s400</a>	
<a href="#">2541</a>	RESOLVER PLS, 12 BIT, 1 RESOLVER, 6OUT/4IN
<a href="#">Dprahir-01 5a400</a>	
<a href="#">8213-Va</a>	PLS SINGLE SLOT MODULE, 12 BIT, 16 HIGH-SPEED OUTPUTS, USES RB-(X) I/O BASE AND SOLID-STATE RELAYS, NO RESOLVER. USES TIME-STAMPED BACKPLANE POSITION
<a href="#">Hmt2010000</a>	THREE RESOLVER, 10,000 TURN TRANSDUCER, 1024 COUNTS/TURN
<a href="#">2732</a>	RESOLVER PLS, 10 BIT, 2 CHANNEL, 8 OUTPUTS TOTAL, 2 SLOT MODULE
<a href="#">196206</a>	20 BIT, TWO CHANNEL, DUAL RESOLVER TRANSDUCER (90-70)
<a href="#">Htt-400-1</a>	DUAL RESOLVER, SINGLE TURN TRANS., ISOLATED RESOLVERS, 2 CONNECTORS

<a href="#">1642</a>	RESOLVER INTERFACE MODULE, 12 BIT, 2 CHANNEL, CONFIGURABLE FOR SINGLE OR MULTI-TURN, H25, HT OR HTT TRANSDUCERS
<a href="#">Nx3a2#-17</a>	RESOLVER PLS WITH 2762-17 MODULE SOFTWARE OPTION, CONTROLNET
<a href="#">2731m</a>	RESOLVER PLS, 10 BIT, 1 CHANNEL, 64 OUTPUTS, 2 SLOT MODULE
<a href="#">Nx1f4d</a>	4 AXIS STEPPER CONTROLLER/INDEXER, ENCODER FEEDBACK REQUIRES 4 STEPPER DRIVES, NETWORK CONNECTED
<a href="#">7272</a>	2 CHANNEL ENDAT 2.1 INTERFACE
<a href="#">Nx3a2p-17</a>	INDUSTRIAL NETWORK, RESOLVER PLS WITH 2762-17 MODULE SOFTWARE OPTION
<a href="#">1862</a>	MODICON QUANTUM: RESOLVER INTERFACE MODULE, 18 BIT, TWO CHANNEL, DUAL RESOLVER TRANSDUCER, 800 I/O
<a href="#">1241</a>	RESOLVER INTERFACE MODULE, 13 BIT, 1 CHANNEL
<a href="#">Nx3a2e-17</a>	INDUSTRIAL NETWORK, RESOLVER PLS WITH 2762-17 MODULE SOFTWARE OPTION
<a href="#">Ht202</a>	MULTI-TURN GEARED SINGLE RESOLVER, 2TURNS, CHECK WEBSITE FOR AVAILABLE RATIOS
<a href="#">Gn3b1-01a-00</a>	GENESIS PLS CONTROLLER, 1 RESOLVER, 6 MECHANICAL RELAYS, 2 FAULT RELAYS, AMCI PRESS CONTROL FUNCTIONS RELAYS AND SUPPRESSORS INCLUDED.
<a href="#">Sd31060ip</a>	STEPPER DRIVES- 6.0 AMP RMS (8.46 A PEAK), 310 VOLT INDEXER WITH DRIVER, 220 VAC INPUT MICRO-STEPPING. FOR ALL AMCI MOTORS
<a href="#">Iplc-1-1/J1</a>	CONTROLLER LIMIT 115VAC
<a href="#">Nx1f2p</a>	2 AXIS STEPPER CONTROLLER/INDEXER, ENCODER FEEDBACK REQUIRES 2 STEPPER DRIVES, NETWORK CONNECTED
<a href="#">Nr25xxxb2pxxx</a>	PROFIBUS DP 28 BIT MULTI-TURN ENCODER
<a href="#">8523</a>	ONE CHANNEL, THREE RESOLVER, FOR 1763 MODULE, WITH MS-20 MS-14 CONNECTORS
<a href="#">Hmt-425m2</a>	THREE RESOLVER, 10,000 TURN TRANSDUCER, CONDUIT., MICRON MOUNT
<a href="#">7961</a>	SSI INTERFACE FOR 90-70, 1 CHANNEL (90-30 PACSYSTEMS RX3I)
<a href="#">Ht-20-60</a>	TRANSDUCER
<a href="#">Sm34-450</a>	STEPPER MOTOR, SIZE 34, 450 OZ-IN, SINGLE SHAFT, 0.50 INCH SHAFT, DBL. FLAT
	MODICON QUANTUM: RESOLVER INTERFACE MODULE, 18 BIT, ONE CHANNEL, DUAL RESOLVER TRANSDUCER,

<a href="#">1861q</a>	QUANTUM
<a href="#">Nx3a2t-17</a>	INDUSTRIAL NETWORK, RESOLVER PLS WITH 2762-17 MODULE SOFTWARE OPTION
<a href="#">Nr25xxxb3pxxx</a>	PROFIBUS DP 30 BIT MULTI-TURN ENCODER
<a href="#">Gn3b1-01a-06</a>	GENESIS PLS CONTROLLER, 1 RESOLVER, 6 MECHANICAL RELAYS, 2 FAULT RELAYS, WITH SERIAL COMM., AMCI PRESS CONTROL FUNCTIONS RELAYS INCLUDED.
<a href="#">1942</a>	13 BIT, TWO CHANNEL, SINGLE RESOLVER TRANSDUCER (90-70)
<a href="#">Nr25xxxb1pxxx</a>	PROFIBUS DP 16 BIT SINGLE-TURN ENCODER
<a href="#">1761-01</a>	1761 WITH REMOTE DISPLAY OUTPUT, USE 6200 DISPLAY
<a href="#">1732h</a>	RESOLVER INTERFACE MODULE, 10 BIT, 2 CHANNEL, SINGLE SLOT
<a href="#">Sd17098i#</a>	9.8 AMP RMS (13.7 A PEAK), 170 VOLT INDEXER WITH DRIVER, MICRO-STEPPING. FOR ALL AMCI MOTORS
<a href="#">Ht-20-8</a>	RESOLVER TRANSDUCER
<a href="#">Sd31060ie</a>	STEPPER DRIVES- 6.0 AMP RMS (8.46 A PEAK), 310 VOLT INDEXER WITH DRIVER, 220 VAC INPUT MICRO-STEPPING. FOR ALL AMCI MOTORS
<a href="#">Nx2a4t-11</a>	RESOLVER INPUT MODULE 4CHANNEL MODBUS TCP/IP
<a href="#">Hmt-425m1s</a>	THREE RESOLVER, 10,000 TURN TRANSDUCER, SIDE CONN., MICRON MOUNT
<a href="#">7262</a>	2 CHANNEL SSI INTERFACE
<a href="#">Sd17060e</a>	STEPPER DRIVES- 6.0 AMP RMS (8.46 A PEAK), 170 VOLT DRIVER, ETHERNET I/P MODBUS TCP, MICRO-STEPPING, INDEXER/DRIVER
<a href="#">Nx1f2c</a>	2 AXIS STEPPER CONTROLLER/INDEXER, ENCODER FEEDBACK REQUIRES 2 STEPPER DRIVES, NETWORK CONNECTED
<a href="#">Htt-425a1s-1000</a>	DUAL RESOLVER, 1,000 TURN TRANSDUCER, MOTOR/SERVO MOUNT FOR 1326
<a href="#">2731-33</a>	RESOLVER PLS, 10 BIT, 1 CHANNEL, 8 OUTPUTS, 2 SLOT MODULE WITH BRAKE INPUT AND QUADRATIC BRAKE ADVANCE
<a href="#">7761h</a>	INTERFACE MODULE SSI 1CHANNEL
<a href="#">098804</a>	CONTROL CARD
<a href="#">8512</a>	RESOLVER PLS, 12 BIT, 8 OUT, 8 IN, HIGH-SPEED DIRECT I/O AND 16 OUT, 8 IN BACKPLANE I/O. TWO ANALOG OUTPUTS - SEE NOTE
	SINGLE RESOLVER, STAINLESS STEEL, FLANGE MOUNT, 3/8

<a href="#">H25-Fe-R3hc</a>	SHAFT W FLAT, END CONNECTOR RESOLVER, NEMA 4 RATED TO 150 DEGREES C
<a href="#">Nx3a2c-17</a>	INDUSTRIAL NETWORK, RESOLVER PLS WITH 2762-17 MODULE SOFTWARE OPTION
<a href="#">1734</a>	RESOLVER INTERFACE MODULE, 10 BIT, 4 CHANNEL