

Aep Transducers

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Aep Transducers Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Aep Transducers T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Tp12bh53r500b	TP12 TRANSDUCER 500BAR ABSOLUTE 1/4 GAS MALE OUT 4-20mA 3 WIRES WITH DIN43650 CONNECTOR
CCMA42500K3	CMAMP AMPLIFIED LOAD CELL 500KG OUT 4-20mA 2 WIRES DIAM. 42 IP67 3 METRE CABLE
TP5/BH38R 500 BAR 4-20 MA TRANSDUCERS (Zerro	
TP5/BH35R 50 BAR 4-20 MA TRANSDUCERS)	
OEG NBRCE-440-1 half wave bridge rectifier	
CCLB50KNI005	CLB 50KN BIDIRECTIONAL FORCE TRANSDUCER WITH M12 MALE CONNECTOR CLASS 00
CONNM12FV8P	M12 FLYING FEMALE 8 POLES CONNECTOR WITH 5 SHIELDED METRE AT 6 WIRES PVC 105° CABLE
CTS45M30	SPHERICAL LOADING HEAD FOR CLB 50/100KN RANGE
CTIC28	LOADING HEAD TIC28 IN AISI
CACCEM30	KNUCKLE JOINT EM30 FOR TC4-TCA-TCE-TS
CCLB600KNI00	CLB 600KN BIDIRECTIONAL FORCE TRANSDUCER WITH M12 MALE CONNECTOR
	M12 FLYING FEMALE 8 POLES CONNECTOR WITH 5 SHIELDED METRE AT

CONNM12FV8P	6 WIRES PVC 105° CABLE
CTS75M56	SPHERICAL LOADING HEAD FOR CLB 600KN
CTIC61	TIC61 LOADING HEAD FOR CLB 600KN MADE OF STAINLESS STEEL
CAT6M56	HIGH RESISTANCE JOINT WITH SMOOTH (NON THREADED) SHAFT FOR THE TENSION USE OF CLB 600KN
CKAL230750KN005	LOAD CELL KAL 750KN DIAM.230 CLASS 00 IP67 5Mt CABLE
CTIC230KAL	LOADING HEAD TIC230 IN AISI FOR KAL DIAM. 230
CBC230KAL	LOADING PLATE FOR KAL LOAD CELL 500-750-1000kN
CAT230KAL	TENSION PIVOT FOR KAL 500-750-1000kN
CCISO1M	COMPRESSION ACCESSORY ACCORDING TO ISO NORM FOR 1MN KAL DYNAMOMETER
CTISO1MA	FEMALE UPPER DRIVE SHAFT FOR KAL DIAM. 230 COMPLETE WITH BOLT AND WASHER
CTISO1MB	MALE LOWER DRIVE SHAFT FOR KAL DIAM. 230mm COMPLETE WITH BOLT AND WASHER ** REGARDING THE ACCREDIA CERTIFICATES, OUR LABORATORY CAN ISSUE AN ACCREDIA ONLY FOR CLASS 0,5 EVEN IF THE SENSORS ARE IN CLASS 00 WHILE TO HAVE THE CLASS 00 CERTIFIED WE HAVE TO SEND THE SENSORS TO I.N.R.I.M. ITALIAN NATIONAL METROLOGICAL INSTITUTE, BELOW YOU FIND THE TWO PRICES **
EMP10FK2	MP10 PLUS DIGITAL INDICATOR 10 CHANNELS 230VAC POWER SUPPLY 2000000 DIVISIONS WITH RS232 / USB OUTPUT AND REMOTE CONTROL
EMP10BK2	MP10 PLUS DIGITAL INDICATOR 2 CHANNELS 230VAC POWER SUPPLY 2000000 DIVISIONS WITH RS232/USB OUTPUT
EMP10B	MP10 PLUS DIGITAL IND 2 CHANNELS 230VAC POWER SUPPLY 200000 DIVISIONS WITH RS232/USB OUTPUT
EMP10ACCMIL7MV	CONNECTOR MIL7 POLES FLYING MALE FOR MP10
FENB2ABB	ACCREDIA CALIBRATION COMPRESSION+TENSION >10 kN ÷ 600 kN, ISO 376, 8 POINTS FOR 4 CYCLES, INCREASING AND DECREASING FORCES (CLASS 00, 0,5, 1, 2, Ucmc = 0,01% FOR RANGES UP TO 50 kN, CLASS 0,5, 1, 2, Ucmc = 0,02% FOR RANGES HIGHER THAN 50 kN)
FENB3ABB	ACCREDIA CALIBRATION COMPRESSION+TENSION >600 kN ÷ 1000 kN, ISO 376, 8 POINTS FOR 4 CYCLES, INCREASING AND DECREASING FORCES (CLASS 0,5, 1, 2, Ucmc = 0,01%)
VARIE CLB 50KN	ACCREDIA CERTIFICATE IN COMPRESSION AND TENSION ISSUED ACCORDING TO ISO 376 NORM BY INRIM FOR SENSORS CLB 50KN IN CLASS 00 COMBINED WITH MP10PLUS
VARIE CLB 600KN	ACCREDIA CERTIFICATE IN COMPRESSION AND TENSION ISSUED ACCORDING TO ISO 376 NORM BY INRIM FOR SENSORS CLB 600KN AND KAL 750KN IN CLASS 00 COMBINED WITH MP10PLUS
DFP MANOMETER 350BAR 1/2GAS	TDFP350B MALE COUPLING
TP12RBCX3R10B	RTP12 TRANSDUCER 10BAR RELATIVE 1/4 GAS MALE OUT 0-5V WITHOUT CONNECTOR **WITH DIRECT CABLE OUTPUT**ADDITIONAL COST QUOTED BELOW**
TPCAVOPVC5M	3 METERS OF PVC WIRED CABLE
TRT	CALIBRATION REPORT FOR PRESSURE TRANSDUCERS
MTRX100NM01	TRX FLANGED TORQUE METER 100Nm CLASS 0,1

MRT8100NM	
MRT8100NM	RT8 ROTATING TORQUE METER 100 Nm +/-10 Volt AMPLIFIED OUTPUT, WITHOUT CONTACT
MTRX100NM005	TRX FLANGED TORQUE METER 100Nm CLASS 0,05
CTC4AMP100KN-10V	TC4AMP LOAD CELL 100KN OUT +/-10VOLT (+10VOLT IN COMPRESSION; -10VOLT IN TENSION) DIAM.127, IP67, 5MT CABLE
EDFI2	DFI2 DIGITAL FORCE INDICATOR 2mV/V INPUT WITH USB OUTPUT AND FEEDER PLEASE NOTE THAT THE NEW DFI2 IS ALWAYS EQUIPPED WITH AN USB PORT USED TO FEED THE INTERNAL BATTERY AND TRANSFER DATA TO A PC TOO IF YOU BUY THE RS232 SERIAL OUTPUT OPTION, DATA WILL BE TRANFERRED TO THE PC THROUGH RS232 SERIAL PORT ONLY WHILE USB PORT WILL BE USED TO FFED THE INTERNAL BATTERY ONLY
SERIAL OUTPUT OPTION	ADDITIONAL COST FOR SERIAL OUTPUT OPTION
TRANSDUCER AEP TP5B/BH3XR 4-20mA 500bar	TRANSDUCER PH49481999
TRANSDUCER AEP TP5B/BH3XR 4-20mA 50 BAR	
CTC4165200KNI15	TC4 LOAD CELL 200kN CLASS 1, IP67, DIAM.165, 5MT CABLE
CTC4127100KNI15	TC4 LOAD CELL 100kN CLASS 1, IP67, DIAM.127, 5MT CABLE
CPBTC4D127	MOUNTING PLATE FOR TC4 Ø 127 IN AISI C/W BOLTS & SCREWS
CTSAMP6350K5-10V	TS-AMP AMPLIFIED LOAD CELL 50KG OUT +/-10VOLT (+10V IN TENSION -10V IN COMPRESSION) DIAM. 63 IP65 WITH M12 MALE CONNECTOR AND M12 FEMALE CONNECTOR C/W 3 MT CABLE
FT1A	
CFT1A500KC25	FT1A 500KG OIML R60 APPROVED LOAD CELL C2 CLASS IP68 WITH 5 METE CABLE AT 6 WIRES
CFT1A500KC21	FT1A 500KG OIML R60 APPROVED LOAD CELL C2 CLASS IP68 WITH 10 METRE CABLE AT 6 WIRES
TC4AMP LOAD CELL 100KN	CTC4AMP100KN-10V OUT +/-10VOLT (+10VOLT IN COMPRESSION; -10VOLT IN TENSION) DIAM.127, IP67, 5MT CABLE
CCM100K3	CM LOAD CELL 100Kg DIAM.35, IP67, 3 MT CABLE
TC 4 AMP LOAD CELL 100KN CTC4AMP100KN-1	
MTRX200NM01	TRX FLANGED TORQUE METER 200 Nm CLASS 0,1
MTRX200NM005	TRX FLANGED TORQUE METER 200 Nm CLASS 0,05
T302 (DGR P01380103 TRIAD)	
CLSC#PT1MA-50-FR420EX632656B	
TP5/BH38R 500 bar OUT 4 – 20 mA	
TP5/BH38R 50 bar OUT 4 – 20 mA	
Tp14bh53r	
Tp14bh53r700b	
Ctc4127100kni15	
Cts63100kc25	
Tp14bh51r2kb	

Tp8txm69500b	TP8 TRANSDUCER 500BAR 2mV/V 150°C FLANGED C/W SILIC. CABLE
Tp12bc53r350b	TP12 TRANSDUCER 350BAR ABSOLUTE 1/4 GAS MALE OUT 0-5 VOLT DIN 43650 CONNECTOR
Ctc41275t5	
Tidro 2kb Tcov	
Ct2020tc25	LOAD CELL T20 20TON C2 CLASS IP68 5 METERS CABLE
Epk2010a230	
Tp-14	
Cc2s8210tc25	
Mp1	
Caccem12	