

Aquametro



Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Aquametro Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Aquametro T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Vzo 4 -Re 0,00125	Art nr. 89763 -- CONTOIL® oil meter with reed pulse generator -- Pulse value 5 ml Measuring principle: ring piston Nominal pressure: PN 25 -- Nominal size: DN 4 mm with internal thread for copper pipe screw connection: 1 / 8 ' ' Installation position: horizontal / vertical Max. Flow: 80 l / h -- Continuous flow: 50 l / h Min. Flow: 1 l / h Max. Permissible temperature: 60 ° C Total quantity on roller counter: 100,000l Pulse value: 0.00125 l -- Min. Readable amount: 0.001 l Measurement deviation: 1 - 2 l / h ± 2.5% of the measured value 2 - 80 l / h ± 1% of the measured value Repeatability: </ = than: 0.2% Built-in safety filter: 0.125 mm
PMK-basic 20 4.0 190 3/4"	92504 aquabasic® cold water meter Measuring principle: multi-jet impeller Cold water meter in dry running design Thread connection: G 1 " Nominal pressure: PN 16 Installation length: 190 mm Nominal size: DN 20 Installation position: horizontal Max. Flow rate: 5 m³ / h Continuous flow: 4 m³ / h Min. Flow rate: 0.025 m³ / h Temperature max. 40 ° C Kvs value: 5.2 m³ / h Pressure loss at: 600 mbar Measuring range: R 160 Inlet section: 0 x DN 20 Outlet section: 0 x DN 20 Protection class: IP 66 Approval MI-001 Registration capacity: 100,000 m3 Min. Readable amount: 0.1 l
98276	Aquastream® M / Puls 97508 mounted / param. System module aquastream® M-Bus / Pulses including assembly and parameterization
	Characteristics: Display of total amount, Quantity resettable (up to 8 counters, 4 from resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Configurable outputs. Nominal diameter: DN 50mm Connection flanges: DN 50 Nominal

VZF II 50 FL 130/25	pressure: PN 25bar Overall length: 350mm Installation position: horizontal / vertical Temperature max .: 130 ° C Measuring range: 750 ... 30000l / h Max. Continuous flow: 20000l / h Max. Measurement deviation: ± 1% of the measured value Repeatability: ± 0.2% Registration ability: 100Mio Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analog: 4 ... 20mA Digital: pulses, frequency, logic Nominal voltage: 24V DC Supply via 4 ... 20mA: 6 ... 30V DC Protection class: IP66 / IP68 / IP69 Ambient temperature: -25 ... + 70 ° C
95593	VZF II electronics for VZF for S / N 4938017
VZO 4 -RE 0,00125	89763 CONTOIL® oil meter VZO 4-RE 0.00125 Rotary piston meter for mineral oil, with roller counter Nominal diameter: DN 4 mm Connection below: G1 / 8 "internal thread Nominal pressure: PN 25 bar Dimensions: 65 x 65 x 79 mm Installation position: horizontal / vertical Temperature max .: 60 ° C Measuring range (at Visc. 1 ... 20 mPa.s): 1 ... 80 l / h Continuous flow rate Qn max: 50 l / h Max. Error: 2.0 ... 80 l / h ± 1% 1 ... 2 l / h + 1 / -2% Repeatability: ± 0.2% Registration capacity: 100,000 l With built-in reed pulse generator RE Contact load max .: 48 V AC / DC, 50 mA, 2 VA Pulse value: 0.00125 l
VZF II 50 FL 130/25	CONTOIL® flow meter for mineral oil. Electronic counter with display. Properties: Display of total amount, Quantity resettable (up to 8 counters, 4 from resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Configurable outputs. Nominal diameter: DN 50mm Connection flanges: DN 50 Nominal pressure: PN 25bar Overall length: 350mm Installation position: horizontal / vertical Temperature max .: 130 ° C Measuring range: 750 ... 30000l / h Max. Continuous flow: 20000l / h Max. Measurement deviation: ± 1% of the measured value Repeatability: ± 0.2% Registration ability: 100Mio Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analog: 4 ... 20mA Digital: pulses, frequency, logic Nominal voltage: 24V DC Supply via 4 ... 20mA: 6 ... 30V DC Protection class: IP66 / IP68 / IP69 Ambient temperature: -25 ... + 70 ° C
vz020	
VZO 15 RC 130/16	Item No.: 92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max flow: 600 l/h Continuous flow: 400 l/h Minimum flow: 20 l/h Max. allowed temperature: 130°C Amount total on roller counter: 1'000'000 l Minimum readable volume: 0.01 l Deviation: 20 - 600 l/h ± 1% of the measured value Repeatability:
VZO 15 RC 130/16	Artikelnr.: 92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max flow: 600 l/h Continuous flow: 400 l/h Minimum flow: 20

	<p>l/h Max. allowed temperature: 130°C Amount total on roller counter: 1'000'000 l Minimum readable volume: 0.01 l Deviation: 20 - 600 l/h ± 1% of the measured value Repeatability:</p>
VZO 4 -RE 0,00125	<p>Item No.: 89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max flow: 80L/h Continuous flow: 50 l/h Minimum flow: 1 l/h Max. allowed temperature: 60°C Amount total on roller counter: 100'000l Pulse value: 0.00125 l Minimum readable volume: 0.001 l Deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm</p>
VZF II 25 RC 130/16	<p>Item No.: 95535 CONTOIL® flow meter for mineral oil. Electronic counter with display. Characteristics: display of amount total, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, temperature, mass and normalized volume in m³, liters, US gallons or tons, kilograms and pounds. Configurable outputs. Nominal diameter: DN 25mm Thread connection device: 1 1/4" Screw connection pipe 1" Nominal pressure: PN 16bar Length: 190mm Installation position: horizontal / vertical Maximum temperature: 130°C Measuring range: 75...3000l/h Max. continuous flow: 2000l/h Max. error of measurement: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analogue and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: - 25...+70°C</p>
AM Viscomaster Dynamic	<p>HFVM11L729HNC3FJREZZZ 95431 Heavy Fuel Viscosity Meter Viscomaster 1 Sensor Range And Performance: Viscosity accuracy ±0.2cP (0-10cP range) then ± 1% FS of calibrated range, Viscosity limit 20,000cP 1 Immersion depth: 0mm: no stem extension and with standard spigot L Wetted parts: 316L Stainless, Diamond Like Carbon coated tines 729 Process connection: 1 1/2-inch Cone Seat Compression fitting 316/316L H Calibration: 2 1/2-inch schedule 40 boundary (Viscosity limits 200cSt=T piece) N Transmitter Housing Option: AquaMetro REDUCED FUNCTIONALITY version (red + Aquametro label) C Output signal: Integral transmitter, channel A = mA + HART, Channel B = mA output, Channel C = RS485 Modbus 3 Indicator: No F Ex approval ATEX flameproof J Application Configuration: Line Viscosity; [4mA=0cSt, 20mA=50cSt] R Calibration range: 5 to 50cP viscosity calibration only, no density calibration) E Language: English inst. Manual config and English. manual Z Future Option 1: Reserved for future options Z Cable entries: 1/2" NPT Z Factory option: Standard product 200966</p>
VC322 Viscosity Controller Step	<p>Art. Nr.: 200973 3-point-step-controll digital universal controller Dimension:96x96 mm Supply: 100..250V AC Input: -viscosity (4-20mA) 0-50cSt -temperature (4-20mA) 0-200 °C Input switchable Output: -2 analog (1 Visco & 1 Temp) -2 relay outputs</p>

VZO 4 -RE 0,00125	89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max flow: 80L/h Continuous flow: 50 l/h Minimum flow: 1 l/h Max. allowed temperature: 60°C Amount total on roller counter: 100'000l Pulse value: 0.00125 l Minimum readable volume: 0.001 l Deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm
VZO 15 RC 130/16	92041 CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 16 Overall length: 165 mm Nominal width: DN 15 mm with thread 3/4" for screw connections: 1/2" Installation position: horizontal/vertical Max. flow: 600 l/h Continuous flow: 400 l/h Min. flow: 20 l/h Max. permissible temperature: 130°C Quantity total on roller counter: 1,000,000 litres Min. readable quantity: 0.01 l Measuring deviation: 20 - 600 l/h ± 1% of the measured value
VZO 4 -RE 0,00125	Item number: 89763 CONTOIL® oil meter with reed pulse generator Pulse value 1.25 ml Measuring principle: ring piston Nominal pressure: PN 25 Nominal width: DN 4 mm with internal thread for copper pipe fitting: 1/8" Installation position: horizontal/vertical Max. flow: 80 l/h Continuous flow: 50 l/h Min. flow: 1 l/h Max. permissible temperature: 60°C Quantity total on roller counter: 100,000l Pulse value: 0.00125 l Min. readable quantity: 0.001 l Measuring deviation: 1 - 2 l/h ± 2.5% of the measured value 2 - 80 l/h ± 1% of the measured value Repeatability: Built-in safety filter: 0.125 mm
VZF II 40 FL 130/25	Item no.: 95544 CONTOIL® flow meter for mineral oil. Electronic counter with display. Characteristics: Display of total quantity, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Parameterizable outputs. Nominal diameter: DN 40mm Connection flanges: DN 40 Nominal pressure: PN 25bar Length: 300mm Installation position: horizontal / vertical Temperature max.: 130°C Measuring range: 225...9000l/h Max. continuous flow: 6000l/h Max. measurement deviation: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: - 25...+70°C
	Item no.: 95512 CONTOIL® flow meter for mineral oil. Electronic counter with display. Characteristics: Display of total quantity, Quantity resettable (up to 8 counters, 4 of resettable), flow rate, Temperature, mass and normalized volume in m3, liters, US gallons or tons, Kilograms and pounds. Parameterizable outputs. Nominal diameter: DN 20mm Connection flanges: DN 20 Nominal pressure: PN

VZF II 20 FL 130/25	25bar Length: 165mm Installation position: horizontal / vertical Temperature max.: 130°C Measuring range: 40...1500l/h Max. continuous flow: 1000l/h Max. measurement deviation: ±1% of the measured value Repeatability: ±0.2% Registration capacity: 100 million Display LCD: 8 digits 8mm high Outputs: 1 analog and 2 digital Analogue: 4...20mA Digital: pulses, frequency, logic Rated voltage: 24V DC Supply via 4...20mA: 6...30V DC Protection class: IP66/IP68/IP69 Ambient temperature: -25...+70°C
80113 / 2017	Nachfolgermodell Aquastream® M/Puls 97508
83552 Rw/Rd 25	
94252 Pmgf 32-Rh1 5.0 150 1 1/4quot;	
In0,1/Rw/Rd 25 83561	
89216,Topas Pmw -	
Pmg 32-Ih (6.0 260 1 1/4quot;)	
Ard15/3315-H3/0	
Ard 20/1221-H2 -In0,1/Rw/Rd 20	
Pmw 32 02b	
Vzo 8 (92630)	
94793	
Art.No. 83527 Rv1/Rd 20	
94588	
Vzo 15 Rc 130/16-Rv0,1	
Vzo 40 Fl 180/25	
Art.No. 92048 Vzo 20 Rc 130/16-Rv1	
94525 50 50 200	
92049 Vzo 20 Fl 130/25	
Vzo-15	
Type:7829 Ennajrhba, Ser No=296865 By Hfvm111729hnc3fjrezzz (95431)	
81153.	
Vz020	
80113	
12886	
4	

80695	
89629 Topas Pmg -	
1	
Ard 20/1221-H2	
93533	
P/N 92280, VzF 50 FI 180/25	
Vzf25fl130/25	
Od03	
94606	
83565 In0,1h/Rw/Rd 25	
Vzo 4 - Re 0,1	
16028	
89654 Topas Pmgf -	
92630 Vzo 8	CONTOIL® oil meter Measuring principle: ring piston Nominal pressure: PN 25 Overall length with PS set: 130 mm Nominal diameter: DN 8 mm with internal thread for copper pipe fitting 1 / 4" Installation position: horizontal / vertical Max. Flow: 200 l / h Continuous flow: 135 l / h Min. Flow: 4 l / h Max. Permissible temperature: 60 ° C Lot totally on roller counter: 1'000'000 l Min. Readable quantity: 0.01 l Bias: 4 - 5 l / h ± 2% of the measured value 5 - 200 l / h ± 1% of the measured value Repeatability: </ = as: 0.2% Built-in safety filter: 0.150 mm
93763	
Vzo 25 Rc 130/16-Rv1	
083509	
Art.No. 92041, Vzo 15 Rc 130/16	
13199	
96167	
96158	
Dip 406 A1/R/Tor/2	
Ard 251222-G6+ip1rwr25	
81169	
Tmc19321	

(83526) Rw/Rd 20
94525
13018
P/N 94101
Vzo 40 Fl 130/25
89224 Topas Pmwf -
Art.No. 92042 Vzo 15 Rc 130/16-Rv0,1
94609
Rw/Rd 20
80522.
12795 Kolben Graphit Rd 25
Vzo 25 Rc 130/16
94249
Vzfa25 Rc130/16
Vzo 20 Fl 130/25-In0,01 91903
89642 Topas Pmgs -
92503 Pmk-Basic 15 2.5 165 1/2quot;
13021
Vzo 4-Re
09190200
P/N: 89763 Vzo 4 -Re 0,00125
89771 Vzo 8 -Re0,0125
94604
P/N: 92041 Type: Vzo 15 Rc 130/16
(83037) Ard 20/1221-A2
80113 Aquapuls 1 L
Ard25/1112-P6-Ina/Rw/Rd25
12985
Art.No. 80113 Aquapuls 1l
P/N: 92680 Type: Vzo 4

94600
83099 Ard 25/3315-G6
P/N: 80695 Type: M-Bus Mini-Master
Hfvm111729hnc3fjrezzz (95431)
94608
89252 Topas Pmwf -
Vzo 20 Rc 130/16
94606 Pmwf-Basic 32 10. 150 1 1/4quot;
13020
92050 (Vzo 20 Fl 130/25-Rv1)
92047 Vzo 20 Rc 130/16
81152
96166.
3
40251
89270;Topas Pmws -
Vzo50fl-130/25
2
Vcs04
Ard25/1112-P7-Dn25-Pn16
94255
96112
Wpd80+od01
94607
8356900
83509
Ard25/1112-P6-Dn25-Pn16
P/N: 89763 Type: Vzo 4 -Re 0,00125
89206 Topas Pmw 32-Rh1 Obsolete, Replaced By 94249 And 96158
89763

92059
94530
Sj35n
30-10000 Lt/H-3/4quot;
Vz025
Aquametro-96166-Ce-Pr3;Fung- Wasserzö;Hler-R49-Dn15-32-Istanbul- Turkiye
Pmd 20 -Gtas - 84025
96044
Contoil Vzo 20 Rv By 92050 (Vzo 20 FI 130/25-Rv1)
89206 Topas Pmw -
83031
92059 Vzo 25 FI 130/25
89244 Topas Pmwf -
81151