



## Arca Regler

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Arca Regler** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Arca Regler T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Typ 824.E110-003</a>	electro-pneumatic positioner Input 4-20mA Plastic hood IP54 simple acting Cable bushing M20x1.5 Air connection G1/4 with position transmitter 3-wire for stroke >= 20mm
<a href="#">Arca Regler</a>	
<a href="#">Arca Regler</a>	
<a href="#">827A.E2-000-M10-G</a>	Intelligent positioner Input 4-20 mA, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 Type 827A.E2-000-M10-G Intelligent positioner Input 4-20 mA, 2-wiring Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4
<a href="#">827A.E2-A00-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP 66 single acting with analog module, feedback signal 4 to 20 mA Cable gland M20x1.5 Air connection G 1/4 Type 827A.E2-A00-M10-G Smart Positioner Input 4-20mA, 2-wiring Metal housing IP 66 single acting Cable gland M20x1.5 Air connection G 1/4 with analog module
	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 Single-acting Cable gland M20x1.5 Air

<a href="#">827A.E2-0B0-M10-G</a>	connection G1/4 with binary module Type 827A.E2-0B0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 Cable gland M20x1.5 Air connection G1/4 with binary module
<a href="#">827A.E2-0S0-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting with SIA module 2 inductive slot initiators Cable gland M20x1.5 Air connection G1/4 Type 827A.E2-0S0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiator
<a href="#">827A.E2-AB0-M10-G</a>	Intelligent positioner Input 4-20 mA, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with analog module, with feedback sensor 4-20 mA with binary module, with electronic limit switch Type 827A.E2-AB0-M10-G Intelligent positioner Input 4-20 mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5
<a href="#">827A.E2-AS0-M10-G</a>	Intelligent positioner Input 4-20mA, without Ex 2-wire connection Metal housing IP66 single acting with analog module, feedback 4 to 20 mA with slot initiators 2 inductive proximity switches Cable gland M20x1.5 Air connection G1/4 Type 827A.E2-AS0-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting with analog module, feedback 4-20mA with SIA module, slot initiator Cable gland M20x1.5 Air connection G1/4
<a href="#">827A.E2-00H-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with HART module Type 827A.E2-00H-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with HART module
<a href="#">827A.E2-A0H-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module, feedback signal 4-20mA with HART module Type 827A.E2-A0H-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with HART module
<a href="#">827A.E2-0BH-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with binary module with HART module Type 827A.E2-0BH-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with binary module with HART module
<a href="#">827A.E2-0SH-M10-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiators with HART module Type 827A.E2-0SH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with slot initiator with HART module
	Intelligent positioner Input 4-20mA, 2-wire connection Metal

<a href="#">827A.E2-ABH-M10-G</a>	housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with binary module with HART module Type 827A.E2-ABH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with binary module with HART module
<a href="#">827A.E2-ASH-M10-G</a>	Type 827A.E2-ASH-M10-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module, feedback sensor 4-20 mA with SIA module, 2 slot initiators, with HART module Type 827A.E2-ASH-M10-G Intelligent positioner Input 4-20mA, 2-wiring Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 with analog module with slot initiator with HART module
<a href="#">827A.E2-00P-M10-G</a>	Intelligent positioner Input digital, 2-wire connection Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with Profibus Type 827A.E2-00P-M10-G Intelligent positioner Input digital, 2-wiring Metal housing IP 66 single acting Cable gland M 20x1.5 Air connection G 1/4 with Profibus
<a href="#">827A.E2-000-M12-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer Type 827A.E2-000-M12-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer
<a href="#">827A.E2-00H-M12-G</a>	Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer with HART module Type 827A.E2-00H-M12-G Intelligent positioner Input 4-20mA, 2-wire connection Metal housing IP66 single acting Cable gland M20x1.5 Air connection G1/4 for external potentiometer with HART module
<a href="#">2101860 Diaphragm, Membrane, Mfi</a>	
<a href="#">827a.X2-Ab0-M10-G</a>	
<a href="#">2174647</a>	
<a href="#">1059110</a>	
<a href="#">2257141</a>	