

Arcol



Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Arcol Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Arcol T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
HS400 100R 5%(J)	Wire resistor in aluminum housing Resistance: 100 ohms Tolerance: $\pm 5\%$ (J) Rated power: 400 watts Nominal voltage: 2,000 V Temperature coefficient: $\pm 150\text{ppm} / \text{K}$ Dimensions (W x H x L): 55.0 x 30.0 x 182.0 mm Connection: solder lugs RoHS (*): Compliant
220164	
220190	
220610	
220630	
220646	
AP836 47R 5%(J)	
FPA100-100RJ	
FPA100-10RJ	
FPA100-1KJ	
FPA600 5K0 5%(J)	
HS 100 1R5	
HS100 2R2 J	
HS100 47R J	
HS100-1KJ	
HS50 4K7 F	
MRA0207 1M B 15PPM TA	

NHS100 E6 100R 5%(J) M193	
RESISTOR HS25 - 2,05 OHM	
RESISTOR HS25 - 5,11 OHM	
RESISTOR HS25 - 8,25 OHM	
HS300 220R 5%(J)	Resistance:220 Ohm Tolerance:±5% (J) Rated capacity:300 Watt Nominal voltage:2500 V Temperature coefficient: ±100ppm/K Dimensions (W x H x L):72.5 x 41.8 x 127.7 mm Connection:screw terminals RoHS (*):Konform
WD300 220R 5% (J)	Resistance:220 ohms Tolerance:±5% (J) Rated capacity:300 watts Nominal voltage:2500V Temperature coefficient: ±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
220981/ HS10 10R 1%(F)	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:10 watts Nominal voltage:160v Temperature coefficient:±100ppm/K Dimensions (W x H x L):16.5 x 8.8 x 15.9mm Connection:solder lugs RoHS (*):Compliant
WD300 220R 5% (J)	Wire resistor in aluminum housing Resistance:220 ohms Tolerance:±5% (J) Rated capacity:±5% (J) Nominal voltage:2500V Temperature coefficient:±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
161227 -WD5 10R 1%(F)	Wire resistor in aluminum housing Resistance: 10 ohm Tolerance: ±1% (F) Rated capacity: 10 watts Nominal voltage: 160v Temperature coefficient: ±60ppm/°C Dimensions (W x H x L): 17.0 x 9.0 x 16.8mm Connection: solder plugs RoHS (*):Compliant
160348 - WD10 10R 1% (F)	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:15 watts Nominal voltage:260V Temperature coefficient:±60ppm/°C Dimensions (W x H x L):21.0 x 11.0 x 20.1mm Connection:solder lugs RoHS (*):Compliant
C300K20RE	
C300K16RE	
6126P-8 1-2E	
Hs50 30r J	
220324	
V5 39r 5%(J)	
Hs50 50k J	
Ordering Code: Hs100 10r J	
Hs100 100r J	

Hs200 20r 1%(F)
Fpa100-100rj Widerstand 100 Ohm / 100 W
08.14 Hs 100 R47 J
Resistor Hs25 - 2,05 Ohm
Hs300hv/50r
Hs100 10r J
Hs100 150r J
Wd25 47r
Hs100-1kj Widerstand 1 Kohm / 100w
Hs200 330r F
220085
220316
220289
Nhs100 4k7 5%(J)
300w 75r 5
Hs100-100rj Widerstand 100 Ohm / 100 W
220317
Fpa100-1kj Widerstand 1 Kohm / 100w
220925
Hs 25 3k9j
Ap836 100r 1%(F) Leistungswiderstand
220911
220508
Hs150 150r 1%(F) (Pack 1x25)
Hs 100rs2,2,10 Ohm
Hs100 15r
Eg-V314/Vi
Typ Hs100 47r J
284-Hs50-0.27 Mfr Pn: Hs50 0r27 5% 50w 0.27 Ohm 5%

220318	
Resistor Hs25 - 5,11 Ohm	
Ap836 100r 1%(F)	
220266	
Fpa100-10rj Widerstand	
Hs100 2r2 J Widerstand	
Hs100 1r5 5%(J)	Wirewound resistor in aluminum housing Resistance: 1.5 ohms ohms Tolerance: ± 5% (J) Rated power: 100 watts watts Rated voltage: 1,900 V Temperature Coefficient: ± 100ppm / K Dimensions (W x H x L): 47.5 x 24.1 x 65.2 mm Connection: solder lugs Customs tariff number: 85332900 Country of origin: Great Britain and Northern Ireland Weight: 0.11 kg Manufacturer Part Number: HS100 1R5 J
Hs10 120r J	
Hs50-10rj	
08 14 Hs 100 R47 J	
Hs50 270r	
220916	
Hs150 75r F	
Hs300 10r 5% (J)	
Resistor Hs25 - 8,25 Ohm	
Hs50 820r 5%(J)	
Acs10s 47r J	
Hs25 R01 J Hs25 0r01 10%(K) And Wd25 0r01 5% (J)	
Wd25 0r01 5% (J)	
Hs200 150r 1%(F) (Pack 1x10)	
220275	
220463	
Hs-100	
300w 75r -5	
Hs50 220r J	
000.001.800	
Hs10 5k6 5%(J)	

Hs300 220r 1%(F) (Pack 1x10)
V5a 18r J
000.000.220
000.001.800 Resistor
Hs50 47r J
Hs200 470r F
Sirvibc100doh9
Hs150 33r 5%(J)
Resistor Hs25 - 12,1 Ohm
Hs50
Hs50 10r 1%
Hs25 0r01 10%(K)
V5a 39r J
Hs 15 10kj
15 Ohm 200w +-5% Hs200 15 R J
V5 18r 5%(J)
Hs25-47rj, By Wd25 47r
Hs25 3k9 J
220274
000.000.220 Resistor
7cs 47r J
Hs25-22r-J
Ap851 25r J 100ppm
Fpa250 10r J
Hs 50 1kj
000.000.047
Hs300 1r8
220253
Acs10s 47r J
000.000.047 Resistor

[Hs150_150r_F](#)

[Hs25_100r_F](#)

[Msr1r005f](#)