

## Arcol



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Arcol** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Arcol Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">HS400 100R 5%(J)</a>	Wire resistor in aluminum housing Resistance: 100 ohms Tolerance: $\pm 5\%$ (J) Rated power: 400 watts Nominal voltage: 2,000 V Temperature coefficient: $\pm 150\text{ppm} / \text{K}$ Dimensions (W x H x L): 55.0 x 30.0 x 182.0 mm Connection: solder lugs RoHS (*): Compliant
<a href="#">220164</a>	
<a href="#">220190</a>	
<a href="#">220610</a>	
<a href="#">220630</a>	
<a href="#">220646</a>	
<a href="#">AP836 47R 5%(J)</a>	
<a href="#">FPA100-100RJ</a>	
<a href="#">FPA100-10RJ</a>	
<a href="#">FPA100-1KJ</a>	
<a href="#">FPA600 5K0 5%(J)</a>	
<a href="#">HS 100 1R5</a>	
<a href="#">HS100 2R2 J</a>	
<a href="#">HS100 47R J</a>	
<a href="#">HS100-1KJ</a>	
<a href="#">HS50 4K7 F</a>	
<a href="#">MRA0207 1M B 15PPM TA</a>	

<a href="#">NHS100 E6 100R 5%(J) M193</a>	
<a href="#">RESISTOR HS25 - 2,05 OHM</a>	
<a href="#">RESISTOR HS25 - 5,11 OHM</a>	
<a href="#">RESISTOR HS25 - 8,25 OHM</a>	
<a href="#">HS300 220R 5%(J)</a>	Resistance:220 Ohm Tolerance:±5% (J) Rated capacity:300 Watt Nominal voltage:2500 V Temperature coefficient: ±100ppm/K Dimensions (W x H x L):72.5 x 41.8 x 127.7 mm Connection:screw terminals RoHS (*):Konform
<a href="#">WD300 220R 5% (J)</a>	Resistance:220 ohms Tolerance:±5% (J) Rated capacity:300 watts Nominal voltage:2500V Temperature coefficient: ±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
<a href="#">220981/ HS10 10R 1%(F)</a>	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:10 watts Nominal voltage:160v Temperature coefficient:±100ppm/K Dimensions (W x H x L):16.5 x 8.8 x 15.9mm Connection:solder lugs RoHS (*):Compliant
<a href="#">WD300 220R 5% (J)</a>	Wire resistor in aluminum housing Resistance:220 ohms Tolerance:±5% (J) Rated capacity:±5% (J) Nominal voltage:2500V Temperature coefficient:±30ppm/°C Dimensions (W x H x L):73.0 x 45.0 x 127.0mm Connection:screw terminals RoHS (*):Compliant
<a href="#">161227 -WD5 10R 1%(F)</a>	Wire resistor in aluminum housing Resistance: 10 ohm Tolerance: ±1% (F) Rated capacity: 10 watts Nominal voltage: 160v Temperature coefficient: ±60ppm/°C Dimensions (W x H x L): 17.0 x 9.0 x 16.8mm Connection: solder plugs RoHS (*):Compliant
<a href="#">160348 - WD10 10R 1% (F)</a>	Wire resistor in aluminum housing Resistance:10 ohms Tolerance:±1% (F) Rated capacity:15 watts Nominal voltage:260V Temperature coefficient:±60ppm/°C Dimensions (W x H x L):21.0 x 11.0 x 20.1mm Connection:solder lugs RoHS (*):Compliant
<a href="#">C300K20RE</a>	
<a href="#">C300K16RE</a>	
<a href="#">6126P-8 1-2E</a>	
<a href="#">Hs50 30r J</a>	
<a href="#">220324</a>	
<a href="#">V5 39r 5%(J)</a>	
<a href="#">Hs50 50k J</a>	
<a href="#">Ordering Code: Hs100 10r J</a>	
<a href="#">Hs100 100r J</a>	

<a href="#">Hs200 20r 1%(F)</a>
<a href="#">Fpa100-100rj Widerstand 100 Ohm / 100 W</a>
<a href="#">08.14 Hs 100 R47 J</a>
<a href="#">Resistor Hs25 - 2,05 Ohm</a>
<a href="#">Hs300hv/50r</a>
<a href="#">Hs100 10r J</a>
<a href="#">Hs100 150r J</a>
<a href="#">Wd25 47r</a>
<a href="#">Hs100-1kj Widerstand 1 Kohm / 100w</a>
<a href="#">Hs200 330r F</a>
<a href="#">220085</a>
<a href="#">220316</a>
<a href="#">220289</a>
<a href="#">Nhs100 4k7 5%(J)</a>
<a href="#">300w 75r 5</a>
<a href="#">Hs100-100rj Widerstand 100 Ohm / 100 W</a>
<a href="#">220317</a>
<a href="#">Fpa100-1kj Widerstand 1 Kohm / 100w</a>
<a href="#">220925</a>
<a href="#">Hs 25 3k9j</a>
<a href="#">Ap836 100r 1%(F) Leistungswiderstand</a>
<a href="#">220911</a>
<a href="#">220508</a>
<a href="#">Hs150 150r 1%(F) (Pack 1x25)</a>
<a href="#">Hs 100rs2,2,10 Ohm</a>
<a href="#">Hs100 15r</a>
<a href="#">Eg-V314/Vi</a>
<a href="#">Typ Hs100 47r J</a>
<a href="#">284-Hs50-0.27 Mfr Pn: Hs50 0r27 5% 50w 0.27 Ohm 5%</a>

<a href="#">220318</a>	
<a href="#">Resistor Hs25 - 5,11 Ohm</a>	
<a href="#">Ap836 100r 1%(F)</a>	
<a href="#">220266</a>	
<a href="#">Fpa100-10rj Widerstand</a>	
<a href="#">Hs100 2r2 J Widerstand</a>	
<a href="#">Hs100 1r5 5%(J)</a>	Wirewound resistor in aluminum housing Resistance: 1.5 ohms ohms Tolerance: ± 5% (J) Rated power: 100 watts watts Rated voltage: 1,900 V Temperature Coefficient: ± 100ppm / K Dimensions (W x H x L): 47.5 x 24.1 x 65.2 mm Connection: solder lugs Customs tariff number: 85332900 Country of origin: Great Britain and Northern Ireland Weight: 0.11 kg Manufacturer Part Number: HS100 1R5 J
<a href="#">Hs10 120r J</a>	
<a href="#">Hs50-10rj</a>	
<a href="#">08 14 Hs 100 R47 J</a>	
<a href="#">Hs50 270r</a>	
<a href="#">220916</a>	
<a href="#">Hs150 75r F</a>	
<a href="#">Hs300 10r 5% (J)</a>	
<a href="#">Resistor Hs25 - 8,25 Ohm</a>	
<a href="#">Hs50 820r 5%(J)</a>	
<a href="#">Acs10s 47r J</a>	
<a href="#">Hs25 R01 J Hs25 0r01 10%(K) And Wd25 0r01 5% (J)</a>	
<a href="#">Wd25 0r01 5% (J)</a>	
<a href="#">Hs200 150r 1%(F) (Pack 1x10)</a>	
<a href="#">220275</a>	
<a href="#">220463</a>	
<a href="#">Hs-100</a>	
<a href="#">300w 75r -5</a>	
<a href="#">Hs50 220r J</a>	
<a href="#">000.001.800</a>	
<a href="#">Hs10 5k6 5%(J)</a>	

<a href="#">Hs300 220r 1%(F) (Pack 1x10)</a>
<a href="#">V5a 18r J</a>
<a href="#">000.000.220</a>
<a href="#">000.001.800 Resistor</a>
<a href="#">Hs50 47r J</a>
<a href="#">Hs200 470r F</a>
<a href="#">Sirvibc100doh9</a>
<a href="#">Hs150 33r 5%(J)</a>
<a href="#">Resistor Hs25 - 12,1 Ohm</a>
<a href="#">Hs50</a>
<a href="#">Hs50 10r 1%</a>
<a href="#">Hs25 0r01 10%(K)</a>
<a href="#">V5a 39r J</a>
<a href="#">Hs 15 10kj</a>
<a href="#">15 Ohm 200w +-5% Hs200 15 R J</a>
<a href="#">V5 18r 5%(J)</a>
<a href="#">Hs25-47rj, By Wd25 47r</a>
<a href="#">Hs25 3k9 J</a>
<a href="#">220274</a>
<a href="#">000.000.220 Resistor</a>
<a href="#">7cs 47r J</a>
<a href="#">Hs25-22r-J</a>
<a href="#">Ap851 25r J 100ppm</a>
<a href="#">Fpa250 10r J</a>
<a href="#">Hs 50 1kj</a>
<a href="#">000.000.047</a>
<a href="#">Hs300 1r8</a>
<a href="#">220253</a>
<a href="#">Acs10s 47r J</a>
<a href="#">000.000.047 Resistor</a>

[Hs150\\_150r\\_F](#)

[Hs25\\_100r\\_F](#)

[Msr1r005f](#)