

Ari Armaturen

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Ari Armaturen Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Ari Armaturen T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Figur 45.601 DN 15	ARI-CONA B Bimetal condensate drain with external screen DN 15 Nominal pressure: PN 40 Material: 1.0460 Connection type: threaded socket Connection type input: threaded socket Rp 1/2 Type of connection output: threaded socket Rp 1/2 Overall length (mm): 95 Controller: R32 PS 1 (bar): 32 bar TS 1 (° C): 250 ° C TS 2 (° C): 450 ° C PS 2 (bar): 14.5 bar Differential pressure (bar): 32 bar
THRUST ACTUATOR type ARI-PREMIO-PLUS	(YOKE VERSION) 2,2-5 kN 4.3.3.PART LIST: Board Support 50.138
THRUST ACTUATOR type ARI-PREMIO-PLUS	(YOKE VERSION) 2,2-5 kN 4.3.3.PART LIST: Trip Slide 50.141
ES11 230VAC Positioner	
TYP:23.470+SINGLE	
ARI-PREIO Type 5 KN , 230 V 60 Hz	
0254000013	Positioner ES11 230VAC
DN15 PN16	
ARI PREMIO 2,2 KN ELEKTRIC THRUST ACTUATOR	4-20 MA OUTPUT,POWER 220 VAC-60HZ
ARI STEVİ 440 CONTROL VALVE - GLOB TYPE DN25 PN16	BODY ENGJL250,CLAP 1.4021(STAINLESS),PTFE SEALING

911410030G191	Electric thrust Ari-Premio-Plus 2G Electric thrust Ari-Premio-Plus 2G 25kn Data sheet: 000033-1.pdf Operating instructions: 0040501007-1.PDF Discount group: I11 Tension: 100-240V AC 50-60Hz Actual speed: 0.38mm/sec Performance: 132Sec Spindle overhang: 83mm Cup: thread M16 Valvor hub: hub 50mm Control: 4-20mA DC Switch outputs: with a relay card Position detector: Analog output map (y out) Heating resistance: 230V 50/60Hz, 15 watts LED status display: Yes
SEAL FOR EQUALIZING VALVE FLAP	4-00584-B2-BF-TCS-ME-SAS-0049,Resim Poz No: ITEM 2
EQUALIZING VALVE FLAP & LEVER	4-00584-B2-BF-TCS-ME-SAS-0049
EQUALIZING VALVE SEAT	4-00584-B2-BF-TCS-ME-SAS-0050
SET OF SEALS FOR DRIVE UNIT	4-00584-B2-BF-TCS-ME-SAS-0047,Resim Poz No: ITEM 3
SECONDARY EQUALIZING VALVE	4-00584-B2-BF-TCS-PO-PID-0002
SECONDARY EQUALIZING VALVE	4-00584-B2-BF-TCS-PO-PID-0002
SOLENOID VALVE FOR SECONDARY EQUALIZING	4-00584-B2-BF-TCS-PO-PID-0006
FLOW CONTROL VALVE	4-00584-B2-BF-TCS-PO-PID-0002
259020080 ARI-SAFE	Full lift safety valve D/G with flanges Fig. ...902 Open lifting device, open bonnet DN 80/125 Set pressure, bar: 16,1 Nominal pressure: PN 40/16 Flanges: DIN PN40 / PN 16 Input: DIN PN40 Output: DIN PN16 Material: EN-JS1049
ARI-PREMIO-Plus 2G TYPE:5,0kN	DN 50
ARI-FABA-Plus 35040	DN150 globe valve metal bellow // UIF code: 505BDGB_150
FABA-Plus 52046	500AHHB_150
RI21 230VAC	0277000032 position indicator
ES11 230VAC	0254000013 position indicator
0389020086	Rollmembran DP34 NBR 800cm ²
PREMIO 2.2 KN PROPORTIONAL VALVE	
Set of chevron cuffs 0490010156	
V-ring PTFE 0490010159	
Repair kit set	
0490000302	Shift carriage unit PREMIO 2.2- 5.0kN
Type: 2,2 kN	3" THREE-WAY AUTOMATIC CONTROL VALVE
0490000071	Board carrier PREMIO complete 2.2-5.0kN BLDC / ESP
Filter dn 150 pn 16 jl1040	
Figur 25.902 DN 25	ARI-SAFE Full-lift safety valve with flanges - open hood - open lift - according to VdTV leaflet 100, AD2000-A2 and EN ISO 4126-1 Open hood/open lift TV.SV.22-663.D/G EN-JS1049 DN 25/ 40 Data sheet: 900005-1.pdf Operating instructions: 0040401000-1.pdf Discount group: I91 Setting pressure (bar g): 10.4 Pressure range (bar): > 9.0 - 16.0 Nominal pressure: PN 40 Flange bore: DIN PN40/PN16 Inlet according to DIN PN40 Outlet according to DIN PN16 Acceptance final test: TV setting certificate
	ARI-STEVI 405 Shut-off valve in straight-through form with flanges EN- JL1040 DN150 Data sheet: 405001-1.pdf Operating instructions: 0040304000-1.pdf Discount group: I51 Nominal pressure: PN 16 Flange bore: according to DIN PN16 Spindle seal: V-rings/PTFE graphite Drive:

Figur 12.405 DN 150	DP34 Effective force (with pneumatic drive): spring opens when air fails Spring range (bar)/stroke (mm): 0.20-0.80 stroke 38mm req. Control pressure (bar): 3.5 bar Max. permissible control pressure (bar): 5.5 Max. closing pressure (bar): 9.2 Spacer column length: L1=228mm Spacer column spacing: 100mm Coupling: Thread M16x1.5
DP34-22G192	Pneumatic actuator DP Pneumatic actuator DP 34 Column diameter 22mm Data sheet: 000003-1.pdf Operating instructions: 0040504000-1.pdf Discount group: I11 Drive: DP34 Effective force (for pneumatic actuator): Spring opens when air fails Valve function: Through-flow operation Spring range (bar)/stroke (mm): 0.20-0.80 stroke 38mm Max. permissible actuating pressure (bar): 6 Distance column length: L1=228mm Distance column spacing: 100mm Coupling: Thread M16x1.5
5,0 KN (90-264VAC)	
Figur 55.470 DN 100	ARI-STEVI 470/422 Straight-through control valve with flanges and shaft-guided cone 1.4581 DN100 Data sheet: 470001-1.pdf Operating instructions: 0040305000-1.pdf discount group: I11 Nominal pressure: PN 16 Flange bore: according to DIN PN16 Cone design: Parabolic cone Kvs value: 160 Characteristic curve: equal percentage spindle seal: EPDM Exterior treatment: unpainted Actuator: AUMA Drive type: SAR 07.2 Type: Automatic AC Design: Non Intrusive with MWG Voltage: 400V/50Hz Current type: 3PH three-phase current torque to be set: DL 30Nm / DSR 30Nm max.dp shut-off (bar): 16 max.dp control operation (bar): 9 Output speed: 5.6 1/min Valve lift: 30mm stroke Coupling: Thread M16x1.5 Actuating time: 80.4sec Connection flange: F10 DIN ISO 5210 Connection type: Connection type A Connection thread: TR20x4 Signal generator: 5 NO contacts max. 250V 1A potential-free, with common reference potential, End position OPEN/CLOSE, selector switch REMOTE, torque error CLOSE/OPEN, 1 changeover contact max. 250V 5A, collective fault message Positioner: 3-point adaptive Input signal: 4 - 20mA 2-wire Position indicator: analog feedback (standard) 4-wire/2-wire active Output signal: 4 - 20mA
Figur 55.470 DN 80	ARI-STEVI 470/422 Straight-through control valve with flanges and shaft-guided cone 1.4581 DN 80 Data sheet: 470001-1.pdf Operating instructions: 0040305000-1.pdf discount group: I11 Nominal pressure: PN 16 Flange bore: according to DIN PN16 Cone design: Parabolic cone Kvs value: 100 Characteristic curve: equal percentage spindle seal: EPDM Exterior treatment: unpainted Actuator: AUMA Drive type: SAR 07.2 Type: Automatic AC Design: Non Intrusive with MWG Voltage: 400V/50Hz Current type: 3PH three-phase current torque to be set: DL 30Nm / DSR 30Nm max.dp shut-off (bar): 16 max.dp control operation (bar): 14.3 Output speed: 5.6 1/min Valve lift: 30mm stroke Coupling: Thread M16x1.5 Actuating time: 80.4sec Connection flange: F10 DIN ISO 5210 Connection type: Connection type A Connection thread: TR20x4 Signal generator: 5 NO contacts max. 250V 1A potential-free, with common reference potential, End position OPEN/CLOSE, selector switch REMOTE, torque error CLOSE/OPEN, 1 changeover contact max. 250V 5A, collective fault message Positioner: 3-point adaptive Input signal: 4 - 20mA 2-wire Position indicator: analog feedback (standard) 4-wire/2-wire active Output signal: 4 - 20mA
22967100MKA53-113F: DN 80 AUTOMATIC MOTORIZED GATE VALVE	VALVE SIZE: DN80 PRESSURE RATING : PN16 MATERIAL : SS REFER DETAIL-1
704235	Thrust actuator ARI-PREMIO Type: 2.2 kN 230 V, 50-60 Hz, In 78/91 mA, P 18/21 VA, V 0,38/0,45 mm/s
0254000013	
901	
55.006	
911100028g191 Ari-Premio 2,2kn	
Ari -Safe	

Le22015ep080
Figur 12.924 Dn 40
Ari Zesa - En-Js1030 - Dn200 Pn16
22046 Dn25
Fig23.046 Dn32 Pn25
23.046 Dn20 Pn25
0466000403
Self Tapping Screw For Ari-Premio 5.0 Kn S/N 444990
Ari -Safe Electronic Controller
2.2kn 115vac
Figur 22.046 Dn 32
1.4408 Dn 20
23.046 Dn15 Pn25
Figur 35.440 Dn 32
Fig23.046 Dn50 Pn25
0254000013 , Type Es11
Figur 25.901 , Dn 100
Ari-Stevi 470/422 (Figur 35.470 Dn 20) Sn1231064336
Figur 67.961
Ari-Stevi 470/422 (Figur 23.470 Dn 25) Sn1231064335
Fig23.046 Dn40 Pn25
52.006
0466000325
Fig. 23.470 Dn125
22046 Dn 50
Vh00000411
Ari-Zesa Fig.012
Figur 72.487
Fig.Vsmwa+ap4 Dn80
55006
Figur 23.006 Dn 150
Sq10 (9600100000g191)
Figur 22.046 Dn 25
Fig23.046 Dn100 Pn25

Elektrischer Schubtrieb Ari-Premio-Plus 2g 2,2kn (911130030g191)
Pn25 Dn20
50.40
Figure 901/902,Werkstoffe
Fig. 12.441 Dn150 Premio 12kn
Ari-Premio 12 Kn
91110000g191 (Sn1231064335)
92052
Figur 23.003 / Dn 50 / Ari-Checko-V
Figur 35.046
Ari-Stevi 440 (Figur 35.440) Sn1231164966
El-Stellantrieb Premio 5kn (911150000g191)
Pn25 Dn200
Sealing Ring-Item 27 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1
Cona S
22047
0466000221
22050 Dn 125
Fig34.046 Dn300 Pn25
Figur 23.470 / Dn 50 / Ari-Stevi 470/422
23.046 Dn25 Pn25
Fig34.046 Dn200 Pn25
45600
Es11 230vac
0466000451
Zetrix Pn40 Dn100
Figur 12.440 Dn 80
95001
12-15 Kn
Figur 22.046 Dn 20
Ari-Stevi 445
Ari-Premio 5.0 Kn, Art N: 911150000g191
Svw 10 44 Bar G 1/2 A, -Not Available, Alternative Model Figur 67.961
Schubantrieb Ari-Premio (Premio 5kn) Artikel-Nr

910000001g191	
Pn25 Dn40	
Ari-Premio-Plus 2g (911160030g191)	
Figur 35.405 Dn 25 Type Ari-Stevi 405	
911100000g191 (Sn1231064336)	
Ri21	
Figur 35.470 Dn 20	
Ari-Safe 12.911	
Ari-Stevi 405 (Figur 35.405) Sn1230563960	
Ari-Stevi 12440	
Figur 35.405 Dn 40	
Fig.921 Pn16 Dn25	
Ta7	
9512440	
Ari -Safe Dn40/65	
9555445	
EPS11.1 Positioner	0254000015 4-20 mA 4763-01200121000004 Type: 4763 Design: electro-pneumatic Control: 2-wire Input signal: 4-20 mA Electrical connection: M20x1.5 Degree of protection: IP54 Connection: G 1/4 Stroke [mm]: 7.5-90 Temperature max .: +70 Temperature min.: -20 Housing material: aluminum
426755 By Ari-Premio (Premio 5kn) Artikel-Nr. 910000001g191	
Fig23.046 Dn20 Pn25	
Premio 5kn (910000001g191)	
Elektrischer Hlk-Schubetrieb Ari-Paco 0,85kn	
911150000g191 (Sn1230563960)	
Ari-Stevi 440	
Figur 12.440 Dn 25	
Spring- Item 37 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1	
224700 + Dp34+ Eps15	
Ari-Premio-Plus 2g (911130030g191)	
Figur 23.470 Dn 25	
Figur 12.901 , Dn 65	
Fig23.046 Dn150 Pn25	
Figur 25.901 , Dn 32	
Figur 22.046 Dn 50	
0490000303	

Ari -Safe Dn 65/100
Ari-Stevi 470/422 (Figur 23.470 Dn 25)
Old Reference Number -- Deufra Oa8 - New Reference Number Sq10
550017-550045
911100000g191 (El-Stellantrieb Premio 2,2kn)
22046 Dn 125
12-470
0254000075
Conas639.
9110400126
Ari-Safe - Trd721
Ari Zesa - En-Js1030 - Dn100 Pn16
1301073555
2.2kn 230vac
Spindle-Item 14 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1
23.470 Dn 25 (Ari-Stevi 470/422)
Figur 35.921 , Dn 50
Dn250/Pn16 Ari Fig.22.046
50.40.3
911250100g191
Ari-Stevi 405 (Figur 35.405 Dn 40)
2.2kn
Figur 22.046 Dn 15
Gasket-Item 7 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1
Ari-Paco 0,85y
Fig34.046 Dn250 Pn25
Premio 2.2kn, Art N: 910000001g191
Fig.Vsmwa+ap4
Zg1
Fig.Vsmwa+ap3.5
Packingrings-Item 31 For Safety Valve Ari Armaturen Type Ari-Safe-P Fig 921 En Iso 4126-1
0277000032
220120300193

[Fig23.046 Dn65 Pn25](#)

[911150000g191 \(Sn1231164966\)](#)

[Figur 22.046 Dn 40](#)

[Pn 40](#)

[Repair Kit For Dn 50](#)

[Figur 22.450 Dn 150](#)