

## Atb Motors B V



Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Atb Motors B V** Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

*Firmamız Atb Motors B V T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	Aıklama
<a href="#">(Motor Maker: Atb , Type: 280s-2x)</a>	DE ROLLER BEARING FOR ELECTRIC MOTOR , (MOTOR MAKER: ATB , TYPE: 280S-2X) / D.No:
<a href="#">(Motor Maker: Atb , Type: 280s-2x)</a>	NDE ROLLER BEARING FOR ELECTRIC MOTOR (MOTOR MAKER: ATB , TYPE: 280S-2X) , / D.No:
<a href="#">Ag 3673410-4</a>	160 L
<a href="#">ENF 63/2C-11</a>	
<a href="#">Af 100l/4k-12 4 Kw</a>	SIEHE ANHANG
<a href="#">Typ Afv 63/4 B-7</a>	SPN-ART.-NR. 041388 SPN-Drehstrommotor weight: 6.1 kg. Statistical commodity code: 85015100 Origin: Austria
<a href="#">Replacement For Engine S / N 3967269-15 / Psn 472206</a>	Three-phase motor Engine type: A 100L / 4K-33S + E3 PSN: 543147 Speed 1: 1450 rpm Speed 2: 1760 rpm Power 1: 3.0 kW Power 2: 3.0 kW Voltage 1: 690/400 V Voltage 2: 460V Frequency 1: 50 Hz Frequency 2: 60 Hz Current 1: 3.45 / 6.0 A Current 2: 5.25 A Type: IMB35 Weight: about 35 kg ++ Since the IE3 engine is often larger, I ask you to check the engine for availability ++
<a href="#">337871</a>	
<a href="#">00329193</a>	Three-phase motor B14 0.75 kW 2880/3450 / min., Voltage range: 200-240 / 346-420 V 50 Hz 200-240 / 346-420 V 60 Hz Protection class IP 65, Insulation class H, Operating mode S3 60%, Ambient temperature 150 ° C, Paint RAL 7021 Origin: European Union (DE) HS 85015100
<a href="#">00337871</a>	Three-phase motor B14 1.50 kW 2830/3400 / min., Voltage range: 200-240 / 346-420V 50 Hz 200-240 / 346-420V 60 Hz Protection class IP 66, Insulation class H, Operating mode S3 60%, Ambient temperature 150 ° C, Paint RAL 7021 Origin: European Union (DE) HS 85015220