

Bachofen

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Bachofen Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Bachofen T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
SC-N2-ATEX bar SWITCHcontrol	60100792 2-way position feedback with 2 NAMUR round initiators Fabr. Pepperl & Fuchs Type: NCN4-12GM35-N0 ATEX identification: for gases: Ex II 2G Ex ia IIB T6-T1 Gb (Zone 1 + 2) for dust: Ex II 2D Ex ia IIIB T135 ° C Db (zone 21 + 22) Ambient temperature -20 ° C to + 70 ° C in closed aluminum housing with optical position indicator Degree of protection: IP67 including operating instructions German / English HS code: 90328900 total net weight 5.00 kg Country of origin Germany
Hydraulic Unit HY-9001-xxxx	- Aluminum tank 10 L - Basic block including return filter and accumulator charging valve - Electric motor 1.1 kW - Gear pump 5 l/min - Max. working pressure: 85 bar - Pressure switch set to 50 bar - Accumulator 1.4 liters
60100792	SC-N2-ATEX bar SWITCHcontrol 2-fold position feedback with 2 NAMUR round initiators Make Pepperl & Fuchs Type: NCN4-12GM35-N0 ATEX identifier: for gases: Ex II 2G Ex ia IIB T6-T1 Gb (Zone 1+2) for dust: Ex II 2D Ex ia IIIB T135°C DB (Zone 21+22) Ambient temperature -20°C to +70°C in a closed aluminum housing with optical position indicator Degree of protection: IP67 including operating instructions

German / English	
1-86-XV-1015	
8021/100VG0004M----A-Z--S----110	Ident number 4073172 Nominal diameter(100): DN 100 (Kvs 95; Cv 110), Function(G): Sliding gate valve 8021, Design(0): GS1-intermediate flange design PN10-PN40 (for flanges according to DIN EN 1092-1, form B), Housing material(0): C-steel 1.0619, Safety position(0): Spring closes, Actuator(4): Diaphragm actuator 250 cm², Springs(-): Standard spring fitting, Sliding disk, movable(-): Carbon material, Sliding disk, fixed(-): Standard coating, Stainless steel 1.4571, Kvs/Cv values(A): red. to 63%, characteristic curve (-): linear, additional special versions (110): i/p positioner, type PS2 6DR5110-ONG00 (or 6DR5110-ONN00), HART, IP66
Ewe 1 Ch 8610	
B1t-M12ss - Pressure Switch	
A057471	
Mp66s K53 No:182312/07 - Dc Servo Motor	
Er20.X0b.G00	
A004421 Wf 18	
Uds-3 44-031551101 - Pressure Switch	
P/N: 137-53-203 Type: Mmz 3600	
Bag/Uds7-881482-118-4-0-10	
Bfs-10-O-G1/4-Ms-We-St	
A004421 Wf 18	
A057473	
Er20 X0b G00	
Ps4102v-Z	
170122985	
Bachofen-Ewe-1-Adc-24-Obsoletereplaced-By-Lmz3600-Adc24-100-Walter-M3;Ller-Ag-Istanbul-Turkiye	