

Bailey&Mackey

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Bailey&Mackey Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Bailey&Mackey Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Type 1392P	Replacement pressure unit per serial number 05 89084 010 Type 1392P Visual Setting Differential Pressure Switch Range: 0.1 to 1 bar Process Connection: 1/4" BSP female, parallel Wetted parts: brass chambers with a beryllium copper diaphragm Seal: Nitrile Electrical Entry: 4-pin plug & socket Switch housing ingress protected to IP65 SPDT microswitch C/W Mounting Bracket Max line pressure 34 bar
0379741047	
05 89682 018	
08A0765004	
10A5554 012	
11 A8479 009	
11A8538112	
11A9047150	
1361A	
1362	
1381	
1381PQ	
1381PV	
1381Q	

1381V	
1382 S658VW13N70HKA	
138LRQ	
1392	
1392P	
1392P 0,2 TO 4 BAR	
1481	
15C9859105	
207CEQ	
2381	
2381Q	
2481	
3312	
3911/2	
5381	
54403028	
815	
92561 016	
CX2334	
MODEL 1382	
PTSPGG1N00	
S-000704.0008	
S2023	
S248CK13N70HKA	
Type 1381 Pressure Switch	Range: 2 to 28 bar Process Connection: 1/2" BSP male, parallel Wetted parts: brass connection with a beryllium copper diaphragm Seal: Nitrile Switch housing ingress protected to IP65 SPDT microswitch rated 10A @ 250V ac CE marked. Manufactured in UK Our Part Ref: S2004
Type 1381 Pressure Switch	Range: -1 to +1 bar Process Connection: 1/2" BSP male, parallel Wetted parts: brass connection with a beryllium copper diaphragm Seal: PTFE Switch housing ingress protected to IP65 SPDT microswitch rated 10A @ 250V ac CE marked. Manufactured in UK Our Part Ref: S2001
05 87439 006	Type 1392P Visual Setting Differential Pressure Switch Range: 0.1 to 1 bar Process Connection: 1/4" BSP female, parallel Wetted parts: brass chambers with a beryllium copper diaphragm Seal: Nitrile Electrical Entry: 4-pin plug & socket Switch housing ingress protected to IP65 SPDT microswitch C/W Mounting Bracket Max line pressure 34 bar
1382	
1381pq-1-1bar G1/4 1381pq-1-1bar G1/4	
.1381 Druckschalter Typ 1381 1/4 Gewindepressure Switch Type 1381 Thread 1/4	
1381q Pressure Swich Range -1/+1 Bar, 28bar Max 10a 250v	

[Lmv/Pns/138 Iq01b Low Pressure Switch](#)

[1381pq Druckschalter Typ 1381pq Gewinde
1/4pressure Switch Type 1381pq 1/4 Thread](#)

[0486596 025](#)

[0382143 023](#)