



Bamo

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Bamo** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Bamo T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Artikel-Nr. M1014027	VE2V STAINLESS STEEL / FPM G1 1/2 " Electric 2-way ball valve stainless steel Process connection G1½ " Housing and ball materials: AISI 316 Ball seal material: PTFE, Material sealing elements: FPM, electric drive, Degree of protection: IP65, Connected load: 45W, Supply voltage: 90 ... 230 V AC 50 / 60Hz or 90..350V DC
BSM 501	bistable switch Switching voltage 4 ... 250 V AC 4 ... 30 V DC, switching current 1 mA ... 3 A VA clamp for pipe d25 ... d40 mm and cable ties made of PA6 30 ... 100 mm Article no. 585100
TURBISWITCH GA 5 VV 1 7 M	Turbidity limit value sensor Version for pipe installation, including TT-HDR transmitter and TR-HDR receiver, for operation with TURBISWITCH GS4 / GS5 evaluation unit Material of fitting and process connection: PVC, Process connection: DN 65 screw connection on both sides, Sealing material: EPDM, including assembly key and suction cup for Maxos disks, Maxos disks with CLEANOSIL® VMF anti-dirt coating, Media temperature +5...+60 °C, pressure max. 4 bar (20 °C) Installation dimension: 202 mm (tolerances: ±2mm) Article no. 422560
TURBISWITCH GS5 G	Evaluation unit for turbidity limit value with display, for connection to the sensors of the TURBISWITCH series, supply voltage: 100V-255VAC / 50-60Hz, turbidity limit value freely adjustable, 2 signal relays (limit value, fault) 250V AC/3A or 30V DC/1A, delay time adjustable 0.1-9.9s, hysteresis adjustable 1-25%, LED display with 2½ digit dot matrix, status signaling using colored LEDs, top hat rail mounting 35x7.5mm DIN EN 50 022 Article no. 410103
BRK 60 / 63 bistable reed contact	bistable reed contact Switching capacity 60 VA / 230 V AC / 1 A Housing made of ABS, protection class IP 55, with stainless steel clamp for pipe

max. 63 mm Article No. 583050
Electrode (For Bsm 501 4-250 V 1m A - 3a Level Control Switch)
Pp-Schwimmer S40 / D42 X 132 Mm
Maximat Cx 40 K 4 V G2 1 L 300 Mm
Membrane Affleurante
Bamophox 322
Maximat Cx 40 K 4 V G2 1 L 250 Mm
903200
Maximat Tc 1 G
Es1s
Maximat Lw Cbx
Rtm 586-01
Brk 60 / 63
Dfm 40 Dn 32 350, 2500 L/H
Cdsp 25 I
Brk60/32
Bsm500
Es 1001 Obsolete, Replaced By Es2001/230
Es2001/230