

Band

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Band Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Band T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
1. BAND	Band Thickness: 0.9 - 1 mm Tensile Force: 4 - 5 N / mm Min. Turning Diameter: 15 mm Conveying Surface: Smooth Carrying Property: Medium Adhesion Thickness: Single Layer
2. BAND	Band Thickness: 1.2 -1.3mm Tensile Force: 8-9 N / mm Min. Turning Diameter: 15mm Conveying Surface: Smooth Carrying Property: Medium Adhesion Thickness: Double Layer
3. BAND	Band Thickness: 1,2 - 1,3mm Tensile Force: 5 - 7 N / mm Min. Turning Diameter: 8mm Conveying Surface: Silky Carrying Feature: Non-stick Thickness: Double Layer
4. BAND	Band Thickness: 0.8 - 1mm Tensile Force: 1,5 - 3 N / mm Min. Turning Diameter: 15mm Conveying Surface: Silky Carrying Property: Medium Adhesion Thickness: Single Layer
5. BAND	Band Thickness: 1,2 - 1,3mm Tensile Force: 7 - 8 N / mm Min. Turning Diameter: 15 mm Conveying Surface: Matte Carrying Feature: Non-stick Thickness: Double Layer
6. BAND	Band Thickness: 1.2-1.3 mm Tensile Force: 8 - 10 N / mm Min. Turning Diameter: 15mm Conveying Surface: Matte Carrying Feature: Smooth Thickness: Double Layer

Band

YURSAT yedek par¼a tedariki yapan bir Őirkettir. Sitemizde bulunan markaların yetkili distrib¼t¼r¼ yada temsilcisi deĐildir.

[7. BAND](#)

Band Thickness: 1.2 -1.3mm Tensile Force: 9-11 N / mm Min.
Turning Diameter: 15 mm Conveying Surface: Smooth
Carrying Property: Medium Adhesion Thickness: Double Layer

[8. BAND](#)

Band Thickness: 1.2-1.3mm Tensile Force: 6-7 N / mm Min.
Turning Diameter: 15mm Conveying Surface: Smooth Carrying
Feature: Non-stick Thickness: Double Layer