

Basler

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Basler Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Basler T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
Decs-250n Cn1sn1n	Negative Forcing Digital Excitation Control System, 120 Vac/125 Vdc, Low (50/60 Hz), 100Base-T (ModbusTCP)
ICRM-15	Inrush Current Reduction Module
DECS-250	24/48VDC, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
DECS-250 CN1SN1N	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
DECS-100 B05	VAR/PF Controller, V, 5 Amp CT secondary
acA1300-75gc	
acA3088	+ 3Meter USB Cable
	Digital Excitation Control System,24/48 Vdc, Internal/External

DECS-250 LN2CN1P	Autotracking, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
DECS-250 LN1CN1P	DECS-250 24/48VDC, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP), PROFIBUS
ES-27/59 3AB1N0N0	Under/Overvoltage Relay, Three-Phase, Three Wire, 120 Vac Nominal Input , Adjustable, 0 to 20 seconds, 50/60Hz
ICRM-1S	Inrush Current Reduction Module
DECS-100 B11	
DECS-100 B15	
DECS-250N LN1SN1N	
ES-74S 7NB0G4N0	
ICRM-7	
TBC	
DECS 250CN1SN1N	VOLTAGE REGULATOR DECS250
ICRM 15	ICRM15 MODULE DECS250 ACCESSORIES
DECS-250 LN2SN1N	AVR DIGITAL EXCITATION CONTROL SYSTEM DECS250
DECS150	Plate+AVR
2000036233	USB 3.0 Interface Card PCIe, Fresco FL1100, 4HC, x4, 4 Ports 92395.2170.GP2,L,V,G, XX.\..172230-101..T.PLM: DWG-00175775
ES-59 3SB1N0N100	ES-59 OVERVOLTAGE RELAY, THRE PHASE, 3 WIRE, SPECIAL VOLTAGE, ADJUSTABLE 0-20 SECONDS, 50/60HZ
E02246209	
color 1/2.3" USB3.0	107821 a2A1920-160ucBAS 1920 x 1200, 160 fps,
2200000568	Lens Basler C23-0824-5M 2/3", 8 mm, F2.4, 5 Mpix
2000033241	Cable USB 3.0, Micro B screw lock/A, 5 m
SN: 22245088	
DECS-250 LN1SN1N	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
ES-25 1EA1N1N0	Sync-Check Relay, Single phase, 415 Vac Nominal Input, Timing instantaneous, 50/60 Hz, Close on Dead Bus
AVC125-10 A1	VOLTAGE REGULATOR Sensing Voltage 100/120 Vac, Sensing Frequency 50/60Hz
BAS-ACC-CBL-2000031224	Basel accessory cable Power I/O Cable M5 4p/open, 10 m for

	cameras: ace CI
DECS-200 DIGITAL EXCITATION CONTROL	
BEI-64F GROUND FAULT RELAY	
DECS-250 CN2SN1N	Digital Excitation Control System, Power Supply: 125 Vac/Vdc, PSS: None, Autotracking: Internal/External Autotracking, Terminals: Spring Type Terminals, Synchronizer: None, Ethernet Communications: 100Base-T (Modbus TCP), Additional Communication Protocol: None
DECS-250 CN1CN1N	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP)
DECS-200, DIGITAL EXCITATION CONTROL SYS	
DECS200	
DECS-150 1NS1V1B1S	Digital Excitation Control System, 125 Vac/Vdc, Internal Autotracking Only, Compression Type Terminals, 100Base-T (Modbus™ TCP)
acA1920-50gm	ID:107759-06 S/N:24262293
DECS-250 LN1SN1N	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
DECS-200, DIGITAL EXCITATION CONTROL SYS	
acA3088-57um	
DECS-250 LN1SN1N	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
Decs-200 Digital Excitation Control system	
AVC125-10 B1	Voltage Regulator, Sensing Voltage 200/240 Vac, Sensing Frequency 50/60Hz
AVC125-10B1	
DECS150	Digital Excitation Control System
AC1300-200um	
CONTROLLER DIGITAL;	SUPPLY VOLTAGE: 120...125 V AC/DC; MONITORED PARAMETERS: YES; INSTALLATION METHOD: PANEL; DISPLAY COLOR: GREEN; FREQUENCY: 50...60 HZ; BRAND: BASLER; MODEL: DECS-400-2C1 U; SERIAL NUMBER: H01739316; ORDER NUMBER: 12454403
DECS 250 CN2 CA 1P	

Decs250	
Avc63-12-A1 (Ex. K63-12b)	
L301kc	
Decs-100	
Cbs 212a	
Aca1300-30gm	
Be3-59t-V	
747-Lm28lf	
Mco2107	
Avc125-10-B1	
Icrm-15	
Avc125-10a1	
Decs-400	
Decs-250 Ln1sn1n	Digital Excitation Control System, 24/48 Vdc, Internal Autotracking Only, Spring Type Terminals, 100Base-T (Modbus™ TCP)
Be1-11g	G6D3M0J2P0E000 Generator Protection System, Dual 5 Amp Nominal, Dual Ground - 5 Amp Nominal, 24 Vdc, Modbus, Vertical (S1 sized) Case, Standard I/O, Normally-Closed Alarm, Current Differential, Copper Ethernet
9116300109(Ex9057900100)	
Decs-250n	
Decs125-15	
Decs-15	
Ral6144-16gm	
A-Ace-1300-60gc	
Be1-25, M1e-A7p-N5u6f	
Es-27/59 3sb1n0n100	Under/Overvoltage Relay Sensing Input Type: Three-Phase, Three Wire Input: Special Voltage 100V Timing: Adjustable, 0 to 20 seconds Frequency:50/60 Hz
Idp-801	
Avc125-10 A1	VOLTAGE REGULATOR Sensing Voltage 100/120 Vac, Sensing Frequency 50/60Hz
Decs-200n	

[Be1-25a, A2-F5-V3-D0](#)

[Be1-25-M1e-A7p-N5u6f](#)