


Beinlich Pump Systems

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Beinlich Pump Systems Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Beinlich Pump Systems T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
ZPD 1-3,20-KIS-L-FCV/R/MAG(22-G)	PE:10000287 Gear metering pump Assembled with: - Magnetic coupling - bellhousing Pump data Number of levels: 1 Theor. Delivery volume: 3.2 ccm / rev Suction connection: S = G 1/2 Pressure connection: D = G 1/2 Speed: max. 750 min-1 Direction of rotation: LEFT (complete a. Drive shaft) Inlet pressure: 0-3 bar Operating pressure: 13 bar Differential pressure: 10 bar Sealing material: FKM Type of sealing: via containment shell Operating viscosity: 100-2000 mPa * s Operating temperature: +25 to +80 ° C prepared for customer. Drive motor Type: worm gear (EN40 Yılmaz Red¼kt¼r) Power: 0.25kW [50Hz] Speed: 200 min-1 Bolt circle: ø82mm (M6) Shaft: ø18x40 mm associated attachments Coupling: MAG DST60 / 22-G Pump bracket: ø 160mm
ZPA 1-1,90-N-L-F/R/1F/STR/VT	external gear pump pump data Number of stages : 1 theoretical Displacement : 1.90 cm3/rev Inlet pressure max. : 0-10 bar Maximum operating pressure: 40 bar Max. pressure: 60 bar (short-term operation) Maximum speed* : 1800 rpm Suction connection : G 1/2 Pressure connection : G 1/2 Direction of rotation : LEFT, seen on drive shaft Type : external teeth straight, free pump shaft Type of sealing: 1-fold shaft sealing ring with support ring *The maximum speed does not apply to viscosities over 800 mPas!
	TIN Zg-Nr. 19-01-0470 Vers. 03 ZAD_8100320 Number of Stages : 1 Theo. Volume : 1,17 cm3/rev Inlet Pressure max. : 0-10 bar Work Pressure max. : 180 bar Peak Pressure max. : 200 bar (Short operation)

ZPD 1-1,17-KIS-L-F/R/3F-SP/VV/024	<p>Speed max.* : 750 min-1 Suction Port : G 1/2 Pressure Port : G 1/2 Sense of Rotation : LEFT (ccw), in View of Drive Shaft Design : External Spur Gear, bare shaft Sealing Type : Triple Radial Shaft Seal with Block Chamber Version : Prepared to mount Pressure Valve Ambient Temperature : -30°C min./ +60°C max. *Indicated maximum Speed is not valid for Viscosities above 2.500 mPa*s! Materials Housing : Spheroidal Cast Iron 1 Center Plate : Spheroidal Cast Iron 1 Gears : Nitrided Steel Drive Shaft : Nitrided Steel Driven Shaft : Nitrided Steel Wear Plates : Stainless Steel 1 hardened Sleeves : High-performance Material 6 Seals : FKM PUMPE zur D 9540 - 046 804</p>
ZPD 1-5,1-KIS-L-F/R/3F-SP/VV	<p>Zg-Nr. 19-01-0558 Vers. 04 ZAD_8100263 SILICON pump data Number of stages : 1 Inlet Pressure max. : 0-10 bar Work Pressure max. : 180 bar Peak Pressure max. : 200 bar (Short operation) Speed max.* : 750 min-1 Suction Port : G 1/2 Pressure Port : G 1/2 Sense of Rotation : LEFT (ccw), in View of Drive Shaft Design : External Spur Gear, bare shaft Sealing Type : Triple Radial Shaft Seal with Block Chamber Version : Prepared to mount Pressure Valve Ambient Temperature : -30°C min./ +60°C max. *Indicated maximum speed is not valid for Viscosities above 2.500 mPa*s! Materials Housing : Spheroidal Cast Iron 1 Center Plate : Spheroidal Cast Iron 1 Gears : Nitrided Steel Drive Shaft : Nitrided Steel Driven Shaft : Nitrided Steel Wear Plates : Stainless Steel 1 hardened Sleeves : High-performance Material 6 Seals : FKM PUMPE zur D 9540 - 046 809</p>
ZPD 1-1,90-KIH-L-F/R/3F-SP/VV	<p>AMIN Zg-Nr. 19-01-0661 Vers. 04 ZAD_8100303 Pump Details Number of Stages : 1 Theo. Displacement : 1,90 cm3/rev Inlet Pressure max. : 0-10 bar Work Pressure max. : 180 bar Peak Pressure max. : 200 bar (Short operation) Speed* max. : 1450 min-1 Suction Port : G 1/2 Pressure Port : G 1/2 Sense of Rotation : LEFT (ccw), in view of drive shaft Design : External Spur Gear, bare shaft Sealing Type : Triple Radial Shaft Seal with Block Chamber Version : Prepared to mount Relief Pressure Valve * Indicated maximum speed is not valid for viscosities above 800 mPas! Materials Housing : Spheroidal Cast Iron 1 Center Plate : Spheroidal Cast Iron 1 Gears : Nitrided Steel Drive Shaft : Nitrided Steel Driven Shaft : Nitrided Steel Sliding Plates : High-performance Material 6 Sleeves : High-performance Material 5 Seals : FKM</p>
TRGD 05/3-0,6-200-FCV/R/K-4M0,75/MAG(10-G)/PTFE	<p>(BP:10001262 +0,75kW Motor) pump unit Consisting of radial piston pump, intermediate flange Bellhousing and MAG clutch and motor pump data Level Number (Stars) : 1-Star theoretical delivery volume: 0.42 ccm/rev Direction of rotation : any Pressure connection : G3/8 Suction connection : G3/4 Vent : G1/4 Inlet pressure : 20 bar max. Operating pressure: 700 bar max. Type of sealing : via the can of the magnetic coupling Temperature : -30°C min. / +60°C max. materials Housing : 1.0570 chemically nickel-plated Shaft : stainless steel 1st Piston housing : 1.0503 nitrided Piston : nitrided steel + coating 3 Bearing : Cylindrical roller bearing with steel cage / spherical roller bearing Seal materials : PTFE drive motor Type : 4-pole three-phase motor Power : 0.75 kW Voltage : 230/400 V Speed : 1500 min-1 Degree of protection : IP55 Insulation class : F Shape : B35 Motor protection : 3 PTC thermistors Accesories MAG clutch : DST75/10-G Bellhousing : Standard motor hub</p>
VES 9201114	<p>pressure relief valve DBV-E-PI/1-06/50-200/VT/S Type of control : Direct controlled Spring Type : compression spring Adjustment range: 50 - 200 bar Backflow : External Seal materials : FKM Material : steel</p>
DBV-I-PI/1-06/50-200/VT/S	<p>Type of control : Direct controlled Spring Type : compression spring Adjustment range: 50 - 200 bar Reverse Current : Internal Seal materials : FKM Material : steel DRUCKBEREICH VON 50 - 200 BAR.</p>
DBV-I-PI/1-06/0-50/VT/S	<p>Type of control : Direct controlled Spring Type : compression spring Setting range : 0 - 50 bar Reverse Current : Internal Seal materials : FKM Material : steel PRESSURE RANGE FROM 0 - 50 BAR.</p>
	<p>TRGD 05/3-0.6-200-FCV/R/K-4M0.75/MAG(10-G)/PTFE (BP:10001262 +0.75kW motor) pump unit Consisting of radial piston pump, intermediate flange Bellhousing and MAG clutch and motor pump data Level Number (Stars) : 1-Star theoretical delivery volume: 0.42 ccm/rev</p>

DIV_9990001	<p>Direction of rotation : any Pressure connection : G3/8 Suction connection : G3/4 Vent : G1/4 Inlet pressure : 20 bar max. Operating pressure: 700 bar max. Type of sealing : via the can of the magnetic coupling Temperature : -30°C min. / +60°C max. materials Housing : 1.0570 chemically nickel-plated Shaft : stainless steel 1st Piston housing : 1.0503 nitrided Piston : nitrided steel + coating 3 Bearing : Cylindrical roller bearing with steel cage / spherical roller bearing Seal materials : PTFE drive motor Type : 4-pole three-phase motor Power : 0.75 kW Voltage : 230/400 V Speed : 1500 min-1 Degree of protection : IP55 Insulation class : F Shape : B35 Motor protection : 3 PTC thermistors Accesories MAG clutch : DST75/10-G Bellhousing : Standard motor hub intermediate flange side</p>
ZPD 2-19.60-KIN-L-F/R/GL-SP/VV/003	
ZPA 3-37,40-H/2-7,80-H-R-F-B/R	<p>ZA__1320007 external gear pump Number of stages : 2 theoretical Displacement : stage 1 = 37.40 cm3/rev Stage 2 = 7.80 cm3/rev Inlet pressure max. : 0-1 bar Maximum operating pressure: 100 bar Max. pressure: 100 bar (short-term operation) Maximum speed* : 1800 rpm Suction connection: stage 1 = G 1 Pressure connection: Level 2 = G 1/2 Direction of rotation : RIGHT, seen on drive shaft Type : external teeth straight, free pump shaft Type of sealing: 1-fold shaft sealing ring Execution : DISA - drive shaft with thread M8x20 * The maximum speed does not apply to viscosities over 800 mPas! Materials for level 1+2 Housing : ductile iron 1 Center plate : ductile iron 1 Gears : nitrided steel Drive shaft : Nitrided steel Pump shaft : nitrided steel Gliding goggles : high performance material 1 Plain bearing: high-performance material 1 Seal materials : NBR</p>
ZPD 2-15,70-KIS-L-FCV/R/MAG(60-G)/024	Repair kit set
ZPI 4-121-NHW-L-FcV/T/K-M11B35/GI/Vt	<p>BP:10001936 Number of stages: 1 Theoretically Delivery volume: 121.0ccm/rev Suction connection: S = SAE3 for ø54.0 Pressure connection: D = SAE2 for ø54.0 Direction of rotation: left (seen on drive shaft) Speed in rpm: 300 Inlet pressure [bar]: max. 3 Operating pressure [bar]: max. 20 Differential pressure [bar] :max. 20 Seal material: FKM(FDA) Fluid temperature°C: max. 100 Ambient temp. °C: min. 10 max. 40 Operating viscosity: 10-200mPa*s Engine included: BG160 Coupling: Softex Bellhousing: ø350mm</p>
ZI_4000031	<p>Internal gear pump Type of toothing: internally toothed Delivery volume: 121.0ccm/rev Seal material: FKM(FDA) Shaft sealing: mechanical seal Suction connection: SAE3 Pressure connection: SAE2 Inlet pressure: 0 to 25bar Operating pressure: max. 100bar Differential pressure: max. 100bar Direction of rotation: left on P-shaft seen Ambient temp. : 10 to 40°C Medium temperature: max.100°C Medium: Food oil without solids Viscosity: 10-200mPa*s ONLY PUMP WITH FREE SHAFT END!</p>
Trgd 05/3-0,6 200-Fcv/Rmag (10-G)	art bp 10001262
Pumpe	<p>Die Angefragte Pumpe war Fluid o tech MKCS11S. Unser Kunde benötigt eigentlich nur den gleichen Durchfluss und den gleichen Druck. Die Abmessungen müssen nicht genau sein. Da es ein neu projekt sein wird. Verwendungszweck; Ethylenglykol + Wasser-Gemisch vorgesehen. Beachten Sie bitte den Anhang.</p>