

Bernard Controls

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Bernard Controls Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Bernard Controls Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Bcd0016197	SQ250 III IP67 POSIGAM+ 3 50Hz 400V 70s
8cd0016384	ASM-6 III IP68 INTELLI+ 3 50Hz 380V 26lmin
Asm6hw	
Asm6db	
SQ10KN060MB0D24B0A0A0J1B	SQ 1 0-60sec-230V1 -ph.50Hz-CI.II + minigam 15175 BC-DEUFRA - variable speed drive type SQ10 with MINIGAM + Positioning time: 60 sec for 90 ' Nominal torque: 80 Nm perm. Control torque: 60 Nm Motor voltage: 230 V 1-ph. 50 Hz Motor power: 0.03 kW Nominal current: 0.6 A Starting current: 0.5 A. Output flange ISO 5211: Combination flange F05 / F07 Weight: 7 kg # Built-in 230 V heating 2 additional travel switches for intermediate position Wiring according to circuit diagram 55671 0/04 # electronic positioner MINIGAM Input: (0) 4..20 mA or 0-10 V; Feedback: (0) 0..20 mA (not galvanically isolated)
71020-003040	BERMAD DIAPHRAGM UNIT FOR 2 "VALVE 400 SERIES
AT14 SWİTCH 52 rpm F10 FLANGE B3 FORM	
Servomotor gas flap DN150 (Atex Certified)	Motorized valve with complete body, 220V, proportional, gas pressure: 80-200mBar
Flame return valve DN 150 (Atex Certified)	Vertical type, flame arrester, flame arrester, deflagration

Main Control Board CI2701	
BCD0019200	SQ10 A IP67 Switch 1 60Hz 120V 5s # According to the enclosed data sheet # Please continue to use the existing socket
part no:41-64-0500.	2" Lug type butterfly valve butterfly valve for WATTS mueller mdl 2.0-88-IHH-6-1 lug style 316SS disc&stem watertrincs
part no:41-64-0500.	5" Lug type butterfly valve butterfly valve WATTS for mueller mdl:5.0-88 IHH-6-1 lug style 316SS disc&stem watertronics
71020-003040	BERMAD DIAPHRAGM UNIT FOR "SERIES 400" VALVE 2 "
SQ10KN035MB0D24A0A0A0J1B	SQ10-35sek-230V1-ph.50Hz-CI.III + minigam L5155 BC-DEUFRA - variable speed drive type SQ10 Positioning time 35 sec. for 90 ° Nominal torque 100 Nm perm. Regular 60 Nm Motor voltage 230 V 1-ph 50 Hz Motor power 0.02 kW Nominal current 0.5 A. Starting current 0.9 A Output flange ISO 5211: Combination flange F05 / F07 Weight 7 kg
SQ80 III IP67 Switch 3 50Hz 400V 60s	8CD0019392 Replacement drive for drive with S / N 19104499.001
AQ0010FB025S3200E0M	AQ00 10-25sec-220 / 230VAC-50Hz-SwitchPositioner L8054 # Please refer to the attached data sheet for further data
SOCKET AQ10	processed according to your information. The indicated price refers to a square. If you need a flat or a hole, the price will differ #
SQ10FC006MB0D24A0A0A0J1B	SQ1 0-6sec-230V1 -ph.50Hz-tuZ 15051 BC-DEUFRA - actuator type SQ10 Positioning time: 6 sec for g0 ' max.torque: 90 Nm Motor voltage: 230 V 1-ph. 50 Hz Motor power: 0.06 kW Nominal current: 1.2 A Starting current: 1.7 A. Capacitor: 10pF Output flange ISO 52'11: Combination flange F05 / F07 Weight: 7 kg Equipment : 2 additional position switches for intermediate positions Switching room heating 230 V Wiring 550 250/12 statistical commodity number 8501 4020 Drive design as serial number 16L1 7453.001
ASM 16	
0A6 2007 07L11243.001	
15L05927.004	
16L03906 001	
17L20348.002	
3410151	
3410160 (CI 2701 230 VOLT)	
3410160 CI 2701	
3410165	
3500051G	
3620003	
6L11387.002	
7510503G	
7510509G	
7510702	
7510946	
8891081	
8CD001	

8CD0013660
8CD0014238
8CD0016685
97700055
97700968
AQ0010FB025PA000E0M
AQ0025FB030PA000E0M
AQ10
AQ25
AS50
AS50F030MBZ0110
ASM10 A IP67
AS-PK060TAZ0110
BCD0003661
BCD0003663
BCD0007115
BCD0008505
BCD0008506
BCD0008928
BCD0012124
BCD0013660 (SQ250)
BCD0015010
BCD0017363
BCD0018354
CI 2701
DIV
EZ0060FAMB 030A0CU
EZ6 230v 50Yz-1a
for AQ3L
L0250
LE10EN35CEZP010
MAS4
MAS4 CLII INTELLI+ POS 400V 50Hz 3ph 60s (-40)
MBS2
OA15

POSIGAM+/ST14
RS258 2500NM/C
RS258 F16
S/N:14L10225.001
S010
SQ 15
SQ10 INTEGRAL+ 230V 50Hz 1ph 6s (-40)
SQ10 POT
SQ100
SQ20
SQ25
SQ250
SQ250III
SQ600
SQ60FA030TA0D24A0A0A0K1B
SQ60FA030TA0D24A0A0A0K1B
SQS0FA030TA0D24A0A0A0DI B
SQX50
ST14+RS1825
ST30
STECKBUCHSE SQ20 / SQ25 I EZ25 unbearbeitet
STX6
Tam 4-20ma
TRACO POWER IN 5V OUT 5V/400MA TEM2- 0511
Varistoren 420 V
zusätzliche Kabelverschraubung 2 x M20 (insgesamt 4)
97000083 Analog input output
9910775 encoder
97702447 board CI2802
97702488
97702490 Display (without cover)
97702493 Transfo V2
2920052 starter 6A
ASP 0,03KW 230VAC

0A15	
SO10 III IP67 POSIGAM+ 1 50Hz 230V 60sec	
97700968	3410165 GAMK(old item code)
AT14 LOGIC POSİTIONER	ELECTRIC ACTUATOR (FLOW REGULATOR VALVE)
AT14 SWITCH	ELECTRIC ACTUATOR (AIR FLUSH VALVE)
AT6L SWITCH	ELECTRIC ACTUATOR (CURLER DISCHARGE VALVE)
AT14 SWITCH	ELECTRIC ACTUATOR (WATER WASH VALVE)
OA8M-30 PN	AD030-71CA50MS, FOR ASISTGAS TEMPERATURE CONTROL VALVE FOR VOC SYSTEM, JOHN ZINK
MODEL: SQ100	ACTUATOR , 17 RPM ,TURN: 12.5
97700968	Kit Gam-K card kit
ASM	
BS100 model 3 phase 400V 0,1Kw actuator	
S010	
0AP	
AQ0015TA030L3200E0M	AQ0015-30Sek-380/415VAC-50Hz-LogicPositioner
AQ0010FB025L3200E0M	AQ00 1 0-255 ek-220 230YAC-50H2-LogicPositioner 18058
AQ50 B3 F07/F10 380 volt	
19A11281.005	AQ0015TA030L3000EOM
Valve	We are writing to you to get a price quote for BERNARD brand gas valve with actuator, according to the actuator features given for Auma Valve in the attachment. The technical drawing of the section where the valve will operate is given in the appendix. Pen number 22. We need a proportional operating valve with a diameter of Ø1000mm. Fluid information is below. For pressure: Let me also inform you that it works in millibar levels between 0 and -1 bar. I expect to receive your offer as soon as possible. Actual gas flow [Am³/h]: 237oC 99,135 Gas flow [Nm³/h]: 51,577 You can get the temperature as 320-380 oC.
VALVE,BALL,WITH ELECTRIC ACTUATOR,DN125 PN16	Ball Valve Features with cast body Globe: AISI 316 Working Pressure: PN16 Dimensions: DN125 Flanged Valve Length:400mm Electric Actuator Features Brand: Bernard Controls AQ10 (AQ0010TA025LA000E0M) Protection Class: IP68 Working Voltage: 380VAC Working Mode: On-Off Operating Temperature: -20°C...+60°C Torque: 100 Nm Position Indicator: On / Off Alternative Operation: Manual Lever It will be used on the water line.
VALVE,BALL,WITH ELECTRIC ACTUATOR,DN150 PN16	Ball Valve Features with cast body Globe: AISI 316 Working Pressure: PN16 Dimensions: DN150 Flanged Valve Length:350mm Electric Actuator Features Brand: Bernard Controls AQ10 (AQ0010TA025LA000E0M) Protection Class: IP68 Working Voltage: 380VAC Working Mode: On-Off Operating Temperature: -20°C...+60°C Torque: 100 Nm Position Indicator: On / Off Alternative Operation: Manual Lever It will be used on the water line.
VALVE, BUTTERFLY, WITH ELECTRIC ACTUATOR, DN500 PN	Ball Valve Features Cast body, shaft and valve stainless steel Spindle: AISI 420 Working Pressure: PN16 Dimensions: DN500 Flanged Valve Length:127mm Electric Actuator Features Brand: Bernard Controls AQ150 (AQ0150TA040L3000E0M) Protection Class: IP68 Working Voltage: 380VAC Working Mode: Proportional (Logic Positioning III) Operating Temperature: -20°C...+60°C Torque: 1500 Nm Alternative Operation: Manual Lever It will be used on the water line.

BCD0024658	AT14 III IP68 Logic V2 3 50Hz 400V 21t/min
Replacement drive for SN 20L12867.002	SQ25KA030TA0D24A0A0A0K1B SQ25-30s-400V3-ph.50Hz-CI.III L5510 BC-DEUFRA - Control drive type SQ25 Positioning time: 30 sec for 90° Nominal torque: 250 Nm Perm. control torque: 140 Nm Motor voltage: 400 V 3-ph. 50 Hz Motor power: 0.03 kW Nominal current: 0.3 A Start-up current: 0.5 A Output flange ISO 5211: combination flange F07/F10 Weight: 17 kg # Heating in the control room 2 additional limit switches for intermediate position Wiring according to circuit diagram S50000/38
ASM-0(6) AT6L LOGIC V2	SM-0 (6) A Control Unit 3 50Hz 400V (New Series AT6L Logic V2) new type DEA VENT LFC10AA003 proportional bernard actuator
RS108	
AQ0080TA055S3300EBM	AQ0080-55Sek-380-415VAC-50Hz-Switch-Potentiometer-F10 L8813
BCD0025448	ST30 III IP68 Switch 3 50Hz 400V 61t/min 09L01979.001
AT6L 3PH 400V 50HZ 60NM 14TR/min 8Tours S4	
97000083 Analog input Output card	
9910775	
97702447 main Board CI2802	
97702488 Terminal Board	
0A8 230V/1PH/1.2A	
SQ250	
KIT CARTE CI2801	STX6 - 20A26551.001 STX6 - 20A26483.005
KIT POSITIONER BOARD 4-20mA for CI2801	STX6 - 20A26551.001 STX6 - 20A26483.005
KIT TRANSFORMER INTELLI+ XI 1Ph 220-230V	STX6 - 20A26551.001 STX6 - 20A26483.005
Q25 3Ph 308-415V 50Hz 0.04 KW 30% 0.30A 0.25 250Nm	
3PH 308-415V 50HZ 0,07 KW 50% 0,43A 0.25 500Nm	
Tam 4-20ma Ma-Stellungsgeber	
Sq20fa005ta0d24a0a0a0k1b	
Aq0010fb025pa000e0m Elektroantriebaq 10 - 230 Volt 50 Hz. 1phasig	
Fq18	
Sq15	
Sq25 Cliii Posigam+ 380v 50hz 3ph Electric Drive	
Bcs0026421	
Aq007lfh01 5pa000e0m	
Bci0011498	
Bm-V Dn100	
Fq50	
Aq0015dh02 5la00pr0m	

Sq-10 Coppia 100nm
Pn10/16 Dn100
97701132
97700801
Sq 15 Elektroantrieb 1-Phasi 230 Volt 50 Hz.
97700703
Sq-25 Coppia 300nm
97700344
7510946 Steckbuchse Sq2o / Sq25 / Ez25 Vk Sw 17/90
Fq04
As50 Elektroantriebas 50 Und 3-Phasen 380 Volt - Stellzeit Stnadard 30 Sec
7510702 Steckbuchse Sq2o / Sq25 I E225 Vk Sw 17145"
Bcs0013194
16103906 001 Bernard Controls Sq20 Stellgliedbernard Controls Sq20 Actuator
Ez0025knmb030a0 Ex.(Ez0025knnb025a0)
Ez6 230v 50yz-1a Bernard Controls Elektroantrieb Ez6 230v 50yz-1a
Deufra Sq25
3410160
97701061
Ez-10
Bcd0007115 Bernard Controls Typ Mas4
Bm-V Dn200
13114494.011
Mas4 Der Antrieb Der Walze Zur Regelung
Sq-60 Coppia 600nm
Sq-10 Coppia 200nm
0a3
Sq60
Pn10/16 Dn200
Bcs0026420
Sq80
Sq10 Iii Ip67 Minigam
12117073 002

Bci0010208	
Oa6	
Bci0008271	
St70 Jgta 23	TRANSMITTER
Bci0008272	
Dn 65 Ansi 150	
Fq08	
Sq25 Iii Ip67 Minigam	
Bcs0001383	
13l13349.011	
Aq0025fb030pa000e0m Elektroantrieb Aq 25230 B 1-Phasen 230 Volt	
Sq6	
Fq30	
As-25-D-360° 400 V Ac	
17l20348.002 Antrieb Sq10	
Bernard Ci2701	
At6l	
Sq-10	
Ci2801	
Sq120	
Ez-15	
Bcs0026419	