



Biffi Italia Srl

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Biffi Italia Srl Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Biffi Italia Srl T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
G02151850045	SEALKIT FOR QUICK EXHAUST VALVE
Electronic Board BIFFI For Actuator model WGR3200	030/32000-42 MRF: BIFFI ITALIA PROCESS BOARD(BASE CARD) OF THE ICON 2004 COMPELET MODEL: DE5703R04C ICON 2004 49LOG1200 TAG:1067-MOV-0027
POWER BOARD FOR ACUATOR BIFFI MODEL: WRG 3200-	030/32000-42
TERMINAL BOARD FOR ACTUATOR BIFFI MODEL: WRG 3200-	030/32000-42
172072E001001	
GB206Q33526C5	SEAL KIT FOR PNEUMATIC CYLINDER
PARTS FOR "BIFFI ITALIA" ACUATOR	TYPE NO.: GPO 0.9C-100-LB SIZE: 8" , 600# ALLOWABLE TEMP. RANGE: -29/65 ¼C SUPPLY PRESSURE RANGE: 180 BAR G
ELECTRIC ACTUATOR	Model F01.600-102/600-15 Power Supply 400V/50Hz/3ph - 0.080 KW Motor Currents In:0.4, Is:0.5, Icc:1.5

RPS 60-S2-B1-CL	Pneumatic drive, Type: Bettis, RPS Function: single-acting Spring rotation direction: clockwise (CW) Control media interface: NAMUR G1/2" Temperature range: -20° ... +100°C Weight: 68kg
RPS 30-S2-B1-CL	Pneumatic drive, Type: Bettis, RPS Function: single-acting Spring rotation direction: clockwise (CW) Temperature range: -20° ... +100°C
RPS 120-S2-B1-CL	Pneumatic drive, Type: Bettis, RPS Function: single-acting Spring rotation direction: clockwise (CW)
ELGA-1.5KR + ICON 010/90-144	Operating time: 33 sec Voltage range: 3PH-400V Frequency: 50-60Hz Torque: 24000 Nm Limitation: S2-15 Protection class: Ex db h ia IIB T4 Gb - Ex h tb IIIC T135 C Db Temperature range: -20/+85°C (-4/+185°F) Electrical connection: N5 - 2x1"+1x1-1/2"+2x3/4"-(STD) Wiring diagram: WD85AT000 Flange: F30 Adaptation to valve: At Purchaser's care dimensions: 487,00x835,00x937,00mm Weight: 289,00 kg
RPS 60-S2-**-CL Rack and Pinion	Spring Return Pneumatic Actuator Ball Valve Pecos Spain Model: FIG.ZV - 2 piece body Connection type: Flanged RF Pressure class: Class600 Body material: Carbon steel A216 WCC Ball material: Stainless steel 1.4408 (CF8M) Seat material: PEEK, Stem material: XM-19, L: 432mm
Quick Exhaust Valve 2P285N0705	
Booster with Flow Regulator and	Bypass 2P271A15R2, BIFFI
RESISTANCE THERMOMETER	P0086814800
RPS 120 S2-C1-CL	Activator O-ring Set and Repair Kit
SEAL KIT ICON2000-030 (-55øC)	PART NUMBER 480030KSL4
WORM WHEEL	PART NUMBER 3800300050
WORM SHAFT,	PART NUMBER 3800300060
POSITION SHAFT	PART NUMBER 3800300110
DRIVE SLEEVE	PART NUMBER 3800300040