

## Bin Master

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Bin Master** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Bin Master T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">213-0020</a>	
<a href="#">399-0022</a>	
<a href="#">530-0486</a>	
<a href="#">530-0663</a>	
<a href="#">530-0736</a>	3DLEVELSCANNNER ELECTRONIC CARD ATEX/FM TYPE "MVL"
<a href="#">416-0687</a>	
<a href="#">530-0088</a>	
<a href="#">280-0060</a>	
<a href="#">Bbr-1</a>	
<a href="#">730-0626</a>	3DLEVELSCANNER-MVL IS FOR USE IN MULTIPLE SCANNER SYSTEMS THAT INCLUDE THE 3D VISUALIZATION
<a href="#">530-0791</a>	

<a href="#">730-0644</a>	SAME AS 3DLS-MVL WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">338-0035</a>	
<a href="#">530-0274</a>	
<a href="#">416-0466</a>	
<a href="#">530-0295</a>	
<a href="#">416-0313</a>	
<a href="#">730-0182</a>	MICROWAVE FLOW / NO FLOW MONITOR WITH REMOTE ELECTRONICS IN NEMA 4X ENCLOSURE, 230 VAC
<a href="#">416-0369</a>	
<a href="#">416-0560</a>	
<a href="#">530-0252</a>	
<a href="#">530-0271</a>	
<a href="#">388-0051</a>	
<a href="#">215-0146</a>	
<a href="#">416-0296</a>	
<a href="#">416-0548</a>	
<a href="#">730-5054</a>	
<a href="#">416-0504</a>	
<a href="#">730-5055</a>	
<a href="#">530-0270</a>	
<a href="#">356-0011</a>	
<a href="#">348-0012</a>	
<a href="#">255-0203</a>	
<a href="#">416-0616</a>	
<a href="#">730-0113</a>	
<a href="#">530-0476</a>	
<a href="#">416-0431</a>	
<a href="#">175-0017</a>	
<a href="#">530-0544</a>	
<a href="#">416-0110</a>	

<a href="#">730-0505</a>	
<a href="#">416-0651</a>	
<a href="#">730-5030</a>	
<a href="#">416-0312</a>	
<a href="#">416-0397</a>	
<a href="#">730-5085</a>	12 TO 30 VDC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">730-0637</a>	SAME AS 3DLS-S WITH FLOUROPOLYMER COATED HORN. NO HAZARDOUS LOCATION APPROVALS
<a href="#">730-0436</a>	
<a href="#">299-0571</a>	
<a href="#">530-0016</a>	
<a href="#">730-0302</a>	
<a href="#">530-0239</a>	
<a href="#">344-0006</a>	
<a href="#">416-0439</a>	
<a href="#">200-9008</a>	
<a href="#">416-0152</a>	
<a href="#">220-0022</a>	
<a href="#">730-0221</a>	MICROWAVE FLOW / NO FLOW MONITOR WITH OPEN REMOTE ELECTRONICS
<a href="#">416-0161</a>	
<a href="#">299-0417</a>	
<a href="#">730-0642</a>	SAME AS 3DLS-ML WITH FLOUROPOLYMER COATED HORN. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">285-0120</a>	
<a href="#">416-0547</a>	
<a href="#">530-0488</a>	30" STANDARD FLOUROPOLYMER SLEEVED PROBE, 1/2" NPT FITTING, 250F (120C) MAXIMUM TEMPERATURE
<a href="#">299-0423</a>	
<a href="#">530-0303</a>	
<a href="#">350-0059</a>	
<a href="#">730-5099</a>	

<a href="#">416-0453</a>	
<a href="#">416-0406</a>	
<a href="#">730-0475</a>	
<a href="#">280-0084</a>	
<a href="#">530-0197</a>	
<a href="#">530-0788</a>	
<a href="#">416-0514</a>	
<a href="#">530-0800</a>	
<a href="#">530-0534</a>	
<a href="#">530-0596</a>	
<a href="#">175-0223</a>	
<a href="#">730-0674</a>	MEDIA CONVERTER KIT IN NEMA 4X ENCLOSURE 10" X 8" X 4"
<a href="#">416-0508</a>	
<a href="#">292-0009</a>	
<a href="#">335-0071</a>	
<a href="#">530-0811</a>	
<a href="#">730-5153</a>	HIGH TEMPERATURE 2-WIRE GUIDED MICROWAVE LEVEL TRANSMITTER, 18-35 VDC, 4 TO 20 MA OUTPUT WITH HART
<a href="#">416-0387</a>	
<a href="#">530-0246</a>	
<a href="#">730-0255</a>	
<a href="#">416-0540</a>	
<a href="#">730-0613</a>	EBOB VER. 5.10 CONTROLLER SOFTWARE WITH MULTI SENSOR SUPPORT
<a href="#">530-0022</a>	
<a href="#">530-0228</a>	
<a href="#">416-0261</a>	
<a href="#">416-0520</a>	
<a href="#">730-0114</a>	
<a href="#">530-0564</a>	
<a href="#">416-0363</a>	

<a href="#">530-0482</a>	
<a href="#">530-0260</a>	
<a href="#">416-0424</a>	
<a href="#">730-0614</a>	
<a href="#">416-0509</a>	
<a href="#">Gr-Ii-Maxima</a>	
<a href="#">388-0049</a>	
<a href="#">730-0377</a>	12 TO 30 (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">730-0416</a>	12 TO 30 VDC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">299-0331</a>	
<a href="#">225-0005</a>	
<a href="#">338-0120</a>	
<a href="#">399-0023</a>	
<a href="#">280-0057</a>	
<a href="#">280-0068</a>	
<a href="#">730-0488</a>	
<a href="#">215-0151</a>	
<a href="#">530-0676</a>	
<a href="#">416-0162</a>	
<a href="#">375-0033</a>	
<a href="#">530-0707</a>	
<a href="#">416-0364</a>	
<a href="#">C-100</a>	
<a href="#">530-0200</a>	
<a href="#">220-0017</a>	
<a href="#">416-0383</a>	
<a href="#">416-0561</a>	
<a href="#">730-0392</a>	
<a href="#">175-0097</a>	
<a href="#">730-5021</a>	

<a href="#">730-0474</a>	
<a href="#">416-0324</a>	
<a href="#">299-0799</a>	
<a href="#">530-0620</a>	
<a href="#">530-0244</a>	
<a href="#">730-0311</a>	
<a href="#">416-0100</a>	
<a href="#">292-0040</a>	
<a href="#">416-0459</a>	
<a href="#">730-0663</a>	
<a href="#">201-9030</a>	
<a href="#">730-5131</a>	
<a href="#">292-0045</a>	
<a href="#">416-0505</a>	
<a href="#">730-0641</a>	SAME AS 3DLS-ML WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">175-0196</a>	
<a href="#">730-0517</a>	
<a href="#">350-0051</a>	
<a href="#">416-0555</a>	
<a href="#">530-0510</a>	
<a href="#">344-0004</a>	
<a href="#">110-0107</a>	
<a href="#">530-0202</a>	
<a href="#">530-0517</a>	
<a href="#">730-0673</a>	
<a href="#">530-0198</a>	
<a href="#">530-0221</a>	
<a href="#">299-0638</a>	
<a href="#">730-0504</a>	
<a href="#">175-0199</a>	

<a href="#">530-0535</a>	
<a href="#">416-0208</a>	
<a href="#">730-5129</a>	
<a href="#">416-0655</a>	
<a href="#">416-0115</a>	
<a href="#">299-0530</a>	
<a href="#">730-0512</a>	
<a href="#">730-0527</a>	
<a href="#">299-0736</a>	
<a href="#">730-0507</a>	
<a href="#">416-0473</a>	
<a href="#">730-0408</a>	115 VAC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">175-0110</a>	
<a href="#">299-0853</a>	
<a href="#">338-0114</a>	
<a href="#">530-0184</a>	
<a href="#">416-0594</a>	3DLEVELSCANNER 6' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">730-0640</a>	3DLEVELSCANNER-ML IS FOR USE IN MULTIPLE SCANNER SYSTEMS THAT DO NOT INCLUDE THE 3D VISUALIZATION
<a href="#">280-0054</a>	
<a href="#">340-0033</a>	
<a href="#">338-0112</a>	
<a href="#">730-5009</a>	
<a href="#">530-0174</a>	
<a href="#">730-0116</a>	
<a href="#">730-5073</a>	
<a href="#">299-0420</a>	
<a href="#">530-0264</a>	
<a href="#">328-0039</a>	
<a href="#">530-0785</a>	

<a href="#">299-0699</a>	
<a href="#">730-0648</a>	EACH MULTI-SCANNER SYSTEM REQUIRES A CONTROLLER THAT IS SUPPLIED WITH 3DVISION SOFTWARE. THE SOFTWARE
<a href="#">258-0092</a>	
<a href="#">416-0613</a>	
<a href="#">730-0522</a>	
<a href="#">530-0489</a>	
<a href="#">201-9035</a>	
<a href="#">Grp30</a>	
<a href="#">350-0060</a>	
<a href="#">299-0723</a>	
<a href="#">530-0103</a>	
<a href="#">416-0310</a>	
<a href="#">530-0242</a>	
<a href="#">299-0535</a>	
<a href="#">299-0615</a>	
<a href="#">530-0215</a>	
<a href="#">290-0102</a>	
<a href="#">416-0499</a>	
<a href="#">530-0555</a>	
<a href="#">530-0524</a>	
<a href="#">730-5083</a>	115 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">344-0003</a>	
<a href="#">730-5170</a>	THE MODEL BM-30 T2 IS A RELIABLE, COMPACT, TWO-PIECE PARTICULATE EMISSIONS MONITOR
<a href="#">730-0136</a>	PROCAP SERIES STANDARD REMOTE CAPACITANCE PROBES
<a href="#">530-0233</a>	
<a href="#">220-0188</a>	
<a href="#">Procapii24</a>	
<a href="#">730-0298</a>	
<a href="#">730-0567</a>	



<a href="#">530-0721</a>	
<a href="#">730-5106</a>	230 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">380-0054</a>	
<a href="#">730-5151</a>	HIGH TEMPERATURE 2-WIRE GUIDED MICROWAVE LEVEL TRANSMITTER, 18-35 VDC, 4 TO 20 MA OUTPUT WITH HART, PROCESS TEMPERATURE FROM
<a href="#">730-5056</a>	
<a href="#">730-0513</a>	
<a href="#">549014-1865</a>	
<a href="#">344-0010</a>	
<a href="#">730-0515</a>	
<a href="#">299-0639</a>	
<a href="#">416-0035</a>	
<a href="#">530-0611</a>	3DLEVELSCANNNER ELECTRONIC CARD ATEX/FM TYPE "S"
<a href="#">530-0232</a>	
<a href="#">416-0563</a>	
<a href="#">530-0091d</a>	
<a href="#">416-0496</a>	
<a href="#">175-0206</a>	
<a href="#">292-0046</a>	
<a href="#">344-0011</a>	
<a href="#">175-0142</a>	
<a href="#">175-0093</a>	
<a href="#">416-0421</a>	
<a href="#">416-0456</a>	
<a href="#">730-0021</a>	
<a href="#">730-0653</a>	
<a href="#">299-0537</a>	
<a href="#">165-0011</a>	
<a href="#">299-0411</a>	
HAZARDOUS LOCATION CSA APPROVED CLASS II, DIV. 2,	

<a href="#">175-0232</a>	GROUPS F G (FOR 2-PIECE CONFIGURATION)
<a href="#">730-0431</a>	
<a href="#">299-0682</a>	
<a href="#">730-0115</a>	
<a href="#">530-0737</a>	3DLEVELSCANNNER ELECTRONIC CARD ATEX/FM TYPE "ML"
<a href="#">530-0325</a>	
<a href="#">416-0481</a>	
<a href="#">7305038c1b5m1hpa</a>	SENSOR
<a href="#">338-0033</a>	
<a href="#">530-0502</a>	
<a href="#">416-0435</a>	
<a href="#">730-0257</a>	
<a href="#">213-0021</a>	
<a href="#">220-0364</a>	
<a href="#">150-5009</a>	
<a href="#">299-0620</a>	
<a href="#">272-0079</a>	
<a href="#">730-5078</a>	115 VAC (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">416-0078</a>	
<a href="#">213-0019</a>	
<a href="#">303-0009</a>	
<a href="#">303-0008</a>	
<a href="#">730-5107</a>	230 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">730-0638</a>	SAME AS 3DLS-M WITH FLOUROPOLYMER COATED HORN. NO HAZARDOUS LOCATION APPROVALS
<a href="#">730-5072</a>	
<a href="#">730-0293</a>	
<a href="#">730-5053</a>	
<a href="#">730-5144</a>	12 TO 30 VDC (SMARTSONIC SANITARY MINI LEVEL TRANSMITTER WITH 4-20 MA OUTPUT)
<a href="#">175-0188</a>	

<a href="#">416-0336</a>	
<a href="#">299-0416</a>	
<a href="#">145-9025</a>	
<a href="#">730-5047</a>	
<a href="#">530-0312-B</a>	
<a href="#">530-0514</a>	RADAR EXPLOSION PROOF STAINLESS STEEL HOUSING
<a href="#">299-0612</a>	
<a href="#">530-0520</a>	
<a href="#">280-0085</a>	
<a href="#">292-0041</a>	
<a href="#">299-0494</a>	
<a href="#">530-0108</a>	
<a href="#">730-0497</a>	
<a href="#">730-0528</a>	
<a href="#">730-0433</a>	
<a href="#">530-0234</a>	
<a href="#">730-0197</a>	
<a href="#">205-0024</a>	
<a href="#">416-0153</a>	
<a href="#">416-0593</a>	3DLEVELSCANNER 4' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">530-0235</a>	
<a href="#">299-0532</a>	
<a href="#">530-0526</a>	
<a href="#">730-0404</a>	115 VAC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">730-0313</a>	
<a href="#">530-0104</a>	
<a href="#">530-0503</a>	
<a href="#">299-0835</a>	
<a href="#">Procapii</a>	

<a href="#">530-0214</a>	
<a href="#">416-0155</a>	
<a href="#">730-0625</a>	
<a href="#">730-0667</a>	
<a href="#">348-0014</a>	
<a href="#">730-0676</a>	
<a href="#">730-0480</a>	SMARTBOB2 MOMENTUM UNIVERSAL COMMUNICATION MODULE
<a href="#">328-0055</a>	
<a href="#">353-0041</a>	
<a href="#">200-1004</a>	
<a href="#">530-0546</a>	
<a href="#">730-0611</a>	12 TO 28 (SMARTSONIC TWO-WIRE HART LEVEL TRANSMITTER WITH 4-20 MA OUTPUT)
<a href="#">530-0287</a>	
<a href="#">530-0196</a>	
<a href="#">416-0124</a>	
<a href="#">255-0172</a>	
<a href="#">530-0300</a>	
<a href="#">530-0222</a>	
<a href="#">220-0016</a>	
<a href="#">344-0005</a>	
<a href="#">530-0229</a>	
<a href="#">730-0250</a>	
<a href="#">730-5080</a>	12 TO 30 (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">416-0602</a>	3DLEVELSCANNER 6' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">999-1001*</a>	
<a href="#">205-0181</a>	
<a href="#">530-0277</a>	
<a href="#">730-0355</a>	
<a href="#">350-0058</a>	

<a href="#">730-5077</a>	
<a href="#">416-0650</a>	
<a href="#">730-5101</a>	
<a href="#">258-0091</a>	
<a href="#">730-0482</a>	24 LIGHT PANEL, 115 VAC, COMPLETE WITH LED LIGHTS AND BUZZER
<a href="#">530-0250</a>	
<a href="#">201-9010</a>	
<a href="#">416-0495</a>	
<a href="#">730-0639</a>	SAME AS 3DLS-MV WITH FLOUROPOLYMER COATED HORN. NO HAZARDOUS LOCATION APPROVALS
<a href="#">292-0049</a>	
<a href="#">530-0212</a>	
<a href="#">416-0297</a>	
<a href="#">730-5166</a>	
<a href="#">530-0513</a>	
<a href="#">530-0101</a>	
<a href="#">730-5161</a>	THE MODEL BM-30 T1 IS A RELIABLE, COMPACT, ONE-PIECE PARTICULATE EMISSIONS TRANSMITTER AND FILTER
<a href="#">416-0634</a>	
<a href="#">530-0720</a>	
<a href="#">290-0107</a>	
<a href="#">416-0365</a>	
<a href="#">530-0259</a>	
<a href="#">145-0045</a>	
<a href="#">416-0522</a>	
<a href="#">530-0070</a>	
<a href="#">530-0495</a>	
<a href="#">285-0125</a>	
<a href="#">530-0102</a>	
<a href="#">299-0607</a>	
<a href="#">416-0546</a>	

<a href="#">350-0054</a>	
<a href="#">530-0543</a>	
<a href="#">530-0210</a>	
<a href="#">328-0064</a>	
<a href="#">416-0607</a>	
<a href="#">299-0640</a>	
<a href="#">530-0084</a>	
<a href="#">Bmt</a>	
<a href="#">730-0410</a>	
<a href="#">730-5071</a>	
<a href="#">416-0614</a>	
<a href="#">730-5152</a>	2-WIRE GUIDED MICROWAVE LEVEL TRANSMITTER, 18-35 VDC, 4 TO 20 MA OUTPUT WITH HART, PROCESS TEMPERATURE FROM -22F TO 195F
<a href="#">280-0004</a>	
<a href="#">416-0465</a>	
<a href="#">730-0544</a>	
<a href="#">201-9028</a>	
<a href="#">115-0025</a>	
<a href="#">175-0123</a>	
<a href="#">416-0566</a>	
<a href="#">Sbrx-Ii</a>	INVENTORY MONITORING SYSTEM 115VAC 60HZ .22A
<a href="#">416-0653</a>	
<a href="#">730-0326</a>	
<a href="#">730-0518</a>	
<a href="#">416-0686</a>	
<a href="#">299-0415</a>	
<a href="#">416-0298</a>	
<a href="#">730-0534</a>	
<a href="#">270-0023</a>	
<a href="#">530-0512</a>	

<a href="#">530-0508</a>	
<a href="#">530-0179</a>	
<a href="#">416-0154</a>	
<a href="#">416-0487</a>	
<a href="#">416-0603</a>	3DLEVELSCANNER 10' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">730-5096</a>	
<a href="#">220-0287</a>	
<a href="#">730-5038</a>	MICROPROCESSOR-DRIVEN SMARTBOB2 REMOTE SENSOR, 115 VAC, CORROSION-RESISTANT POLYCARBONATE ENCLOSURE, AIR
<a href="#">730-0006</a>	
<a href="#">730-0635</a>	SAME AS 3DLS-M, WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS
<a href="#">299-0619</a>	
<a href="#">730-0003</a>	
<a href="#">730-0439</a>	
<a href="#">730-0002</a>	
<a href="#">530-0483</a>	
<a href="#">416-0376</a>	
<a href="#">299-0670</a>	
<a href="#">730-0178</a>	
<a href="#">730-0448</a>	
<a href="#">530-0257</a>	
<a href="#">416-0402</a>	
<a href="#">303-0010</a>	
<a href="#">220-0212</a>	
<a href="#">530-0485</a>	
<a href="#">730-5102</a>	
<a href="#">730-0438</a>	
<a href="#">225-0003</a>	
<a href="#">299-0419</a>	

<a href="#">530-0554</a>	
<a href="#">416-0033</a>	
<a href="#">730-0117</a>	
<a href="#">416-0478</a>	
<a href="#">730-0352</a>	
<a href="#">730-0450</a>	12 LIGHT PANEL, 115 VAC, COMPLETE WITH LED LIGHTS AND BUZZER
<a href="#">Fds-1000</a>	
<a href="#">416-0461</a>	
<a href="#">318-0168</a>	
<a href="#">280-0071</a>	
<a href="#">340-0090</a>	
<a href="#">730-0023</a>	
<a href="#">730-0119</a>	
<a href="#">530-0248</a>	
<a href="#">416-0518</a>	
<a href="#">730-0449</a>	8 LIGHT PANEL, 115 VAC, COMPLETE WITH LED LIGHTS AND BUZZER
<a href="#">165-0028</a>	
<a href="#">999-1000*</a>	
<a href="#">299-0422</a>	
<a href="#">328-0062</a>	
<a href="#">530-0634</a>	
<a href="#">299-0410</a>	
<a href="#">270-0024</a>	
<a href="#">730-5133</a>	VIBRATING ROD LEVEL SENSOR WITH FLEXIBLE CABLE EXTENSION, 20 TO 250V AC/DC
<a href="#">730-0523</a>	
<a href="#">299-0534</a>	
<a href="#">416-0500</a>	
<a href="#">275-0010</a>	
<a href="#">299-0536</a>	



<a href="#">730-0562</a>	3DLP-R-GSM, BINMASTER REMOTE 3DLINKPRO WITH GPRS CELLULAR MODEM
<a href="#">338-0118</a>	
<a href="#">730-0559</a>	3DLEVELSCANNER-S WITH 7.67" DIAMETER HORN, 20-36 VDC, 4-20 MA OUTPUT / HART PROTOCOL, AND RS-485
<a href="#">338-0008</a>	
<a href="#">416-0554</a>	
<a href="#">220-0187</a>	
<a href="#">299-0531</a>	
<a href="#">530-0505</a>	36" STANDARD FLOUROPOLYMER SLEEVED PROBE, 1/2" NPT FITTING, 250F (120C) MAXIMUM TEMPERATURE
<a href="#">730-5079</a>	115 VAC (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">530-0504</a>	20" STANDARD FLOUROPOLYMER SLEEVED PROBE, 1/2" NPT FITTING, 250F (120C) MAXIMUM TEMPERATURE
<a href="#">299-0424</a>	
<a href="#">338-0111</a>	
<a href="#">299-0588</a>	
<a href="#">730-0180</a>	
<a href="#">416-0474</a>	
<a href="#">416-0430</a>	
<a href="#">416-0506</a>	
<a href="#">730-0432</a>	
<a href="#">416-0660</a>	
<a href="#">299-0614</a>	
<a href="#">730-0532</a>	
<a href="#">213-0025</a>	
<a href="#">730-0533</a>	
<a href="#">730-0483</a>	PROCAP SERIES STANDARD REMOTE CAPACITANCE PROBES
<a href="#">416-0472</a>	
<a href="#">388-0037</a>	
<a href="#">213-0007</a>	
<a href="#">730-0020</a>	
<a href="#">299-0004</a>	

<a href="#">416-0592</a>	3DLEVELSCANNER 2' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">730-5076</a>	
<a href="#">730-0669</a>	SMARTSONIC TWO-WIRE HART LEVEL TRANSMITTER
<a href="#">730-0418</a>	
<a href="#">730-5010</a>	SINGLE PIECE, TRIBOELECTRIC BROKEN BAG DETECTOR, 115 VAC
<a href="#">299-0407</a>	
<a href="#">350-0039</a>	
<a href="#">416-0595</a>	3DLEVELSCANNER 10' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">299-0634</a>	
<a href="#">730-5105</a>	230 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">416-0475</a>	
<a href="#">730-0044</a>	
<a href="#">416-0599</a>	3DLEVELSCANNER 10' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">730-0042</a>	
<a href="#">220-0368</a>	
<a href="#">290-0071</a>	
<a href="#">730-5098</a>	
<a href="#">299-0009</a>	
<a href="#">530-0199</a>	
<a href="#">730-0312</a>	
<a href="#">730-0318</a>	
<a href="#">416-0476</a>	
<a href="#">416-0480</a>	
<a href="#">530-0158</a>	
<a href="#">730-5028</a>	
<a href="#">730-0536</a>	
<a href="#">530-0506</a>	4-20 MA OUTPUT
<a href="#">175-0230</a>	

<a href="#">730-0508</a>	
<a href="#">730-5097</a>	
<a href="#">530-0786</a>	
<a href="#">416-0419</a>	
<a href="#">280-0005</a>	
<a href="#">730-5123</a>	
<a href="#">530-0168</a>	
<a href="#">530-0579</a>	
<a href="#">730-5069</a>	
<a href="#">530-0733</a>	
<a href="#">416-0551</a>	
<a href="#">201-9033</a>	
<a href="#">530-0321</a>	
<a href="#">416-0510</a>	
<a href="#">730-5039</a>	MICROPROCESSOR-DRIVEN SMARTBOB2 REMOTE SENSOR, 230 VAC, CORROSION-RESISTANT POLYCARBONATE ENCLOSURE, AIR INLET
<a href="#">530-0267</a>	
<a href="#">730-0098</a>	
<a href="#">530-0183</a>	
<a href="#">175-0237</a>	
<a href="#">272-0084</a>	
<a href="#">292-0001</a>	
<a href="#">730-0354</a>	
<a href="#">530-0553</a>	
<a href="#">416-0160</a>	
<a href="#">175-0239</a>	
<a href="#">416-0379</a>	
<a href="#">730-5154</a>	MICROPROCESSOR-DRIVEN SMARTBOB2 AO REMOTE SENSOR, 115 VAC, CORROSION-RESISTANT POLYCARBONATE ENCLOSURE
<a href="#">530-0523</a>	

<a href="#">299-0064</a>	
<a href="#">530-0243</a>	
<a href="#">416-0341</a>	
<a href="#">530-0487</a>	15" STANDARD FLOUROPOLYMER SLEEVED PROBE, 1/2" NPT FITTING, 250F (120C) MAXIMUM TEMPERATURE
<a href="#">530-0072</a>	
<a href="#">530-0787</a>	
<a href="#">299-0010</a>	
<a href="#">730-5070</a>	115 VAC (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">299-0421</a>	
<a href="#">344-0013</a>	
<a href="#">530-0735</a>	
<a href="#">175-0098</a>	
<a href="#">299-0412</a>	
<a href="#">225-0004</a>	
<a href="#">730-5159</a>	
<a href="#">416-0598</a>	3DLEVELSCANNER 6' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">416-0657</a>	
<a href="#">730-0412</a>	12 TO 30 VDC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">730-0633</a>	
<a href="#">530-0268</a>	
<a href="#">416-0080</a>	
<a href="#">730-0004</a>	
<a href="#">299-0641</a>	
<a href="#">530-0211</a>	
<a href="#">730-5124</a>	
<a href="#">416-0295</a>	
<a href="#">260-0400</a>	
<a href="#">200-1007</a>	
<a href="#">299-0418</a>	

<a href="#">416-0617</a>	
<a href="#">416-0377</a>	
<a href="#">530-0236</a>	
<a href="#">730-0652</a>	SAME AS 3DLS-ML WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">530-0529</a>	
<a href="#">299-0575</a>	
<a href="#">388-0040</a>	
<a href="#">344-0001</a>	
<a href="#">299-0584</a>	
<a href="#">220-0370</a>	
<a href="#">299-0609</a>	
<a href="#">323-0024</a>	
<a href="#">175-0107</a>	
<a href="#">299-0414</a>	
<a href="#">730-0390</a>	
<a href="#">530-0017</a>	
<a href="#">416-0454</a>	
<a href="#">416-0511</a>	
<a href="#">530-0273</a>	
<a href="#">730-0668</a>	
<a href="#">416-0601</a>	3DLEVELSCANNER 4' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">530-0254</a>	
<a href="#">730-0561</a>	3DLEVELSCANNER-MV WITH 7.67" DIAMETER HORN, 20-36 VDC, 4-20 MA OUTPUT / HART PROTOCOL, AND RS-485
<a href="#">388-0039</a>	
<a href="#">175-0127</a>	
<a href="#">730-0045</a>	
<a href="#">416-0418</a>	
<a href="#">530-0571</a>	
<a href="#">350-0052</a>	

<a href="#">416-0501</a>	
<a href="#">175-0178</a>	
<a href="#">730-0096</a>	
<a href="#">730-0350</a>	
<a href="#">730-0363</a>	115 VAC (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">416-0639</a>	
<a href="#">730-0537</a>	EBOB CONTROLLER SOFTWARE WITH GRAPHICAL DISPLAY AND INVENTORY HISTORY IN A SQL DATABASE
<a href="#">416-0597</a>	3DLEVELSCANNER 4' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">730-5038-C1-B5-M3-H30</a>	MICROPROCESSOR SMARTBOB-II REMOTE SENSOR 110VAC
<a href="#">530-0613</a>	3DLEVELSCANNER ELECTRONIC CARD ATEX/FM TYPE "MV"
<a href="#">299-0688</a>	
<a href="#">730-0469</a>	
<a href="#">530-0387-A</a>	
<a href="#">416-0552</a>	
<a href="#">917-0001</a>	
<a href="#">730-5075</a>	
<a href="#">416-0558</a>	
<a href="#">730-5167</a>	
<a href="#">530-0237</a>	
<a href="#">416-0463</a>	
<a href="#">530-0069</a>	
<a href="#">730-0646</a>	ACOUSTIC LEVEL SENSOR RL, 4-20 MA AND RS-485 OUTPUT. FOUR-WIRE 24 VDC POWER
<a href="#">416-0460</a>	
<a href="#">225-0031</a>	
<a href="#">416-0618</a>	
<a href="#">730-0524</a>	
<a href="#">530-0247</a>	
<a href="#">416-0374</a>	
<a href="#">416-0265</a>	

<a href="#">175-0198</a>	
<a href="#">530-0695</a>	
<a href="#">530-0511</a>	
<a href="#">530-0552</a>	
<a href="#">530-0082</a>	
<a href="#">730-5084</a>	12 TO 30 VDC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">730-0560</a>	3DLEVELSCANNER-M WITH 7.67" DIAMETER HORN, 20-36 VDC, 4-20 MA OUTPUT / HART PROTOCOL, AND RS-485
<a href="#">416-0503</a>	
<a href="#">730-0519</a>	
<a href="#">398-0090</a>	
<a href="#">280-0070</a>	
<a href="#">175-0118</a>	
<a href="#">416-0600</a>	3DLEVELSCANNER 2◆◆ NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">416-0521</a>	
<a href="#">530-0477</a>	
<a href="#">730-0451</a>	16 LIGHT PANEL, 115 VAC, COMPLETE WITH LED LIGHTS AND BUZZER
<a href="#">416-0515</a>	
<a href="#">175-0179</a>	
<a href="#">416-0477</a>	
<a href="#">175-0109</a>	
<a href="#">416-0652</a>	
<a href="#">730-5050</a>	PARTICULATE MONITOR CONTROL UNIT, 24 VDC, 50/60 HZ, TWO SPST RELAY OUTPUTS, NEMA 4X ALUMI-
<a href="#">416-0220</a>	
<a href="#">Vr-21-Spdt</a>	VIBRATING ROD SENSOR 20/250VAC 3VA 5AMP
<a href="#">299-0613</a>	
<a href="#">272-0085</a>	
<a href="#">270-0022</a>	
<a href="#">730-0526</a>	

<a href="#">530-0276</a>	
<a href="#">416-0407</a>	
<a href="#">416-0085</a>	
<a href="#">416-0432</a>	
<a href="#">530-0213</a>	
<a href="#">416-0513</a>	
<a href="#">530-0296</a>	
<a href="#">530-0515</a>	
<a href="#">212-0010</a>	
<a href="#">730-0351</a>	
<a href="#">416-0571</a>	
<a href="#">175-0012</a>	
<a href="#">280-0018</a>	
<a href="#">299-0564</a>	
<a href="#">530-0245</a>	
<a href="#">299-0667</a>	
<a href="#">730-0675</a>	
<a href="#">730-0643</a>	SAME AS 3DLS-MVL WITH FLOUROPOLYMER COATED HORN. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">220-0275</a>	
<a href="#">730-0437</a>	
<a href="#">730-5027</a>	
<a href="#">530-0570</a>	
<a href="#">270-0063</a>	
<a href="#">730-5110</a>	
<a href="#">299-0413</a>	
<a href="#">730-5022</a>	
<a href="#">530-0265</a>	
<a href="#">530-0241</a>	
<a href="#">730-0632</a>	



<a href="#">416-0207</a>	
<a href="#">299-0533</a>	
<a href="#">730-5150</a>	2-WIRE GUIDED MICROWAVE LEVEL TRANSMITTER, 18-35 VDC, 4 TO 20 MA OUTPUT WITH HART, PROCESS TEMPERATURE FROM -22F TO 195F
<a href="#">730-0521</a>	
<a href="#">730-0662</a>	
<a href="#">530-0530</a>	
<a href="#">530-0288</a>	
<a href="#">416-0642</a>	
<a href="#">416-0367</a>	
<a href="#">416-0596</a>	3DLEVELSCANNER 2' NECK EXTENSION KIT, CONTAINS TOP AND BOTTOM STAINLESS STEEL FITTINGS
<a href="#">530-0225</a>	
<a href="#">416-0266</a>	
<a href="#">730-0636</a>	SAME AS 3DLS-MV WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS
<a href="#">290-0090</a>	
<a href="#">299-0408</a>	
<a href="#">730-5108</a>	12 TO 30 VDC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">730-0181</a>	MICROWAVE FLOW / NO FLOW MONITOR WITH REMOTE ELECTRONICS IN NEMA 4X ENCLOSURE, 110 VAC
<a href="#">730-0414</a>	12 TO 30 VDC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">730-5094</a>	
<a href="#">730-0146</a>	PROCAP SERIES STANDARD FLUSH MOUNT CAPACITANCE PROBES
<a href="#">299-0409</a>	
<a href="#">Bmrx115</a>	
<a href="#">730-0634</a>	SAME AS 3DLS-S WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS
<a href="#">350-0056</a>	
<a href="#">175-0121</a>	
<a href="#">348-0016</a>	

<a href="#">416-0046</a>	
<a href="#">530-0612</a>	3DLEVELSCANNNER ELECTRONIC CARD ATEX/FM TYPE "M"
<a href="#">530-0012</a>	
<a href="#">730-0577</a>	
<a href="#">416-0340</a>	
<a href="#">416-0464</a>	
<a href="#">416-0396</a>	
<a href="#">530-0509</a>	
<a href="#">730-5156</a>	MICROPROCESSOR-DRIVEN SMARTBOB2 AO REMOTE SENSOR, 230 VAC, CORROSION-RESISTANT POLYCARBONATE ENCLOSURE
<a href="#">530-0146</a>	
<a href="#">220-0021</a>	
<a href="#">730-5103</a>	
<a href="#">530-0599</a>	
<a href="#">416-0517</a>	
<a href="#">730-5162</a>	THE MODEL BM-30 T2 IS A RELIABLE, COMPACT, TWO-PIECE PARTICULATE EMISSIONS MONITOR AND FILTER
<a href="#">530-0258</a>	
<a href="#">730-0001</a>	
<a href="#">730-0506</a>	
<a href="#">280-0061</a>	
<a href="#">730-0110</a>	
<a href="#">530-0256</a>	
<a href="#">730-5049</a>	PARTICULATE MONITOR CONTROL UNIT, 120/230 VAC, 50/60 HZ, TWO SPST RELAY OUTPUTS, NEMA 4X
<a href="#">730-5074</a>	
<a href="#">530-0240</a>	
<a href="#">416-0373</a>	
<a href="#">530-0042</a>	
<a href="#">299-0610</a>	
<a href="#">730-0443</a>	

<a href="#">165-0002</a>	
<a href="#">416-0612</a>	
<a href="#">220-0066</a>	
<a href="#">730-5081</a>	12 TO 30 (SMARTSONIC LEVEL TRANSMITTER)
<a href="#">730-5104</a>	115 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">398-0533</a>	
<a href="#">201-9029</a>	
<a href="#">416-0565</a>	
<a href="#">280-0035</a>	
<a href="#">730-0591</a>	EACH MULTI-SCANNER SYSTEM REQUIRES A CONTROLLER THAT IS SUPPLIED WITH 3DVISION SOFTWARE.
<a href="#">730-0647</a>	SAME AS 3DLS-RL WITH EXTENDED TEMPERATURE UP TO 365F. NO HAZARDOUS LOCATION APPROVALS.
<a href="#">730-0498</a>	
<a href="#">416-0507</a>	
<a href="#">165-0026</a>	
<a href="#">220-0366</a>	
<a href="#">530-0662</a>	
<a href="#">416-0557</a>	
<a href="#">730-5122</a>	
<a href="#">416-0519</a>	
<a href="#">730-0525</a>	
<a href="#">175-0083</a>	
<a href="#">285-0132</a>	
<a href="#">530-0194</a>	
<a href="#">416-0497</a>	
<a href="#">530-0310</a>	
<a href="#">212-0038</a>	
<a href="#">303-0011</a>	
<a href="#">290-0069</a>	
<a href="#">730-5100</a>	

<a href="#">530-0531</a>
<a href="#">165-0014</a>
<a href="#">165-0029</a>
<a href="#">299-0735</a>
<a href="#">416-0384</a>
<a href="#">220-0322</a>
<a href="#">530-0238</a>
<a href="#">730-0256</a>
<a href="#">280-0072</a>
<a href="#">530-0674</a>
<a href="#">299-0681</a>
<a href="#">530-0094</a>
<a href="#">Bmrx</a>
<a href="#">530-0180</a>
<a href="#">299-0616</a>
<a href="#">416-0654</a>
<a href="#">Rcd-25-250v-Ac</a>
<a href="#">730-0202</a>
<a href="#">530-0013</a>
<a href="#">730-0292</a>
<a href="#">416-0502</a>
<a href="#">299-0637</a>
<a href="#">730-0005</a>
<a href="#">730-5029</a>
<a href="#">530-0649</a>
<a href="#">530-0711</a>
<a href="#">416-0283</a>
<a href="#">730-0099</a>
<a href="#">356-0010</a>
<a href="#">730-0479</a>
PROCAP SERIES STANDARD REMOTE CAPACITANCE PROBES

<a href="#">416-0590</a>	
<a href="#">730-0568</a>	
<a href="#">299-0679</a>	
<a href="#">730-0481</a>	20 LIGHT PANEL, 115 VAC, COMPLETE WITH LED LIGHTS AND BUZZER
<a href="#">416-0059</a>	
<a href="#">416-0545</a>	
<a href="#">530-0044</a>	
<a href="#">530-0701</a>	
<a href="#">730-5011</a>	SINGLE PIECE, TRIBOELECTRIC BROKEN BAG DETECTOR, 230 VAC
<a href="#">175-0181</a>	
<a href="#">530-0614</a>	
<a href="#">530-0619</a>	
<a href="#">299-0636</a>	
<a href="#">730-0406</a>	115 VAC (SMARTSONIC SANITARY LEVEL TRANSMITTER WITH 4 -20 MA OUTPUT)
<a href="#">292-0036</a>	
<a href="#">175-0099</a>	
<a href="#">530-0749</a>	
<a href="#">730-0489</a>	
<a href="#">530-0249</a>	
<a href="#">530-0255</a>	
<a href="#">398-0543</a>	
<a href="#">416-0311</a>	
<a href="#">416-0462</a>	
<a href="#">220-0373</a>	EXPLOSION PROOF,CSA APPROVED CLASS I, II III, DIV I II, ALL GROUPS, INTRINSICALLY SAFE
<a href="#">730-0514</a>	
<a href="#">348-0009</a>	
<a href="#">730-5158</a>	
<a href="#">338-0113</a>	

<a href="#">380-0058</a>	
<a href="#">416-0109</a>	
<a href="#">416-0323</a>	
<a href="#">730-0043</a>	
<a href="#">530-0653</a>	
<a href="#">730-0598</a>	BINMASTER 3D MULTIVISION SOFTWARE WORKS IN CONJUNCTION WITH ALL MODELS OF THE 3DLEVELSCANNER SENSORS
<a href="#">730-5092</a>	VIBRATING ROD LEVEL SENSOR, 20 TO 250V AC/DC, HIGH TEMP PROBE ASSEMBLY FOR MAXIMUM PROCESSTEMPERATURE 480F (250C). MUST ADD ROD PIPE EXTENSION BELOW
<a href="#">416-0375</a>	
<a href="#">416-0325</a>	
<a href="#">530-0272</a>	
<a href="#">530-0231</a>	
<a href="#">530-0182</a>	
<a href="#">530-0251</a>	
<a href="#">398-0093</a>	
<a href="#">201-9034</a>	
<a href="#">416-0394</a>	
<a href="#">416-0498</a>	
<a href="#">110-0048</a>	
<a href="#">730-5082</a>	115 VAC (SMARTWAVE PULSE RADAR TRANSMITTER 6.3 GHZ WITH 4-20 MA OUTPUT)
<a href="#">730-5136</a>	
<a href="#">730-0520</a>	
<a href="#">730-0353</a>	
<a href="#">416-0380</a>	
<a href="#">416-0467</a>	
<a href="#">416-0556</a>	
<a href="#">299-0624</a>	
<a href="#">530-0266</a>	
<a href="#">530-0185</a>	

<a href="#">530-0633</a>
<a href="#">350-0049</a>
<a href="#">416-0294</a>
<a href="#">350-0053</a>
<a href="#">730-0022</a>
<a href="#">530-0577</a>
<a href="#">730-5086</a>
<a href="#">175-0227</a>
<a href="#">416-0378</a>
<a href="#">416-0641</a>
<a href="#">416-0259</a>
<a href="#">175-0120</a>
<a href="#">212-0042</a>