

B&K - Br¼el&Kjaer Vibro

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

B&K - Br¼el&Kjaer Vibro Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız B&K - Br¼el&Kjaer Vibro T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
AS-022	Vibration acceleration sensor For stationary use, 5 m integral cable open cable end, no cable protection Sensitivity 100 mV / g Temperature range -50 ... + 125 ° C Sensor supply -24 VDC Order code: AS-022 Material no .: C001346.01 Stat. Goods no .: 9031 90 00 Country of origin: DE
VS-069	Vibration speed sensor Standard for stationary use, 5 m cable open end With the following configuration: Temperature range: -40 ... + 80 ° C Measurement direction: vertical Cable protection: with steel protection hose Order code: VS-069 Material no .: X081242.04 9031 90 00 DE
VST-100 KIT 1	with accessories: - Handheld meter VST-100 - Carrying case AC-7316 - Docking station AC-7312 - Protective cover AC-7313 - Holding magnet AC-276 - Coiled cord AC-438 - AS-063 acceleration sensor Material no.: C107885.001
VST-100 KIT 2	with accessories: - Handheld meter VST-100 - Carrying case AC-7316 - Docking station AC-7312 - Protective cover AC-7313 - Holding magnet AC-276 - Coiled cord AC-438 - AS-063 acceleration sensor - Report & Route Manager PC Software REO/VST-100 Material no.: C107885.002
Type 2270-S	
Force Transducer TYPE8230	
Power Amplifier TYPE2718	
VIBRATION EXCITER TYPE4809	
Type:VS-068	M/N: X08124207 S/N: 00016101
VS-068 vibration velocity sensor	Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40...+80°C Measuring direction: horizontal Cable length K: 5 m, open end Cable protection: with steel protective hose Order code: VS-068 Material no.: X081242.07

VS-069 vibration velocity sensor	Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40...+80°C Measuring direction: vertical Cable length K: 5 m, open end Cable protection: with steel protective hose Order code: VS-069 Material no.: X081242.04
VIBROCONTROL 960 Single-channel	vibration monitoring system for connecting vibration velocity sensors Power supply +24 VDC Order code: VC-960 Material no.: C106383.001
VS-068	Vibration velocity sensor Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40...+80°C Measuring direction: horizontal Cable length K: 5 m, open end Cable protection: with steel protective cover Order code: VS-068 Material no.: X081242.07
VS-069	Vibration velocity sensor Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40...+80°C Measuring direction: vertical Cable length K: 5 m, open end Cable protection: with steel protective hose Order code: VS-069 Material no.: X081242.04
Vs-068	Vibration speed sensor Standard for stationary use, 5 m cable open end With the following configuration: Temperature range: -40 ... + 80 ° C Measurement direction: horizontal Cable protection: with steel protection hose Order code: VS-068 Material no .: X081242.07
Vs-069	Vibration velocity Sensor
As-062/050/0	Vibration acceleration sensor For stationary use, 5 m integral cable open cable end, no cable protection Sensitivity 100 mV / g Temperature range -50 ... + 125oC Sensor Supply Constant Current (CCS) Order code: AS-062/050/0 Material no .: C006549.01 Stat. Product No .: 9031 90 00 Country of origin: DE
Vs-069,M/N:X08124204 - Vibrasyon Sens¼r¼	