

Bk Precision

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Bk Precision Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Bk Precision Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Bk8540	ELEKTRONISCHE DC-LAST, 60V, 30A, 150W
BK 8540	
545	TESTER
2160a Cal D	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60, ROHS COMPLIANT: NA
9151	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:20V, OUTP
2190b Cal Du	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:1
8540cald	PROG DC ELECTRONIC LOAD 60V 150W, DC LOAD TYPE:FIXED, OPERATING VOLTAGE RANGE:0V
2160a	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:60MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI

9173	POWER SUPPLY, PROGRAMMABLE, 2 O/P, 0-20V, 5A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAG
8514	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, PRODUCT RANGE:8500 SERIES, POWER RATING:1200W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERAT
8520	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:120V, OPERATING CURRENT MAX:240
Vsp4030	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:40V, OUTPUT CURRENT:30A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
889bcald	BENCH LCR/ESR METER WITH COMPONENT TEST, EXTERNAL HEIGHT:150MM, EXTERNAL WIDTH:2
8522	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:500V, OPERATING CURRENT MAX:120
8500refurb	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE RANGE:0.1V TO 120V, OPERATING CURRENT RANGE:30A, POWER RATING:300W, EXT
1443	OSCILLOSCOPE
4040acal	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION
9171	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-20V, 5A, 100W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAG
1541b	OSCILLOSCOPE
2540	DIGITAL STORAGE OSCILLOSCOPE, SCOPE BANDWIDTH:60 MHZ, SCOPE CHANNELS:2, SCOPE TYPE:DIGITAL, SERIES:254X SERIES, RISE TIME:5.83NS, SAMPLE RATE:1 GSA/S
2160a Cal Du	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60
2658a	ANALYZER, SPECTRUM, 50KHZ TO 8.5GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 8.5GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
9123a	POWER SUPPLY, BENCH, 30V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT

	CURRENT
886cald	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4
Xln10014	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:100V, OUTPUT CUR
2692a0s2	AMPLIFIER
Xln6024cal	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
Bk2530b	OSCILLOSCOPE, DIGITAL, 2X25MHZ, 500MS/S, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:25MHZ, METER DISPLAY TYPE:TFT, SAMPLING RATE:500MSPS, INPUT IMP
1823acald	FREQUENCY COUNTER, 2.4GHZ, 8 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:DATA HOLD / FREQUENCY / PERIOD / RATIO / REMOTE SELF TEST / START-STOP / TIME IN
Xln6024-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT CURR
Pr261	SNIFFER PROBE SET, TEST PROBE FUNCTIONS:FREQUENCY, FOR USE WITH:BK PRECISION 2615A, 2620A, 2625 AND 2630 SERIES SPECTRUM ANALYZER, ROHS COMPLIANT: NA
2522c	OSCILLOSCOPE, 20MHZ, 2 CHANNEL, 40MSPS, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:20MHZ, METER DISPLAY TYPE:CRT COLOUR, SAMPLING RATE:40M
1673cal	1673 CALIBRATED
8514cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
2522bcal	20 MHZ-10MS/S DSO W/2 PROBES
9115	POWER SUPPLY, BENCH, AC-DC, 0-80V, 60A, 1.2KW, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX
886caldu	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4
2522bcaldu	20 MHZ-10MS/S DSO W/2 PROBES
1745acald	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP, ROHS COMPLIANT: NA
	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-70V, 1.5A, 105W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF

9172	OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLT
Pr26m	TEST PROBE, TEST PROBE FUNCTIONS:ELECTROMAGNETIC FIELD, FOR USE WITH:B K PRECISION 2650A SERIES HAND HELD SPECTRUM ANALYSERS, PRODUCT RANGE:-, PROBE
1541d Cal	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:40
1790cal	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
2630cal	CALIBRATION WITH CERTS BK P/N 2630 SKU # 52F6288
2125	OSCILLOSCOPE
2652a	ANALYZER, SPECTRUM, 50KHZ TO 3.3GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 3.3GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
4079	WAVEFORM GENERATOR ARB / FUNCTION, 50MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1260	VIDEO TEST INS
9185	POWER SUPPLY, PROGRAMMABLE, 0-600V, 350MA, 210W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE M
1745acaldu	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
Vsp12010	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:120V, OUTPUT CURRENT:10A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950
8502cal	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
4084awg	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V
2658cal	POWER QUALITY ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RA
9182	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-20V, 10A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:
570	TESTER
1791	POWER SUPPLY, BENCH, 64V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:64VDC, OUTPUT CURRENT:10A, POWER RATING:640W, IN

Xln10014-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:100V, OUTPUT CUR
1760acal	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUT
Xln6024cald	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
2190b Cal	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:1
2125a Cal	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
1422	OSCILLOSCOPE 20MHZ
8500caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8510caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1760acald	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:3 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30V, OUTPUT C
4085	FUNCTION GENERATOR FREQUENCY/PULSE 40MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
8500cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
Vsp6020gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60V, OUTPUT CURRENT:20A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
4075gpib	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
490	TUBE TESTER/ANALYZER
2658caldu	POWER QUALITY ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RA
4040acald	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION, ROHS COMPLIANT: NA
9152	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:30
	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY

1790	OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32VDC, OUTPUT CURRENT:20A, POWER RATING:640W, IN
540	TESTER
Vsp2050	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:50A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
Xln8018-Gl	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:80VDC, OUTPUT CURRENT:18A, POWER RATING:1.44KW, IN
490b	ANALYZER REJUVENATOR 1/.5AMP 6.3/12V
Xln3640	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:36V, OUTPUT CURR
1790caldu	POWER SUPPLY, BENCH, 32V, 640W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
2650a	ANALYZER, SPECTRUM, 50KHZ TO 3.3GHZ, SPECTRUM ANALYZER TYPE:HANDHELD, TEST FREQUENCY RANGE:50KHZ TO 3.3GHZ, SENSITIVITY DBM:-127DBM, EXTERNAL HEIGHT:7
1657	POWER SUPPLY, AC, 135VAC / 270VAC, 1.5KVA, POWER SUPPLY OUTPUT TYPE:FIXED, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:270VRMS, OUTPUT CURRENT:6ARMS, POWER RATIN
8524	PROGRAMMABLE DC ELECTRONIC LOAD 60V 5KW, PRODUCT RANGE:8500 SERIES, POWER RATING:5000W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2522bcald	20 MHZ-10MS/S DSO W/2 PROBES, ROHS COMPLIANT: NA
8510cal	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8502	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATING VOLTAGE MAX:500V, OPERATING CURRENT MAX:15A
4084	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
4084caldu	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULA
205	VOLTAGE-CONTINUITY TESTER ROHS COMPLIANT: NA
4040acaldu	SIGNAL GENERATOR, FREQUENCY/PULSE, 20MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION

2120bcald	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30, ROHS COMPLIANT: NA
9130cal	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
4084awgcald	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ,CALIBRATEDW/ DATA
4034	SIGNAL GENERATOR, PULSE, 50MHZ, PRODUCT RANGE:-, NO. OF CHANNELS:1 CHANNEL, SIGNAL GENERATOR TYPE:PULSE, BANDWIDTH:50MHZ, SIGNAL GENERATOR MODULATION:
9130cald	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
1823acaldu	FREQUENCY COUNTER, 2.4GHZ, 8 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY
866b	DEVICE PROGRAMMER, IC PRODUCT TYPE:PROGRAMMER, UNIVERSAL, IC INTERFACE TYPE:PARALLEL, USB, NO. OF DEVICES SUPPORTED:41699, FEATURES:CONNECTOR FOR IN-C
4076	WAVEFORM GENERATOR ARB / FUNCTION, 50MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1476	OSCILLOSCOPE BENCH 10MHZ
3026	FUNCTION GNRTR
8540caldu	PROG DC ELECTRONIC LOAD 60V 150W, DC LOAD TYPE:FIXED, OPERATING VOLTAGE RANGE:0V
4033	SIGNAL GENERATOR, PULSE, 50MHZ, PRODUCT RANGE:-, NO. OF CHANNELS:1 CHANNEL, SIGNAL GENERATOR TYPE:PULSE, BANDWIDTH:50MHZ, SIGNAL GENERATOR MODULATION:
560a	CIRCUIT CARD
8526	PROGRAMMABLE DC ELECTRONIC LOAD 500V 5KW, PRODUCT RANGE:8500 SERIES, POWER RATING:5000W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERAT
2650caldu	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5
Vsp6020	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60V, OUTPUT CURRENT:20A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
1045a	TESTER
4079refurb	BK 4079 REFURBISHED BY NEWARK
	SPECTRUM ANALYZER, ANALYZER POWER SUPPLY:BATTERY/DC, BANDWIDTH MAX:3.3GHZ,

2650	BANDWIDTH MIN.:50KHZ, SPECTRUM ANALYZER TYPE:HAND HELD ROHS COMPLIANT: NA
1541d Cal Du	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:40
1794	POWER SUPPLY, LINEAR, 32V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:32VDC, OUTPUT CURRENT:30A, INPUT VOLTAGE:115VAC, LOAD
2640	FIELD STRENGTH METER 2GHZ -45 TO -110DBM, FREQUENCY MEASURING RANGE:100KHZ TO 2GHZ, AMPLITUDE ACCURACY: 3DB, CONNECTOR TYPE:N COAXIAL, EXTERNAL HEIGHT
2522a	OSCILLOSCOPE
4075	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1541d	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:40MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI
2160a Cal	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:60
2160	OSCILLOSCOPE
4011acaldu	FUNCTION GENERATOR FREQUENCY/PULSE, 5MHZ, SIGNAL GENERATOR TYPE:FUNCTION, SUPPLY
2540b-Gen	OSCILLOSCOPE, DIGITAL, 2CH, 60MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:60MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMORY
4084awgcaldu	SIGNAL GENERATOR, ARB / FUNCTION, 20MHZ,CALIBRATED W/ DATA + UNCERT
1652caldu	TRIPLE OUTPUT DIGITAL DISPLAY DC POWER SUPPLY
8514caldu	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
2650cal	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5
Xln6024	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT CURR
1747	POWER SUPPLY, DC, 60V, 5A, 560VA, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:60V, OUTPUT

4040	FUNCTION GENERATOR
Vsp12010odi	POWER SUPPLY
4078	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
1541dcald	OSCILLOSCOPE, 40MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:40MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM, RI
8510	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 120V, PRODUCT RANGE:8500 SERIES, POWER RATING:600W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2120bcal	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
8518	PROGRAMMABLE, DC, ELECTRONIC, LOAD, 60V, PRODUCT RANGE:8500 SERIES, POWER RATING:1200W, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE MIN:0.1V, OPERATI
2658	POWER QUALITY ANALYZER, ANALYZER POWER SUPPLY:BATTERY/DC, BANDWIDTH MAX:8.5GHZ, SPECTRUM ANALYZER TYPE:HAND HELD ROHS COMPLIANT: NA
2542b-Gen	OSCILLOSCOPE, DIGITAL, 2CH, 100MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:100MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMOR
8510cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
9150	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:5.
2542	DIGITAL STORAGE OSCILLOSCOPE, SCOPE BANDWIDTH:100 MHZ, SCOPE CHANNELS:2, SCOPE TYPE:DIGITAL, SERIES:254X SERIES, RISE TIME:3.5NS, SAMPLE RATE:1 GSA/S
1251	VIDEO TEST INS
4078gpib	WAVEFORM GENERATOR ARB / FUNCTION, 25MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK, SUPPLY VOLTAGE RANGE:100V TO 240V, EXTE
2650cald	SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HAND HELD, FREQUENCY MEASURING RANGE:5, ROHS COMPLIANT: NA
4012acaldu	SWEEP FUNCTION GENERATOR FREQ/PULSE 5MHZ, SIGNAL GENERATOR TYPE:SWEEP FUNCTION

2190b	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:100MHZ, METER DISPLAY TYPE:CRT COLOUR, INPUT IMPEDANCE:1MOHM
2542b	OSCILLOSCOPE, 2-CHAN, 100MHZ, 1GSPS, PRODUCT RANGE:2540B SERIES, SCOPE CHANNELS:2 DIGITAL, BANDWIDTH:100MHZ, SAMPLING RATE:1GSPS, DISPLAY MEMORY DEPTH
866c	PROGRAMMER, EPROM, USB INTERFACE, SUPPORTED FAMILIES:-, KIT CONTENTS:-, FEATURES:FAST AND HIGH PERFORMANCE, POWERFUL PROGRAM SOFTWARE, SUPPORTS WINDOW
4084caId	FUNCTION GENERATOR FREQUENCY/PULSE 20MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULA
8502caId	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1760acaIdu	POWER SUPPLY, BENCH, 4.5V, 350W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUT
XIn3640-GI	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:36V, OUTPUT CURR
2534	OSCILLOSCOPE, 60MHZ, 2 CHANNEL, 400MSPS, SCOPE TYPE:DIGITAL, SCOPE CHANNELS:2, BANDWIDTH:60MHZ, METER DISPLAY TYPE:LCD COLOR, SAMPLING RATE:400MSPS, I
9174	POWER SUPPLY, PROGRAMMABLE, 2 O/P, 0-70V, 1.5A, 210W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:2 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLT
XIn8018	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAGE MAX:80V, OUTPUT CURR
1856dcaId	FREQUENCY COUNTER, 3.5GHZ, 9 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY, ROHS COMPLIANT: NA
XIn6024caIdu	PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUT
2120bcaIdu	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
2658caId	8.5GHZ SPECTRUM ANALYZER, SPECTRUM ANALYZER TYPE:HANDHELD, FREQUENCY MEASURING RANGE:50KHZ TO 8.5GHZ, ROHS COMPLIANT: NA
886cal	DIGITAL MULTIMETER, EXTERNAL HEIGHT:175MM, EXTERNAL WIDTH:86MM, EXTERNAL DEPTH:4

8522refurb	8522 REFURBISHED
8502caldu	PROG, DC, ELECTRONIC, LOAD, 500V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
8514cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R
1745acal	POWER SUPPLY, BENCH, 35V, 560W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTP
1249a	VIDEO TEST INS
1050	TESTER
1476a	OSCILLISCOPE 10MHZ 2CHANNEL
9181	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-36V, 4A, 144W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTAG
4045	SWEEP FUNCTION GENERATOR, ARB, 20MHZ, SIGNAL GENERATOR TYPE:DDS, MODULATION TYPE:AM / FM, SUPPLY VOLTAGE RANGE:90V TO 264V, EXTERNAL HEIGHT:88MM, EXTE
4086awg	SIGNAL GENERATOR, ARB / FUNCTION, 80MHZ, SIGNAL GENERATOR TYPE:ARB / FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V
1673caldu	1673 CALIBRATED W/ DATA + UNCERT
Vsp2050-Refurb	POWER SUPPLY, BENCH, 20V, 1.2KW, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20VDC, OUTPUT CURRENT:50A, POWER RATING:1.2KW
2125a Cal D	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30, ROHS COMPLIANT: NA
Vsp2050gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:20V, OUTPUT CURRENT:50A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
9184	POWER SUPPLY, PROGRAMMABLE, 1 O/P, 0-200V, 1A, 200W, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1 OUTPUT, OUTPUT VOLTAGE MIN:0V, OUTPUT VOLTA
9153	SINGLE OUTPUT PROGRAMMABLE DC POWER SUPPLY, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:60VDC, OUTPUT CURRENT:9A, LOAD REGUL
1673cald	1673 CALIBRATED W/ DATA
2630	ANALYZER, SPECTRUM, 0.15MHZ TO 1.05GHZ, SPECTRUM ANALYZER TYPE:BENCH, FREQUENCY MEASURING

	RANGE:150KHZ TO 1.05GHZ, EXTERNAL HEIGHT:125MM, EXTERNAL WID
9130caldu	POWER SUPPLY, BENCH, 30V/5V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS
4086	FUNCTION GENERATOR FREQUENCY/PULSE 80MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
4087	FUNCTION GENERATOR, FREQ / PULSE, 120MHZ, SIGNAL GENERATOR TYPE:FUNCTION, MODULATION TYPE:AM / FM / FSK / PSK, SUPPLY VOLTAGE RANGE:198V TO 242V / 99V
1795	POWER SUPPLY, LINEAR, 64V, POWER SUPPLY OUTPUT TYPE:ADJUSTABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:64VDC, OUTPUT CURRENT:15A, INPUT VOLTAGE:115VAC, LOAD
1856dcaldu	FREQUENCY COUNTER, 3.5GHZ, 9 DIGIT, 1PPM, COUNTER MEASURING FUNCTIONS:FREQUENCY
Vsp4030gpib	BENCH POWER SUPPLY, OUTPUT TYPE:VARIABLE, NO. OF OUTPUTS:1, OUTPUT VOLTAGE:40V, OUTPUT CURRENT:30A, POWER RATING:1.2KW, APPROVAL CATEGORIES:EN60950, C
2125a Cal Du	OSCILLOSCOPE, 30MHZ, 2 CHANNEL, SCOPE TYPE:BENCH, SCOPE CHANNELS:2, BANDWIDTH:30
859	UNIVERSAL, SUPPORTED FAMILIES:WINDOWS 98/ME/NT/2000/XP/2003/XPX64/VISTA, SUPPORTED DEVICES:PC BA
8500cald	PROG, DC, ELECTRONIC, LOAD, 120V, DC LOAD TYPE:PROGRAMMABLE, OPERATING VOLTAGE R