



Blickle

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Blickle Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Blickle Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Lk-Poev 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Heavy duty wheel with elastic solid rubber tires 'Blickle EasyRoll', with Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: black Tread / tires: Made of high-quality elastic solid rubber in smooth running quality 'Blickle EasyRoll'. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Vulcanised tire. Base hardness: 65 ° Shore A Wheel Ø: 125 mm Tire width: 40 mm Load capacity: 250 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 80 ° C
Lk-Poth 125k-3	Sheet steel swivel castor, heavy version, with screw-on plate Wheel with thermoplastic polyurethane tread, with heavy Polyamide wheel center Housing: Made of strong sheet steel, with double ball bearings in the slewing ring, with slewing ring seal. The special one Dynamic Blickle riveting of the slewing ring results in a minimal slewing ring clearance with smooth running and a high one Lifetime due to the strain hardening of the ball raceways. Bolted wheel axle. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: dark gray Tread / Tire: Made of high quality, thermoplastic polyurethane. Wheel center / rim: Made of high-quality, break-proof polyamide 6. Base hardness: 94 ° Shore A Wheel Ø: 125 mm Wheel width: 40 mm Load capacity: 350 kg Bearing type: ball bearing Overall height: 155 mm Plate size: 140 x 110 mm Screw hole distance: 105 x 75-80 mm Screw hole Ø: 11 mm Throat castor: 48 mm Temperature resistance: -25 ° C to 70 ° C
	Heavy-duty flange wheel with Blickle polyurethane tread Softthane®, with cast wheel center Technical specifications: • Wheel Ø: 200 mm, wheel width: 50 mm, load capacity at 4

GSTA 200/4	km / h: 700 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, hole circle Ø: 100 mm Tread: • high-quality polyurethane elastomer Blickle Softhane®, hardness 75 Shore A. • Very high driving comfort thanks to particularly thick, elastic tread • very gentle on the floor, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical bond with the wheel center
101323	
102554	
102556	
106636	
123584	
125/ 15Ê	
137904	
137905	
150131	
150749	
263541	
267302	
577361	
605063	
620989	
850265	
850415	
913866	
ALTH 125/15 K	
ALTH 200	
ALTH 200x50/20-40K	
B-ALST 125K	
B-G 80G	
BH-ALBS 200K	
BH-ALST 100K-3	

BH-ALST 160K - 579557
BH-ALTH-101K-1 (284307)
BH-POEV 160K
BH-SETH 200K
BO-GTH 150K
B-PATH 200R
BPA-TPA 50G
B-PHN 200G
B-POEV 160K
B-RD 162R-VLI
BS-GB 160K
B-V 162R
B-V 202R
B-VE 200R
B-VEHI 125R
B-VPP 160R
FSTH 50X18/17-10K
FTH 52x15/12-12K
F-ZP 125R-F
GB 150/20-50K
GB 152/25K
GB 250/25K
GBN 202/35H7
GSPO 80/20K
GSTN 150/25H7 (754394)
GTH 200/25K
GTHN 200/30H7
GTHN 251/40H7
GTHN 252/40H7
HPO 82X70/20-70K

HRP-POA 63G
HRSP-POA 72G
JPPR 1001 5100
L -RD 202R
L-ALEV 125K-FI
L-ALEV 200K-SG
L-ALST 125K-FI
L-ALST 160K-FI
L-ALST 200K-FI
L-ALST 80K-FI
L-ALTH 100 K FI
L-ALTH 150K
L-ALTH 150K-FI
L-ALTH 150K-FL
L-alth 80K-as
LE-PATH 200R-FI
LE-POEV 160K-FI
LER-VE 100R
LE-VE 200R-FI
LEX-PO 125KD-FI
LEZ-PO 75G-FI
LH-ALBS 160K
LH-ALST 200K
LH-GB 200K
LH-GB 200K-FI
LH-SE 202K-ST-SG
LH-SETH 200K-FI
LH-SPO 175G-FI
LI PHN 102 G
LI-PHN 200G
LK-ALBS 100K-1-FI

LK-ALBS 200K-FI
LK-ALST 100K-1-FI
LK-ALST 160K
LK-ALST-160K-FI 627034
LK-ALTH 80K-FI
LK-G125G-1
LK-POEV 160K
LKR-ALTH 100K-FI-AS
LKR-ALTH 125K
LO-ALTH 250K
LO-GTH 150K
LPA-PATH 50 G-FI
L-PATH 80G-FI
LPA-TPA 100G-FI-ELS
L-POEV 100 K FI
L-POEV 100K
L-POEV 1250K-FI
L-POEV 80K-FI
L-PTH 200R
LRA-TPA 75K-FK-GS10
LRA-TPA75K-FI-FK
LRA-TPA75K-FK
LRA-VPA 50 G FI
LRA-VPA 50 G-ES
LRA-VPA 75K-FA
L-RD 162-FI-VLI
L-RD125R-FI
LSD-GB 302K-RAH-RI4H
LSD-GTH 302K-RI4H
LSD-GTH-100K

LSD-SE-300K
LS-GB 160K-ST
LS-GB 160K-ST-RI4
LS-GSPO 152K-35
LS-GTH 300K-ST
LS-SETH 125K
L-V 125R
L-V 162R
L-V 200K
L-V 200K-FI
L-V 202R
L-VPP 160R-FI
P 340/25-90K
POEV 100/8K-SG
POEV 125/15R
POEV 160/20
PS 310/25-75K
PS 315/25-75K
PS 430/25MM -90K
PS 430/30MM-90K
RTH 200x85/50-4+2
SPKVS 150K
SPO 125/15G
SPO 125/20K
SP-ZP 100C-FI-F
SP-ZP 80C-FI-F
S-ZP 125R-F
TPA 101/12G-ELS
TPA 80/12G-ELS
V 350/25-75K
WH 160

[BH-ALST-150XK](#)

[BH-ALST-150XK FI](#)

[LK-SPO 80G](#)

754876 Pressed steel swivel castor, heavy duty, with top plate fitting, Heavy-duty wheel made of polyamide Technical specifications: • Wheel Ø: 80 mm, wheel width: 37 mm, load capacity at 4 km/h: 350 kg, Bearing type: plain bearing, total height: 110 mm, plate size: 100 x 85 mm, Screw hole distance: 80 x 60 mm, screw hole Ø: 9 mm, overhang Castor: 40mm Housing: LK series • Strong sheet steel, electrogalvanised, blue passivated, Cr6-free • Double ball bearing in the slewing ring • Stable central bolt (from wheel Ø 125x50 mm) • Slewing ring seal • Minimum slewing ring play, smooth running, long service life the special dynamic Blickle riveting Wheel: SPO series • high-quality polyamide 6, unbreakable, hardness 70 Shore D, very robust, heavy version, color natural white Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -25 °C to +80 °C, reduced load capacity above +35 °C

[GSTA 250/4](#)

754387 Heavy-duty flanged wheel with Blickle polyurethane tread Softhane®, with cast wheel body Technical specifications: • Wheel Ø: 250 mm, wheel width: 60 mm, load capacity at 4 km/h: 800 kg, Number of screw holes: 4, screw hole Ø: 16.5 mm, center hole Ø: 60 mm, bolt circle Ø: 100 mm Tread: • High-quality Blickle Softhane® polyurethane elastomer, hardness 75 Shore A • Very high level of driving comfort thanks to the particularly thick, elastic tread • very floor-friendly, low-noise operation • low rolling resistance • very abrasion resistant • high cut and tear resistance • Color green, non-marking, non-staining • very good chemical connection with the wheel center wheel body: • robust cast iron • Center bar with center hole and screw holes • Screw holes with spherical collar countersinks • lacquered, color silver Other characteristics: • Assembly using spherical collar screws and spherical collar nuts according to DIN 74361 • high chemical resistance to many aggressive media • Temperature resistance: -30 °C to +70 °C, briefly up to +90 °C, Reduced load capacity above +40 °C

[L-ALST 150K](#)

755956 Stahlblech-Lenkrolle, mittelschwere Ausführung, mit Anschraubplatte, Schwerlast-Rad mit Polyurethan-Laufbelag Blickle Softhane®, mit Aluminium-Radkörper Technische Daten: • Rad-Ø: 150 mm, Radbreite: 50 mm, Tragfähigkeit bei 4 km/h: 400 kg, Lagerart: Kugellager, Gesamthöhe: 190 mm, Plattengröße: 140 x 110 mm, Schraublochentfernung: 105 x 75-80 mm, Schraubloch-Ø: 11 mm, Ausladung Lenkrolle: 60 mm Gehäuse: Serie L • Stahlblech, galvanisch verzinkt, blau passiviert, Cr6-frei • zweifache Kugellagerung im Drehkranz • stabiler Mittelbolzen (ab Rad-Ø 150 mm) • Drehkranzabdichtung • minimales Drehkranzspiel, leichtgängiger Lauf, hohe Lebensdauer durch die spezielle dynamische Blickle-Vernietung Rad: Serie ALST • Laufbelag: hochwertiges Polyurethan-Elastomer Blickle Softhane®, Härte

	<p>75 Shore A, Farbe grn, spurlos, kontaktverfrbungsfrei • Radkrper: Aluminium-Druckguss, Farbe silbergrau Sonstige Eigenschaften: • hohe chemische Bestndigkeit gegen viele aggressive Medien • Temperaturbestndigkeit: -20 °C bis +70 °C, kurzzeitig bis +90 °C, verringerte Tragfhigkeit bei ber +40 °C</p>
LS-GSPO 150K-35-ST-RI4	<p>Technical data: • Wheel Ø: 150 mm, wheel width: 55 mm, load capacity at 4 km/h: 2,500 kg, Bearing type: ball bearing, overall height: 205 mm, plate size: 175 x 140 mm, screw hole distance: 140 x 105 mm, screw hole Ø: 14 mm, Swivel castor projection: 65 mm Housing: LS series • Particularly robust welded steel construction, galvanized, yellow passivated, Cr6-free • Axial deep groove ball bearings ISO 104 and tapered roller bearings ISO 355 im slewing ring • Welded, very stable central bolt, screwed and secured • Protected against dust and splash water • Grease nipples Wheel: GSPO series • high quality cast polyamide, reaction cast, unbreakable, hardness 80 Shore D, color natural beige</p>
BH-ALST 100K-3	<p>752602 Sheet steel fixed castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blicke Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm Housing: BH series • Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blicke Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C</p>
LH-ALST 100K-3	<p>684464 Sheet steel swivel castor, heavy-duty version, with screw-on plate, Heavy-duty wheel with Blicke Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 100 mm, wheel width: 40 mm, load capacity at 4 km/h: 320 kg, Bearing type: ball bearing, total height: 140 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blicke Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C</p>
	<p>625418 Sheet steel fixed castor, heavy-duty version, with</p>

BH-ALST 125K-3	screw-on plate, Heavy-duty wheel with Blicke Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm Housing: BH series • Sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blicke Softhane®, hardness 75 Shore A, color green, traceless, contact discoloration free • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
LH-ALST 125K-3-FI	625517 Sheet steel swivel castor, heavy-duty version, with screw-on plate, with 'stop-fix' lock, Heavy-duty wheel with Blicke Softhane® polyurethane tread, with Aluminum wheel body Technical data: • Wheel Ø: 125 mm, wheel width: 40 mm, load capacity at 4 km/h: 370 kg, Bearing type: ball bearing, total height: 165 mm, plate size: 140 x 110 mm, screw hole distance: 105 x 75-80 mm, screw hole Ø: 11 mm, Projection swivel castor: 45 mm Housing: LH series • strong sheet steel, galvanized, blue passivated, Cr6-free • heavy fork and base plate • double ball bearings in the slewing ring • very stable center bolt, screwed and secured • Particularly insensitive to shocks and impacts thanks to four special shaped, hardened bearing shells Wheel: ALST series • Running surface: high-quality polyurethane elastomer Blicke Softhane®, hardness 75 Shore A, color green, non-marking, non-staining from contact • Wheel body: die-cast aluminum, color silver gray Other characteristics: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load capacity at over +40 °C
913865	LH-ALST 150XK-FI Sheet steel swivel castor, heavy-duty version, with screw plate, with 'stop-fix' brake, heavy-duty wheel with Blicke Softhane® polyurethane tread, with aluminium wheel center
913866	BH-ALST 150XK Sheet steel fixed castor, heavy-duty version, with screw plate, Heavy-duty wheel with Blicke Softhane® polyurethane tread, with aluminium wheel center
265751	
448746	
754450	HTH 82x65/20-71K Forklift roller with polyurethane tread Blicke Extrathane®, with metal wheel body Technical data: • Wheel diameter: 82 mm, wheel width: 65 mm, load capacity at 4 km/h: 590 kg, Ball bearing: 6204 ZZV, axle hole diameter: 20 mm, clamping length: 71 mm Tread: • high-quality polyurethane elastomer Blicke Extrathane®, hardness 92 Shore A • low rolling resistance • very abrasion-resistant • high cut and tear resistance • Color light brown, traceless, contact discoloration free • very good chemical bond with the wheel body wheel body: • Metal Other

features: • high chemical resistance to many aggressive media • Temperature resistance: -20 °C to +70 °C, briefly up to +90 °C, reduced load-bearing capacity above +40 °C
B-Alst 160k Rolle
Lh-Gsp080k-Fi
Lk-Alst 100k-1-Fi Rad
Alth 125/15 K Extrathane Schwerlastrad
Li-Phn 200ik
L-V 200k Rolle
L 150/160 -L-160.60.03
Le-Path 200r-Fi Rolle
Bh-Spo 100k-1
Lk-Alth 80k-Fi Lenkrolle Mit Bremse
L-Vpp 160r-Fi Drehen. Rolle Mit Bremse (Schwarzer Gummi)
Rad Mit Polyurethankabel D-200mm,Blickle Gth 200/25k
Fuehrungsrolle Fpo 25x10/6-6k
622106
Gspo 152/35k
B-V 162r Stahlblech-Bockrolle
Bs-Gth 252k
Bo-Alth-200k
Lra-Tpa75k-Fi-Fk Umlenkrolle
F-Zp 125r - F Roller
Le-Poev 100r-Fistahlblech-Lenkrollen
Fsth 70x25/20-15k
L-Poev 1250k-Fi Rolle
Bh-Seth 200k Rolle Fest
150*45
Lenkrolle 150 Mmlh-Seth 150k
Bh- Alst 100k-3
L -rd 202r Lenkrollen

Lh-Gth 200k
Gth202/30k
Bh-Gspo 125k
Bpa-Poa 50g
Lsd-Gth-100k Rolle Drehbar
Lk-Albs 100k-1-Fi
Lsd-Se 250k-Ra
Bh-Gsp080k
Bh-Albs 200k Fixierte Rolle
150749 Le-Poev 201k-Sg
Lsoa-Albs 200k-Ra-761312
Lh-Gth 160k
Gb 200/20k
Lh-Gth 125k-1
B-Poev 160k Rollen Schwenkkrane
Rad Mit Polyurethankabel D- 250mmblickle Gth 252/30k
102556 Super-Elastik-Vollgummi- Reifenbsev 4.00-4-Rp
B-Rd 162r-Vli Nicht Drehbar Rolle (Grauer Gummi)
Lk-Po 200k-St-Fs
Lk-Poev 160k Drehbarer
Bh-Poev 160k Nicht Drehbar
125/ 15?
L-Alth 150k-Fi Rolle Drehbar
Alev 125/15k
101323 Rad Fest Blickle B-Ve 100rident- Nummer: 101323
B-Alev-161k
L-Alst 160k-Fi
Lk -Alst 100k-1-Fi

Ls-Se 160 K
Bs-Gth 604k
B-Vpp 160r Nicht Drehbar Rolle (Schwarzer Gummi)
Bh-Gspo 100k-3
562876
Lra-Tpa75k-Fk Rolle
Lh-Gth 202k
Bk-G 125g-1
Lez-Po 75g-Fi
Lh-Gb 200k-FI Lenkrollen
L-Alst 160k-Fi Rolle
Lk-Spo 160g-Fi
850415 B-Poev 201k-Sg
Lh-Gsp080k-St
Lh-Gth 175k
Sp-Zp 80c-Fi-F Lenkrolle Mit Bremse
Bsd-Se 200 K
457283
45336
Fsth 100x25 15k
Gev 520/40k
B-Pth 200r
Gth 504/60k
752607
137904 Lenkrolle Ls-Gb 202 K
Se 252/25 K
Ls-Vle 310k
B-Ve 200r Rolle Fest
106636 Rad Drehbar Mit Bremseblickle Le-Ve 100r-FI Ident-Nummer: 106636

Gspo 80/20k Heavy Duty Polyamide Block Wheel
562884
Rad Alev 125/15k
Bs-Se 160 K
L-V80r-St
Spkvs250k
L-Alst 250k-3-St
Bpa-Vpa 50k
Gthn 252 40h7
Lex-Po 125kd-Fi Roller
Ps 315/25-75k Rad
L-Path 80g-Fi Lenkrolle Mit Bremse
Lh-Gb 200k Lenkrollen
Bh-Alst 200k
Das Rad Fest, Stahlblech, Dbh-Poev 100k-1
Ls-G 250k
Lkra-Tpa 101g-Gs12
Bh-Svs 127k
Lh-Gth 125k-3
Lh-Alst 100k-3
Hrsp-Poa 72g 757023 Radkopf
Gth 202/35k
Gth150/20k
Rth 200x85/50-4+2 Rad
102554 Super-Elastik-Vollgummi-Reifenbsev 3.00-4-Rp
Ls-Alb 200k-Ra-760676
L-Alev 125k-Fi
Lk-Alst 100k-1-Fi P. Roller With Brake
Poev 125/15r Rad

L-Alst 125k-Fi Rolle	
150131 B-Poev 201k-Sg	
46714	
115643	
L-Po 125r-Fi-Fp	
Geva 300/5	
45369	
L-Alst 200k-Fi	
Ls-Gb 250k-St-Ri2	
Brd162r	
Se 252/25k	
Lh-Gth 100k-3	
Lsd-Gth 302k-Ri4h	
B-Alth 100k	
00227278	
L-Poev 100 K Fi Stahlblech Lenkrollerad- Und Drehkrantzbremsse "stop-Fix"	
Lh-Albs 160 K Rad Rotor Ohne Bremsse	
L-V 162r Stahlblech-Lenkrolle	
Gth 177 / 25k	Wheel with polyurethane tread Blicke Extrathane®, with cast iron wheel center Wheel: Tread / Tires: Made of high-quality polyurethane elastomer Blicke Extrathane®. Tread color: light brown Wheel center / rim: Made of cast iron, with grease nipple, painted. Surface hardness: 92 ° Shore A Wheel Ø: 175 mm Wheel width: 80 mm Load capacity: 1300 kg Bearing Type: Ball Bearing Axle hole Ø: 25 mm Hub length: 80 mm Temperature resistance: -25 ° C to 70 ° C
250/20k	
L-Alth 100 K Fi Stahlblech Lenkrolle Mit Feststeller	
250/20k-Sg	
Lrd162rst	
Lh-Gth 127k-Is	
Albs 100/15k	
451697	

Lsd-Se 200 K
115646
S-Zp 125r - F Roller
Gthn 252/40h7 Radident-Nummer: 104572
Lk-Albs 200k-Fi Drehbare Rolle
Lh-Gth 150k
Lo-Alth-200k-St
125 15?
Sp-Zp 100c-Fi-F Lagerung Rad Drehbar Mit Bremsed=100 Mm Sp-Zp 100c-Fi-F
Bh-Albs 200 K Das Rad Nicht Drehbar Ohne Bremse
Bs-Gspo 302k
Bh-Gspo 65k
Gthn 251/40h7 Ruota Di Frizione
Lra-Vpa 50 G Fi Stahlblech Apparate - Lenkrollerad- Und Drehkranzbremse
318451
B-Alev 125k
Ls-Vle 310k-Ra
Lkra-Tpa 101g-Fi-Gs12
Das Rad Drehbar Mit Bremse, Blechlh- Poev 100k-1-Fi
Gspo125/25k
Hth80x40/20-40k
L-Alth 80k-As Rad Mov.
Hth 60x35/15-35kpolyurethan- Laufrollenlaufbelag Gegossen
606541
Bh-Spo 150k
L-Alst 80k-Fi Pov. Rolle Mit Bremse
470088

[Zwillings-Lenkrolle Lsd-Gth-252k-Rah-Ri2h](#)

[Ls-Ps 310k](#)

[B-Alst 200k](#)

[Antriebsraeder Rth 200x85/50-4+2](#)

[Rk-Hth 060x035/32x09-35-Zgabelhubwagen-Rolle Mit Polyurethan-Laident-Nummer: 148149](#)

[Gth 200/25k Rad](#)

[Rolle Nicht Drehbar D:100
Chape:100x85b-Poev 100k](#)

[Lh-Gth 127k](#)

[9990014272](#)

[Se-252/25k](#)

[\(754880\) Lk-Vsth-65k](#)

Sheet steel compact swivel castor with mounting plate Wheel with Blicke Extrathane® polyurethane tread, with steel wheel center Housing: Made of strong pressed steel, with double ball bearing in the turntable, with slewing ring seal. Wheel axle bolted. Galvanized, blue passivated, Cr6-free. Wheel: Tread color: light brown Tread / Tire: Made of high-quality polyurethane elastomer Blicke Extrathane®. Wheel center / rim: Made of steel. Tread poured. Surface hardness: 92 ° Shore A Wheel Ø: 65 mm Wheel width: 40 mm Load capacity: 250 kg Bearing Type: Ball Bearing Total height: 92 mm Plate size: 100 x 85 mm Screw hole distance: 80 x 60 mm Screw hole Ø: 9 mm Discharge swivel castor: 40 mm Temperature resistance: -25 ° C to 70 ° C

[463935 \(Fsth 40x20/10-8k\)](#)

[B-Alth 100k Rad Fix.](#)

[L-Rd 162-Fi-Vli Drehen. Rolle Mit Bremse. \(Grauer Gummi\)](#)

[Gth 200 25k](#)

[L-Alth 150k Rolle Drehbar](#)

[B-G 80g Rad](#)

[B-Alst 200k Rolle](#)

[L-Rd125r-Fi Rollen](#)

[B-Alst 125k Rolle](#)

[595678](#)

[45377](#)

B-Vehi 125r
L-Alev 200k-Sg Rad
Bh-Alst 160k
Ls-Gth 604k
Geva 250/4
B-Phn 200ik
761312
Lra-Vpa 50 G-Es Stahlblech Apparate - Lenkrolleeinsteckstift 11mm
B-Alst 160k
137905 Lenkrolle Mit Feststeller Ls-Gb 202k-St
850265 Le-Poev 201k-Sg
Ls-Gth 252k
Alt -160/20 K
L-Poev 100k Rolle
Lh-Seth 200k-Fi Rolle Lenkrolle Mit Bremse Stop-Fix
Ls-Seth 125k Swivel Castors
L-Poev 80k-Fi Rolle
P 340/25-90k Rad
Spo 125/20k Rad
Alev 250/25 K
B-Path 200r Rolle
Li Phn 102 G
Bh-Alst 250k
Rht 225x70/120 - 12 - P
Le-Poev 160k-Fi Rollen Schwenkkrane
Lpa-Vpa 50k
Le-Ve 200r-Fi Rolle Drehbar
L-V 200k-Fi Lenkrolle Mit Bremse

Bh-Po 200k-Es
Ps 310/25-75k Rad
L-Alev-161k
L-Alst 200k-Fi Rolle
127 P02
Lh-Gth 100k-1
760676
Lpa-Path 50 G-Fi Rolle
51615
Bsd-Spo 160k-35
L-V 125r Stahlblech-Lenkrolle
B-V80r
Fsth 80x25/25-15k
Rad, Stahlblech, Bh-Alth 180k
Gthn 200/30h7 Rad
Ff125