

## Bourdon Haenni

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Bourdon Haenni** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Bourdon Haenni T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">Pbsn-1.3.B22.R.A1.44.03.2.1</a>	SUCCESSOR: Materialnr 11092906 Product industrial pressure transmitter PBSN Housing material stainless steel 1.4301 AISI 304 1 Accuracy ± 0.5% FS 3 Measuring range 0 ... 10 bar (EN) B22 Pressure type relative (against environment) R Output signal 4 ... 20 mA A1 Electrical connection DIN EN 175301-803 A (DIN 43650 A), 4-pin 44 Process connection G 1/2 B EN 837-1 (G31) 03 Process connection material stainless steel 1.4404 AISI 316L 2 Seal NBR standard 1
<a href="#">MEX5-D30.B19</a>	11011143 Product industrial pressure gauge with Bourdon tube made of stainless steel Housing can be filled with damping fluid MEX Dimension nominal size 100 mm 5 Housing connection radial below D Process connection G 1/2 3 Damping fluid without 0 Measuring range 0 ... 4 bar (EN) B19
<a href="#">MEX5-A31.B31</a>	10279822 Product industrial pressure gauge with Bourdon tube made of stainless steel Housing can be filled with damping fluid MEX Dimension nominal size 100 mm 5 Housing connection radial below for wall mounting A Process connection G 1/2 3 Damping fluid BH1, glycerin 86% 1 Measuring range 0 ... 100 bar (EN) B31

<a href="#">MEX5-D31.B22</a>	10282943 Product industrial pressure gauge with Bourdon tube made of stainless steel Housing can be filled with damping fluid MEX Dimension nominal size 100 mm 5 Housing connection radial below D Process connection G 1/2 3 Damping fluid BH1, glycerin 86% 1 Measuring range 0 ... 10 bar (EN) B22
<a href="#">MEX3-F21.B22</a>	10278181 Product industrial pressure gauge with Bourdon tube made of stainless steel Housing can be filled with damping fluid MEX Dimension nominal size 63 mm 3 Housing Housing 1.4301, rear connection F Process connection G 1/4 2 Damping fluid BH1, glycerin 86% 1 Measuring range 0 ... 10 bar (EN) B22
<a href="#">MEX5-F30.B38</a>	10286471 Product industrial pressure gauge with Bourdon tube made of stainless steel Housing can be filled with damping fluid MEX Dimension nominal size 100 mm 5 Housing Housing 1.4301, rear connection F Process connection G 1/2 3 Damping fluid without 0 Measuring range 0 ... 400 bar (EN) B38
<a href="#">ED701 820.413.A25.19</a>	Transmit. Press. 4.20mA A25.19
<a href="#">CTX-3.3.9.B20.0</a>	Product Industrial pressure transmitter CT Housing material Stainless steel 1.4301 AISI 304 X Output signal 4 ... 20 mA 3 Process connection G 1/2 B EN 837-1 (G31) 3 Seal FKM 9 Measuring range 0 ... 6 bar (EN) B20 Output connection DIN EN 175301-803 A (DIN 43650 A), 4-pin 0
<a href="#">PA210.009AX01</a>	Material No. 11041703 process display for current loop Display: 7-segment LED display, 4 digits, 10 mm high Supply:Supplied via current loop Input: Current 4...20 mA Connection: plug-in spring terminal Housing: DIN housing 48 x 24 with clamping frame Protection class: Front IP65 according to DIN 60529
<a href="#">11G2003</a>	
<a href="#">Ed 505/311.211/065</a>	DAT: 0310 ID: 0955. 0241C Pe: 0...6 bar Ia: 4...20ma UB: +12...30vdc
<a href="#">Pt-1,</a>	
<a href="#">Pt-5</a>	
<a href="#">Ed 505</a>	
<a href="#">Pbsn-1.2.B20.R.A1.53.05.2.3.000</a>	Order code: PBSN-1.2.B20.R.A1.53.05.2.3.000 old code / SAP code: Housing material: AISI 304L stainless steel, 1.4301 Accuracy: 0.7% Printing unit: bar Pressure range and unit: Pressure range for bar 0 ... 6 bar Print Type: Relative Output signal: 4 ... 20 mA Output connection: Shielded cable, 1.5 m Process connection: 1/2 "NPT Material process connection: stainless steel AISI 316L, 1.4404 Seal: FKM (Viton) Turn-Down: No turn-down
<a href="#">Pbmn-23b20ra144032</a>	
<a href="#">Pt-4</a>	

<a href="#">Psmn-24b12ra1u3912</a>
<a href="#">Pbmn 15 B41 R A</a>
<a href="#">Rdhn Ea6131</a>
<a href="#">Psmn-24b15ra1u3912</a>
<a href="#">Pbmn-23b41ra144034</a>
<a href="#">Pt-2,</a>
<a href="#">T08406.0003</a>
<a href="#">11096772</a>
<a href="#">Pbsn-1.2.B24.R.A1.</a>
<a href="#">Pt-3,</a>