

## B&R

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**B&R** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız B&R Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunulmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">7cm211 7 Modul</a>	
<a href="#">8v1090.00-2</a>	ACOPOS servo amplifier, 3x 400-480 V, 8.8 A, 4 kW, line filter, Braking resistor and electronic safe restart interlock integrated
<a href="#">8ac121.60-1</a>	ACOPOS Einsteckmodul, HIPERFACE Interface
<a href="#">8ac122.60-3</a>	ACOPOS plug-in module, Resolver interface 10 kHz
<a href="#">Ac 112</a>	Acopos 1090 Karte
<a href="#">B R X20 Cp1484</a>	
<a href="#">B R 5pc720.1505-K01 5pc7201505k01 Rev.</a>	REV. 00 5P62:R016953-011 5P62: R016953-011 Panel PC 720 15".
<a href="#">X67at1322</a>	X67 Temperatur Eingangsmodul, 4 Eingnge Widerstandsmessung, 2- oder 4-Leitermessung, PT100, PT1000, KTY10, KTY84, Auflsung 0,1 K
<a href="#">X67dm9321.L12</a>	X67 Digitales Mischmodul, 16 Kanle wahlweise als Ein- oder Ausgang parametrierbar, 24 VDC, 0,5 A, Eingangsfilter parametrierbar, 2 Ereigniszhler 50 kHz, M12-Anschlussstechnik, X2X Link Adressschalter, High-Density-Modul
<a href="#">7ex270.50-1</a>	
<a href="#">X20AI4222</a>	X20 analog input module, 4 inputs, ± 10 V, 13 bit converter resolution, Parameterizable input filter
<a href="#">PLC CPU X20CP1484</a>	
<a href="#">PLC X20IF1082 ETHERNET</a>	COMMUNICATION
<a href="#">PLC X20DI6371 DIGITAL INPUT 6 CH</a>	
<a href="#">PLC X20AT2222 ANALOG INPUT 2CH</a>	
<a href="#">PLC X20AI1744 ANALOG INPUT 2CH</a>	

<a href="#">PLC X20HB2880 2X HUB 100</a>	BASE-TX
<a href="#">PLC X20BC8083 2X FAST</a>	ETHERNET HUB
<a href="#">PLC X20PS9400 POWER SUPPLY</a>	MODULE
<a href="#">PLC X20DI9371 DIGITAL INPUT</a>	12 CH
<a href="#">PLC X20DO9322 DIGITAL</a>	OUTPUT 12 CH
<a href="#">PLC X20PS2100 POWER SUPPLY</a>	MODULE
<a href="#">3CP380.60-1 / CPU</a>	
<a href="#">2609540</a>	Endverbleib T¼rkei
<a href="#">PPE-PS</a>	PPE-PS by B&R - Buy or Repair at Radwell - Radwell.co.uk
<a href="#">X20TB12</a>	X20TB12 by B&R - Buy or Repair at Radwell - Radwell.co.uk
<a href="#">X20TB06</a>	X20TB06 by B&R - Buy or Repair at Radwell - Radwell.co.uk
<a href="#">AI MODUL X20AI1744</a>	
<a href="#">3CP360.60-2 Rev.60</a>	41460169396
<a href="#">BLOCK,X20TB12</a>	
<a href="#">MOD¼L,X20 BM 01</a>	
<a href="#">8LSA55.EA030D000-3</a>	
<a href="#">X20ps3310</a>	
<a href="#">4b120000590</a>	
<a href="#">3do4796</a>	
<a href="#">5p30:Bmw-07</a>	
<a href="#">X20ai2622</a>	X20 analog input module, 2 inputs, ± 10 V or 0 to 20 mA / 4 to 20 mA, 13 bit converter resolution, Input filter can be parameterized
<a href="#">X20di9371</a>	X20 digital input module, 12 inputs, 24 VDC, sink, Parameterizable input filter, 1-wire technology
<a href="#">2ex100501</a>	
<a href="#">3am0506</a>	
<a href="#">3bm1509</a>	
<a href="#">X20at4222</a>	X20 temperature input module, 4 inputs resistance measurement, PT100, PT1000, resolution 0.1 ° C, 3-wire technology
<a href="#">X20bm01</a>	
<a href="#">3ps4659</a>	

<a href="#">2di4266</a>	
<a href="#">8lsa44.E3030d100-0</a>	
<a href="#">8v1045.00-2</a>	
<a href="#">8ce007</a>	
<a href="#">3at350.6</a>	
<a href="#">8cr015</a>	
<a href="#">Ai774</a>	Analog Input
<a href="#">Af101</a>	Analog Interface
<a href="#">3di450609</a>	
<a href="#">X20cpu1483</a>	
<a href="#">X20ao2622</a>	X20 analog output module, 2 outputs, ± 10 V or 0 to 20 mA / 4 to 20 mA, 13 bit converter resolution
<a href="#">3do6506</a>	
<a href="#">X20ac0sh1</a>	
<a href="#">Am051</a>	
<a href="#">8ce010</a>	
<a href="#">2do4286</a>	
<a href="#">X20ac0sc1</a>	
<a href="#">8cr010</a>	
<a href="#">3bp150.41 Plc Rock</a>	
<a href="#">0ps1200.1</a>	
<a href="#">X20do9322</a>	X20 digital output module, 12 outputs, 24 VDC, 0.5 A, source, 1-wire technology
<a href="#">8v1090.00-1</a>	ACOPOS servo amplifier, 3 x 400-480 V, 8.8 A, 4 kW, line filter and Integrated braking resistor
<a href="#">5p30:Bmw-13</a>	
<a href="#">Kit Steuerung 500</a>	
<a href="#">3nc1506</a>	
<a href="#">3ex45066-2</a>	
<a href="#">X20cp1584</a>	X20 central unit, ATOM 0.6 GHz, 256 MB DDR2 RAM, 1 MB SRAM, exchangeable program memory: CompactFlash, 1 slot for X20 interface modules, 2 USB interfaces, 1 RS232 interface, 1 ethernet interface 10/100/1000 Base-T, 1 POWERLINK interface, incl. feed module, Terminal block 1x

X20TB12, slot cover and X20 end plate on the right  
X20AC0SR1 enclosed, Order program memory separately!

[4a0006.00-000](#)

[8ce005](#)

[2cp100601](#)