



## Bruel Kjaer

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyatı ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Bruel Kjaer**  
Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Bruel Kjaer T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen Özel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*

¼r¼n	A¼ıklama
<a href="#">Ds-1053/03/030/010/1/9</a>	
<a href="#">Geräuschmesser / 2250</a>	
<a href="#">4294: Calibration Exciter</a>	
<a href="#">VIBROCONTROL 1100 Typ C11 CCS</a>	with default settings Measurement and monitoring electronics for vibrations Power supply: 115/230 VAC Order code: VC-1100-C11-CCS Material no .: C100008.001 Stat. Goods no .: 9031 80 80 Country of origin: DE
<a href="#">AS-063</a>	Vibration acceleration sensor For mobile & stationary use With the following configuration: Sensitivity 100mV/g Temperature range - 50...+125°C Electrical connectionAxial plug connection Sensor supply constant current Order code: AS-063 Material no.: C102705.001
<a href="#">AO0573-S-0100</a>	Sensor connection cable Double shielded cable AC0141, 10 meters Connector MIL-C-5015 - Open cable end Material no.: CMN3533.01
<a href="#">Type 4229</a>	
<a href="#">Bit J353b03</a>	
<a href="#">Ec 1001 40</a>	
<a href="#">Od 1051</a>	
<a href="#">Type 2240</a>	

<a href="#">In 081</a>	
<a href="#">As 062</a>	
<a href="#">Ao 0087 D050</a>	
<a href="#">Ao0573 S 0050</a>	
<a href="#">2239 A</a>	
<a href="#">As 062 050 0</a>	
<a href="#">1as 063 050 0</a>	
<a href="#">Qb 0013</a>	
<a href="#">Vs-168</a>	
<a href="#">3560 B 120</a>	
<a href="#">Vibrocontrol 4000</a>	Schwingungs¼berwachungssystem PS-420
<a href="#">2250 D D00</a>	
<a href="#">Vs 068</a>	VS-068 vibration speed sensor Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40 ... + 80 ° C Measuring direction: horizontal Cable length K: 5 m, open end Cable protection: with steel protection hose Order Code: VS-068 Material no .: X081242.07 Stat. Product No .: 9031 90 00 Country of origin: DE
<a href="#">Ua 0546</a>	
<a href="#">Vs 069</a>	VS-069 vibration velocity sensor Standard for stationary use, 5 m cable With the following configuration: Temperature range: -40 ... + 80 ° C Measuring direction: vertical Cable length K: 5 m, open end Cable protection: with steel protection hose Order Code: VS-069 Material no .: X081242.04 Stat. Product No .: 9031 90 00 Country origin: DE
<a href="#">As 063</a>	
<a href="#">York, Sk.371-03636-00 Kommunikationskarte</a>	<371-03637-000>- VibroControl 4000 CI-411
<a href="#">1100 C11</a>	