

Cameron

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Cameron Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Cameron T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
4. COMPRESSOR ACTUATOR NO:AAP1800.535-0001	FOR INLET VALVE STAGE 1 AND STAGE 2 SL.NO:CB-15304 MODEL:TAE+55M 4R2 RCD130.—01 No's(Common for both actuator)
5. COMPRESSOR ACTUATOR NO:AAP0540008-01205	FOR BY-PASS VALVE OF Process -1, . SL.NO:CB-15304 MODEL:TAE+55M 4R2 RCD130.—01 No's
6. COMPRESSOR ACTUATOR NO:AAP0540008-01206	FOR BY-PASS VALVE OF Process -2, SL.NO:CB-15304 MODEL:TAE+55M 4R2 RCD130.---01 No's
Demco 4" DM5000 Series Replacement Seat	Part No J002207-021
Demco 2" DM5000 Series Replacement Seat	Part No J001876-011
Nuflo 2" WECO 150 Liquid Flow Meter	Connection Type: 1502 WECO Thread to Thread Connection Size: 2" Bore Size / Flow Rate: 2", 40 - 400USGPM. Pressure Rating: 15000psi Body Material: A286 Stainless Steel Rotor Material: CD4MCU Internals/Bearings: Standard Design Temperature: -20 Deg F to 250 Deg F CSA Explosion Proof
Calibration Certificate for above meter	

100002077	Model 3030AN Magnetic Pick-up for above meter
100003474	Calibrated Redress Kit for 2" Meter above
Calibration Certificate for Redress kit	
VALVE 1/2INCH AIR EJECTOR CAMERON ITS-32	
TA3000	
TA 6000 EJECTOR FILTER	
TA 6000 TA 2000 AIR FILTER	
9A-10101231	NUFLO Liquid 2" 1502 Weco Meter Fluid Type: Liquid End Connection Type: [W1] 1502 Weco – Wing to Thread Series: [NF] NuFlo Certification: PED / ATEX / IECEx Model / Bore Size / Flowrate: [L02] 2", 40-400 USGPM End Connection Size: 2" Body Material: A286 Pressure Rating: 1500 PSI (103.4 Mpa) Rotor Material: CD4MCU Internals / Bearings: Standard Linearity (Grade): +/- 1.00% Conduit Connections: 2 @ 180 Degrees Design Temperature Range: -20 F to 450 F Brazing Option: Brazed Plating Option: Nitrided Documentation / Reports: Material Test Report Hydrostatic Test Chart, 10 min. Flow Test Certificate Flow Curve
2296695-01	Certification: II 2 GD Ex d II T6 Gb Ta = -40C to +70C10203 Ex tD A21 IP6X T85 Connection: (2) ¾" NPT Female Conduit Openings. Power: D-Size Lithium Battery, Main or Backup Power (Included) Externally Supplied 6.0 to 30 VDC Loop Powered (4 to 20mA Output) Outputs: 4 to 20 mA Rate, 8.0 to 30 VDC Required Volumetric Pulse Output, Isolated 60 mA Max @ 50 VDC RS-485 Communications, Baud Range 300 to 115.2K Amp & Square Flowmeter Frequency, Open-Drain Transistor, 50 mA @ 30 VDC Inputs: Turbine Meter Input, Adjustable Sensitivity, 0 to 3500 Hz Remote Reset Input, Isolated, 3.0 to 30 VDC Pulse Input, Isolated, 3.0 to 30 VDC Displays: 8 Digit LCD Total Display BBL 6 Digit LCD Rate Display BPD Totalizer Increments and Flow Rate, Units to be Specified Logging: 384 Daily Logs 768 Hourly Logs 345 Event Logs Communication Protocols: RTU- Mode Modbus Enron Modbus Interface Software (Included): Configuration to Include Multi-Point and Gas Calibration Real Time Data Downloads of Reports, Charts Exports to .XLS and CSV Contains 9A-90099000 Lithium Battery
Calibration / Material Certificates	
P0540016-00074	
9a50179024	CIRCUIT BOARD
9a-100002077, Msi Pc51-16e	
044431-01	
Nuflo Flow Meter Rf 3	

9a-100005135	
Ta-6000(50)(1100/150)	
00003	
Injector Filter For Ta 2000	
Cp2b	COUNTER
Sku 14026335984	
Model 242 E	
Cd -20 A Volt : 230vac	
Model: 256	
201073302	KIT
01233 P 1401435	
Sku 14011470022	
20400	SPRING
Cd -20 A Volt : 110vac	
9a-100079965 S/N 3sbf17727	
9a-100015379	
044351-01	
201073303	REBUILD KIT
2197012-83	
Mb 796039-00003	
6449090370	REBUILD KIT
9a-100005136	
9a-100062996 S/N 4sbf12518	
202ebstsblrdnn03	RECORDER
6818030099	POPPET
Model 202 E	
216485304	PART
288a, 288c	
619012-89-01	
Mb796039-004	
223183101	HEAD

9a-30099004,7,2vdc,	
223183001	UNIT
681801	SEAT
619012-03-06-96	
Aap1404040-00217	
271193308	
6818020099	SEAT
Sor 9ba-Kb45-N4-F1a-9a	
602153-01	
044437-01	
9a-30099004	
Ze544-002a-220	INTERFACE CARD 32CHANNEL DIGITAL OUTPUT
Aamb796039-00004	
044974-02	
9a-100003474	
216434702	CYLINDER
Ze544-005a-840	DISPLAY MODULE 16BUTTON LED RED