



Camlock

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Camlock Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Camlock T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;2"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 2" x 1 1/2", CL150 , RF , SCH XS, B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1, ----- Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1
FLANGE;A350-LF2 CL.1;#150;RF;4"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 4" x 1 1/2", CL150 , RF , SCH STD., B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1,
FLANGE;A350-LF2 CL.1;#150;RF;4"X1.1/2"	REDUCING THRD FLG , ITCS A350-LF2 CL.1, 4" x 1 1/2", CL150 , RF , SCH STD., B16.5REDUCING THRD FLG , ITCS A350-LF2 CL.1, ---- Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. Material certificate: EN 10204 Type 3.1Flange shall be manufactured in accordance with "WRP-SPC-MTE-GEN-026". Flanges shall be NPT, taper threads in accordance with ASME B1.20.1. EN 10204 Type 3.1
	GASKET , 2" , 316L SS-FG , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THK , 316L SS INNER RING , 316L SS OUTER RING , CL150 , B16.5 , B16.20 ---- Commodity Code: PGG153L5315BL01 GASKET , 316L

GASKET;SPIRAL WOUND;2";#150 316L SS;1/8"	STAINLESS STEEL WINDING, FLEXIBLE GRAPHITE FILLED , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THICK , 316L STAINLESS STEEL INNER RING , 316L STAINLESS STEEL OUTER CENTERING RING , CLASS 150 , PER ASME B16.5 , PER ASME B16.20Commodity Code: PGG153L5315BL01
GASKET;SPIRAL WOUND;4";#150 316L SS;1/8"	GASKET , 4" , 316L SS-FG , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THK , 316L SS INNER RING , 316L SS OUTER RING , CL150 , B16.5 , B16.20 ---- Commodity Code: PGG153L5315BL01 GASKET , 316L STAINLESS STEEL WINDING, FLEXIBLE GRAPHITE FILLED , SPIRAL WOUND LOW STRESS , 1/8" (3.2 MM) THICK , 316L STAINLESS STEEL INNER RING , 316L STAINLESS STEEL OUTER CENTERING RING , CLASS 150 , PER ASME B16.5 , PER ASME B16.20Commodity Code: PGG153L5315BL01
FITTINGS;STUD BOLT;A320-L7;5/8"x4"	STUD BOLT (CONT) , 5/8" x 4" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , A194-7, S3 , B1.1 , XYLAN 1424 COATED , DIA (IMP) X LEN (MET)STUD BOLT (CONT) , 5/8" x 4" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS, PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , XYLAN 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS, PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , XYLAN 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1
FITTINGS;STUD BOLT;A320-L7;5/8"x7"	STUD BOLT (CONT) , 5/8" x 7" , CR-MO A320-L7 , W/ 2 HVY HEX NUTS , A194-7, S3 , B1.1 , XYLAN 1424 COATED , DIA (IMP) X LEN (MET) ---- Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS , PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , XYLAN 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1Commodity Code: PB1BLL2ASS1W002 CONTINUOUS THREAD STUD BOLT , CHROME-MOLYBDENUM PER ASTM A320 GRADE L7 , WITH 2 HEAVY HEX NUTS , PER ASTM A194 GRADE 7, SUPPLEMENTARY REQUIREMENT S3 FOR LOW TEMPERATURE , PER ASME B1.1 WITH DIMENSIONAL RECOMMENDATIONS PER ASME B16.5/ASME B16.47/MSS SP-44 , XYLAN 1424 TOP COATED , DIAMETER (IMPERIAL) X LENGTH (METRIC) Material certificate: EN 10204 Type 3.1
F150-SS-NPT	1 1/2 NPTM SNAPLOCK ADAPTOR SS
B150-SS-NPT	1 1/2 NPTM SNAPLOCK COUPLER SS
DC150-SS	1 1/2 SNAPLOCK DUST CAP SS
2" Ball Valves, Manual Lever	Operations, Full Bore, PN16, Bronze Material, NPTF, RPTFE Seat
4" Ball Valves, Manual Lever	Operations, Full Bore, PN16, Bronze Material, NPTF, RPTFE Seat
2" NPT cap SS316/316L	
4" NPT cap SS316/316L	
4" cam-lock adaptor type F	(male cam-lock / female NPT) Bronze
4" cam-lock adaptor type D	(female cam-lock / female NPT) Bronze
4" hose c/w cam-lock	couplers type C one end, type E other end (male / female), length 10mtr
CAMLOCK 991S01-21-1AGV BOLT (3222346929)	

[SMP S400S 4303](#)

[991S01-21-1AGV BOLT \(3222346929\)](#)

[991R2-2AZ 3222343802](#)

[V.N.009.1/00.](#)