



Catu

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Catu Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Catu T¼rkiye Distrib¼t¼r¼ veya temsilcisi deęildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Catu Ci-465-10/30-M	Single-pole voltage tester 10-30 kV. In one piece. Integrated Operating rod. Approved according to NF C-18-311, EDF. Wall bracket included.
Catu Cz-54r	Rescue box 24 kV for wall mounting - GB
Catu Ce-4-21-C	2-part telescopic earth rod 90kV 2m, hexagon version. Open air (can be used when it rains). According to IEC 61235.
Catu Mp-60/05-1	Site insulation mat according to IEC / EN 61111. Class 4 (36kV AC / 54kV DC), dimensions: 0.6 x 1 m, thickness: 5mm
Catu Mt-9801	Earthing and short-circuiting device 10 kA / 1s consisting of: 3x clamp MT-817-C, connection round conductor Ø 5-16mm 3x clamp MT-814/2 flat conductors 0-16mm 1x clamp MT-840/1 round conductor Ø 5-28mm 3x connection cable 1.5m 50mm ² 1x grounding cable 2.5m 25mm ²
Catu Cg-20-B-R	Electrically insulating gloves. Class 2 - Max. Voltage 17000V, size 9, length: 14 ' / 360mm. Color red. Straight edges. According to IEC 60903.
Catu Cg-20-C-R	Electrically insulating gloves. Class 2 - Max. Voltage 17000V, size 10, length: 14 ' / 360mm. Color red. Straight edges. According to IEC 60903.
Catu Cc-965-10/30	Indoor and outdoor (can also be used in precipitation) Voltage tester 10-30 kV. Acoustic and optical signal. With self-test device. According to DIN EN 61243-1.
CATU CE-4-21-C	2-part telescopic earthing rod 90kV 2m, Hexagon version. Open air (can be used when it rains). According to IEC 61235.

CATU CC-765-10/36-C	Voltage tester 10-36kV Customs tariff number: 90303380 FR End fitting "C": hexagonal male 12 mm on flats, for hexagonal end fitting sticks.
Hochspannungsdetektor 36 kV / CATU CC-765-10 / 36	
Schall- und Lichtwarnmelder / CATU CE-4-21 33kV	66kV 90kV Isolierstab
CC-765-55/20-C	Voltage tester 5.5-20kV - hexagon
CC-765-3/10-C	Voltage tester 3-10kV
CE-4-21-K	2-part telescopic earthing rod 2m, Universal knurling. Open air (can be used when it rains). According to IEC 61235
CATU CC-265-225/420	Voltage Detector 225 - 420 kV Weight: 1,800 kg, Customer tariff number: 90303380 Country of origin: France
CATU CC-260-150/420	DETECTEUR DE TENSION HTB 150/420kV Weight:, Customer tariff number: 90303380 Country of origin: France
CATU CE-4-30-C	Earthing rod 150 kV, from 1.75 m to 3 m, 2 kg already equipped with hexagon. Weight: 2,200 kg, Customer tariff number: 70191990 Country of origin: France
CATU CE-9-5603-C	Adjustable telescopic stick Weight: 3,7 kg Dimensions: folded 2,15m / entirely unfolded 5,60m
CATU CL-2-5/36-2 5-36kV	Voltage tester 5 - 36 kV with integrated telescopic rod (0.33 - 0.90 m), optically Neon tube HV Detector 5/36 KV weight: 0.321 kg, Customer tariff number: 90303380 Country of origin: FRA
CATU CL-4-41-*	NEON TUBE HV DETECTOR 5/40KV
CATU CG-20-B-R	Electrically insulating gloves. Class 2 - Max. Voltage 17000V, size 9, length: 14 ' / 360mm. Color red. Straight edges. According to IEC 60903.
CATU CG-20-C-R	Electrically insulating gloves. Class 2 - Max. Voltage 17000V, size 10, length: 14 ' / 360mm. Color red. Straight edges. According to IEC 60903.
CATU CZ-54R	Rescue box 24 kV for wall mounting - GB
CATU CF-5-90-E	Reinforced earthing rod 2.00m bayonet
CATU MP-11/11	Site insulation mat according to IEC / EN 61111. Class 0 (1000 V). Dimensions: 1 x 1 m. Thickness: 2 mm. Please note the dimensions!
CATU MT-9801	Earthing an short-circuiting system
CATU CC-765-10/36-K	Voltage tester 10-36kV
CC - 265 - 90/225 + CM - 4535 - K 3,5 MT	170 KV-MELDERSET

MT - 835 - H	154 KV ERDUNGSSET VERRIEGELT
CC - 765 - 10/36 - K - SE T	10 - 36 DETEKTOR + STANKA
MT - 613 - 2	OG LEITUNGSERDUNGSSET
CATU MT-830-P	Three-part telescopic pole up to 45 kV Length 0.64 / 1.5 m Hexagon version
Stick with neon lamp	(gibt es so ein Artikel?)
MV Voltage Detector # 1600400501	
Switch Stick Prong 4215	
CC-765-10/36-K	Voltage tester 10-36kV
CATU CG-117	Pneumatic glove tester
CATU CC-765-10/36-K	Voltage tester 10-36kV I.E.C. COMPACT H.V. DETECTOR 10/36 kV, universal end fitting K Weight: 0.700 kg, customer tariff number: 90303380 Country of Origin: France
CATU CE-4-21-K	2-part telescopic earthing rod 2m, universal knurling. Outdoor (usable when it rains). According to IEC 61235. Telescopic insulating stick according to IEC61235. Length 1.2/2.0m. Rated insulation: 90kV. Universal end fitting. Weight: 1,850 kg, customer tariff number: 70191990 Country of origin: France
CATU CC-765-10/36-C	
(271960) AT-49/025	
10006150	
10006151	
10006312	
11111	
251208	
251476	
251477	
251515	
251521	
251567	
251780	
271029	
271208	

271253
271254
271254 CATU MO-630
271397
271484
271495
271527
271544
271742(MS-124)
271873
271874
272023
272064
272128
272410
28102014
64599004
AL-201/1
AL-201/1-1
AL-204
AL-205/5
AL-230-Z-EX
AL-240
AL-240-S-BL-111-EX
AL-318
AL-62-A
AL-63-A
ALM-6/25
ALM-6/8
ALP-4/3
AM - 65

AM -20
AM-18/1
AM-208/1
AM-346
AM-49/1
AM-51/2
AM-510-EX
AM-910
AP - 461
AP-373
AP-467
AP-510-GB
ARC-40-B-L
ARC-40-B-L / 251559
AT-54/1
BAR22
BAR-52
BOOTS
C-765-10/36-K
CATU AL-62-A
CATU AP-510-GB
CATU CC-760-00
CATU CC-765-04/14-US
CATU CG-10-D
CATU CG-35/2
CATU CG-40-D
CATU CG-98-C
CATU CI-4-K
CATU CL-1-06
CATU CL-40010 (1 Pack = 3 Pcs.)

CATU CL-4-41/2
CATU CL-5-36
CATU CL-7-10/30-K
CATU CL-8-36
CATU CL-8-36/1
CATU CT-7-40/1
CATU CZ-53-E/2
CATU CZ-55-MR
CATU DT-102
CATU M-24-35
CATU M-78-665 EMPTY PLASTICAL CASE FOR EARTHING EQUIPMENT
CATU M-78723
CATU M-87-384
CATU MO-180-ARC4
CATU MO-185-B
CATU MO-185-BL with facelift
CATU MO-186
CATU MO-65209
CATU MO-65234
CATU MP-213
CATU MP-60/03-5
CATU MT-5805
CATU MT-613
CATU MT-635/1-C
CATU MT-6613
CATU MT-6613 (35/16)
CATU MV-137/(*) INSULATING BOOTS,20000 V, ACC. TO EN50321,SIZE 39-45
CATU MV-137/41 (1 Set = 1 Pair)
CATU MV-137/44

CATU MV-226-41 (1 Set = 1 Pair)	
CATU-KIT-ARC-01	
CATU-MT-1920	
CC 765-10/36 OG	
CC-245-225/550-K	
CC-245-63/90-C	
CC-245-63/90-K	
CC-245-90/225-K	
CC-360/40-14	
CC-363-K	
CC-365-3/10-(K)	
CC-760-00	
CC-760-5/36-C	
CC-765-04/14-US	
CC-765-10/	
CC-765-10/30-K	
CC-765-10/36*	
CC-765-10/36-C	
CC-765-3/10*	
CC-765-3/10C	
CC-765-5.5/20-(*)	
CC875-10/36	
CC-965-10/30	
CD-104	
CE-4-21-	
CE-4-21-C	
CE-421-K	
CE-75-C	
CATU CE-75-K	75kV Transport length : 1.15m Total length : 2m.
CF-3-72-E	

CF-5-40-(K)
CG.02.C
CG-05-B
CG-05-C
CG-1-09-NR
CG-10-A-R
CG-10-B-R
CG-10-C
CG-10-C-R
CG-10-D
CG-10-D-R
CG-1-10-NR
CG-117
CG-118
CG-12/S-(*)
CG-15
CG-15-C
CG-20
CG-2-09-NR
CG-20-B
CG-20-C493-310
CG-2-10-NR
CG-30-B-R
CG-30-C
CG-30-D-R
CG-3-10-NR
CG-35/1
CG-35/2
CG-35-2
CG-36

CG-37
CG-40-C
CG-40-D
CG-411-NR
CG-96-(*)
CG-98-C
CG-99-D
CGA-0-(*)-B
CGA-1-(*)-NB
CGA-4-(* **)-NB
CGM. 00 C/B
CGM-00-09
CGM-0-09
CGM-2-08
CGM-2-09
CGM-4-10
CGM-4-11
CI-10-D
CI-4-K
CL 400 LUMIFIX
CL-1-06
CL-2-10/30
CL-2-5/10
CL-2-5/36-2
CL-2-5/36-2 M511360/060
CL-4
CL4/03-36/2US
CL-4-10/30-2
CL-4-10/30-M
CL-4-41-C
CL-4-41-K

CL-465-10/30-M
CL-5-36
CL-7-10/30-C
CL-7-10/30-K
CL-8-05
CL-8-36
CL-8-36/1
CM 45
CM-03-K
CM-1-10
CM-4360-E
CM-6-15
CM-7-10-A
CS-45
CS-90
CT-7-25/1
CT-7-40/1
CT-9-45
CZ-53-E
CZ-53-E/2
CZ-53-MR
CZ-53-MR/2
CZ-53-R
CZ-54E
CZ-54-MR
CZ-54-R
CZ-55-MR
CZ-55R
CZ-60
DT-102

DT-104
Etche 36KV TST NS
EXTRAIT DE L'ARRETE DU 30 AVRIL 1951
GLB3-36
GLBOO-36
KIT-01
KIT-ARC-03
KIT-ARC-10-C
KIT-ARC-12-C-L
KIT-ARC-25-B-L
KIT-ARC-40-B-2XL
LCM-50
LS-7088-B
LS-7088-B size 8
M-24-150-S
M-24-35
M-78-665
M-78723
M-87-295
M-87-370
M-87-384
M-87-71
M-881622
M-881635
M-881956
M-952120
M952170
M-95-864
MF-62
MG-103-S

MG-163/1
MG-603
MG-603/1
MIT-6613
MO-11010
MO-131/1
MO-132
MO-156
MO-180-ARC4
MO-181/1-B
MO-182/1-B
MO-182/1-J
MO-184
MO-185
MO-185-B
MO-186
MO-431-30
MO-510-03
MO-563M
MO-61001
MO-61002
MO-64502
MO-65203
MO-65204
MO-65205
MO-65206
MO-65207
MO-65209
MO-65211
MO-65222

MO-65230
MO-65232
MO-65234
MO-65246
MO-65248
MO-66005
MO-67103
MO-67302
MO-67601
MO-68013
MO-68017
MO-68019
MO-68113
MO-68117
MO-68119
MO-68701
MO-68702
MO-68703
MO-68704
MO-69050
MO-69T30
MO-71
MO-72005
MO-72006
MO-72007
MO-72162
MO-834
MO-852
MP-100/03-10
MP-100/05-10
MP-100/05-5

MP-100/10-5
MP-100/3*10
MP-11/11
MP-213
MP-42/11
MP-42/16
MP-510/2
MP-514/2
MP-60/03-5
MP-60/05-1
MP-607/2-I
MP-634/2-D
MP-700-2
MP-700-3
MP-700-4
MP-700-5
MS-118
MS152
MS-920
MT.814
MT-1910
MT-1910-D-3X150KS250
MT-1920
MT-405-D
MT-406
MT-4804
MT-508/46
MT-5805 3
MT-613
MT613/DR3.5

[MT-615/2-7.5](#)

[MT-635/1-C](#)

[MT-650](#)

[MT-6613/1](#)

[MT-731-E](#)

[MT-814/2](#)

[MT-840/1](#)

[MT-8407](#)

[MT-853](#)

[MT890](#)

[MT891](#)

[MT893](#)

[MT895](#)

[MT-9801](#)

[MV-135](#)

[MV-135-43](#)

[MV-137/\(*\)](#)

[MV-137/41](#)

[MV137/45](#)

[MV-137/47](#)

[MV-222-41](#)

[MV-226-41](#)

[MX-701](#)

[MX-704](#)

[NG 920](#)

[RFG TR01](#)

[SFETV10](#)

[SLB-K2-HVWP/L](#)

[SUPPLY/59](#)

[TCG38](#)

TCG70	
TIP:CL. 4-42/2 5-40KV is not known by their manufacturer	
TIPPER TIE CLIPPER 621R	
CL-4-41C Detex OG	
MS-920	low voltage tester 12-690VAC
154 kV Lokale Erdungsausr¼stung	k¼nnen sie uns einen Produkt vorschlagen
154-kV-Spannungssteuerstift	
CATU CZ-54-E	24 kV rescue box for wall mounting - ES Spanish version
CZ-54-E	
CATU CC-765-10/36-K	Voltage tester 10-36kV IEC COMPACT H.V. Detector 10/36 kV , Universal end fitting K 90303380 FR
CATU CZ-53-R	Portable rescue kit 24kV - GB
CATU CC-765-10/36-K	Voltage tester 10-36kV
CATU CT-7-40/1	Insulation stool 45 kV - interior
CATU CG-40-C-R	Electrically insulating gloves. Class 4 - Max Voltage 36000V, Size 10 , Length : 16'/410mm. Color Red. Straight Edge. According to IEC 60903.
CATU MV-226-41	safety shoes with electrically insulating soles; Shoe, summer Size 41 (size not mentioned in request, please when ordering specify ! Size 39 - 47) Based on EN ISO 20345
CATU CZ-60	Insulated cable cutter 25 kV. Handles with handguard. Opening width approx. 30 mm for cables or ropes up to approx. 150 mm ² . Forged steel blade head. Length 630mm. weight 2.2 kg.
CATU KIT-ARC-65-B-XL	Arc protection set size XL - according to EN61482-1-1
CATU CL-8-36	2-pole phase comparator 2-36kV
CATU CE-4-21-K	2 parts telescopic grounding rod 2m Universal border Outdoor (usable when it rains) According to IEC 61235
1. Item	3.6: Warning signs for safety regulations consisting of signs, stands & other accessories necessary Safety Padlock Catu ref: AL-230-111-EX à 2 per center Warning Sign Catu ref: AP-510-GB à 5 per center (Language of the sign should be English, Arabic can be added if possible) "Danger" Sign Catu ref: AM-61-GB à 5 per center (Language of the sign should be English, Arabic can be added if possible) ALU WARNING SIGN (LIGHTENING) (Aluminum Warning Sign - phosphorescent) Catu ref: AM-49/1 à 10 pcs per center Instruction Plate Catu ref: AM-20-GB à 5 per center (Language of the plate should be English, Arabic can be added if possible) RED/WHITE 25M

	LONG PLAST. CHAIN (Red / White 25M plastic chain) Catu ref: AL-31/25 à 2 pcs per center ROUND ALUMUNIUUM WARNING SING (Round Aluminum Warning Sign) Catu ref: AM-467-GB à 5 pcs per center SAFETY BOUNDARY (Delinator) Catu ref: AL-316 à 5 pcs per center
2.Item 3.13: Portable earthing 132 kv	CLAMP 40KA/15-60MM H-TYPE (Catu brand "MT-735-H" or equivalent) à 9 pcs per center EARTH CLAMP 40KA (Catu brand "MT-843" or equivalent) à 9 pcs per center CARRYING BAG FOR 2M MAJOR ROD (CARRYING BAG FOR 2M EARTH ROD) (Catu brand "CM-3-04" or equivalent) à 3 pcs per center CU CABLE 150MM² (150MM² COPPER CABLE) (Catu brand "M-24-150-S" or equivalent) à 18 pcs per center CARRYING BAG FOR CLAMPS+CABLE (Catu brand "M-87-153" or equivalent) à 3 pcs per center STICK ELEMENT L=2.00M (2M GROUND ROD) (Catu brand "CM-6-20" or equivalent) à 3 pcs per center DIRECT ASSEMBLING KIT 150MM² (150MM² ASSEMBLY KIT) (Catu brand "MCC-150" or equivalent) à 9 pcs per center CONNECTION ADAPTOR H/U3 FEMALE (H/U3 FEMALE CONNECTION ADAPTER) (Catu brand "CI-3-H" or equivalent) à 3 pcs per center ASSEMBLING EQUIPMENT - if required
cc 765 10/36 kv	
CATU AL-230-111-EX	Padlock 50x6 mm, red, key 111
cc-765-10/36-k 10-36kv	
CL-2-5/36-2	
mo-284	
271281 CATU CC-765-10/36-C	
271208 CATU CE-4-21-C	
CL-2-5-36-2 (5-36kv) 25152	
/ (CC-765-10/30-K + CE-TL-2-020-K)	
MAGNETİC SINYAL PYRAMID	"ELECTRİC HAZARD "TO WORK ON EHV OR BATTERIES CATU ACA-10
PLASTIC POSTER FOR HEV CATU AP-72	
GROUP LOCK BOX CATU SL-106	
GLOVES BOX CATU CG-35-2	
UNDERS.FOR INSULATING GLOVES CATU CG-80-H	
CC-765-10/36-K-SET 10-36	
OG CC785-290-K	
271616	CATU CG-10-B Electrically insulating gloves Class 0 - Max. Voltage 1000V Size 9, Length : 14'/360mm Color beige, straight edges According to IEC 60903 Weight: 0.250kg

271296	CATU CGM-0-09 Electrically insulating gloves, composite. Kl. 0 - Max. voltage 1000 V. Size 9, Length:14'/360mm, Two Tone Beige/Orange, According to IEC 60903. Arc fault tested class 2 according to IEC61482-1-2 and ATPV cal/cm ² . Weight: 0.360kg
271068	CATU MV-137/43 Insulating boots size. 43 20 kV, according to EN 50321 Weight: 2.65kg
271071	CATU MV-137/45 Insulating boots size. 45 20 kV, according to EN50321 Weight: 2.65kg
271165	CATU MO-11000 Colorless safety glasses according to EN 166 / EN 170 Weight: 0.09kg
271418	CATU MO-11010 UV Fitovers Weight: 0.09kg
MO-11010	
251521 / CI-2-5/36-2	
CE-4-21	
CC7651036Ksp	Voltage tester for 10-36 kV - IEC61243 - Universal coupling - Electronic voltage tester for switchgear and Overhead lines, can be used when it rains - Ultimate capacitive voltage tester technology - Universal nominal frequencies 50 / 60 Hz - Visual and acoustic display with built-in Self-testing device - In plastic case with 9 V battery (6LR61) and supplied with a screw-on, hook-shaped contact electrode - Operating temperature -15 to +40 °C (climate class N), Storage temperature -25 to + 55 °C - Dimensions (excluding hooks) - 370 x 165 x 145 mm - CE marking corresponding to EMC interference immunity Guidelines - According to IEC61243 10-36 kV
CATU CC-765-10/36-C	Voltage tester 10-36kV. According to IEC 61243. Hexagonal coupling.
CATU MP-100/05-5 Matting	ELECTRICAL INSULATING MATTING - Maximum Safe Working Voltage - 36000V Class 4
CZ-55-FM	SAFETY KIT
3615xCL40010	Permanent voltage indicator - 5-75 kV - 7 LEDs - Housing diameter Ø 40 mm - Length 110 mm - Permanent indoor voltage indicator for constant monitoring of the voltage - Attachment to bare round conductor Ø 5-20 mm and flat conductor 1-20 mm - Display by 7 LEDs - has an articulated arm - Weight - 60 g
MT-1910EP	
CN-7-005-036-K	
CATU CN-7-005/036-K	DTSC 010/036 Kv emb K
CE-3-24-C 36 kV	
Catu Cg-10-A-R	

Catu Cg 117
271366
Catu Mo-65204
251521 / CI-2-5/36-2
Catu Mp-514/2
(Cz-50-Mr Is Obsolete), Replaced By Catu Cz-54-Mr
Mo-56009
CI-40010
Cg-40-D-R
271268 Catu Cc 765 10 36 K
Catu Mo-65248
Catu CI-8-05
251476 Cs 45
Mo-187
Mt-5805
Mv-137
Catu Kit-Arc-40-B-L
Mo-185-BI
(271960) At-49/025 Self Adhesive Warning Sign
Prel-Ce-5-90k
(271268) Cc-765-10/36-K
Catu Ci-4-K
Cg-4-10-Nr
251567 Cg-40-C
Catu Mo-65203
Mp-100/02-10
Mo-11000
Mv-226
251476 Cs-45

Mp-60/05-10	
Catu Al-205 (271544)	
Mv-136	
10006150 Block;Type:Circuit Breaker	
Arc-55-B Is Not Available Anymore, Superseded By Either Kit-Arc-40-B Oder Kit-Arc-65-B	
Catu Mo-65246	
Catu-Kit-Arc-01	
CATU CG-4-10-NR	Electrically insulating gloves. Class 4 - Max. voltage 36000 V, Size 10, Length: 16'/410mm, Two-tone Beige/Red. Rolled edges. According to IEC 60903. Minimum order quantity: 6 pairs
Cc875-10/36 C Replaced By Cc-765-10/36-C	
Catu Cl-40010	
Kit-Arc-40-B-2xl	
Cl-1-05	
Mv-136-B	
271208 Ce-4-21-C Telescopic Insulating Stick According To Iec61235. Length 1,2/2,0m. Rated In	
Mp-123	
Catu Cga-1-10-Nb	
Mo-134	
Catu Mt-830-P	
251515 Cm 1 10	
Cc-245-66/132-C	
Mv-137/43	
Cg-40-C Cg-4-10-Nr	
271208, Ce-4-21-C	
251916	
Mt-6613	
Cg-40-C-R	
Cg-4-(*)-Nr	

251208 Ce 4 21 C
Mit-6613
Catu Cg-30-B-R
251477 Cg-35-2
Catu Cga-1-11-Nb
Catu Al-63-A
Cc-765 10/36 K 10-36kv
Glb3-36 / By Catu Cg-30-B-R
Cm-50
271208 Ce 4 21 C
10006312 Lock;Type:Box
Cf-5-40-C
Cm-4360-C
251780 Cc-765-3/10-C
251208 Ce-4-21-C
Catu Mo-65205
Catu Cg-37
Catu Cg-10-D-R
Catu Kit-Arc-65-B-L
Mo-69t40
Catu Cga-1-09-Nb
251515 Cm-1-10
(Cz-50-Mr Is Obsolete), Replaced By Cz-54-Mr
Cf-5-40-E
Catu Cg-10-C-R
1482bp410
Mv-137/44
Catu Alp-4/3
Mo?71

10006161
Cc-245-150/420-K
Catu Cg-10-B-R
Cl-4-41/2
Mv-227
251780 Cc 765 3 10 C
Catu Mo-65206
Catu Al-318
Catu Cg-411-Nr
10006151 Block;Type:Circuit Breaker
Sfetv10 / By Catu Cg-117
Catu Mo-65207
Catu Cz-54-Mr
Catu Mv-137/41
Catu Cg-30-D-R
251477 Cg 35 2
(271517) Mt-6613
Glboo-36 / By Catu Cg-10-A-R
Mo-180-Arc12
Prel-Cf390k
Mp-22
251489
Mp-32-10
Mv-228