



Cd Automation

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Cd Automation Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Cd Automation Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|--|---|
| REVO-S-1PH | REVO-S-1PH Nominal current 35A Maximum main voltage 480V No Aux. Voltage without HB and/or Analog Input up to 210A included Logic Input SSR Zero Crossing Firing Control mode in Open loop No Fuse No fan CE EMC For European Market Manual in Italian language Standard Version with or without Fuse |
| RSX30420SZ0F0011 | REVO-SX Three zones 4,5A Maximum main voltage 230V No auxiliary voltage Logic Input SSR - Zero Crossing firing Zero Crossing Firing Control mode in open loop Fuse + Fuse Holder No fan CE EMC For European Market Version 1 Standard |
| REVO RS3030-44A80H0021 | Solid State Contactor 30A |
| REVO RS3150-44A40H1021 | Solid State Contactor 150A |
| REVO RS3030-44A80H0021 | Solid State Contactor 30A |
| REVO RS3030-44A80H0021 | Solid State Contactor 30A |
| RS3180-44A40H1021 | REVO-S-3PH Nominal current 180A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 4 Cycles Control mode in open loop Fixed Fuse + Current Transformer + Heater Break Fan voltage 110V CE EMC For European Market Manual in English language Standard Version with or without Fuse |
| REVO RS3030-44A80H0021 | Solid State Contactor 30A |
| REVO RS3030-44A80H0021 | Solid State Contactor 30A |
| REVO S IFH 1PH (DA 30 A 40A) | |

| | |
|--|--|
| RS1040-40SZ0Y0021/002 | REVO-S-1PH Nominal current 40A Maximum main voltage 480V No Aux. Voltage without HB and/or Analog Input up to 210A included Logic Input SSR Zero Crossing Firing Control mode in Open loop Fuse and Fuse Holder + Current Transformer No fan CE EMC For European Market Manual in English language Standard Version with or without Fuse |
| 23835-64322-0033 | |
| 271SSR | |
| CD3000M | |
| CD3000M 2PH/35A/400V/480V/170:265V/10KPot/BF008/NF/EM | |
| CD3000M-DRIVE | |
| CD3000S 1PH/45A/220V/480V/12:24V/SSR/ZC/NF/HB/EM | |
| CD3000S 2PH | |
| CD3000S 2PH/125A/400V/480V/170:265V/SSR/ZC/IF | |
| CD3000S 2PH/15A/-/480V/NO/SSR/ZC/NF/IM | |
| CD3000S 2PH/25A/-/480V/NO/SSR/ZC/NF/EM | |
| CD3000S 2PH/35A/-/480V/NO/SSR/ZC/NF/EM | |
| CD3000S 2x10A/-/240V/NO/SSR/ZC/NF/EM | |
| CD3000S-1PH | |
| CD3000S-1PH / 25A / 480V / NO / SSR / ZC / NF / - / - / 0 / IM | |
| CD3000S-1PH / 35A / 480V / 12:24 / SSR / ZC / NF / HB / - / 0 / IM | |
| CD3000S-1PH-45A-480V-SSR | |
| CD3000S-2PH-10A-480V-480V-NO-SSR-ZC-NF-EN | |
| CD31.45A.HA.SI UL | |
| CD3200-0045480460CL | |
| DM2150-42SZ052020 | |
| DM3075-42AB002020 | |
| DS1025-20SZ000020 | |
| DS104544SZ010020 | |
| DS1060-20SZ000020 | |

| | |
|--|---|
| DS12XX-20SZ000020 | |
| DS2010-40SZ000000 | |
| M30225-42VC0V3022 | |
| RCL090-42APO_00_21 | |
| RCL-15043AEWH2021 | |
| RCL180-42APO_2021 | |
| RCL280-42APO_2021 | |
| RE3035-42APIA3026 | |
| RE3-04541VPUV30X2 | |
| RE3075-42ADIA3023 | |
| REVO M-2PH RM2280-42ABUY2021 | |
| RKP2-04-M-000-00 | |
| RM3060-45ABUH2011 | |
| RM3060-45RB0Y2021 | |
| RM3150-45RB0Y2011 | |
| RM3210-45RB0Y2021 | |
| RS1030-40SZ0Y0011/002 | |
| RS1040-44SZ0H00X1 | |
| RS3400-42A80H2021 | |
| SCR CD3000S 1PH/25A/-/480V/NO/SSR/ZC/NF/EM | |
| SCR CD3000S 1PH/45A/-/480V/NO/SSR/ZC/NF/EM | |
| CD3000M 2PH/150A/380V | |
| RS1040-44SZ0H0011 | REVO-S-"PH Nominal current 40A Maximum main voltage 480V With HB and/or Analog Input 12:24V ac-dc up to 210A Logic Input SSR Zero Crossing Firing Control mode in Open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in Italian language Standard Version with or without Fuse |
| RS3030-44A80H0021 | Dimensions (WxHxD) 108x121x185 mm - 1,83Kg REVO-S-3PH Nominal current 30A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC |

| | |
|---------------------------------------|--|
| | For European Market Manual in English language Standard Version with or without Fuse |
| SSR090-60SR0F0021 | REVO-SSR 90A Nominal Current depend on °C/W of Heath Sink Maximum main voltage 600V No Auxiliary Voltage Logic Input SSR Random Firing Control mode Open loop Fuse + Fuse Holder No fan CE Approve Manual in English language Standard Version with or without Fuse |
| SSR062-44V80X0025 | REVO-SSR 62A Nominal Current depend on °C/W of Heath Sink Maximum main voltage 480V Auxiliary voltage 12-24V ac dc with HB option 0:10 V Analog Input Burst Firing 8 Cycles ON at 50% Power Demand Control mode Open loop Fuse + Fuse Holder + Current Transformer + Heather Breack Alarm + Multiple cable No fan CE Approved Manual in English language Second fuse normally used with phase to phase voltage supply(additional price) |
| RC3300-45VEUQ2042 | REVO-C-3PH Nominal current 300A Extrarapid Fixed Fuse Included Maximum load voltage 480V Auxiliary voltage supply range: 342 to 528Vac Input: 0-10V dc Firing: Phase Angle - Linear Soft Start Control Mode: Voltage Option: Current Limit + Heater Break + Data Logger Fan 230V CE Approved Load Type: 3 Phase Transformer coupled with normal resistance Communication: N°1 Modbus RTU - Retransmission 0:10V |
| CD 3000 Power | |
| SOLID STATE CD-RS1040 | REVO THE RELAY EVOLUTION 480V 40A MOD.:RS1040-44SZ0X0021 SER.NO.:056547-167061-001 |
| RS1040-44SZ0X0021 | REVO-S-1PH Nominal current 40A Maximum main voltage 480V With HB and/or Analog Input 12:24V ac-dc up to 210A Logic Input SSR Zero Crossing Firing Control mode in Open loop Fuse and Fuse Holder + Current Transformer + Heather Break + Multiple cable with connectors No fan CE EMC For European Market Manual in English language Standard Version with or without Fuse |
| RC2150-45VB002000 | REVO-C-2PH Nominal current 150A Extrarapid Fixed Fuse Included Maximum load voltage 480V Auxiliary voltage supply range: 342 to 528Vac Input: 0-10V dc Firing: Burst firing - No Soft Start Control Mode: Open Loop No Option Fan 230V CE Approved Load Type: Normal Resistive Load with 3 Phase Star without neutral Connection Communication: |

| | |
|---|---|
| DS2010-10SZ000L20 | N°1 Modbus RTU - No Retransmission CD3000S-2PH Nominal current 10 A Maximum main voltage 480V No Auxiliary Voltage Logic Input SSR Zero Crossing Firing Control Mode - Open Loop No Fuse - No Option No Fan - for unit < 45A CE EMC + cUL® listed and cULus 508® listed Manual in English language IP Protection standard |
| CD3000S SOLID STATE | |
| RS3090-44A60F2021 | REVO-S-3PH Nominal current 90A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog input 4:20mA Burst firing 6 cycles Control mode in open loop Fixed fuse Fan voltage 220V hrs CE EMC For European Market Manual in English language Standard version with fuse |
| RC2300-42ABU02000 | REVO-C-2PH Nominal current 300A Extrarapid Fixed Fuse Included Maximum load voltage 480V Center Leg Bar - L2-T2 trough bar Auxiliary voltage supply range: 180 to 265Vac Input: 4-20 mA Firing: Burst firing - No Soft Start Control Mode: Voltage No Option Fan 230V CE Approved Load Type: Normal Resistive Load with 3 Phase Star without neutral Connection Communication: N°1 Modbus RTU - No Retransmission |
| RS1030-40SZ0Y0011/002 | REVO-S-1PH Nominal current 30A Maximum main voltage 480V No Aux. Voltage without HB and/or Analog Input up to 210A included Logic Input SSR Zero Crossing Firing Control mode in Open loop Fuse and Fuse Holder + Current Transformer No fan CE EMC For European Market Manual in Italian language Standard Version with Fuse |
| Model RS3030-44A80H0025 | Dimensions (WxHxD) 108x121x185 mm - 1,83Kg Features : REVO-S-3PH Nominal current 30A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in English language High Sensitivity HB below 5A Version |
| Model RS3040-44A80H0021 | Dimensions (WxHxD) 108x121x185 mm - 1,83Kg Features : REVO-S-3PH Nominal current 40A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in English |

| | |
|--|--|
| RS3040-44A80H0021 | language Standard Version with Fuse REVO-S-3PH Nominal current 40A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in English language Standard Version with Fuse |
| RS3040-44A80H0021 | REVO-S-3PH Nominal current 40A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in English language Standard Version with Fuse |
| M-RS1-60-210 | |
| RS3040-44V80H0021 | REVO-S-3PH Nominal current 40A Maximum main voltage 480V Auxiliary Voltage 12:24V ac-dc Analog Input 4:20mA Burst Firing 8 Cycles Control mode in open loop Fuse and Fuse Holder + Current Transformer + Heather Break No fan CE EMC For European Market Manual in English language Standard Version with Fuse |
| RS3040-44A80H0011 REVO S | |
| RC2800-45ABUC2010 | EVO-C-2PH Nominal current 800A Extrarapid Fixed Fuse Included Maximum load voltage 480V Auxiliary voltage supply range: 342 to 528Vac Input: 4-20 mA Firing: Burst firing - No Soft Start Control Mode: Voltage Option: Heater Break + Wi-Fi Fan 230V CE Approved Load Type: Normal Resistive Load with 3 Phase Delta Connection Communication: N°1 Modbus RTU - No Retransmission |
| DS1045-44SZ010020 | UNITA SCR CD3000S 1PH/45A/480V/12:24V/SSR/ZC/NF/HB/0/EM CD3000S-1PH Nominal current 45 A Maximum main voltage 480V 12:24V ac-dc Auxiliary Voltage Logic Input SSR Zero Crossing Firing Control Mode - Open Loop No Fuse - HB Option No Fan CE EMC For European Market Manual in English language IP Protection standard |
| RSX403-20SZ0F0021 | REVO-SX Four zones 3,5A Maximum main voltage 230V No auxiliary voltage Logic Input SSR - Zero Crossing firing Zero Crossing Firing Control mode in open loop Fuse + Fuse Holder No fan CE EMC For European Market Manual in English language Version 1 Standard |

| |
|--|
| 22557-59947-001 |
| Cd3000s 1ph/45a/-/480v/12:24v /Ssr/Zc/Nf/Hb/Em |
| Rs109040sz0f00x1 |
| Cd3s10045240024ssrhb |
| Cd3000m 3ph 44 Kw |
| Cd3m20400480460hb |
| Rs1090-44sz0h0011 |
| Rs1030-44sz0h0011 |
| Cd3200-15a-480v-170:265v-0/5v-Pa-V-Nf-UI |
| Rs106040sz0f00x1 |
| Cd3000a |
| Cd3000s-2ph-10a-480v-480v-No-Ssr-Zc-Nf-En Halbleiterrelaiscd3000s-2ph-10a-480v-480v-No-Ssr-Zc- Nf-En |
| Rs104040sz0000x1 |
| Rs 2150-04dz0f2130 |
| Cd3000m Modul 2ph/150a/440v/480v Aux400vca |
| Cd32000035480460cl |
| Cd3000s-2ph-15a-480v-Ssr |
| Cd3s20010480ssrlc |
| Cd3000m 3ph 65kw |
| Cd3000m 2ph/150a/380v/480v/170:265v/Ssr/Zc/If/Hb/Fan110v/Em |
| Cd3000s 2ph/125a/400v/480v/170:265v/Ssr/Zc/If Thyristor Block |
| Rkp2-04-M-000-00 Unita Revo Kp |
| Cd3m10300480230 |
| Cd3000m 3ph 25 Kw |
| C30300-42sz0h2021 |
| Rcl280-42apo 2021 Rcl280-42apoy2001 120x350x230cm |
| Cd3000m 2ph/75a/380v/480v/170:265v/Ssr/Zc/Nf/Hb/110vfan/Em |
| Rcl090-42apo 00 21 Rcl090-42apoy0021 93x269x170cm |

| | |
|---|---|
| Cd3s10045480024ssrnb | |
| Cd3000s-2ph 480v-75a-480v-Ssr | |
| Thyristor-Regler 480v 35a 5-30vdc Input, Thy07-01 | |
| Leistungsregler Triac Cd3000m-3ph/30a/.../480v/170;265/4-20ma/Zc/Nf | |
| Cd3000s-2ph 480v-75a | |
| Cd3s10060480ssr | |
| Cd3000m 2ph | |
| Cd3000m 3ph 56 Kw | |
| Leistungsregler Triac Cd3000m-3ph/45a/.../480v/170;265/4-20ma/Zc/Nf | |
| Rcl180-42apo 2021 Rcl180-42apoy2001 93x279x170cm | |
| Cd3000s-2ph-10a-480v-Ssr | |
| Rs1060-44sz0h0011 | |
| Rs103040sz0000x1 | |
| Cd31.Ct025/0,05w | |
| Cd3000m 1ph/15a/230v/480v/170:265v/4-20ma/Bf008/Nf | |
| Cd3000m-3ph-60a-480v-170-265v-0-10v-Bf004-Nf | CD3000M-3PH-60A-480V-170-265V-0-10V-BF004-NF Power Controller, 3 phase, 60A, Suitable for loads up to 480Vac, External 170 to 265Vac Auxiliary Supply Required, 0-10V Input, Burst Firing set at 4 cycles, No Fuse, Dimensions 138 (H) x 148 (W) x 123 (D) mm |
| Leistungsregler Triac Cd3000m-3ph/75a/.../480v/170;265/4-20ma/Zc/Nf | |
| Cd 3000s-3ph-30a-460v-Ssr | |
| Cd3m30300480460hb | |
| Thyristor-Regler 480v 15a 5-30vdc Input, Thy07-02, Art.-Nr. Cd3000s | |
| Ssr Revo Rm3040-42vbuh-0021 | |
| Rs1040-44sz0h0011 | |
| Rs2210-44a80f2031 | |
| Cd3000 45/60/ 75a | |