



Cedes

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Cedes Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Cedes Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

| rn | Aıklama |
|---|---|
| 445I-P4s1320yd | *** Successor to Safe4-1320-30 *** GuardShield Safe 4 safety light curtain Pair (transmitter and receiver) Hand protection (30 mm resolution), Protective field height 1320mm, Range: 18m Goods tariff no. Country of origin ECCN 8536501990 MX Weight about 5.78 |
| 445I-106427 | Safe 4 Connection Cap A, Cable Gland Gewicht ca. 58,967 kg 85366990 CH |
| 114 559 | Cegard/mini-MOD SY-2000-36 , NB , BCK , CC |
| Object 100F | |
| Part no: 104948 | |
| HW 100SW100 | |
| cegard/Mini SY-2000-36, NB, BCK, CC | 113 606 Range (m): 0.0-4.0 Elements/beams: 36/174 Length/protection (mm): 2000/1600 |
| Cedes | |
| safe c3 | |
| GridScan/Mini SY-2030-21 ,SB, N | 113 264 With door blanking Resolution: 50 mm at bottom 500 mm, 190 mm at upper part Output: Push-pull Test: Active low Edge length: 2030 mm Protection height: 1800 mm Elements: 21 |
| GridScan/Pro SY-2000-20 | 114 988 With door blanking Resolution: 50 mm at bottom 500 mm, 185 mm at upper part Output: Push-Pull and FSS Test: Active low Edge length: 2060 mm Protection height: 2000 mm Elements: 20 |
| 103 785 | ELS 263 receiver NPN/DO, 5m cable |
| BB 10 - T 33/76B/115-7M | |
| GridScan/Mini SY-2030-21, SB, N | 113 264 |
| | 114 988 With door blanking Resolution: 50 mm at bottom |

| | |
|---|--|
| GridScan/Pro SY-2000-20 | 500 mm, 185 mm at upper part Output: Push-Pull and FSS Test: Active low Edge length: 2060 mm Protection height: 2000 mm Elements: 20 |
| SAFEC 3 V2 | |
| APS – Absolute Positioning System | + 10meter Streifen |
| S4L-AEF2N-KH1-LH1F2-ACDA07553 | |
| Swiss mode/ GLS126 slot type sens¼r. | |
| GridScan/Pro SY-2500-22 | includes transmitter and receiver, as well as connection cable |
| 103 311 | ELS 263 transmitter, RW 6m, 5m cable |
| SY-2500-22 | |
| 104 569 | ELS 263 transmitter, RW 6m, connector M8 |
| 104 570 | ELS 263 receiver NPN/LO, connector M8 |
| 103 716 | Receiver cable 5m, connector M8 |
| 103 717 | transmitter cable 5m, connector M8 |
| GRIDSCAN/PRO, PNP/NPN (PUSH-PULL) UND FSS. 10...30VDC, 50 MA, | SY-2500-22 |
| Els264 | |
| 100688 | |
| Els263npn-D0 | |
| 445I-P4s3400yd | |
| S400s-Kef5n-Lf10-Acd67 | |
| S400s-Kef5n-Lf24-Ccd62 | |
| Cegardmax-74 | |
| Els263npn-L0 | |
| 100687 | |
| 300223 | |
| 101397 | |
| 103-005-0016r | LIGHT CURTAIN 24VDC .3AMP 500MA 270MM RESOLUTION |
| S400s-Krf5n-Lf10-Acd70 | |
| 100697 | |
| 100700 | |