

## Chevronepi

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Chevronepi** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Chevronepi T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">285</a>	"GASKET SEAL"
<a href="#">3320-M-Dt-150-1941</a>	SEAL FOR INTERNAL RECA2 88.9X6.45 HU
<a href="#">Ch-S-0 0528</a>	RUBBER SEAL INTERNAL DIAMETER 132.7 MM OUTSIDE DIAMETER 460 MM THICKNESS/LENGTH 6 MM
<a href="#">Ch-S-00526</a>	"OTHER SEAL SEAL TYPE RUBBER SEAL INTERNAL DIAMETER 145.4MM OUTSIDE DIAMETER 460MM THICKNESS/LENGTH 6MM PROFILE TYPE RING."
<a href="#">Ch-S-00531</a>	RUBBER SEAL INTERNAL DIAMETER 237.5 MM OUTSIDE DIAMETER 460 MM THICKNESS/LENGTH 6 MM
<a href="#">Ch-S-00532</a>	SEAL TYPE: RING; INTERNAL DIAMETER: 212.1 MM; OUTSIDE DIAMETER: 460 MM; THICKNESS/LENGTH: 6 MM
<a href="#">Ch-S-00533</a>	"OTHER SEAL SEAL TYPE RUBBER SEAL INTERNAL DIAMETER 186.7MM OUTSIDE DIAMETER 460MM THICKNESS/LENGTH 6MM PROFILE TYPE RING."
<a href="#">Chv -981101</a>	"GASKET SEAL"

<a href="#">Chv-Tam0077-P</a>	5-1/2 HIGH HARDNESS GASKET
<a href="#">Chv-Tam0079-P</a>	SPECIAL PACKING FOR HYDRAULIC TEST; TYPE: PACKING INTERNAL DIAMETER: 177.80 MM; OUTSIDE DIAMETER: 244.80 MM
<a href="#">Chv-Tam0080-P</a>	GASKET
<a href="#">Chv-Tam0081-P</a>	GASKET.
<a href="#">Chv-Tam0084-P</a>	GASKET.
<a href="#">Chv-Tam0086-P</a>	GASKET.
<a href="#">Chv-Tam0254-P</a>	"SEAL - SPECIAL FOR HYDRAULIC TEST; TYPE OF TEST; INTERNAL DIAMETER: 198.80 MM; OUTSIDE DIAMETER: 244.80 MM; DESIGN: CHEVRONEP PATTERN I; MATERIAL: POLYMER HARDNESS 70 SHORE D; MAXIMUM WORKING PRESSURE: 18000 PSI PACKING 7 5/6 HIGH HARDNESS"
<a href="#">Hms145x175x14</a>	SEAL FOR ROTARY SHAFT; SPECIAL TYPE; MATERIAL: MILL RIGHT N NITRILE SHAFT DIAMETER: 145 MM; HOUSING DIAMETER: 175 MM THICKNESS: 14 MM; SHORE HARDNESS: 75 A; FLUIDS: ISO HM32 OIL TEMPERATURE RANGE: -40 TO 120° C; MAXIMUM PRESSURE: 0.5 BAR;
<a href="#">Mhs95x120x13</a>	SEAL FOR ROTARY SHAFT; SPECIAL TYPE; MATERIAL: MILL RIGHT N NITRILE SHAFT DIAMETER: 95 MM; HOUSING DIAMETER: 120 MM; THICKNESS: 13 MM SHORE HARDNESS: 75 A; FLUIDS: OIL ISO HM32 RANGE TEMPERATURE: -30 TO 100° C; MAXIMUM PRESSURE: 0.03 MPA
<a href="#">O-Ring 524.5 Mm</a>	O-RING; INTERNAL DIAMETER: 524.5 MM; OUTSIDE DIAMETER: 544.5 MM; THICKNESS: 10MM; MATERIAL:NITRILE; SHORE HARDNESS: 90 A
<a href="#">O-Ring 813 Mm</a>	O-RING; INTERNAL DIAMETER: 813 MM; OUTSIDE DIAMETER: 829 MM; THICKNESS: 8MM; MATERIAL: NITRILE; SHORE HARDNESS: 90 A