



Chiaravalli

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Chiaravalli Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Chiaravalli T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	A¼ıklama
Rp3-2-A-Bc-11	Chiaravalli bevel gear Item number: R3141210 Reduction: 2 to. Nominal torque: 12.2 Nm at n1 = 1400 min-1 28.1 Nm at 50 min-1 Weight: 2.00 kg Lubrication: including oil filling (lifetime lubrication) Oil filling quantity: 0.08 liters, synthetic oil Installation position: B 5 Drive shaft: 14 h7 x 30 mm, one-sided Hollow output shaft: 14 H7 x 112 mm Customs tariff number: 84834023 further technical data and dimensions according to catalog
Chm 090 U 50 P90 B14 Cht 90 L4 / Ie3	motor and reducer
Rck 11 - 100 X 145	Chiaravalli clamping set Series: RCK 11 Code number: 06110100 Shaft bore: 100 H8 mm Outside diameter: 145 h8 mm Max. Torque: 26300 Nm Clamping pressure: shaft 200 N / mm ² Hub 107 N / mm ² Weight: 6.0 kg Clamping screws: 5 x M12 x 80 - 12.9 - DIN912 Tightening torque: 145 Nm Customs tariff number: 84834029
CH 04 P 20 P63 B14 B3	Chiaravalli worm gear Reduction: 20 Perm. Drive power: 0.37 kW (n1 = approx. 1400min-1) permissible nominal torque: 38 Nm Weight: 2.1 kg Splash lubrication: including oil filling Oil capacity: 0.06 liters (synthetic oil, 320 cSt) Version: P, with side housing processing Dimensions: pitch circle 65 mm, centering 50 h8 mm Installation position: B3 Output hollow shaft: 18 H7 x 64 mm Motor flange: IEC 63 B14 (dia. 90 mm) Motor shaft bore: 11 E7 x 23 mm Color: RAL 9022 in: aluminum housing
MOTOR TYPE : CHT 36A4 B14	RED¼KT¼R : CH03P
0000236000380	Coupling sleeve GF 38 Da=85;B=50 Curved tooth type - Mat. Polyamide
00103820	Coupling hub GF 38-N Curved tooth type - undrilled

CHB-03 P R.60 63F11	Worm gear / reduction: 60: 1
IEC CHT BV 03 63B14	Motor mounting flange (The motor mounting flange is unfortunately not clear)
IEC CHT BV 03 63B5	or as a B5 variant Motor mounting flange
CHB-04 P R.35 63F11	Worm gear / reduction: 35: 1
CHT BV 03/04-11	Connection set for worm gearboxes CHB 03/04
CHT BV 04 F	Transmission output flange
B14 CHT 71 B4 B14 0.37 kW	Three-phase motor Efficiency class: IE2 Voltage: 230/400 V Design: IM B14 Speed: 1400 rpm Power: 0.37 kW
CHBR-06 R.15	060020300601500 Worm gear / reduction: 15: 1
CH 03 P 15 P63 B14 B3	Chiaravalli worm gear Reduction : 15 Permitted drive power: 0.22 kW Permitted nominal torque: 16 Nm Weight : 1 kg Splash lubrication including oil filling Oil capacity: 0.035 liters (synthetic oil, 320 cSt) Execution : P Dimensions: dt 65mm, dz 50 h8 mm Installation position : B3 Output hollow shaft : 14 H7 x 55 mm Motor flange: IEC 63 B14 (diam. 90 mm) Motor Shaft Bore : 11 E7 x 23mm Color scheme : RAL 9022 Customs tariff number: 84834025 in : aluminum housing Additional equipment : without
FCA 63 B4 B14a UL	ART00751
ch-03 p r 15 63 b14	
0000680000400	
02001912	
02003812	
02201920	
02201940	
02203820	
02203840	
0396830000400	
0397320110220	
06400030	
0818751100130	
10219020	
14M 85 192	
20219060	
30015014	
94070001	
94071541	
A430562	
A470712	
B016A8014	

CHM-30 50 63B14 U	
CHS 3	
CHS3T10M2085 CHS3 TS C160 R10 TS M2+ CHT 90 S6 B14	
CHS3T10M2085+CHT 80 A4 B	
CHT56B4	
CHV10-CH	
M07299000B3	
RXK80-120X155	
CHT 132 S6	
No: 1707-154	Engine cover only front
CH-03 R. 7 63F11	060020100300760 Worm gear i=1:7 Old designation: CHB-03 R. 7 63F11
S750000003795	Block barrier, Form C-AB 30 27400030
0818726121010	connector 12B-1 Steel - make Rexnord according to DIN 8187 with a straight strap
0818701121010	Roller chain 12B-1 Steel - make Rexnord according to DIN 8187 with a straight strap Packing unit 5 meters
60 teeth / 24 teeth (2.5 ratio) Module 4.5	Attached module includes 6 of the 4.5 bevel gear pairs.
35502516	Bevel gear module 5 I 1:2.5 Z16 Bevel gear with straight teeth SPECIAL CH EXECUTION GLEASON SYSTEM Materials: C45 SPECIAL CH EXECUTION
36502540	Bevel gear module 5 I 1:2.5 Z40 Bevel gear with straight teeth SPECIAL CH EXECUTION GLEASON SYSTEM Materials: C45
CK_00120352	Sprocket 12B-3 Z 38 manufactured according to drawing no.: 11180002010 Material: C45 - (1.0503)
CHO-83	
CHM/CHM 040-075 750 OBS 63-B5 B3 CHT 63 B4	F600100001361 Transmission-motor combination Consisting of: 1 piece 060010107505084 - CHM-75 50 80B14 B3 1 piece 0600102407519 - CHT 40/75/90 - 19 1 piece 060010104001565 - CHM-40 15 63B5 U 1 piece 0600401804065 - CHT 63 B4 B 5 KW.0.18
CHM-63 7,5 90B14 U	060010106300794
CHM-63 7,5 90B5 U	060010106300795
CHT 90 L2 B5 kW 2,2 EFF.IE3	0600422002095IE3 Electric motor / efficiency class IE3 Size: 90 L2 / 2 poles RPM: 2800 / 7.38 Nm P=2.2kW / 230/400V / 4.51A / Cos Phi: 0.82 W grade: 85.9% / flange connection B5
GFAS 40 NN	Coupling GFAS 40 NN complete Da=95;L=115 Curved tooth type - consisting of: 1clutch hub - unb. 1 clutch hub - unused incl. steel sleeve and locking and sealing rings
GFA 80 LL	0000241000800 Kupplung, komplett Da=175; L=285 Curved tooth type - consisting of: 1 steel coupling sleeve + locking and sealing rings 2 coupling hubs long - undrilled
F600100001391	CH_07 50 90_B5 B8 CHT 90 S4 1.10 Kw 230/400V-50Hz 1 Mounting position: B8 1 piece 0600201008085 - CHT IEC BV 08 80 B5 1 piece 060020100705090 - CH-07 R. 50 90F24 EFF.IE3 1 piece 0600411004095IE3 - CHT 90 S4 B 4 kW 1.1

CH-04 P R.100 63F11	Worm gear i=1:100
CH 08 RAM 28 I 20 HUB Q35 MM REDİCTOR	
CH 08 RAM 28 I 20 HUB Q35 MM REDİCTOR	
060060108203010	CHO 82 R. 30
0600601073084	IEC CHO072/73/82/83 80 B14 motor mounting flange
0600601073075	IEC CHO072/73/82/83 71 B5 motor mounting flange
0600601073094	IEC CHO072/73/82/83 90 B14 motor mounting flange
0600601073095	IEC CHO072/73/82/83 90 B5 motor mounting flange
0600601072004	IEC CHO072/73/82/83 100/112B14 motor mounting flange
0600601072005	IEC CHO072/73/82/83 100/112 B5 motor mounting flange
060010104004064	CHM-40 40 63B14 U with B14 motor mounting flange
060010104004065	CHM-40 40 63B5 U with B 5 motor mounting flange
060010105000774	CHM-50 7,5 71B14 U
0000611000600	Clamping set RCK11/ 60x 90
CHM-63U	37253 Chm/63/45/0/30/Pi/0/0/A/S/Ex Com. 37253dis. Cd6345x30
060020200401460	CH-04P R.14 63F11 Worm gear i=1:14 Old designation: CHB-04 P R.14 63F11
0600201004064	IEC CHT BV 04 63B14 motor mounting flange
0600201004065	IEC CHT BV 04 63B5 motor mounting flange
REACTION BRACKET x W86	BC-RBS0086W
SHORT FLANGE FOR W86	BC-RPW0086C
REDUCER CHPC80, CHB08 i= 192 PAM80 B5	BC-RPW86198-01
CH08 RED¼KTÖR, i= 40.90B5,	BC-RPW86409-01
0000238000380	Coupling hub GF 38-L Da=60 Curved tooth type - long hub - undrilled
060020200410060	CH-04 P R.100 63F11 Worm gear i=1:100 Your item no.: Old designation: CHB-04 P R.100 63F11
CH-06 R.10 80F19	060020100601080 Worm gear i=1:10 Old designation: CHB-06 R.10 80F19
S60010002694	ANGULAR GEAR R3141107 RP 14-07 R.1/1
CH-04 P R.100 63F11	Worm gear i=1:100 Old designation: CHB-04 P R.100 63F11
16A-2 (ASA80-2)	70"
CHMR-50 50 U	060010305005000
060010103000764	CHM-30 7,5 63B14 U
060010105001084	CHM-50 10 80B14 U
060010103001064	CHM-30 10 63B14 U
0221163402000C	SPB 200-4 TL 3020 B=82; NL=45 V-belt pulley for TL bushing
0000873020281	Cone clamping bush 3020-28

GE-T 28-38 SG	
060010102501054	CHM-25 10 56B14 U
0600201004064	IEC CHT BV 04 63B14 Motor mounting flange
CHML-40 100 63B14 U	060010904010064
060020200410060	CH-04 P R.100 63F11 Aluminum worm gear Delivery without motor mounting flange Reduction: i=100 Motor hollow shaft 11H8 + keyway 4 mm Hollow shaft 18H7 + keyway 6 mm Oil filling: 0.06 liter ISO VG335
IEC CHT BV 04 63B5	Motor mounting flange
IEC CHT BV 04 63B14	Motor mounting flange
CHM-50 U	
060020200501470	CH-05 P R.14 71F14 Aluminum worm gear Reduction ratio: i=14 Supplied without motor mounting flange Hollow motor shaft 14E8 + groove 5 mm Hollow shaft 25H7 + groove 8 mm Hollow motor shaft 14E8 + groove 5 mm
0600201005074	IEC CHT BV 05 71B14 Motor mounting flange
0600201005075	IEC CHT BV 05 71B5 Motor mounting flange
0600403704074IE2	CHT 71 B4 B14 kW 0,37 E-motor / efficiency class IE2 Electric motor / size: 71B4 / 4 poles RPM: 1400 / 2.58 Nm / P= 0.37kW 230/400V / 1.12 A / Cos Phi: 0.74 / W-degree: 65.00% Flange connection B14
CHML-40 100 63B14 U	Aluminum worm gear Reduction: i=100 Slip clutch adjustable from 20-45 Nm Motor mounting flange 63 B14 (y 90 mm) Hollow motor shaft y 11E8 + groove 4 mm Hollow shaft 18H7 + groove 6 mm : 0.04 liters ISO VG329
IEC CHT MV 63 71B14	Engine mounting flange Outside = 105 mm Bolt circle = 85 mm Series: CHM 063
CHT-PC 63 D.11 300	Aluminum pre-stage gearbox Reduction i3 Motor flange 63B5 (140) Motor hollow shaft, 11E8 + groove 4 mm Gear flange 71B14 (105) Gear shaft 11H7 + groove 4 mm
CHT MV 63 FA	Gearbox mounting flange FA Outside 180 mm 4 holes 11 mm on bolt circle 150/165 mm Distance gearbox center - flange surface [R1] 82 mm
Slotted nut/14H GUK6 M30X1,5 ZN	self-locking groove nut
00981003000060000	Slotted nut/14H GUK6 M30X1.5 ZN, self-locking slotted nut
M6 - Z-24	Straight Piston Gear
CHS 8 1/30	
M09199085B3 GEARMOTOR + A650802	
K40390 AF PAM-90	i:67,78
0600403704074IE2	CHT 71 B4 B14 kW 0.37 IE2 Electric motor / efficiency class IE2 Electric motor / size: 71B4 / 4 poles RPM: 1400 / 2.58 Nm / P= 0.37kW 230/400V / 1.12 A / Cos Phi: 0.74 / W-degree: 65.00% Flange connection B14
060060106203090	CHO 62 R. 30 Spur-hypoid gear Reduction ratio: i=30 Supplied without motor mounting flange Hollow shaft 25H8 + groove 8mm Oil filling: 0.38 liters ISO VG222
0600601052074	IEC CHO52/53/62/63 71 B14 Input flange Outer diameter y = 105 mm Bolt circle y = 85 mm Hole y = 7 mm Inner circle y = 70 mm Material thickness = 4 mm

Ch-05p I:100 5004501201
0000680000400 Spannsatz Rck80/ 40x 53
Cht56b4 Motor 0,09 Kw, Imb14
Gf-As-32-L
Ch 04 P 100 P63 B14 B3
Vg-06b1
Ch 05p I:7 Pam:80 B5 F19
6216603 Red. Tecnomec3
Ch07-80:1-D30+80/90/B5-Ch07-08
Cht 63 A4 B14
Trapezoidal Thread Spindle Tpn 20x4 Length 540mm + Front End 40mm M20 Fine Thread
Chtpc 71
Ch 04 P 35 P63 B14 B3
Cht 132 M4 B5 Kw 7,5
C-Abu 30
Rck11 40x75
10030000731 S-128-02-004
12,7 Mm 1/2quot; B1 7,75 Mm D2 4,45 Mm D1 8,51 Mm A 17.0 G Max.Mm 11,81 F Cm 0,50 Kg/M 0,70 Caric.Rott
G0eb02500036
10020000139 At10-1800
Chm-30u I=30 Nr.10051011k
Chm-063-80b14/Cht-80-B4
Chmre 090 U 30 B3 (M09430000b3)
29251748
(100810) Ch 05 P 18 P80 B14 B3
M9116174
Ch-06 I=24 80f19
Spct 280x5
Rck11
Cht100la4
Chs2-Ts (Trapezgewinde Tr 20x4)
Chm25 U Pam 56 B14 I 60
P216-14m-40
Ch-03 P.R.7 63f11

Cht 100 Lb-4/Ie3 B14
Ch 05r I:7 Pam:80 B5 F19
Ch 03 P 60 P63 B14 B3
Cht 63 A4 B5
60-3mr-09
Rck 55 35x45x34
At10 Z32
Gfas25 Nn
Che-06r.6480f19
At10-660
Chm 090 I=20
06b-1
Rck 55 50x60x36
101284
Rck80
P144-14m-40
Ch 06r I:100 Pam 71 B5 F14
200 M06115087u
Ch-05p U Nr.5001501201 By Ch 05 P 18 P80 B5 B3
Tipo Rct-T (23120/012-05/15)
Chm 030
10209020
101285
Rck11 65x90
23120/003-11/14
00204002 (With Finishing)
Giunto Giflex Gfa-40-Nn
Rck 19 D30 X 60
Cht 132 S4 B5
Rck11 65x95
S24/32
Ch-05p I:60 5010501301
321-240-018
23120/004-12/14 Chb07, Pam=19, I=50, Nr: 30013008

Rcm-As30
23120/062-05/16
M3 1:1 Z20
Gfas-56
Ch 03 P U Serien-Nr.: 2010201001
Gfas-32-Nn
Rck40- 60x90
9003900706
28-5mr-25
Rxx80-120x155 Spannsatz
Rck 40 D.30/55
32-T10-1210
Rck 80
Rck 13 D.60/90
Mvf44f3563i
0396830000400 Stimrad Md 3 Z 40zb:30 / Gb:50 / Nd:80 / Vb:20
Chm 130 7,5 132 B5 B3 Montiert V6
Rck11 70x110
P264-14m-55 For Model Å5ks324xaa236w8
12b-1 3/4 Qrc 1905
2240 14m Gt 37
Chn 110
06400020
Type : Ch 05 P 7 P80 B14 B3 (100797)
Ch 06r I:7 Pam 80 B5 F 19
Chs2 Ts-C200-R30-Ts-M2-Pr
5001501101
Ch08
Asg03-1quot;1/2 Code Nr. 94103801n
Zahnriemen Htd
Rck11 50x80
(100819) Ch 05 P 36 P71 B14 B3
14m 85 192 Zahnriemenscheiben Htd Zentriert
00204002 (Pre-Drilled)
Type : Chs 2 - Rs ? 5 - De- 530 ? Tl
30-3mr-09

Rck11 60x90
Chc-3 I:80 51.3 2006201216
Ch 07 U 25 P90 B5
(100821) Ch 05 P 45 P71 B14 B3
S.Iso08b-1.
30015014 Chain Tensioner Sprocket Type Tn14 10v-1
Ch-07 I=15 90f24
Mv L78
94070001 Chain Tensioner Body Type E 1
Cht 90I2 B5
Chr 08
Cht 90 L6 B5 (Ae650905)
94071541 Tensioner For Single Row Chain Er4- 5/8 10v-1
Rck 40 35x60
Type : Ch 05 P 7 P80 B5 B3 (100798)
71 B5
Cho-82/105610
Ch-03 P R 20 56 F 9
0818751100130 Kettenradscheibe 10b-1 Z 13
M1 Z20 Z.
M1 Z37 Z
Chm-40 U
Rck61-25x47
10b-2 5/8 Qrc 1588/2
Ch 04 P 35 P63b 5 B3
Chs3
Rck11 35x60
0397320110220 Kegellrad Md 2 Z 22 1:1
Rck 80-18-26
Chmre 63-10
Trc-T1
Rck16 20x47
R3141110
(104123) Che 05 P 45 P71 B14 B3

M09140097b
Ch 05 Pf1 10 P71 B14 B3
Rck1360x90
40-14m- 85f
2011201405 Motor-Variator
29353580
Cht 63b4 B14 Iec 60034-30
Fu 3x400v, 7,5 Kw 18 A
23120/007-04/15 / 800-8mgt-30
94030112
5010 501101
Cht 63 A4 B3
C-Rs-10
3020 F.50
A470562s
Che-06 R.6480f19
R3141211
M9116169 For Model Å5ks324xaa235w8
Cht 71 B2 B14
Chm0,75-B5
19/24
Ch 04 Pf 35 P63 B5
Rck13-30x55
Fca 56 A-4 B14a
Zr 400 G
Type : Chm 50 U 7,5 P71 B14 B3
Chm0,75-B3+cht9014
Rck11 40x70
Chmre 130 U 50 B3
Kupplung Calettatori Rck 11 D. 50/80
Chm 40 U 20 P63 B14 B3
Chv 10 P80 B5
Cht 63 B6 B14 0.12kw
Rck55-30x40
M911aymg
Chs 3 Getriebe

[02509208](#)

[70057011](#)

[Rgs 6-25](#)

[Rck 55 40x50x35](#)

[Ch 05 P 18 P80 B5 B3](#)

[101283](#)

[Ch07 24 Pam 90 I](#)

[Cht-90-S2](#)

[N24/30bgg](#)

[1/2x5/16z](#)

[Ch 07 U 40 P90 B14 B3](#)