



Cla-Val

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Cla-Val Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Cla-Val Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
2050b-4kg1	CV050100A11506-1 Fire pressure relief valve Angle pattern DN150 (6") / ANSI 150 RF UL listed FM approved 213 kg 83x83x90
*Cv050100a11507-Sws/B	Fire pressure relief valve CLA-VAL 2050B-4KG1/SWS(angle) DTBTB , DN150 / ANSI 300RF Epoxy RAL 3000 (red) CRL : 7,0-21,0 bar [10,0bar] UL approved
SOL090-005/UL	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
22217-18G	Repair Kit for main valve CLA-VAL Model 100G Size DN 200 (8") NBR diaphragm NBR disc NBR O-ring Fiber Space Washer
SOL090-005/UL	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar(4,8bar) For use on UL listed valves 90-21 class ANSI300
50B-4KG1X Fire Protection Pressure Relief Valve	Size matters: Size: inlet(in) \ outlet(in) 1.1/2"
300347-V13-BS-D-10	Pressure holding control valve CLA-VAL 55L-60 3/4 "NPT / PN25 7.0 -21.0 bar (7.0 bar)
1" (3410AR-116.3)	
3/4" UL/FM	
6" 300PSİ UL/FM	
55L-60 3/4"NPT / PN 16	300347-V13-BS-C-10 Pressure relief control CLA-VAL 1,4-14,0bar [5,0bar] UL / FM approved
CLA-VAL 55L-60	Pressure releif valve 1/2" NPTF / PN16 UL listed FM approved Bronze / BUNA Pressure range 1.4 - 14.0 bar (factory preset 5.0bar)
NG1E-124-01 / KCHOS , DN 100/PN 10-	*CV124001N11002-KCHOS ON - OFF float control valve with float installed on valve CLA-VAL CF1-C1 + 1 x valve position

16	indicator + x gauge cock upstream CSA-12 , Rp1/21 and manometer Rp 1/2" (0-16bar)
CV090021G12007	PRessure reducing valve CLA-VAL 90G-21(globe) , DN200 / ANSI 300RF CRD : 30-165 PSI (2.1 - 11.6 bar) preset at 70 Psi. Epoxy coated RED RAL 3000 UL approved
DN200 MONITORING SWITCH BUTTERFLY VALVE	
V-5544B	EPDM Diaphragm GE 300 / PN 10-16
300889-150	EPDM Diaphragm GE 150 / NGE 200 PN 10-16
PRV-1A 6 PRESS REG FXF PN	
PRV-1A 8 PRESS REG FXF PN	
2991201B	
2991801J	
01240B	
6799317A	
2993501C	
01243F	
00529J	
21223101J	
6774604A	
6818505H	
601217	Repair Gasket Kit 341GF 202139-01F 2991201B NOSE SEAL ASSY 2991801J BUMPERS 01240B O RING 6799317A PIN, COTTER 2993501C GUARD 01243F O RING 00529J O RING 21223401JPIN 6774604A WSHR 6818505H RING 00590A O RING 01242H O RING 1 of each included
212234-01J	Link Pin for C-Clip
6774604A	Washer
352GF	
DN150	
58845-51-NM	Air Release & Vacuum Breaker Valve MModel 33A Screwed 2" NPT ASTM B148 NiA1Bz and cover Monel float & trim NBR rubber parts
20035609H 100-300	
20035609H	BS/BUNA pressure relief valve CLA-VAL 55-L, NPT 3/4" - PN 25 100-300PSI(7,0-21,0 BAR) FM Approved

02-10 Inpsection Certificate	
300347-V13-BS-D-10	Pressure Relief Valve Model 55L-60 3/4" NPTF -PN25 UL Listed FM approved Body&Cover: Bronze Trim: Stainless Steel Rubber: NBR Pressure Range: 7.0 - 21.0 bar [factory preset 7.0 bar] Pressure Range: 100-300 psi [factory preset 100psi]
CV090021G10656	Pressure Reducing Valve 90G-21 Globe Dn65 (2 1/2") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)
CV090021G11006	Pressure Reducing Valve 90G-21 Gloge DN100 (4") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)
*CV050100A12007/B	Model 2050B-4KG1(angle) Pressure Relief Valve DN200 (8') ANSI 300RF UIL listed FM approved
21005206G	Pressure relief Valve Model 55L-60 1" NPTF-PN25
Pressure Relief Valve Model 55L-60	3/4" NPTF -PN25 300347-V13-BS-D-10
204890-01A	Crank Shaft
29904-01J	Crank Shaft Bushing
Cap Cla-Val ISO45 PUR with fastening rope	603122
C-3422	
2700203K	3410AR116.3 1"NPT Outlet 1/2!! NPT 300psi
SOL090-005/UL	CRD/KX1 Rp 3/8" /PN25 2,1-11,6bar [5,0 bar] For use on UL listed valves 90-21 class ANSI 300
CV050100G12006	Model 50B-4KG1 DN200(8")/ ANSI 150RF UL listed FM approved Main valve ductile iron ASTM A536 fusion bounded epoxy coated (internal/external) red RAL3000 CRL-60: 1,4-14,0 bar
DN80 PN16 DELUGE VALVE	
DN100 PN16 DELUGE VALVE	
DN150 PN16 DELUGE VALVE	
21056731D	Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed
SOLO90-005/UL - CRD3/8 KX121-11.6 BAR-PRESET	(4,8) BAR - CRD 3/8)

21056731D	Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed
SOL090-005/UL	Pressure reducing control CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
3410AR-116.3	AIR RELIEF VALVE-FM
CL469DJL-Anti Water Hammer Valve (3/4")	DN100 PN16 diaphragm gasket
IALIFT34-200-01	Analogical lift sensor e-Lift-34 GE200/NGE 250, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
IALIFT34-100-01	Analogical lift sensor e-Lift-34 GE100/NGE 125-150, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
90A/G-21	CV090021G11009/ DN100 /ANSI 300 psi DN100/ 4"
90A/G-21 ANSI 300 psi/	DN150
300347-V12-BS-D-10	55L-60 Pressure relief valve 1/2" NPTF PN25 UM LİSTED FM APPROVED BODY & COVER: BRONZE TRİM: STAINLESS STEEL RUBBER: NBR PRESSURE RANGE: 7.0-21.0 BAR [factory preset 7.0 BAR]
22217-13H	Repair kit for main valve Model 100G/50B-4KG1 DN50 2" NBR Diaphragm NBR disc NBR O-ring Fiber space washer
22217-14F	Repair kit for main valve model 100G/50B-4KG1 DN65 2"1/2 NBR diaphragm NBR disc NBR o-ring Fiber Space washer
22217-16A	Repair kit for main valve model 100G/50B-4KG1 DN100 4" NBR Diaphragm NBR disc NBR o-ring Fiber space washer
CKCRD-STD-02	repair kit CRD 1,0-5,3/2,1-21,0bar
91698-01/KH	SS-303/EPDM repair kit GE3/8" KH
CKCV-STD-01	repair kit CV
CKX43-STD-01	repair kit X43Rp 3/8" Rp 1/2" MO4 0,2mm
Powertrol Valve, 3/8" Model 100-2, P/N 100-02-126J	
T28.31031-3"	134-83 3"-12"
T28.31041 4"	134-83
6quot;Druckreduzierventil	
2991201b	

3450-Ar116	
134/05 2??	
35-Ww 2	
55f 3/4?	
100gs	
20071003e Str Assy 344gf100m 300	
2100 G	
Set Of Inspection Certificate En 10204-3.1	- material certificate for valve body and cover - pressure test certificate - conformity certificate
50a-20	
300041-Wm-L10-N200-Dpc-R-T02	
55L-60 3/4"npt / Pn 25	Pressure relief valve CLA-VAL 55L-60 3/4"NPT / PN 25 7,0 - 21,0 bar [7,0 bar] UL / FM approved Part number: 300347-V13-BS-D-10 Country of origin: Switzerland Custom tariff no : 8481.8090
2quot; Druckreduzierventil	
55f 3/4?- Ss316- H185- Set Pressure 1,4 - 14 Bar- Pn 25	
4quot; Druckreduzierventil	
Cla-Val 340af	Pressure Fuel Servicing Adapter
Ã39;6 Quot;- Differenzdruck Einstellbereich 3-10 Bar	
380-Dn 25	
29028054	
22422a	
Ã39;3 Quot;- Differenzdruck Einstellbereich 3-10 Bar	
790-01	
90g-21 (Globe) 1 1/2" Scewed	Pressure reducing valve CLA-VAL ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 11.0 Kg
50b-4kg1	
50-G1e-48cgs Dn 50 / Ansi 150rf	
730-01	
	Pressure relief control CLA-VAL 55L-60 3/4"NPT / PN 16 1,4 -

300347-V13-Bs-C-10	14,0 bar [5,0 bar] UL / FM approved Net weight per piece : 2 kg/pce Country of origin: Switzerland Custom tariff no : 8481.8090
134/83 3??	
134-G1e-05msy	"ON - OFF" solenoid DELUGE control valve CLA-VAL Model 134-G1E-05MSY DN 250 / Class ANSI 150RF
1quot; Series 33a	
341gf-Vd3ssbvm100g30	
58754-32	
8quot; Circulation Relief Valves	
8quot; Main Relief Valves	
8quot; Druckreduzierventil	
58754-23	
3quot; Druckreduzierer	
2050b 4kg 4?	
40-28ags W/Rofc Al/Ss/Ss 6	
690-01	
3m Ir 1100	
20213901f Kit, Rppt 341gf 2ha	
6 "pressure Reducer Valve, Locked, 300 Psi	
698-06	
100af	
90g-21 (Globe) Dn 100	Pressure reducing valve ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 56.0 Kg
20389702e Kit, Rppt D-3 2has	
2" Hava Tahliye Vanasi, 500psi, Ductil D¼k¼m.Model 33a,	