



## Cla-Val

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Cla-Val** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Cla-Val Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">2050b-4kg1</a>	CV050100A11506-1 Fire pressure relief valve Angle pattern DN150 (6") / ANSI 150 RF UL listed FM approved 213 kg 83x83x90
<a href="#">*Cv050100a11507-Sws/B</a>	Fire pressure relief valve CLA-VAL 2050B-4KG1/SWS(angle) DTBTB , DN150 / ANSI 300RF Epoxy RAL 3000 (red) CRL : 7,0-21,0 bar [10,0bar] UL approved
<a href="#">SOL090-005/UL</a>	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
<a href="#">22217-18G</a>	Repair Kit for main valve CLA-VAL Model 100G Size DN 200 (8") NBR diaphragm NBR disc NBR O-ring Fiber Space Washer
<a href="#">SOL090-005/UL</a>	Pressure reducing control CLA-VAL CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar(4,8bar) For use on UL listed valves 90-21 class ANSI300
<a href="#">50B-4KG1X Fire Protection Pressure Relief Valve</a>	Size matters: Size: inlet(in) \ outlet(in) 1.1/2"
<a href="#">300347-V13-BS-D-10</a>	Pressure holding control valve CLA-VAL 55L-60 3/4 "NPT / PN25 7.0 -21.0 bar (7.0 bar)
<a href="#">1" (3410AR-116.3)</a>	
<a href="#">3/4" UL/FM</a>	
<a href="#">6" 300PSİ UL/FM</a>	
<a href="#">55L-60 3/4"NPT / PN 16</a>	300347-V13-BS-C-10 Pressure relief control CLA-VAL 1,4-14,0bar [5,0bar] UL / FM approved
<a href="#">CLA-VAL 55L-60</a>	Pressure releif valve 1/2" NPTF / PN16 UL listed FM approved Bronze / BUNA Pressure range 1.4 - 14.0 bar (factory preset 5.0bar)
<a href="#">NG1E-124-01 / KCHOS , DN 100/PN 10-</a>	*CV124001N11002-KCHOS ON - OFF float control valve with float installed on valve CLA-VAL CF1-C1 + 1 x valve position

<a href="#">16</a>	indicator + x gauge cock upstream CSA-12 , Rp1/21 and manometer Rp 1/2" (0-16bar)
<a href="#">CV090021G12007</a>	PRessure reducing valve CLA-VAL 90G-21(globe) , DN200 / ANSI 300RF CRD : 30-165 PSI (2.1 - 11.6 bar) preset at 70 Psi. Epoxy coated RED RAL 3000 UL approved
<a href="#">DN200 MONITORING SWITCH BUTTERFLY VALVE</a>	
<a href="#">V-5544B</a>	EPDM Diaphragm GE 300 / PN 10-16
<a href="#">300889-150</a>	EPDM Diaphragm GE 150 / NGE 200 PN 10-16
<a href="#">PRV-1A 6 PRESS REG FXF PN</a>	
<a href="#">PRV-1A 8 PRESS REG FXF PN</a>	
<a href="#">2991201B</a>	
<a href="#">2991801J</a>	
<a href="#">01240B</a>	
<a href="#">6799317A</a>	
<a href="#">2993501C</a>	
<a href="#">01243F</a>	
<a href="#">00529J</a>	
<a href="#">21223101J</a>	
<a href="#">6774604A</a>	
<a href="#">6818505H</a>	
<a href="#">601217</a>	Repair Gasket Kit 341GF 202139-01F 2991201B NOSE SEAL ASSY 2991801J BUMPERS 01240B O RING 6799317A PIN, COTTER 2993501C GUARD 01243F O RING 00529J O RING 21223401JPIN 6774604A WSHR 6818505H RING 00590A O RING 01242H O RING 1 of each included
<a href="#">212234-01J</a>	Link Pin for C-Clip
<a href="#">6774604A</a>	Washer
<a href="#">352GF</a>	
<a href="#">DN150</a>	
<a href="#">58845-51-NM</a>	Air Release & Vacuum Breaker Valve MModel 33A Screwed 2" NPT ASTM B148 NiA1Bz and cover Monel float & trim NBR rubber parts
<a href="#">20035609H 100-300</a>	
<a href="#">20035609H</a>	BS/BUNA pressure relief valve CLA-VAL 55-L, NPT 3/4" - PN 25 100-300PSI(7,0-21,0 BAR) FM Approved

<a href="#">02-10 Inpsection Certificate</a>	
<a href="#">300347-V13-BS-D-10</a>	Pressure Relief Valve Model 55L-60 3/4" NPTF -PN25 UL Listed FM approved Body&Cover: Bronze Trim: Stainless Steel Rubber: NBR Pressure Range: 7.0 - 21.0 bar [factory preset 7.0 bar] Pressure Range: 100-300 psi [factory preset 100psi]
<a href="#">CV090021G10656</a>	Pressure Reducing Valve 90G-21 Globe Dn65 (2 1/2") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)
<a href="#">CV090021G11006</a>	Pressure Reducing Valve 90G-21 Gloge DN100 (4") ANSI 150RF UL listed Ductile iron ASTM A536 main valve Fusion bounded epoxy coated RAL 3000(red) CRD: 30-165psi (2.1-11.6 bar) factory pressure preset 70psi (4.8bar)
<a href="#">*CV050100A12007/B</a>	Model 2050B-4KG1(angle) Pressure Relief Valve DN200 (8') ANSI 300RF UIL listed FM approved
<a href="#">21005206G</a>	Pressure relief Valve Model 55L-60 1" NPTF-PN25
<a href="#">Pressure Relief Valve Model 55L-60</a>	3/4" NPTF -PN25 300347-V13-BS-D-10
<a href="#">204890-01A</a>	Crank Shaft
<a href="#">29904-01J</a>	Crank Shaft Bushing
<a href="#">Cap Cla-Val ISO45 PUR with fastening rope</a>	603122
<a href="#">C-3422</a>	
<a href="#">2700203K</a>	3410AR116.3 1"NPT Outlet 1/2!! NPT 300psi
<a href="#">SOL090-005/UL</a>	CRD/KX1 Rp 3/8" /PN25 2,1-11,6bar [5,0 bar] For use on UL listed valves 90-21 class ANSI 300
<a href="#">CV050100G12006</a>	Model 50B-4KG1 DN200(8")/ ANSI 150RF UL listed FM approved Main valve ductile iron ASTM A536 fusion bounded epoxy coated (internal/external) red RAL3000 CRL-60: 1,4-14,0 bar
<a href="#">DN80 PN16 DELUGE VALVE</a>	
<a href="#">DN100 PN16 DELUGE VALVE</a>	
<a href="#">DN150 PN16 DELUGE VALVE</a>	
<a href="#">21056731D</a>	Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed
<a href="#">SOLO90-005/UL - CRD3/8 KX121-11.6 BAR-PRESET</a>	(4,8) BAR - CRD 3/8)

<a href="#">21056731D</a>	Air Release Valve - Simple Lever Type CLA-VAL Model 3410AR-116.3 Inlet size: 1" NPTF Outlet size: 1/2" NPTF (1" Size Supplies Std. with 1/2" & 3/4" Bushing Included) Orifice size: 1/16" Pressure rating: 300 psi Ductile Iron ASTM A536 body fusion bounded epoxy coated red RAL 3000 (ext) Stainless steel trim & float FM approved UL listed
<a href="#">SOL090-005/UL</a>	Pressure reducing control CRD/KX1 Rp 3/8" PN25 2,1 - 11,6 bar (5,0bar) For use on UL listed valves 90-21class ANSI300
<a href="#">3410AR-116.3</a>	AIR RELIEF VALVE-FM
<a href="#">CL469DJL-Anti Water Hammer Valve (3/4")</a>	DN100 PN16 diaphragm gasket
<a href="#">IALIFT34-200-01</a>	Analogical lift sensor e-Lift-34 GE200/NGE 250, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
<a href="#">IALIFT34-100-01</a>	Analogical lift sensor e-Lift-34 GE100/NGE 125-150, 12-24 V/DC IP68 Junction box Z101/SS +2x option for X105 Sensor 10m on e-Lift 34
<a href="#">90A/G-21</a>	CV090021G11009/ DN100 /ANSI 300 psi DN100/ 4"
<a href="#">90A/G-21 ANSI 300 psi/</a>	DN150
<a href="#">300347-V12-BS-D-10</a>	55L-60 Pressure relief valve 1/2" NPTF PN25 UM LİSTED FM APPROVED BODY & COVER: BRONZE TRİM: STAINLESS STEEL RUBBER: NBR PRESSURE RANGE: 7.0-21.0 BAR [ factory preset 7.0 BAR]
<a href="#">22217-13H</a>	Repair kit for main valve Model 100G/50B-4KG1 DN50 2" NBR Diaphragm NBR disc NBR O-ring Fiber space washer
<a href="#">22217-14F</a>	Repair kit for main valve model 100G/50B-4KG1 DN65 2"1/2 NBR diaphragm NBR disc NBR o-ring Fiber Space washer
<a href="#">22217-16A</a>	Repair kit for main valve model 100G/50B-4KG1 DN100 4" NBR Diaphragm NBR disc NBR o-ring Fiber space washer
<a href="#">CKCRD-STD-02</a>	repair kit CRD 1,0-5,3/2,1-21,0bar
<a href="#">91698-01/KH</a>	SS-303/EPDM repair kit GE3/8" KH
<a href="#">CKCV-STD-01</a>	repair kit CV
<a href="#">CKX43-STD-01</a>	repair kit X43Rp 3/8" Rp 1/2" MO4 0,2mm
<a href="#">Powertrol Valve, 3/8" Model 100-2, P/N 100-02-126J</a>	
<a href="#">6quot;Druckreduzierventil</a>	
<a href="#">2991201b</a>	
<a href="#">3450-Ar116</a>	
<a href="#">134/05 ???</a>	

<a href="#">35-W w 2</a>	
<a href="#">55f 3/4?</a>	
<a href="#">100gs</a>	
<a href="#">20071003e Str Assy 344gf100m 300</a>	
<a href="#">2100 G</a>	
<a href="#">Set Of Inspection Certificate En 10204-3.1</a>	- material certificate for valve body and cover - pressure test certificate - conformity certificate
<a href="#">50a-20</a>	
<a href="#">300041-W m-L10-N200-Dpc-R-T02</a>	
<a href="#">55L-60 3/4"npt / Pn 25</a>	Pressure relief valve CLA-VAL 55L-60 3/4"NPT / PN 25 7,0 - 21,0 bar [7,0 bar] UL / FM approved Part number: 300347-V13-BS-D-10 Country of origin: Switzerland Custom tariff no : 8481.8090
<a href="#">2quot; Druckreduzierventil</a>	
<a href="#">55f 3/4?- Ss316- H185- Set Pressure 1,4 - 14 Bar- Pn 25</a>	
<a href="#">4quot; Druckreduzierventil</a>	
<a href="#">Cla-Val 340af</a>	Pressure Fuel Servicing Adapter
<a href="#">Ä39;6 Quot;- Differenzdruck Einstellbereich 3-10 Bar</a>	
<a href="#">380-Dn 25</a>	
<a href="#">29028054</a>	
<a href="#">22422a</a>	
<a href="#">Ä39;3 Quot;- Differenzdruck Einstellbereich 3-10 Bar</a>	
<a href="#">790-01</a>	
<a href="#">90g-21 (Globe) 1 1/2" Scewed</a>	Pressure reducing valve CLA-VAL ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 11.0 Kg
<a href="#">50b-4kg1</a>	
<a href="#">50-G1e-48cgs Dn 50 / Ansi 150rf</a>	
<a href="#">730-01</a>	
<a href="#">300347-V13-Bs-C-10</a>	Pressure relief control CLA-VAL 55L-60 3/4"NPT / PN 16 1,4 - 14,0 bar [5,0 bar] UL / FM approved Net weight per piece : 2 kg/pce Country of origin: Switzerland Custom tariff no : 8481.8090

<a href="#">134/83 3??</a>	
<a href="#">134-G1e-05msy</a>	"ON - OFF" solenoid DELUGE control valve CLA-VAL Model 134-G1E-05MSY DN 250 / Class ANSI 150RF
<a href="#">1quot; Series 33a</a>	
<a href="#">341gf-Vd3ssbvm100g30</a>	
<a href="#">58754-32</a>	
<a href="#">8quot; Circulation Relief Valves</a>	
<a href="#">8quot; Main Relief Valves</a>	
<a href="#">8quot; Druckreduzierventil</a>	
<a href="#">58754-23</a>	
<a href="#">3quot; Druckreduzierer</a>	
<a href="#">2050b 4kg 4?</a>	
<a href="#">40-28ags W/Rofc Al/Ss/Ss 6</a>	
<a href="#">690-01</a>	
<a href="#">3m Ir 1100</a>	
<a href="#">20213901f Kit, Rppt 341gf 2ha</a>	
<a href="#">6 "pressure Reducer Valve, Locked, 300 Psi</a>	
<a href="#">698-06</a>	
<a href="#">100af</a>	
<a href="#">90g-21 (Globe) Dn 100</a>	Pressure reducing valve ANSI 150RF CRD: 30 - 165 PSI (2.1 - 11.6 bar) preset at 70 PSI Epoxy coated RED RAL 3000 UL approved Unit net weight : estimated 56.0 Kg
<a href="#">20389702e Kit, Rppt D-3 2has</a>	
<a href="#">2" Hava Tahliye Vanasi, 500psi, Ductil Dök¼m.Model 33a,</a>	