



Columbus Mckinnon

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Columbus Mckinnon Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Columbus Mckinnon Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
HSE 50.1 N-1-2B-H / S-1-Tr	Pfaff-silberblau screw jack Customs tariff number: 84834025 With the following configuration Size: HSE 50.1 N Type: 1 lifting spindle: Tr 40 x 8 RH Gear ratio: 6: 1 Stroke per revolution: 1.33 mm Installation position: M2B Execution: H / S Drive side right: Yes Drive side left: Yes Head design: I Stroke: 370 mm Spindle extension VL (manual): 5 mm Installation dimension v. Screw on the housing: to the end of head I. Installation dimension: 73 mm Lubrication: Gearbox with synthetic oil filling Surface treatment: primed Operating instructions: SHE_HSE_MKR_Ba1_Ba2_de Process code: 0
PN: N00401313	RATCHET DISC ASSEMBLY
PN: N00404732	FRICTION DISC
PN: N04307655	HAND CHAIN (STAINLESS STEEL
PN: N00400668	CONNECTING LINK
	CMEP-HBE Pfaff-silberblau screw jack Customs tariff number: 84834025 With the following configuration Size: SHE 3.1 N Type: 1 lifting spindle: Tr 30 x 6 RH Offer ZNR_DE: A13_01_105_000_2400BL01 Translation: 6:1 Stroke per

SHE 3.1 N-1-1A-A - F / S-2-Tr	revolution: 1.00 mm Installation position: M1A Version: A - F / S Drive Side Right: Yes Drive side left: Yes Head design: II Stroke: 105mm Spindle extension VL (manual): 158 mm installation dimension Housing screwing: up to the end of head II Installation dimension: 309 mm Lubrication: grease Surface treatment: primed Process code: 0
CMEP-MKR	M2-1-1A-5-320-31-N-T20x4 Pfaff-silberblau spindle lifting element With the following configuration Size: M2 N Type: 1 lifting spindle: Tr 20 x 4 RH Offer ZNR_DE: A18_01_002_0000_0100 Translation: 4:1 Stroke per revolution: 1.00 mm Installation position: M1A Version: F / SF Drive side right: Yes Drive side left: Yes Head design: GK (fork head) stroke: 320 mm Spindle extension VL (manual): 31 mm Installation dimension from housing screw: to center hole head GK Installation dimension: 187 mm Lubrication: Grease Process code: 0
Wb	CHAIN HOIST 1/4TON LOAD 16SPD 6.3AMP 110/120/60V
M2-1-1a-5-160-0-L-T20x4	
4233	HOIST
M2248	
R	HOIST
1754626cf8ft	CHAIN HOIST