

Comer Srl

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Comer Srl Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Comer Srl T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



| ¼r¼n | A¼ıklama |
|-----------------------------------|---|
| DRIVE AX - 100K.2 | ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) * POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 4,0 kW (Duty S1) * RATED TORQUE : 25,3 Nm * RATED FREQUENCY : 51,7 Hz * RATED CURRENT : 9,3 A * RATED SPEED : 1510 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 PTC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * INSULATION CLASS : F * ENCODER ELTRA EH80C1024Z5/28L14X3MR.197+295 1024ppr 10pins * PAINTING : BLACK RAL 9005 * NOTES : motor will be provided with free connector for encoder, without 3 mt. of cable |
| Drive AX 100K.5 | |
| Drive AX 100K.3 | |

[Drive AX 100K.2](#)

[Drive AX 100K.1](#)

[DRIVE AX - 100K.2](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) * POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 5,6 kW (Duty S1) * RATED TORQUE : 25,1 Nm * RATED FREQUENCY : 72,6 Hz * RATED CURRENT : 12,4 A * RATED SPEED : 2130 r.p.m. * CONSTANT POWER SPEED : 3650 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 x KLIXON NC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * INSULATION CLASS : F * ENCODER SICK DFS60- (PLEASE SPECIFY PPR) - TTL or HTL (PLEASE SPECIFY) * PAINTING : BLACK RAL 9005

[DRIVE AX - 100K.2 , encoder SFM60-HMKT 0K02](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 5,6 kW (Duty S1) * RATED TORQUE : 25,1 Nm * RATED FREQUENCY : 72,6 Hz * RATED CURRENT : 12,4 A * RATED SPEED : 2130 r.p.m. * CONSTANT POWER SPEED : 3650 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 x KLIXON NC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * MAXIMUM ABSOLUTE SPEED : 6000 r.p.m. * INSULATION CLASS : F * Encoder SFM60-HMKT 0K02 absolute multi-turn HIPERFACE (Sick) 1024ppr * PAINTING : BLACK RAL 9005

[15KW RPM3030](#)

[DRIVE AX 100K.2](#)

[Rtlpvr 160 S Dc Motor](#)

[Pwt132 K.5](#)

[100k.3 Drive-Ax Motor](#)

[Skr 80-2b 380v](#)

[615/12](#)

[Tetravec -160l.3](#)

[Ntb 47ca](#)

[Rtlpvr 160 S](#)

[17 8-Mka Fd C8](#)

[Skg 63-2a](#)

| |
|---|
| Tetravec - 160l.5 |
| Type: Ax/Ac 132 K4 |
| 814/12 |
| Pg 502 Mc 23,1 Elc42 |
| Mp77s ? K40 |
| Tvc-Pvr 132 K5 |
| 17 8-Mka Cb C8 Motorbetriebskondensator |
| Ntb 900 Cc |
| Drive Ax 100k. 5 Motor |
| Ersatzkette Fur Comer Să196;Ge E21 F Nr. E21-Ksk-Ef404-68 |
| 603/12 |
| Mp77s - K40 |
| Tetravec 132k.4 |
| 100k.3 |
| Skg 63-2a. |
| Tetravec 132.L2 26 Kw, 1500 U/Min, 380 Volt |
| 458.20n V24 F40 Nm400 |
| Comer-Srl-F3;R-Bremse-45820n-V24- F40-Nm400-Istanbul-Turkiye |
| Pwt160lip54 |
| Skg 63-2a. Electric Motor |
| 17 8-Mka Cb C8 |
| Ntb 47 |
| 17 8-Mka Fd C8 Motorbetriebskondensator |
| Drive Ax - 100k.3 |
| 11510016 |
| Comer Motor TS-PVA100L5 V3 |
| Drive Ax 100k.5 |
| |

[614/12](#)

[Ersatzkette Fur Comer S¼ge E21 F Nr.
E21-Ksk-Ef404-68](#)

[Ntb 900 Cc Bimetallic Thermostat](#)

[Drive Ax 160L.3](#)