

## Comer Srl

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Comer Srl** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Comer Srl T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunulmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">DRIVE AX - 100K.2</a>	ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) * POLES : 4 * RATED VOLTAGE : 380 V * OUTPUT POWER : 4,0 kW (Duty S1) * RATED TORQUE : 25,3 Nm * RATED FREQUENCY : 51,7 Hz * RATED CURRENT : 9,3 A * RATED SPEED : 1510 r.p.m. * PROTECTION DEGREE : IP54 * MOUNTING : B3/B5 (PIEDI E FLANGIA) * FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm * SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm * BALANCING : FULL KEY (FITTED) * VIBRATION GRADE : A * BEARINGS : STANDARD (BALLS) * TERMINAL BOX : STANDARD TERMINAL BOX ON TOP * TEMPERATURE SENSORS : 2 PTC * COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz * INSULATION CLASS : F * ENCODER ELTRA EH80C1024Z5/28L14X3MR.197+295 1024ppr 10pins * PAINTING : BLACK RAL 9005 * NOTES : motor will be provided with free connector for encoder, without 3 mt. of cable
<a href="#">Drive AX 100K.5</a>	
<a href="#">Drive AX 100K.3</a>	

[Drive AX 100K.2](#)

[Drive AX 100K.1](#)

[DRIVE AX - 100K.2](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) \* POLES : 4 \* RATED VOLTAGE : 380 V \* OUTPUT POWER : 5,6 kW (Duty S1) \* RATED TORQUE : 25,1 Nm \* RATED FREQUENCY : 72,6 Hz \* RATED CURRENT : 12,4 A \* RATED SPEED : 2130 r.p.m. \* CONSTANT POWER SPEED : 3650 r.p.m. \* PROTECTION DEGREE : IP54 \* MOUNTING : B3/B5 (PIEDI E FLANGIA) \* FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm \* SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm \* BALANCING : FULL KEY (FITTED) \* VIBRATION GRADE : A \* BEARINGS : STANDARD (BALLS) \* TERMINAL BOX : STANDARD TERMINAL BOX ON TOP \* TEMPERATURE SENSORS : 2 x KLIXON NC \* COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz \* INSULATION CLASS : F \* ENCODER SICK DFS60- (PLEASE SPECIFY PPR) - TTL or HTL (PLEASE SPECIFY) \* PAINTING : BLACK RAL 9005

[DRIVE AX - 100K.2 , encoder SFM60-HMKT 0K02](#)

ASYNCHRONOUS MOTOR (FREQ. CONVERTER DUTY) POLES : 4 \* RATED VOLTAGE : 380 V \* OUTPUT POWER : 5,6 kW (Duty S1) \* RATED TORQUE : 25,1 Nm \* RATED FREQUENCY : 72,6 Hz \* RATED CURRENT : 12,4 A \* RATED SPEED : 2130 r.p.m. \* CONSTANT POWER SPEED : 3650 r.p.m. \* PROTECTION DEGREE : IP54 \* MOUNTING : B3/B5 (PIEDI E FLANGIA) \* FLANGE : DIAM. 250 mm, CENTERING 180 mm, BOLT CIRCLE 215 mm \* SHAFT DIMENSIONS (Ø x L) : 38 x 80 mm \* BALANCING : FULL KEY (FITTED) \* VIBRATION GRADE : A \* BEARINGS : STANDARD (BALLS) \* TERMINAL BOX : STANDARD TERMINAL BOX ON TOP \* TEMPERATURE SENSORS : 2 x KLIXON NC \* COOLING METHOD : IC416A AXIAL BLOWING FAN 3x400Vac 50Hz \* MAXIMUM ABSOLUTE SPEED : 6000 r.p.m. \* INSULATION CLASS : F \* Encoder SFM60-HMKT 0K02 absolute multi-turn HIPERFACE (Sick) 1024ppr \* PAINTING : BLACK RAL 9005

[15KW RPM3030](#)

[DRIVE AX 100K.2](#)

[Rtlpvr 160 S Dc Motor](#)

[Pwt132 K.5](#)

[100k.3 Drive-Ax Motor](#)

[Skr 80-2b 380v](#)

[615/12](#)

[Tetravec -160l.3](#)

[Ntb 47ca](#)

[Rtlpvr 160 S](#)

[17 8-Mka Fd C8](#)

[Skg 63-2a](#)

<a href="#">Tetravec - 160l.5</a>
<a href="#">Type: Ax/Ac 132 K4</a>
<a href="#">814/12</a>
<a href="#">Pg 502 Mc 23,1 Elc42</a>
<a href="#">Mp77s ? K40</a>
<a href="#">Tvc-Pvr 132 K5</a>
<a href="#">17 8-Mka Cb C8</a> <a href="#">Motorbetriebskondensator</a>
<a href="#">Ntb 900 Cc</a>
<a href="#">Drive Ax 100k. 5 Motor</a>
<a href="#">Ersatzkette Fur Comer Să196;Ge E21 F</a> <a href="#">Nr. E21-Ksk-Ef404-68</a>
<a href="#">603/12</a>
<a href="#">Mp77s - K40</a>
<a href="#">Tetravec 132k.4</a>
<a href="#">100k.3</a>
<a href="#">Skg 63-2a.</a>
<a href="#">Tetravec 132.L2 26 Kw, 1500 U/Min, 380</a> <a href="#">Volt</a>
<a href="#">458.20n V24 F40 Nm400</a>
<a href="#">Comer-Srl-F3;R-Bremse-45820n-V24-</a> <a href="#">F40-Nm400-Istanbul-Turkiye</a>
<a href="#">Pwt160lip54</a>
<a href="#">Skg 63-2a. Electric Motor</a>
<a href="#">17 8-Mka Cb C8</a>
<a href="#">Ntb 47</a>
<a href="#">17 8-Mka Fd C8</a> <a href="#">Motorbetriebskondensator</a>
<a href="#">Drive Ax - 100k.3</a>
<a href="#">11510016</a>
<a href="#">Comer Motor</a> TS-PVA100L5 V3
<a href="#">Drive Ax 100k.5</a>

[614/12](#)

[Ersatzkette Fur Comer Säge E21 F Nr.  
E21-Ksk-Ef404-68](#)

[Ntb 900 Cc Bimetallic Thermostat](#)

[Drive Ax 160L.3](#)