

A-342



Crosby

Garanti: 12 ay

Bu ¼r¼ne ait T¼rkiye ii kapı teslim fiyat ve teslim s¼resi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

Crosby Markası, tedarik s¼resi iin l¼tfen bizimle iletiŐime geiniz.

Firmamız Crosby T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.

¼r¼n	Aıklama
Typ G-417	7013035 Bow rope sleeve type G-417 Diameter 32-35 mm
G-417	7013048 Bow rope sleeve type G-417 Diameter 44-48 mm
7013035	Bow rope sleeve type G-417 Diameter 32-35 mm
7013048	Bow rope sleeve type G-417 Diameter 44-48 mm
Liste 18 Pos.	Bitte um Kontrolle und Angebot
Crane pennant, 2 meters long 6x19 IWRC Galv	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv	. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye(SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders) 8 ton SWL x 5m long.	22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders) 5 ton SWL x 5m long.	6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 16mm x 19mm, SWL 3.25 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 19mm x 22mm, SWL 4.75 ton
Green pin standard shckles	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 22mm x 25mm, SWL 6.5 ton
	bow shackles with safety bolt, to EN13889, hot dipped

Green pin standard shckles,	galvanized, 25mm x 28mm, SWL 8.5 ton
Green pin standard shckles,	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 32mm x 35mm, SWL 12 ton
1000 kg SWL Chain blocks with certificate	
Crane pennant, 2 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 2 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
Crane pennant, 5 meters long 6x19 IWRC Galv.	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
Crane pennant, 5 meters long	6x19 IWRC Galv. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
2 legs (Spreaders)	8 ton SWL x 5m long. 22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
2 legs (Spreaders)	5 ton SWL x 5m long. 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
1090125	Crosby safety hook set SS-4055 - 11.5to for old hooks 319, 320 and 322
1093541	Crosby safety hook set SS-4055 - 22to 22 to. - for old hooks 319, 320 and 322
G-450 16 mm	7504530-2 Crosby wire rope clips G-450 Nominal width 16 mm 5/8 "- HOT GALVANIZED"
G-450 9-10 mm	Crosby wire rope clips G-450 Nominal width 9-10 mm 3/8 "- HOT GALVANIZED"
G-429 14 - 16 mm	Crosby wire rope clips G-429 Nominal width 14 - 16 mm 9/16 - 5/8 "
3313042	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 3/4 in., WLL: 25 t EN 13889 Nominal size 1 3/4 in., WLL: 25 t

3313212	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 1/4 in., WLL: 12 t EN 13889 Nominal size 1 1/4 in., WLL: 12 t
3313210	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 in., WLL: 8.5 t EN 13889 Nominal size 1 in., WLL: 8.5 t
25 TON MCKISSICK BLOCK, FOR WIRE SIZE 28.5 MM	M-491G/2032315 MCKISSICK
12 TON MCKISSICK BLOCK, FOR WIRE SIZE 19 MM	M-491G/2021163 MCKISSICK
4 TON MCKISSICK BLOCK, FOR WIRE SIZE 10 MM	M-491G/2020170 MCKISSICK
7504529	Crosby wire rope clips G-450 Nominal size 3 - 4 mm "1/4" "-HOT GALVANIZED" As an alternative to HG223, we offer: Crosby - with fork-fork
3013085	Crosby rigging screw galvanized HG-228 1/4 "x 4" fork - fork
6000000	Crosby rigging screw galvanized HG-228 5/16 "x 4-1 / 2" fork - fork
Range 143-163PSI	
RANGE 131-149PSI	
4100743	IP lifting clamp IPU10 0.5 EN 13155 Load capacity: 0.5 tons Gripping range 0-16MM
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM
Crosby S-265 (1290848)	WLL: 3,2
G2130A 4-3/4T 3/4" ALLOY BOLT TYPE SHK	1219516
G2130A 6-1/2T 7/8" ALLOY BOLT TYPE SHK	1219534
S265 1,2TX13MM	Ersetzt Art. 1290740
Rope Terminal Ø10mm	
BEP MBL 90T	Shackle Mooring No 852
1068389	HR1000M M36X130MM 6000000
(S65) CROSBY - 1068389	FAM 02TD2
CROSBY G341 16MM 5/8" WELDLESS SLING LINK GALV.	

CROSBY G209 3/4T 5/16" SCREW PIN ANCHOR SHACKLE	
CROSBY 1208 WEST 4" SHEAVE bb	
CROSBY G341 10MM 3/8" WELDLESS SLING LINK GALV	
CROSBY A336 8-10MM 3/8" GR6 LOK-A-LOY	
A-1337 32-10 (ID: 1015181)	Crosby Lock-a-loy
WLL: 25T (ID: 1262095)	Crosby Bow shackle with safety bolt
1018552	CROSBY G209 9-1/2T 1-1/8" SCREW PN ANCH
1018516	CROSBY G209 6-1/2T 7/8" SCREW PIN ANCH. SHACKLE
1018598	CROSBY G209 13-1/2T 1-3/8" SCREW PIN AN SHACKLE
Crosby HR125 - 1"A, ID: 1016964	
DOUBLE CLEVIS LINK S-247	Material item number : 00013195 Manufacturer : CROSBY Manufacturer part no. : 1013049
ALLOY CHAIN 8MM	Material item number : 00013196 Manufacturer : CROSBY Manufacturer part no. : Gr. 100 - 273729
LEBUS L-140 STANDARD RATCHET	Material item number : 00013197 Manufacturer : CROSBY Manufacturer part no. : 1048404
G-8142 EYE NUT M20 DIN 582	
LIFTING EYE GR8	Material item number : 00013199 Manufacturer : Green Pin Manufacturer part no. : GPAL20
LIFTING EYE LENGTH AS DIN580 GR8	Material item number : 00013200 Manufacturer : Green Pin Manufacturer part no. : GPAL20DIN
4100731	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM 2701663
4100733	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM 2701665
4100745	IP lifting clamp IPU10 2 EN 13155 Load capacity: 2 tons Gripping range 0-35MM 2701677
1.1/2G2.1/1 JLT-J05-15-A	
Crosby G209	1018491
2092120/	CROSBY Wirbelhaken - SHUR-LOC S-1326 10 MM
KLEMENSİ 16 MM G-450 crosby	
KLEMENSİ 28 MM G-450 crosby	
	Crosby Wire Rope Clips G-450 Nominal width 16 mm "5/8 "" -

7504530-2/	HOT GALVANIZED"
7504531/	Crosby Wire Rope Clips G-450 Nominal width 28-30 mm
G-2140	Alloy Bolt type Anchor Shackle WLL: 40T, ID: 1021138
Clip 3/8" Wire G-429 Fist Grip(Gergi Halatı Clamsi	
589714	EGKN-10-10
IPH10--2703297	
5-S-3 Stock No : 297235	
HR 125 M16	
Shackle 1/4" Crosby 2130 Grade6 bolttype	
Shackle 3/8" Crosby 2130 Grade6 bolttype	
Shackle 1/2" Crosby 2130 Grade6 bolttype	
Shackle 5/8" Crosby 2130 Grade6 bolttype	
Shackle 3/4" Crosby 2130 Grade6 bolttype	
Shackle 1" Crosby 2130 Grade6 bolttype	
G-2130	Crosby G-2130 Bolt Type Anchor Shackle WLL: 0,5T, Part No.: 1019466
951111MFA-P:VALVE	~ OMNI 951, 3/4 MNPT X 1 FNPT, 316 SST MATERIALS WITH METAL SEAT, THREADED CAP, PED
HG-228 G-6323 -	1032714 SSGPMBGG191 2 163 403 412 ROPE TENSIONER, JAW-JAW, 3/4" X 12", 2.36 TONS
HG-228 G-6323 -	1032778 SSGPMBGG221 8 163 407 818 ROPE TENSIONER, JAW-JAW, 7/8" X 18", 3.27 TONS
HG-228 G-6323 -	1032830 SSGPMBGG251 8 163 410 018 ROPE TENSIONER, JAW-JAW, 1" X 18", 4.54 TONS
HG-228 G-6323 -	1032894 SSGPMBGG321 8 163 411 418 ROPE TENSIONER, JAW-JAW, 1-1/4" X 18", 6.90 TONS
HG-228 G-6323 -	SSGPMBGG642 4 ROPE TENSIONER, JAW-JAW, 2-1/2" X 24", 27.20 TONS
G-450 G-6240	1010079 CLGRP08 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 8 MM (5/16"), EN 13411-5 TYPE B
G-450 G-6240	1010097 CLGRP10 STEEL ROPE TERMINAL, HOT DIP

G-450 G-6240	GALVANIZED, 10 MM (3/8"), EN 13411-5 TYPE B 1010131 CLGRP12 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 13 MM (1/2"), EN 13411-5 TYPE B
G-450 G-6240	1010195 CLGRP19 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 19 MM (3/4"), EN 13411-5 TYPE B
G-414	G-6120 1037675 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 10 MM (3/8")
G-414	G-6120 1037791 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 22 MM (7/8")
1035018	
1014155	
1048636	
Swivel 3 Te	Swivel No: 3-S-2, Steel, Red Operating Temperature: -40° C to +204° C Onshore Working Load Limit: 3 Tons
Crosby Shackles x 8 ea.	Crosby G 2130, Steel, Galvanized, Operating Temperature: - 40° C to +204° C Onshore Working Load Limit: 2 Tons
98832835	SHACKLE, BOLT TYPE ANCHOR, WLL 1.5T
98871566	SAFETY, SHACKLE, 4 PART ANCHOR, BOW, - G-2130, SWL 3.25T C/W COTTER PINS
END LINK WELDLESS S340 1/2 SUPPLIER CODE: 75535	
SHACKLE ANCHOR S-213 2T SUPPLIER: 75535,	
SHACKLE ANCHOR S-213 3 1/4 TON SUPPLIER: 75535,	
LINK, END WELDLESS S-340 (312) SUPPLIER:	75535
VALVE, RLF, CROSBY, 95114XMFA- SPL, 261PSI	Valves, Relief Type of bonnet/cover CLOSED Type of construction CONVENTIONAL Flow, max 7.327 m ³ /h Set pressure 17.99 bar 261 psi Temperature, max 38 °C Temperature, min -35 °C Size, inlet 1/2 in Size, outlet 1/2 in Size, orifice, actual 0.545 cm ² Mat, body MONEL Service(s) SEAWATER Type of end connection NPT MALE x FEMALE Mat, bonnet MONEL Mat, spring INCONEL X750 Type, cap SCREWED Manufacturer THE CROSBY GROUP Manufacturer Part Number 95114XMFA-SPL
3K4 JOS-E-45-J	
CHAIN HOOK / MODEL:S1317	SHUR-LOC CLEVIS HOOK, 6MM PIN AUTOMATIC LOCKING HOOK, CAPACITY:1450KG, EN 1677-3 (CERTIFICATE INCLUDED) / CROSBY / 1028991 /
Hr125 Hoist Ring 8000# 7/8 X 2.75 -	or equivalent -MPT THREAD

Crosby 1016953	
Hr125 Hoist Ring 5000# 3/4 X 2.25 - Crosby 1016931	or equivalent -MPT THREAD
Hr125 Hoist Ring 4000# 5/8 X 2 - Crosby 1016920 or	or equivalent - MPT THREAD
Hr125 Hoist Ring 2500# 1/2 X 2 - Crosby 1016909 or	equivalent - MPT THREAD
TYPE B, ASME B30.26	56-58 MM (2-1/4"), EN 13411-5 HOT DIP GALVANIZED
TL13N	
3M8HCA	Serial No: 13185990 & 13185991 & 13185972 & 13185973
2,5K2HCA	Serial No: 13185986 & 13185987 & 13185988 & 13185989 & 13185952 & 13185969 & 13185970 & 13185971
10049938	
10050309	
G-4163	WLL: 6,5 ton Bow shackle with safety bolt
Type WLL 6 ½ Ton 7/8	Chackle Bolt
0.2t M6	
1.5d2 Jbs-E-55-J/Spl	
961101mfa	
1019579 Hochfeste Schäkel	
1019533 Hochfeste Schäkel G 2130	
1.5h3 Jbs-E-15x-J -Spl	
G2150 1019953	Shackle straight with nut and split pin
1018516 (G209)	
1019686 Hochfeste Schäkel S 2130	
089115 (Obsolete - No Replacement) Nozzle	
G-340	Crosby G-340 1014093 WLL: 2,95 t.
1014365	CROSBY Master Link A-342
1025896-L1327	Eye hooks
1019953 Hochfeste Schäkel G 2150	
1.5d2 Jlt-Jos-E-56x-J/Spl-Spl	
G-450	G-450 1/2" 12-13 MM 1010131

P/N:136161	
1.5h3jos-E15c-Pspl	
A-1337	
1019524 Hochfeste Sch¼kel S 2130	
1022923	
1.5h3 Jbs-E-Or-15-L	
1018614	
G-209	Crosby anchor shackle with eyelet pin G-209 EN 13889 Nominal size 5/16 in., WLL: 0.75 t
G 2150 1019873	Shackle straight with nut and split pin
1022238	
1019677 Hochfeste Sch¼kel G 2130	
123834	
1010015 G450	
1018534.	
L320an-1022457	Eye hooks
Uni1950	
10143604	
04-4749-065	
1022260	
1019613 Hochfeste Sch¼kel G 2130	
S-91740	
1.5g2.5 Jbs-E-45-J	
A-345	Master Link Assembly WLL: 38,5to Crosby-Artikel-Nr.: 1014814
1.5e2 Jos-E-55x-J /Spl-Spl	
1014348 Aufh¼ngeglied	
Z091147b1ra5p1	
1014342-Obsolete-Alternative 1014348 Master Link	
A-342	Alloy Master Links

1014348	
1022293	
Grade 100 Alloy Chain	Nominal thickness: 26mm Crosby Item No .: 1210232
S-91328 / Inconel 625	
1.5g2.5 Jos-E-26-D	
1.5h3 Jos-E-26-D	
1019953	CROSBY Sch¼kel G-2150 - 25 to
1019622 Hochfeste Sch¼kel S 2130	
G2150 1019935	Shackle straight with nut and split pin
1015104	
0.5t Ip10 222.701.674	
951101mfa	
1022246	
Lok-A-Loy 10 Alloy Connection Link	WLL: 41,0to Crosby-Artikel-Nr.: 1015181
320/C	
961111mfa	
1.5f2 Jbs-E-16-L	
G-408	G-408 1/2" 11-13 MM 1037595
1037318	
951101ma	
1014319 Aufh¼ngeglied	
1022932	
101517 2	
1019515 Hochfeste Sch¼kel G 2130	
L320an-1022446	Eye hooks
1019962 Hochfeste Sch¼kel S 2150	
1018570	
1022424	
1019542 Hochfeste Sch¼kel S 2130	
10195794	
Hg-228 1/2x12"	3000000

[039973 \(Obsolete - No Replacement\)](#)
[Disc Bushing](#)