

A-342



## Crosby

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Crosby** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Crosby Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">Typ G-417</a>	7013035 Bow rope sleeve type G-417 Diameter 32-35 mm
<a href="#">G-417</a>	7013048 Bow rope sleeve type G-417 Diameter 44-48 mm
<a href="#">7013035</a>	Bow rope sleeve type G-417 Diameter 32-35 mm
<a href="#">7013048</a>	Bow rope sleeve type G-417 Diameter 44-48 mm
<a href="#">Liste 18 Pos.</a>	Bitte um Kontrolle und Angebot
<a href="#">Crane pennant, 2 meters long 6x19 IWRC Galv</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv</a>	. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye(SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
<a href="#">2 legs (Spreaders) 8 ton SWL x 5m long.</a>	22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">2 legs (Spreaders) 5 ton SWL x 5m long.</a>	6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">Green pin standard shckles</a>	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 16mm x 19mm, SWL 3.25 ton
<a href="#">Green pin standard shckles,</a>	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 19mm x 22mm, SWL 4.75 ton
<a href="#">Green pin standard shckles</a>	, bow shackles with safety bolt, to EN13889, hot dipped galvanized, 22mm x 25mm, SWL 6.5 ton
	bow shackles with safety bolt, to EN13889, hot dipped

<a href="#">Green pin standard shckles,</a>	galvanized, 25mm x 28mm, SWL 8.5 ton
<a href="#">Green pin standard shckles,</a>	bow shackles with safety bolt, to EN13889, hot dipped galvanized, 32mm x 35mm, SWL 12 ton
<a href="#">1000 kg SWL Chain blocks with certificate</a>	
<a href="#">Crane pennant, 2 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 2 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 5 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC® S-1316) (in.) (SWL 6.5t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long 6x19 IWRC Galv.</a>	Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master LinkCrane pennant, 5 meters long 6x19 IWRC Galv. Hard Eye Each End SWL 18 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 18t) other end with Crosby Master Link
<a href="#">Crane pennant, 5 meters long</a>	6x19 IWRC Galv. Hard Eye Each End SWL 8 Ton to include one end with Crosby Shur-Loc hook Eye (SHUR-LOC®S-1316A) (in.) (SWL 8t) other end with Crosby Master Link
<a href="#">2 legs (Spreaders)</a>	8 ton SWL x 5m long. 22mm 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">2 legs (Spreaders)</a>	5 ton SWL x 5m long. 6 x 36 IWRC galv wire rope, term in hard eyes fitted into master link with shur loc safty hooks at ends.
<a href="#">1090125</a>	Crosby safety hook set SS-4055 - 11.5to for old hooks 319, 320 and 322
<a href="#">1093541</a>	Crosby safety hook set SS-4055 - 22to 22 to. - for old hooks 319, 320 and 322
<a href="#">G-450 16 mm</a>	7504530-2 Crosby wire rope clips G-450 Nominal width 16 mm 5/8 "- HOT GALVANIZED"
<a href="#">G-450 9-10 mm</a>	Crosby wire rope clips G-450 Nominal width 9-10 mm 3/8 "- HOT GALVANIZED"
<a href="#">G-429 14 - 16 mm</a>	Crosby wire rope clips G-429 Nominal width 14 - 16 mm 9/16 - 5/8 "
<a href="#">3313042</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 3/4 in., WLL: 25 t EN 13889 Nominal size 1 3/4 in., WLL: 25 t

<a href="#">3313212</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 1/4 in., WLL: 12 t EN 13889 Nominal size 1 1/4 in., WLL: 12 t
<a href="#">3313210</a>	Crosby anchor shackle G 2130 with nut and cotter pin Nominal size 1 in., WLL: 8.5 t EN 13889 Nominal size 1 in., WLL: 8.5 t
<a href="#">25 TON MCKISSICK BLOCK, FOR WIRE SIZE 28.5 MM</a>	M-491G/2032315 MCKISSICK
<a href="#">12 TON MCKISSICK BLOCK, FOR WIRE SIZE 19 MM</a>	M-491G/2021163 MCKISSICK
<a href="#">4 TON MCKISSICK BLOCK, FOR WIRE SIZE 10 MM</a>	M-491G/2020170 MCKISSICK
<a href="#">7504529</a>	Crosby wire rope clips G-450 Nominal size 3 - 4 mm "1/4" "- HOT GALVANIZED" As an alternative to HG223, we offer: Crosby - with fork-fork
<a href="#">3013085</a>	Crosby rigging screw galvanized HG-228 1/4 "x 4" fork - fork
<a href="#">6000000</a>	Crosby rigging screw galvanized HG-228 5/16 "x 4-1 / 2" fork - fork
<a href="#">Range 143-163PSI</a>	
<a href="#">RANGE 131-149PSI</a>	
<a href="#">4100743</a>	IP lifting clamp IPU10 0.5 EN 13155 Load capacity: 0.5 tons Gripping range 0-16MM
<a href="#">4100731</a>	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM
<a href="#">4100733</a>	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM
<a href="#">Crosby S-265 (1290848)</a>	WLL: 3,2
<a href="#">G2130A 4-3/4T 3/4" ALLOY BOLT TYPE SHK</a>	1219516
<a href="#">G2130A 6-1/2T 7/8" ALLOY BOLT TYPE SHK</a>	1219534
<a href="#">S265 1,2TX13MM</a>	Ersetzt Art. 1290740
<a href="#">Rope Terminal Ø10mm</a>	
<a href="#">BEP MBL 90T</a>	Shackle Mooring No 852
<a href="#">1068389</a>	HR1000M M36X130MM 6000000
<a href="#">(S65) CROSBY - 1068389</a>	FAM 02TD2
<a href="#">CROSBY G341 16MM 5/8" WELDLESS SLING LINK GALV.</a>	

<a href="#">CROSBY G209 3/4T 5/16" SCREW PIN ANCHOR SHACKLE</a>	
<a href="#">CROSBY 1208 WEST 4" SHEAVE bb</a>	
<a href="#">CROSBY G341 10MM 3/8" WELDLESS SLING LINK GALV</a>	
<a href="#">CROSBY A336 8-10MM 3/8" GR6 LOK-A-LOY</a>	
<a href="#">A-1337 32-10 (ID: 1015181)</a>	Crosby Lock-a-loy
<a href="#">WLL: 25T (ID: 1262095)</a>	Crosby Bow shackle with safety bolt
<a href="#">1018552</a>	CROSBY G209 9-1/2T 1-1/8" SCREW PN ANCH
<a href="#">1018516</a>	CROSBY G209 6-1/2T 7/8" SCREW PIN ANCH. SHACKLE
<a href="#">1018598</a>	CROSBY G209 13-1/2T 1-3/8" SCREW PIN AN SHACKLE
<a href="#">Crosby HR125 - 1"A, ID: 1016964</a>	
<a href="#">DOUBLE CLEVIS LINK S-247</a>	Material item number : 00013195 Manufacturer : CROSBY Manufacturer part no. : 1013049
<a href="#">ALLOY CHAIN 8MM</a>	Material item number : 00013196 Manufacturer : CROSBY Manufacturer part no. : Gr. 100 - 273729
<a href="#">LEBUS L-140 STANDARD RATCHET</a>	Material item number : 00013197 Manufacturer : CROSBY Manufacturer part no. : 1048404
<a href="#">G-8142 EYE NUT M20 DIN 582</a>	
<a href="#">LIFTING EYE GR8</a>	Material item number : 00013199 Manufacturer : Green Pin Manufacturer part no. : GPAL20
<a href="#">LIFTING EYE LENGTH AS DIN580 GR8</a>	Material item number : 00013200 Manufacturer : Green Pin Manufacturer part no. : GPAL20DIN
<a href="#">4100731</a>	IP lifting clamp IPU10 1st EN 13155 Load capacity: 1 to Gripping range 0-20MM 2701663
<a href="#">4100733</a>	IP lifting clamp IPU10 3 EN 13155 Load capacity: 3 tons Gripping range 0-40MM 2701665
<a href="#">4100745</a>	IP lifting clamp IPU10 2 EN 13155 Load capacity: 2 tons Gripping range 0-35MM 2701677
<a href="#">1.1/2G2.1/1 JLT-J05-15-A</a>	
<a href="#">Crosby G209</a>	1018491
<a href="#">2092120/</a>	CROSBY Wirbelhaken - SHUR-LOC S-1326 10 MM
<a href="#">KLEMENSİ 16 MM G-450 crosby</a>	
<a href="#">KLEMENSİ 28 MM G-450 crosby</a>	
	Crosby Wire Rope Clips G-450 Nominal width 16 mm "5/8 "" -

<a href="#">7504530-2/</a>	HOT GALVANIZED"
<a href="#">7504531/</a>	Crosby Wire Rope Clips G-450 Nominal width 28-30 mm
<a href="#">G-2140</a>	Alloy Bolt type Anchor Shackle WLL: 40T, ID: 1021138
<a href="#">Clip 3/8" Wire G-429 Fist Grip(Gergi Halatı Clamsi</a>	
<a href="#">589714</a>	EGKN-10-10
<a href="#">IPH10--2703297</a>	
<a href="#">5-S-3 Stock No : 297235</a>	
<a href="#">HR 125 M16</a>	
<a href="#">Shackle 1/4" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 3/8" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 1/2" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 5/8" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 3/4" Crosby 2130 Grade6 bolttype</a>	
<a href="#">Shackle 1" Crosby 2130 Grade6 bolttype</a>	
<a href="#">G-2130</a>	Crosby G-2130 Bolt Type Anchor Shackle WLL: 0,5T, Part No.: 1019466
<a href="#">951111MFA-P:VALVE</a>	~ OMNI 951, 3/4 MNPT X 1 FNPT, 316 SST MATERIALS WITH METAL SEAT, THREADED CAP, PED
<a href="#">HG-228 G-6323 -</a>	1032714 SSGPMBGG191 2 163 403 412 ROPE TENSIONER, JAW-JAW, 3/4" X 12", 2.36 TONS
<a href="#">HG-228 G-6323 -</a>	1032778 SSGPMBGG221 8 163 407 818 ROPE TENSIONER, JAW-JAW, 7/8" X 18", 3.27 TONS
<a href="#">HG-228 G-6323 -</a>	1032830 SSGPMBGG251 8 163 410 018 ROPE TENSIONER, JAW-JAW, 1" X 18", 4.54 TONS
<a href="#">HG-228 G-6323 -</a>	1032894 SSGPMBGG321 8 163 411 418 ROPE TENSIONER, JAW-JAW, 1-1/4" X 18", 6.90 TONS
<a href="#">HG-228 G-6323 -</a>	SSGPMBGG642 4 ROPE TENSIONER, JAW-JAW, 2-1/2" X 24", 27.20 TONS
<a href="#">G-450 G-6240</a>	1010079 CLGRP08 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 8 MM (5/16"), EN 13411-5 TYPE B
<a href="#">G-450 G-6240</a>	1010097 CLGRP10 STEEL ROPE TERMINAL, HOT DIP

<a href="#">G-450 G-6240</a>	GALVANIZED, 10 MM (3/8"), EN 13411-5 TYPE B 1010131 CLGRP12 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 13 MM (1/2"), EN 13411-5 TYPE B
<a href="#">G-450 G-6240</a>	1010195 CLGRP19 STEEL ROPE TERMINAL, HOT DIP GALVANIZED, 19 MM (3/4"), EN 13411-5 TYPE B
<a href="#">G-414</a>	G-6120 1037675 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 10 MM (3/8")
<a href="#">G-414</a>	G-6120 1037791 RADANSA, HEAVY DUTY, HOT DIP GALVANIZED, 22 MM (7/8")
<a href="#">1035018</a>	
<a href="#">1014155</a>	
<a href="#">1048636</a>	
<a href="#">Swivel 3 Te</a>	Swivel No: 3-S-2, Steel, Red Operating Temperature: -40° C to +204° C Onshore Working Load Limit: 3 Tons
<a href="#">Crosby Shackles x 8 ea.</a>	Crosby G 2130, Steel, Galvanized, Operating Temperature: - 40° C to +204° C Onshore Working Load Limit: 2 Tons
<a href="#">98832835</a>	SHACKLE, BOLT TYPE ANCHOR, WLL 1.5T
<a href="#">98871566</a>	SAFETY, SHACKLE, 4 PART ANCHOR, BOW, - G-2130, SWL 3.25T C/W COTTER PINS
<a href="#">END LINK WELDLESS S340 1/2 SUPPLIER CODE: 75535</a>	
<a href="#">SHACKLE ANCHOR S-213 2T SUPPLIER: 75535,</a>	
<a href="#">SHACKLE ANCHOR S-213 3 1/4 TON SUPPLIER: 75535,</a>	
<a href="#">LINK, END WELDLESS S-340 (312) SUPPLIER:</a>	75535
<a href="#">VALVE,RLF,CROSBY,95114XMFA- SPL,261PSI</a>	Valves, Relief Type of bonnet/cover CLOSED Type of construction CONVENTIONAL Flow, max 7.327 m³/h Set pressure 17.99 bar 261 psi Temperature, max 38 °C Temperature, min -35 °C Size, inlet 1/2 in Size, outlet 1/2 in Size, orifice, actual 0.545 cm² Mat, body MONEL Service(s) SEAWATER Type of end connection NPT MALE x FEMALE Mat, bonnet MONEL Mat, spring INCONEL X750 Type, cap SCREWED Manufacturer THE CROSBY GROUP Manufacturer Part Number 95114XMFA-SPL
<a href="#">3K4 JOS-E-45-J</a>	
<a href="#">CHAIN HOOK / MODEL:S1317</a>	SHUR-LOC CLEVIS HOOK, 6MM PIN AUTOMATIC LOCKING HOOK, CAPACITY:1450KG, EN 1677-3 (CERTIFICATE INCLUDED) / CROSBY / 1028991 /
<a href="#">Hr125 Hoist Ring 8000# 7/8 X 2.75 -</a>	or equivalent -MPT THREAD

<a href="#">Crosby 1016953</a>	
<a href="#">Hr125 Hoist Ring 5000# 3/4 X 2.25 - Crosby 1016931</a>	or equivalent -MPT THREAD
<a href="#">Hr125 Hoist Ring 4000# 5/8 X 2 - Crosby 1016920 or</a>	or equivalent - MPT THREAD
<a href="#">Hr125 Hoist Ring 2500# 1/2 X 2 - Crosby 1016909 or</a>	equivalent - MPT THREAD
<a href="#">TYPE B, ASME B30.26</a>	56-58 MM (2-1/4"), EN 13411-5 HOT DIP GALVANIZED
<a href="#">TL13N</a>	
<a href="#">3M8HCA</a>	Serial No: 13185990 & 13185991 & 13185972 & 13185973
<a href="#">2,5K2HCA</a>	Serial No: 13185986 & 13185987 & 13185988 & 13185989 & 13185952 & 13185969 & 13185970 & 13185971
<a href="#">10049938</a>	
<a href="#">10050309</a>	
<a href="#">G-4163</a>	WLL: 6,5 ton Bow shackle with safety bolt
<a href="#">Type WLL 6 ½ Ton 7/8</a>	Chackle Bolt
<a href="#">0.2t M6</a>	
<a href="#">1.5d2 Jbs-E-55-J/Spl</a>	
<a href="#">961101mfa</a>	
<a href="#">1019579 Hochfeste Schäkel</a>	
<a href="#">1019533 Hochfeste Schäkel G 2130</a>	
<a href="#">1.5h3 Jbs-E-15x-J -Spl</a>	
<a href="#">G2150 1019953</a>	Shackle straight with nut and split pin
<a href="#">1018516 (G209)</a>	
<a href="#">1019686 Hochfeste Schäkel S 2130</a>	
<a href="#">089115 (Obsolete - No Replacement) Nozzle</a>	
<a href="#">G-340</a>	Crosby G-340 1014093 WLL: 2,95 t.
<a href="#">1014365</a>	CROSBY Master Link A-342
<a href="#">1025896-L1327</a>	Eye hooks
<a href="#">1019953 Hochfeste Schäkel G 2150</a>	
<a href="#">1.5d2 Jlt-Jos-E-56x-J/Spl-Spl</a>	
<a href="#">G-450</a>	G-450 1/2" 12-13 MM 1010131

<a href="#">P/N:136161</a>	
<a href="#">1.5h3jos-E15c-Pspl</a>	
<a href="#">A-1337</a>	
<a href="#">1019524 Hochfeste Sch¼kel S 2130</a>	
<a href="#">1022923</a>	
<a href="#">1.5h3 Jbs-E-Or-15-L</a>	
<a href="#">1018614</a>	
<a href="#">G-209</a>	Crosby anchor shackle with eyelet pin G-209 EN 13889 Nominal size 5/16 in., WLL: 0.75 t
<a href="#">G 2150 1019873</a>	Shackle straight with nut and split pin
<a href="#">1022238</a>	
<a href="#">1019677 Hochfeste Sch¼kel G 2130</a>	
<a href="#">123834</a>	
<a href="#">1010015 G450</a>	
<a href="#">1018534.</a>	
<a href="#">L320an-1022457</a>	Eye hooks
<a href="#">Uni1950</a>	
<a href="#">10143604</a>	
<a href="#">04-4749-065</a>	
<a href="#">1022260</a>	
<a href="#">1019613 Hochfeste Sch¼kel G 2130</a>	
<a href="#">S-91740</a>	
<a href="#">1.5g2.5 Jbs-E-45-J</a>	
<a href="#">A-345</a>	Master Link Assembly WLL: 38,5to Crosby-Artikel-Nr.: 1014814
<a href="#">1.5e2 Jos-E-55x-J /Spl-Spl</a>	
<a href="#">1014348 Aufh¼ngeglied</a>	
<a href="#">Z091147b1ra5p1</a>	
<a href="#">1014342-Obsolete-Alternative 1014348</a> <a href="#">Master Link</a>	
<a href="#">A-342</a>	Alloy Master Links



<a href="#">1014348</a>	
<a href="#">1022293</a>	
<a href="#">Grade 100 Alloy Chain</a>	Nominal thickness: 26mm Crosby Item No .: 1210232
<a href="#">S-91328 / Inconel 625</a>	
<a href="#">1.5g2.5 Jos-E-26-D</a>	
<a href="#">1.5h3 Jos-E-26-D</a>	
<a href="#">1019953</a>	CROSBY Sch¼kel G-2150 - 25 to
<a href="#">1019622 Hochfeste Sch¼kel S 2130</a>	
<a href="#">G2150 1019935</a>	Shackle straight with nut and split pin
<a href="#">1015104</a>	
<a href="#">0.5t Ip10 222.701.674</a>	
<a href="#">951101mfa</a>	
<a href="#">1022246</a>	
<a href="#">Lok-A-Loy 10 Alloy Connection Link</a>	WLL: 41,0to Crosby-Artikel-Nr.: 1015181
<a href="#">320/C</a>	
<a href="#">961111mfa</a>	
<a href="#">1.5f2 Jbs-E-16-L</a>	
<a href="#">G-408</a>	G-408 1/2" 11-13 MM 1037595
<a href="#">1037318</a>	
<a href="#">951101ma</a>	
<a href="#">1014319 Aufh¼ngeglied</a>	
<a href="#">1022932</a>	
<a href="#">101517 2</a>	
<a href="#">1019515 Hochfeste Sch¼kel G 2130</a>	
<a href="#">L320an-1022446</a>	Eye hooks
<a href="#">1019962 Hochfeste Sch¼kel S 2150</a>	
<a href="#">1018570</a>	
<a href="#">1022424</a>	
<a href="#">1019542 Hochfeste Sch¼kel S 2130</a>	
<a href="#">10195794</a>	
<a href="#">Hg-228 1/2x12"</a>	3000000

[039973 \(Obsolete - No Replacement\)](#)  
[Disc Bushing](#)