

Datapaq

Garanti: 12 ay
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Datapaq Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

Firmamız Datapaq T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.



¼r¼n	A¼ıklama
TB0253	EasyTrack3 heat protection container - aluminum Construction, ceramic insulation. Includes heat sink (TB9550 C58). Suitable data logger: EasyTrack3 (ET6063, ET4043) and earlier EasyTrack. Container with handle (x1). Heat protection performance: 40 min. @ 300 ° C (572 ° F); 2 hours @ 200 ° C (392 ° F); 6 hours @ 100 ° C (212 ° F). Dimensions: 265 mm (10.4 inch) (H) x 185mm (7.3 inch) (W) x 110mm (4.3 inch) (L). Weight: 3.0kg (6.5lbs).
ET6063	EasyTrack3 data logger (6 channel). Measuring range - 150 ° C up to 500 ° C (-238 ° F to 932 ° F) Accuracy +/- 0.5 ° C, type K thermocouples, 18,000 Measured values / channel, programmable measuring interval (0.5 s to 60 min), Start / stop button, operating temperature 85 ° C (185 ° F), USB port (CI1150 cable). Incl. CI cable, replaceable 9 V battery (2 pieces), manual, Brief instructions and calibration certificate. Compatible with EasyTrack Insight and EasyTrack Insight Professional software version 8.5 (or higher). Replaces ET4041, ET5051 and ET6061
PA0011	Surface measuring probe with clamp, length: 1.5 m. PTFE insulated cable, 0 - 265 ° C maximum.

CC0049	Carry bag. With shoulder strap for storing and carrying the whole Systems with ET3, Easytrack or Easytrack2
TUS	
PA0053	Magnetic sensor surface, length 1.5 m., PTFE cable. PTFE insulated cable, 0 - 265°C maximum.
PA0021	Air sensor with clamp, length: 1.5 m. PTFE insulated cable, 0 - 265°C maximum.
ET3	
Tpag21 / Tp2086	
Tp2019-Tx	
Pa0060b	
Pa0974b.	
Tp0106a	
Pa0055	
Pa1581	
Pa0061	
Tb4005	
Pa0025	Clamp probe air, length: 6 m. PTFE insulated, 0 - 265 ° C maximum temperature.
Pa0032	
Pa0012	Probe surface with clamp, length: 3.0 m. PTFE insulated cable, 0 - 265 ° C maximum.
421757	
Pa0053	
SW5210	Insight software for EasyTrack, different languages Including: Digital quick start guide and user manual on the CD. French SW5211; German SW5212; Spanish SW5213, Portuguese SW5214; Japanese SW5215; simplified Chinese SW5216; Italian SW5217; Korean SW5218; Slovak SW5219; Czech SW52110; Traditional Chinese SW52111; Russian SW5211
Pa0021/ Pa0011	
Tb1066	
Pa0016	Clamp probe surface, length: 6 m. PTFE insulated, 0 - 265 ° C maximum temperature.
Pa0765	
Pa0054c	

Pa0063	
Tb4526	
Pa0973	
Pa0082	
Fs-438-10	
Part No. Cx-211-6b	
Pa1361	
Di718b-E-B	
Cs1001	
Part No. Wa-001-1	
Sws210	
Datapaq Tamir Ve Kalibrasyonu	
Pa0021	Probe air with clamp, length: 1.5 m. PTFE insulated cable, 0 - 265 ° C maximum
Pa005	
Pa0995	
421756	
Pa07611	
Pa0022	Air probe with clamp, length: 3.0 m. PTFE insulated cable, 0 - 265 ° C maximum.
Tb4938	
XI-Mp0030	
Sc0001	
Pa0764	
Pa1582	
Pa0060	
Pa0056	
Pa0763	
Std-Tx1-10	
Pa07612	
Pa0762	

Tr0005b	
Cs2084	
Ete-254-112-2 Easytrack2 System	
Sw5137+tb4526+tp2019- Tx+pa1582+cs2084+cs1001	
Pa1351	
Pa0054	
Fti-331-162	
Pa0767	
Tr000s	
Pa0011	Probe surface with clamp, length: 1.5 m. PTFE insulated cable, 0 - 265 ° C maximum.