

## Delavan

Garanti: 12 ay  
Bu ¼r¼ne ait T¼rkiye i¼i kapı teslim fiyat ve teslim s¼resi i¼eren teklifimizi almak i¼in **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi i¼in +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.  
**Delavan** Markası, tedarik s¼resi i¼in l¼tfen bizimle iletiŐime ge¼iniz.

*Firmamız Delavan T¼rkiye Distrib¼t¼r¼ veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen ¼r¼nlerde sadece Orjinal ve yeni ¼r¼n teklifi sunmaktadır. Bu sitede g¼sterilen ¼zel marka adları ve ticari markalar ilgili sahiplerinin m¼lkiyetindedir, talep durumunda kaldırılmaktadır.*



¼r¼n	A¼ıklama
<a href="#">26089</a>	
<a href="#">32000</a>	
<a href="#">A00703071</a>	
<a href="#">A00703079</a>	
<a href="#">A00703087</a>	
<a href="#">A00703094</a>	
<a href="#">A297940056</a>	
<a href="#">A312120056</a>	
<a href="#">A383310016</a>	
<a href="#">SDXIII -W 113000001</a>	
<a href="#">Nozzle 00100-60W 1</a>	
<a href="#">00100-604W 1,50</a>	

<a href="#">SDX 703-075, 1,9 mm</a>	Pressure in nozzles: 35-40 bar (Nozzle pressure) Fine particles can be reused in slurry. Solid content in Slurry should not exceed 65%. N2 inlet temperature: 185°C Product temperature: 45-49°C Exhaust temperature: 90-95°C Gas throughput: 13500 m <sup>3</sup> /h Slurry throughput: 1200 L/h Nozzle type: 3 x SDX 703-075, 1,9 mm Pressure in nozzles: 35-40 bar Fine particles can be reused in slurry. Solid content in Slurry should not exceed 65%.
<a href="#">Sonac Db413 No 5675 Mc</a>	
<a href="#">Microwave 320 Level</a>	
<a href="#">W196000019</a>	
<a href="#">W19600-1</a>	
<a href="#">Sna 11 (30609-11)</a>	
<a href="#">Sonac P/No: O1c 38510</a>	
<a href="#">A171470006</a>	
<a href="#">Sonac 011l</a>	