

## Delvo



Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin [info@yursat.com.tr](mailto:info@yursat.com.tr) e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.

**Delvo** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

*Firmamız Delvo Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.*

rn	Aıklama
<a href="#">DLV30A20P-ASK</a>	Art.-Nr.: 95310000 Torque range: 1.2 - 3.0 Nm / Optional 0.4 - 1.6 Nm Screw size: 2.6 - 5.0 mm (metric) 2.5 - 4.0 mm (self-forming) Speed 1,200 - 2,000 rpm Power: 44W Launch: push launch, axial push launch Direction of rotation: reversible Design: straight Features: Brushless motor, blade grounding, soft start Voltage: 40 V DC (from the control unit) Blade holder: quick-change chuck, Allen key 1/4" (6.35 mm) Weight: 0.72kg Scope of delivery: Tool with torque cap (DLW 5201), cable 3 m, Suspension, additional clutch spring and bit NK35(No.2 x 7 x 75). Matching control unit: DLC70S-WGB or DLR70S-WGB (not included Delvo electric screwdriver Item no.: 37308100 Country of origin: Japan 8467 29 85
<a href="#">838631</a>	Delvo DLV16SL-CKE electric screwdriver MPN DLV16SL-CKE Manufacturer Delvo Handy, brushless electric screwdriver - Ergonomic and compact -Brushless electric screwdriver - Torque repeatability: 3% -Stepless speed adjustment - Mechanical shut-off clutch -Transparent torque protection sleeve -Quick-change chuck for blades and keys -Blade holder according to DIN-ISO 1123: 1/4" Technical data: -Speed: 700 - 1000 rpm -Torque: 0.2 - 1.6 Nm -Starter: lever -Voltage: DC 20 - 30V -Power consumption: 48 W -Head screw: 2.2 - 4.2 mm -Tapping screw: 2.0 - 3.2 mm -Bit type: 1/4" hexagon
<a href="#">Dlv7331-Cme</a>	
<a href="#">Dlv7335-Cke</a>	
<a href="#">Dlv7325-Cke</a>	
<a href="#">Dlv7321-Bmn</a>	
<a href="#">Dlv30lp-Lku</a>	
<a href="#">Dlv70II-Mkg</a>	
<a href="#">Dlv8234-Lku</a>	
<a href="#">Dlv7321-Bku</a>	

<a href="#">Dlv5820hu</a>
<a href="#">Dlv45lp-Spc(Lku)</a>
<a href="#">Dlv12sl-Cke</a>
<a href="#">Dir5040a-Wu</a>
<a href="#">148037 Screwdriver</a>
<a href="#">Dlc 70s-Wgb</a>
<a href="#">912.154-47m</a>
<a href="#">Dvl30lp-Mkg</a>
<a href="#">Dlv30sp-Spc</a>
<a href="#">Dlv5840u</a>
<a href="#">Dlc035olu</a>
<a href="#">Dlv7419ha-Bme</a>
<a href="#">Dlv02sl Cke</a>
<a href="#">Dlv30hl-Lku</a>
<a href="#">Dlv7329-Bme</a>
<a href="#">Dlv70lp-Mkg</a>
<a href="#">Dlv7349-Bme</a>
<a href="#">Dlv 8540-Mke</a>
<a href="#">Dir5040a Screwcounter</a>
<a href="#">Dir705-Wub</a>
<a href="#">148111 Power Cord Assembly</a>
<a href="#">Dlv30hp-Mjg</a>
<a href="#">Dlv7410a-Bme</a>
<a href="#">Dlv7331-Bmn</a>
<a href="#">Dlv16sl</a>
<a href="#">Dlv30sl-Lku</a>
<a href="#">Dlv30hp-Spc(Lku)</a>
<a href="#">Dlv30hp-Mkg</a>
<a href="#">Dlv7530-Bke</a>
<a href="#">Dir5040a-Wn</a>

<a href="#">Dlv45sp-Lku</a>	
<a href="#">Dlv8244-Lku</a>	
<a href="#">Dlv30hp-Ike</a>	
<a href="#">Dlv45sp-Ike</a>	
<a href="#">Dlv30hl-Mjg</a>	
<a href="#">Dlv30sp-Spc(Lku)</a>	
<a href="#">148033</a>	
<a href="#">Dlv30ll-Lku</a>	
<a href="#">Dlv12sl Bke</a>	
<a href="#">Dlv7134-Lku</a>	
<a href="#">Dlv45sl-Mkg</a>	
<a href="#">Dlv8124-Lku</a>	
<a href="#">Dlv30sl-Mkg</a>	
<a href="#">Dlv7331-Cke</a>	
<a href="#">Dlv73-73-Cke</a>	
<a href="#">Dlv30sp-Lku</a>	
<a href="#">Dlv70lp-Ike</a>	
<a href="#">Dlv7530-Mke</a>	
<a href="#">Dlv45lp-Ike</a>	
<a href="#">Dlv02sl-Cke</a>	
<a href="#">Dlv30sl-Spc(Lku)</a>	
<a href="#">Dlv12sl Cke</a>	
<a href="#">Dlv 16sl-Cke</a>	Power Driver with brushless motor, wear-resistant Torque range: 0.2-1.6 Nm Speed: 700-1000 rpm. Quick-change coupling for bit ¼ " Forward / reverse Ergo Grip Torque locking sleeve Weight: 0.47 kg Total length: 235 mm Incl. Controller -DLC1165-WGB Power switch with control LED Power and connection cable to the screwdriver
<a href="#">Dlv30lp-Mjg</a>	
<a href="#">Dlr5040a-We</a>	
<a href="#">Dlv7420ha-Bme</a>	
<a href="#">Supports Vertical 70cm Orizontal 70cm</a>	
<a href="#">Dlv7540-Mke</a>	

<a href="#">Dlv45sl-Iku</a>
<a href="#">Dlv45sl-Ike</a>
<a href="#">Dlv16sl Bke</a>
<a href="#">Dlv8530-Mke</a>
<a href="#">Dlv7313-Cme</a>
<a href="#">Dlv45ll-Mkg</a>
<a href="#">Dlv30ll-Iku</a>
<a href="#">Dlv30ll-Mkg</a>
<a href="#">Dlv45ll-Spc(Lku)</a>
<a href="#">Dlv7335-Cme</a>
<a href="#">Dlv7321-Bke</a>
<a href="#">Dlv30sp-Mkg</a>
<a href="#">Dlr70s-Wgb</a>
<a href="#">Dlv 30lp-Ike</a>
<a href="#">Dlv30hl-Ike</a>
<a href="#">Dlv7550-Mke</a>
<a href="#">Dlv 7550 Bke 500 Min 0.5s/3.5s</a>
<a href="#">8144</a>
<a href="#">Dlv30hl-Iku</a>
<a href="#">Dlv70ll-Ike</a>
<a href="#">8134</a>
<a href="#">148033 Screwdriver</a>
<a href="#">Dlv30lp-Spc(Lku)</a>
<a href="#">Dlv45lp-Iku</a>
<a href="#">Dlv45ll-Iku</a>
<a href="#">Dlv30ll-Ike</a>
<a href="#">Dlv7124-Lku</a>
<a href="#">Dlv45sl-Spc(Lku)</a>
<a href="#">Dlv7331-Bke</a>
<a href="#">Dlv8154-Lku</a>

<a href="#">Dlv45lp-Lku</a>	
<a href="#">Dlv 8540-Mke Elektroschrauber</a>	
<a href="#">912.154-47m Power Cord Assembly</a>	
<a href="#">Dlv7321-Cme</a>	
<a href="#">Dlv7144-Lku</a>	
<a href="#">Dlv30ll-Spc(Lku)</a>	
<a href="#">Dlv7333-Cme</a>	
<a href="#">Ntw-1r</a>	
<a href="#">Dlv7429a-Bme</a>	
<a href="#">DLV30A12L-ABK</a>	Electric screwdriver -with lever starter -for direct connection 230 V. -Speed 1,200 rpm -Torque continuously adjustable 0.4 - 3.0 Nm -with shut-off clutch
<a href="#">Dlv45sp-Iku</a>	
<a href="#">Dlv45sp-Mkg</a>	
<a href="#">Dlv30sp-Iku</a>	
<a href="#">Dlv8134-Lku</a>	
<a href="#">Dlv45lp-Mkg</a>	
<a href="#">Dlv30ll-Mjg</a>	
<a href="#">Dlv45sp-Spc(Lku)</a>	
<a href="#">Dlv7323-Cke</a>	
<a href="#">Dlv7410ha-Bme</a>	
<a href="#">Dlv30lp-Ike</a>	
<a href="#">Dlv16sl-Bke (Esd)</a>	The variable speed adjustment allows you an optimal Screw tightening speed to choose. Equipped with a grounding mechanism Compliant with CE and UL standards specifications Starting procedure: lever start Speed: 700 - 1,000 rpm Torque: 0.2 - 1.6 Nm Screw size (cap screw): 2.2 - 4.2 mm Screw size (tapping screw): 2.0 - 3.2 mm Weight: 0.47 kg Voltage: 20 - 30 V DC Power consumption: 48 W Power supply DLC16S-WGB input voltage: 100 - 240 V AC, 50/60 Hz Output voltage: 20 - 30 V DC Function: Speed check Plug shape: Europe Mass: 0.38 kg
<a href="#">Dlv7540-Bke</a>	
<a href="#">Dlv7321-Cke</a>	
<a href="#">Dlv30sl-Ike</a>	
<a href="#">Dlv8144-Lku</a>	

<a href="#">Tw-1r</a>
<a href="#">Dlv02sl Bke</a>
<a href="#">148037</a>
<a href="#">Dlv8540-Mke</a>
<a href="#">Dlv30sp-Mjg</a>
<a href="#">Dlv7550-Bke</a>
<a href="#">Dlv8550-Mke</a>
<a href="#">148111</a>
<a href="#">Dlv30hp-Iku</a>
<a href="#">Dlv30sl-Iku</a>
<a href="#">Dlv30lp-Mkg</a>
<a href="#">Dlv5820u</a>
<a href="#">Dlv30hp-Sp Unknown</a>
<a href="#">Dlv30sl-Mjg</a>
<a href="#">Dlv7339-Bme</a>
<a href="#">Dlv7333-Cke</a>
<a href="#">Dlv16sl-Cke</a>
<a href="#">Dlv45sl-Lku</a>
<a href="#">Dlv8540-Bke</a>
<a href="#">Dlv7319-Bme</a>
<a href="#">Dlv30hl-Spc(Lku)</a>
<a href="#">Dlv30hl-Mkg</a>
<a href="#">Dlv30hp-Lku</a>
<a href="#">Dlv8224-Lku</a>
<a href="#">Dlv7325-Cme</a>
<a href="#">Dlv45ll-Lku</a>
<a href="#">Dlv8550-Bke</a>
<a href="#">Dlv7331-Bme</a>
<a href="#">Dlv30lp-Iku</a>
<a href="#">Dlv7419a-Bme</a>
<a href="#">Dlv8130-Spc(Jke)</a>

<a href="#">Dir5340-Wu</a>
<a href="#">Dlc1213a-Gg</a>
<a href="#">Dlv7321-Bme</a>
<a href="#">Dlc1213-Lub</a>
<a href="#">Dlv30sp-Ike</a>
<a href="#">Dlv45II-Ike</a>
<a href="#">Dlv7323-Cme</a>
<a href="#">Dlv8530-Bke</a>
<a href="#">Dir5040a</a>
<a href="#">Dlv16sl Cke</a>
<a href="#">Dlc705-Wub</a>
<a href="#">Dlc1213a-Gg 5pin</a>
<a href="#">Dlc165-Wub</a>
<a href="#">Elektroschrauber Dlv8550-Mke</a>
<a href="#">Dlv7331-Bku</a>