

Denios

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine baŐvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz.
Denios Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Denios Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunulmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
201352	<p>Spiral earthing cable with 1 stainless steel earthing clamp Medium Duty 120 mm and 1 eyelet, 3 m extension length, ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type MD: length 120 mm, opening angle approx. 15 mm (for barrels, containers up to 200 liters) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 60 Outer width (mm): 25 Outer depth (mm): 3180 Equipment: 1 stainless steel pliers MD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 3000</p>
	<p>Spiral earthing cable with 1 stainless steel earthing clamp Medium Duty 120 mm and 1 eyelet, 5 m extension length,</p>

[201353](#)

ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type MD: length 120 mm, opening angle approx. 15 mm (for barrels, containers up to 200 liters) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 60 Outer width (mm): 25 Outer depth (mm): 5180 Equipment: 1 stainless steel pliers MD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 5000

[201354 Heavy Duty](#)

ALTERNATIVE TO POS 1 Spiral earthing cable with 1 stainless steel earthing clamp Heavy Duty 235 mm and 1 eyelet, 3 m extension length, ATEX avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable - With 1 ring eyelet and 1 earthing clamp type HD: length 235 mm, opening angle approx. 40 mm (for containers from 200 liters, larger system parts, IBCs, Mixing tanks, mobile tanks, tank vehicles etc.) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 105 Outer width (mm): 40 Outer depth (mm): 3295 Equipment: 1 stainless steel pliers HD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 3000

[201355 Heavy Duty](#)

ALTERNATIVE TO POS2 Spiral earthing cable with 1 stainless steel earthing clamp Heavy Duty 235 mm and 1 eyelet, 5 m extension length, ATEX - avoids the risk of explosion from sparking or static Charging - low electrical resistance with high mechanical strength - Chemically resistant and abrasion-resistant cable sheath - Approved according to ATEX II 1GD T6, thus fulfills the VGSEB regulation 734.6 for the EX area - ATEX version with stainless steel pliers - Stainless steel pliers with long service life and "bite resistance" even under the harshest operating conditions - for a safe and durable connection - With 1 ring eyelet and 1 earthing clamp type HD: length 235 mm, opening angle approx. 40 mm (for containers from 200 liters, larger system parts, IBCs, Mixing tanks, mobile tanks, tank vehicles etc.) - Cable cross section: 4 mm², total cable diameter: 6 mm - Ø eyelet: 10 mm Material: stainless steel Approval / Certificate Description: 94/9 / EC DECLARATION OF CONFORMITY Atex protection class: Ex II 1 GD T6 Outer height (mm): 105 Outer width (mm): 40 Outer depth (mm): 5295 Equipment: 1

	stainless steel pliers HD / 1 ring eyelet Version: spiral earthing cable Cable length (mm): 5000
117044	
117138	
117138W	
165242	
214474	
250676	
31408	
715033	
F¼r RAL 5010	
GFT 33.15	
PE Blau	
RAL 5010	
117721	Heating jacket for 30 liter drums, 0 - 90°C thermostat, 870 - 1020 mm, 200 watts Suitable for: 25 - 30 liter steel and plastic drums Intended use : Keep warm/warm up Version : jacket heating Place of installation : indoors External width (mm) : 1020 External depth (mm) : 80 External height (mm) : 400 Cable length (mm) : 5000 Container circumference min (mm) : 870 Material : Nylon, polyurethane coated Surface : Teflon coated Color: Black Power (W) : 200 Rated Voltage (V) : 240 Control range max (°C) : 90 Fabric Material : NYLON/POLYESTER Approval / Certificate : EU Directive (2014/35/EU), EU Directive (2014/30/EU), EU Directive (2011/65/EU) Equipment : analogue temperature controller Degree of protection IP : IP 44 Weight (kg) : 1.8 Customs tariff number: 85144000 Country of origin : United Kingdom
156179	HEATING JACKET FOR 205 LITRE DRUMS, 0 - 90°C THERMOSTAT, 1800 - 1950 MM, 1100 WATT Heating jacket for 200 liter drums, 0 - 90°C thermostat, 1800 - 1950 mm, 1100 watts - Medium power heating jacket: for rapid heating of media in applications requiring require a fast heating rate up to approx. 50 - 70°C Suitable for: 200 - 220 liter steel and plastic drums Intended use : heating Version : jacket heating Place of installation : indoors Outside width (mm) : 1950 External depth (mm) : 100 External height (mm) : 850 Cable length (mm) : 5000 Container circumference min (mm) : 1800 Material : nylon/glass fiber thread silicone b Color: Black Power (W) : 1100 Rated Voltage (V) : 240 Control range max (°C) : 90 Fabric material : NYLON Approval / Certificate : EU Directive (2014/35/EU), EU Directive (2014/30/EU), EU Directive (2011/65/EU) Equipment : analogue temperature controller Degree of protection IP : IP 44 Weight (kg) : 5
	Base-line collection tray made of polyethylene (PE) for 2

267371	barrels, with PE grid Grating: plastic Version: accessible Material: plastic Collection volume [l]: 220 Total load capacity [kg]: 760 Weight [kg] : 27.5 External width [mm]: 865 External depth [mm] : 1245 External height [mm]: 375 Approval: DIBt Approval / Certificate Description 1 : Z-40.22- 252 Color orange Brand: DENIOS base line Storage capacity: 200 liter barrels: 2
267499	Collection tray classic-line made of polyethylene (PE) for 2 barrels, with PE grid, 1330x930x410 - Access pockets in the floor area enable safe transport and assembly with barrel lifters, pallet trucks and forklifts from all 4 sides. - Highly resistant to oils, acids, alkalis and other aggressive substances - Legally compliant: seamlessly manufactured and absolutely liquid-tight - Stable construction with good shock and impact resistance, even for large ones Temperature fluctuations Grating: plastic Version: accessible Material: plastic Collection volume [l]: 220 Total load capacity [kg]: 800 Weight [kg] : 43.9 External width [mm]: 1330 External depth [mm]: 930 External height [mm]: 410 Approval: DIBt Approval / Certificate Description 1 : Z-40.22- 55 Brand: DENIOS classic line Storage capacity: 200 liter barrels: 2
M28-0051-200-10	
K22-0193-14	
Kbe 9050	
M28-083610	
129124	
Dgf 4	
195-291	
M28-0836-14	
Gefahrstoffregalanlage	
183-508	
M32-0062-10	
M28-0845-10	
M32-0096-10	