



Deprag

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaŐabilirsiniz. **Deprag** Markası, tedarik sresi iin ltfen bizimle iletiŐime geiniz.

Firmamız Deprag Trkiye Distribtr veya temsilcisi deĐildir. Firmamız sipariŐ durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
Vibrator	
140S250 140U/MIN Nr 100207703	
67X-2521	306720F ADVANCED LINE Motor with external parts made of stainless steel. The performance data are based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance in oil-free operation of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX-conform EX II 2D Ex h IIIC T80 ° C Db X EX II 2G Ex h IIC T6 Gb X Nominal power 0.09 kW Direction of rotation reversible Idle speed 100 1 / min Max.permmissible torque 5.00 Nm Air consumption at nominal load 0.30 m³ / min Operating pressure 6.0 bar Min. Supply air hose Ø OD / ID - / 6 Min. Exhaust hose Ø OD / ID - / 6 Working temperature range -20 ° C - 110 ° C ATEX working temperature range -20 ° C - 40 ° C Max. Axial force 340 N Max. Radial force (dimension a) 165 N Dimension a 9.0 mm Output spindle-shaped key
337802	
330255 PZD1X4,6X127	
331002 PHI2X6,1X27	
325567 PHI1X4,6X127	
324686	
803985	

3269521	Spindel .M3
3270042	Idler pinion M0,5Z9DA6x15,5DI1
406228	Motor housing .346-X38-31U
67X-0225	Motor with external parts made of stainless steel. The performance data are based on the specified operating pressure and lubricated supply air. Please take into account a reduction in performance of approx. 10-20% for oil-free operation. ATEX-conform EX II 2D Ex h IIIC T130 ° C Db X EX II 2G Ex h IIC T4 Gb X Nominal power 0.20 kW Direction of rotation reversible Nominal speed 1200 rpm Idle speed 2400 rpm Nominal torque 1.60 Nm Starting torque 2.40 Nm Stall torque 3.00 Nm Air consumption at nominal load 0.37 m ³ / min Operating pressure 6.0 bar Min. Supply air hose Ø OD / ID - / 10 Min. Exhaust hose Ø OD / ID - / 10 Working temperature range -20 ° C - 110 ° C ATEX working temperature range -20 ° C - 40 ° C Max. Axial force 510 N Max. Radial force (dimension a) 1170 N Dimension a 11.0 mm Output spindle-shaped key Please check the following technical changes for the alternative engine: The motor fulfills the ATEX temperature class T4 (previously: T6). The ATEX marking has changed. The performance data (power, speed, torque or Axial / radial forces) of the motor have changed.
007F05	
100686320	
103181E	
104-230-S1	
1136636/09	
1202767/12	
202-30	
208001A	
300004B	
300735	
306770B	
310519B	
320E27 0042-D	
320E27-0018-D (416500-H)	
320EGA27-0022	
320EGA36-0120	
323036	

3275961
341357B
345-308-31
345-3258U
346-328 U
347-310-31U
347-328U
347-520-31UL
347-528-31
347Z-328U
370195
370197
382687B
384210C
400373D
400611E
400611E
406282B 346-230-31U
412799B
442507
444550H
6060836A
6060891A
6061104A
6061107A
6061275B
6074512
63-001F01
63-018F07
63X-018F03

67X-0725
68-P025F-000-9
716
803587
8037563
805435
807427
820454A
826357
830721
AST11-1
DEPRAG PV16BN
E6,3
GDS 070-190SXI
GDS 100-190SXI
GDS009-1000BY
HAS/040
HP101-R25B
HS 043-H19B
II 2GDC IIC-TG(80 C)X
KMO-AST1X-2,5M
M24 104-230-S1
P0383X-P00-IFR
PLU 180D-80X
SH 150- 180BX
SMP 140-3/4 ZAEX
SMP 85
SN 25
SS 150- 280BX
SZG 11022/0.75

[TYP 347-328-31 BEST.-NR. 386369 B](#)

[TYP 67-093](#)

[67X-747](#)

306770I ADVANCED LINE Motor with external parts made of stainless steel. The performance data are based on the stated operating pressure and oiled supply air t. Please take into account a reduction in performance for oil-free operation of approx. 10-20%. You can find more information in our product catalogue: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.90 kW Direction of rotation reversible Rated speed 80 rpm Idle speed 160 rpm Rated torque 107.40 Nm Starting torque 161.10 Nm Stalling torque 204.10 Nm Air consumption at nominal load 1.40 m³/min Operating pressure 6.0 bar Min. supply air hose Ø OD / ID - / 12 Min. exhaust hose Ø OD / ID - / 12 Working temperature range -20 °C - 110 °C ATEX working temperature range -20 °C - 40 °C Max. axial force 1160 N Max. radial force (dimension a) 3790 N Dimension a 20.0 mm Output spindle shape Key Please check the following technical changes for the alternative engine: The ATEX marking has changed. The overall length of the motor changes by +5 mm The spindle diameter changes from 19 mm to 24 mm. The performance data (power, speed, torque or axial/radial forces) of the motor have changed.

[1136493/09](#)

[444785A](#)

spare parts kit .67X-0*25 Spare parts set consisting of fins, sealing rings, O-rings and silencers

[104-230-S1](#)

Motor M24

[306710E ADVANCED LINE Motor](#)

67X-081 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 240 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m³/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side

[306710G ADVANCED LINE Motor](#)

67X-331 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 60 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m³/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C -

	<p>110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side</p>
306710I ADVANCED LINE Motor	<p>67X-581 Motor with external parts made of stainless steel. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Further information can be found in our product catalog: D6400 ATEX compliant EX II 2D Ex h IIIC T80 °C Db X EX II 2G Ex h IIC T6 Gb X Rated power 0.08 kW Direction of rotation can be reversed Idle speed 8 1/min Max. permissible torque 2.00 Nm Air TV consumption at nominal load 0.23 m³/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID 6 / 4 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 200 N Max. radial force (dimension a) 240 N Dimensions: 7.0 mm Output spindle shape round, flattened on one side</p>
342EGA-0012	<p>Further information can be found in our product catalog: D3480 Hand screwdriver type Bauf orm straight Bauf orm Electric drive type Start type: pressure start Torque range 0.15 Nm - 1.20 Nm Speed range 700 1/min - 1000 1/min Two-stage speed changeover Direction of rotation can be reversed Switch off mechanical clutch Torque switch-off parameter ESD capable yes Output spindle shape hexagon socket ISO1173 - F6.3 Insertion tool external hexagon ISO1173 - E6.3 Sound pressure level 68.0 dB(A) Vibration value in m/s² < 2.5</p>
208005D	<p>BASIC LINE engine 63X-018F05 Motor with robust gray cast iron housing. The performance data is based on the specified operating pressure and oiled supply air t. Please take into account a reduction in performance when operating oil-free of approx. 10-20%. Reduced maintenance effort thanks to the QuickVChange slat changing system: slats can be changed in just a few minutes without dismantling the motor minutes. Further information can be found in our product catalog: D6200 ATEX compliant EX II 2D Ex h IIIC T130°C Db X EX II 2G Ex h IIC T4 Gb X Rated power 0.60 kW Direction of rotation can be reversed Rated speed 270 1/min Idle speed 540 1/min Rated torque 21.00 Nm Starting torque 31.50 Nm Stalling torque 39.90 Nm Air TV consumption at nominal load 0.90 m³/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 13 Min. exhaust hose Ø AD / ID - / 13 Working temperature range -20°C - 110°C ATEX working temperature range -20 °C - 40 °C Max. axial force 70 N Max. radial force (dimension a) 360 N Dimensions: 20.0 mm Output spindle form fitting spring</p>
445700A	<p>140S25U Rated power 0.20 kW Direction of rotation can be reversed Rated speed 70 1/min Idle speed 140 1/min Rated torque 27.00 Nm Starting torque 40.00 Nm Stalling torque 50.00 Nm Air TV consumption at nominal load 0.37 m³/min Operating pressure 6.0 bar Min. supply hose Ø AD / ID - / 10 Working temperature range -20°C - 110°C Output spindle shape customer-specific The performance data is based on</p>

the specified operating pressure and oiled supply air.

[Liste amahang](#)

[GEARING DEPRAG 396982E](#)

[406020-D CLUTCH BEARING](#)

[BEARING NEEDLE DEPRAG 802358
\(2X11,8\)](#)

[VALVE PIN 406112](#)

[396030A](#)

[BEARING NEEDLE DEPRAG 802368
\(2X15,8\)](#)

[1272703/16](#)

104-230 S1 2500 U/Min 6.3 bar max

[Gds009-1000by Schleif-Maschine](#)

[386360a](#)

[833790](#)

[1236618/14 Luftmotor 344-740-31u](#)

[6060875a](#)

[444570f](#)

[Has/040 Schlauch Antistatisch Mit
Verbindungen](#)

[Gds 100-190sxi](#)

[365996](#)

[Hr105-R60v](#)

[Gda 070-190bx](#)

[5933 140s25u](#)

[Dreb 13/15](#)

[383143a](#)

[67-058? Deprag Pneumatic Motor](#)

[3659192](#)

[365997](#)

[339269?](#)

[444500g Motor 67-04251 Advanced Line
\(P=100 W,N=90 U/Min,T=10,5 Nm\)](#)

[310519b Schleifmaschine Gat 812-221bx](#)

2100716717	
326949/2	
208003b	
3658543	
Baf60090	
Pv 16bn Pneumatische Bohrmaschine Klasse Explosionsschutz 1exibii Bt6	
63x-124 F01 208001h	
6061275b Winkelschleifmaschine Ga815-190bx Mit Gewinkeltem Antrieb Ga 815-190bx	
Kmo-Ast30-5m	MOTOR CABLE 5METER FOR AST30
4065661	
Hs 043-H19?	
3660053	
323035	
344859/3	
802511	
6060836? Pneumatische Bohrmaschine	
6074508	
343428	
802092	
385777a	
406282 B 346-230-31u - Deprag Tornavida Motoru	
440015a	
63x-007f07	
386363c	
833780	
388730a	
6078615	
63-001f01 Pneumomotor	

388721a	
3217253	
802063	
445538e	
3658694	
326947	
Pbo100	
67-093	
414010 B	
802452	
Gd070-153wyi	
388730-A	MOTOR CABLE 5METER FOR AST30
1254724	
802435	
007f05 Luftmotor Leistung 0,6 Kw, Leerlaufdrehzahl 1460 U/Min, Drehmoment 7.8 Nm	
782175 Pneumatic Motor 101-030-2	
Pv16bn Bohrmachine	
388731a	
353657c	
444550h Motor67-012	
444500g	
802292	
445251a (Oem)	
6060874a	
Pv16bn	
377521uf	DRIVER
63x-124 F01 208001h Elektromotor	
6060874a Lubricator 6060874a D = 3/4 "p = 8 Bar	
820454?	

830721 Drill Chuck
100686320 Luftmotor
344862/3
Pv16bn Pneumatic Drill
63x-001f01
388720-A DRIVE 230V
347-428u
1202767/12 Pneumatikantrieb347-328-7
342 Ega-019
347-520-31
386460 B
385778a
6060836?
B257-50mdw-Sz
446227b
347z-238
833783
Pv 16bn Pneumatische Bohrmaschine
P 0383x-P00-Ife
310519b Winkelschleifmaschine Gat812-221bx
Deprag Pv16bn Pneumatische Bohrmaschine
63-018f07 Luftmotor
802430
63x-007f07 Air Motor
335637
6061107a Pneumatische Bohrmaschine Dp Eigensichere 220-011 Bxoex 6061107a Deprag (Atex)
48-381-3fsr - Obsolete, Replacement P0383x-P00-Ifr
345-308u

1611-Es / 0,75-1	
Gds 070-190sxi	
Pv16bn Pneumatische Bohrmaschine Mit Schlauch Komplett Mit Verbindungen Zu 30m	
3217265	
1255417	
Ast30-1-230v	DRIVE 230V
6061104?	
444550e	
Pv16bn Pneumatische Bohrmaschine	
Sn 25 Pneumatisches Nadel-Abbruchhammer	
67x-2521	
326950/4	
Pv16bn Pneumatikbohrer Pv16bn	